

# Package: terra (via r-universe)

October 30, 2022

**Type** Package

**Title** Spatial Data Analysis

**Version** 1.6-33

**Date** 2022-10-28

**Depends** R (>= 3.5.0)

**Suggests** parallel, tinytest, ncdf4, sf (>= 0.9-8), deldir, XML, leaflet

**LinkingTo** Rcpp

**Imports** methods, Rcpp

**SystemRequirements** C++11, GDAL (>= 2.2.3), GEOS (>= 3.4.0), PROJ (>= 4.9.3), sqlite3

**Encoding** UTF-8

**Language** en-US

**Maintainer** Robert J. Hijmans <r.hijmans@gmail.com>

## Description

Methods for spatial data analysis with vector (points, lines, polygons) and raster (grid) data. Methods for vector data include standard operations such as intersect and buffer. Raster methods include global, local, zonal, and focal computations. The predict and interpolate methods facilitate the use of regression type (interpolation, machine learning) models for spatial prediction, including with satellite remote sensing data. Processing of very large files is supported. See the manual and tutorials on <<https://rspatial.org/terra/>> to get started. 'terra' is a replacement for the 'raster' package ('terra' can do more, and it is faster and easier to use).

**License** GPL (>=3)

**URL** <https://rspatial.org/terra/>

**BugReports** <https://github.com/rspatial/terra/issues/>

**LazyLoad** yes

**Repository** <https://rspatial.r-universe.dev>

**RemoteUrl** <https://github.com/rspatial/terra>

**RemoteRef** HEAD

**RemoteSha** 54c452eff54fa6b765c8ff9aee50e5702a2ed442

**R topics documented:**

terra-package	6
activeCat	19
add	20
adjacent	20
aggregate	22
align	23
all.equal	24
animate	25
app	26
approximate	28
Arith-methods	30
as.character	31
as.data.frame	32
as.list	33
as.raster	34
as.spatvector	34
atan2	36
autocorrelation	37
barplot	38
boundaries	39
boxplot	40
buffer	41
c	43
cartogram	44
catalyze	44
cells	45
cellSize	47
centroids	48
clamp	49
classify	50
click	52
coerce	53
colors	54
combineGeoms	55
Compare-methods	57
compareGeom	58
concat	59
contour	60
convHull	61
costDist	62
cover	63
crds	64
crop	65
crosstab	67
crs	68
deepcopy	69

densify . . . . .	70
density . . . . .	71
deprecated . . . . .	72
depth . . . . .	72
describe . . . . .	73
diff . . . . .	74
dimensions . . . . .	75
direction . . . . .	77
disagg . . . . .	78
distance . . . . .	79
dots . . . . .	82
draw . . . . .	83
erase . . . . .	83
expanse . . . . .	85
ext . . . . .	86
extend . . . . .	88
extract . . . . .	89
extremes . . . . .	92
factors . . . . .	92
fillHoles . . . . .	94
fillTime . . . . .	95
flip . . . . .	96
focal . . . . .	97
focal3D . . . . .	99
focalCor . . . . .	101
focalCpp . . . . .	102
focalMat . . . . .	104
focalReg . . . . .	105
focalValues . . . . .	106
freq . . . . .	106
gaps . . . . .	107
gdal . . . . .	108
geom . . . . .	109
geomtype . . . . .	110
global . . . . .	111
gridDistance . . . . .	112
head and tail . . . . .	113
hist . . . . .	114
ifel . . . . .	115
image . . . . .	116
impose . . . . .	117
initialize . . . . .	118
inplace . . . . .	119
inset . . . . .	120
interpIDW . . . . .	122
interpNear . . . . .	124
intersect . . . . .	125
is.bool . . . . .	126

is.lonlat . . . . .	128
lapp . . . . .	129
layerCor . . . . .	131
linearUnits . . . . .	132
lines . . . . .	133
makeTiles . . . . .	134
makeVRT . . . . .	135
mask . . . . .	137
match . . . . .	138
Math-methods . . . . .	139
mem . . . . .	140
merge . . . . .	141
mergeTime . . . . .	143
modal . . . . .	144
mosaic . . . . .	145
na.omit . . . . .	146
NAflag . . . . .	147
names . . . . .	148
nearest . . . . .	150
normalize.longitude . . . . .	151
north . . . . .	151
not.na . . . . .	153
options . . . . .	154
origin . . . . .	155
pairs . . . . .	155
patches . . . . .	156
perim . . . . .	158
persp . . . . .	158
plet . . . . .	159
plot . . . . .	161
plotRGB . . . . .	165
predict . . . . .	167
project . . . . .	170
quantile . . . . .	173
query . . . . .	174
rapp . . . . .	175
rast . . . . .	177
rasterize . . . . .	179
rasterizeGeom . . . . .	181
rasterizeWin . . . . .	182
rcl . . . . .	184
read and write . . . . .	185
rectify . . . . .	187
relate . . . . .	187
rep . . . . .	190
replace_dollar . . . . .	191
replace_layers . . . . .	192
replace_values . . . . .	193

resample . . . . .	194
rescale . . . . .	195
RGB . . . . .	196
rotate . . . . .	197
sapp . . . . .	199
sbar . . . . .	200
scale . . . . .	201
scatterplot . . . . .	202
scoff . . . . .	203
sds . . . . .	204
segregate . . . . .	205
sel . . . . .	206
selectHighest . . . . .	207
selectRange . . . . .	208
serialize . . . . .	209
setValues . . . . .	210
shade . . . . .	211
sharedPaths . . . . .	212
shift . . . . .	213
sieve . . . . .	214
simplifyGeom . . . . .	215
sort . . . . .	216
sources . . . . .	216
SpatExtent-class . . . . .	217
Spatial interpolation . . . . .	218
SpatRaster-class . . . . .	221
spatSample . . . . .	222
SpatVector-class . . . . .	224
spin . . . . .	224
split . . . . .	225
sprc . . . . .	226
stretch . . . . .	227
subset . . . . .	228
subset_dollar . . . . .	229
subset_double . . . . .	231
subset_single . . . . .	232
subst . . . . .	233
summarize . . . . .	234
summary . . . . .	236
svc . . . . .	237
syndif . . . . .	238
tapp . . . . .	239
terrain . . . . .	240
text . . . . .	242
tighten . . . . .	243
time . . . . .	244
tmpFiles . . . . .	245
topology . . . . .	246

transpose . . . . .	247
trim . . . . .	248
union . . . . .	249
unique . . . . .	250
units . . . . .	251
update . . . . .	252
valid . . . . .	253
values . . . . .	254
vect . . . . .	255
vector_layers . . . . .	258
viewshed . . . . .	258
voronoi . . . . .	260
vrt . . . . .	261
weighted.mean . . . . .	262
where . . . . .	263
which.lyr . . . . .	264
width . . . . .	265
window . . . . .	266
wrap . . . . .	267
writeCDF . . . . .	268
writeRaster . . . . .	269
writeVector . . . . .	271
xmin . . . . .	272
xyRowColCell . . . . .	273
zonal . . . . .	275
zoom . . . . .	277

<b>Index</b>	<b>279</b>
--------------	------------

---

terra-package	<i>Description of the methods in the terra package</i>
---------------	--

---

## Description

terra provides methods to manipulate geographic (spatial) data in "raster" and "vector" form. Raster data divide space into rectangular cells (pixels) and they are commonly used to represent spatially continuous phenomena, such as elevation or the weather. Satellite images also have this data structure. In contrast, "vector" spatial data (points, lines, polygons) are typically used to represent discrete spatial entities, such as a road, country, or bus stop.

The package implements two main classes (data types): `SpatRaster` and `SpatVector`. `SpatRaster` supports handling large raster files that cannot be loaded into memory; local, focal, zonal, and global raster operations; polygon, line and point to raster conversion; integration with modeling methods to make spatial predictions; and more. `SpatVector` supports all types of geometric operations such as intersections.

Additional classes include `SpatExtent`, which is used to define a spatial extent (bounding box); `SpatRasterDataset`, which represents a collection of sub-datasets for the same area. Each sub-dataset is a `SpatRaster` with possibly many layers, and may, for example, represent different weather

variables; and `SpatRasterCollection` and `SpatVectorCollection` that are equivalent to lists of `SpatRaster` or `SpatVector` objects.

These classes hold a C++ pointer to the data "reference class" and that creates some limitations. They cannot be recovered from a saved R session either or directly passed to nodes on a computer cluster. Generally, you should use `writeRaster` to save `SpatRaster` objects to disk (and pass a filename or cell values to cluster nodes). Also see `wrap`.

The `terra` package is conceived as a replacement of the `raster` package. `terra` has a very similar, but simpler, interface, and it is faster than `raster`. At the bottom of this page there is a table that shows differences in the methods between the two packages.

Below is a list of some of the most important methods grouped by theme.

## SpatRaster

### I. Creating, combining and sub-setting

<code>rast</code>	Create a <code>SpatRaster</code> from scratch, file, or another object
<code>c</code>	Combine <code>SpatRasters</code> (multiple layers)
<code>add&lt;-</code>	Add a <code>SpatRaster</code> to another one
<code>subset</code> or <code>[[</code> , or <code>\$</code>	Select layers of a <code>SpatRaster</code>
<code>selectRange</code>	Select cell values from different layers using an index layer

### II. Changing the spatial extent or resolution

Also see the methods in section VIII

<code>merge</code>	Combine <code>SpatRasters</code> with different extents (but same origin and resolution)
<code>mosaic</code>	Combine <code>SpatRasters</code> with different extents using a function for overlapping cells
<code>crop</code>	Select a geographic subset of a <code>SpatRaster</code>
<code>extend</code>	Add rows and/or columns to a <code>SpatRaster</code>
<code>trim</code>	Trim a <code>SpatRaster</code> by removing exterior rows and/or columns that only have NAs
<code>aggregate</code>	Combine cells of a <code>SpatRaster</code> to create larger cells
<code>disagg</code>	Subdivide cells
<code>resample</code>	Resample (warp) values to a <code>SpatRaster</code> with a different origin and/or resolution
<code>project</code>	Project (warp) values to a <code>SpatRaster</code> with a different coordinate reference system
<code>shift</code>	Adjust the location of <code>SpatRaster</code>
<code>flip</code>	Flip values horizontally or vertically
<code>rotate</code>	Rotate values around the date-line (for lon/lat data)
<code>t</code>	Transpose a <code>SpatRaster</code>

### III. Local (cell based) methods

#### Apply-like methods:

<code>app</code>	Apply a function to all cells, across layers, typically to summarize (as in <code>base::apply</code> )
<code>tapp</code>	Apply a function to groups of layers (as in <code>base::tapply</code> and <code>stats::aggregate</code> )
<code>lapp</code>	Apply a function to using the layers of a <code>SpatRaster</code> as variables
<code>sapp</code>	Apply a function to each layer
<code>rapp</code>	Apply a function to a spatially variable range of layers

---

#### Arithmetic, logical, and standard math methods:

<code>Arith-methods</code>	Standard arithmetic methods (+, -, *, ^, %, %/, /)
<code>Compare-methods</code>	Comparison methods for <code>SpatRaster</code> (==, !=, >, <, <=, >=)
<code>Logic-methods</code>	Boolean methods (!, &,  )
<code>Math-methods</code>	<code>abs</code> , <code>sign</code> , <code>sqrt</code> , <code>ceiling</code> , <code>floor</code> , <code>trunc</code> , <code>cummax</code> , <code>cummin</code> , <code>cumprod</code> , <code>cumsum</code> , <code>log</code> , <code>log10</code> , <code>log2</code> , <code>log1p</code> , <code>acos</code> , <code>acosh</code> , <code>asin</code> , <code>asinh</code> , <code>atan</code> , <code>atanh</code> , <code>exp</code> , <code>expm1</code> , <code>cos</code> , <code>cosh</code> , <code>sin</code> , <code>sinh</code> , <code>tan</code> , <code>tanh</code> , <code>round</code> , <code>signif</code>
<code>Summary-methods</code>	<code>mean</code> , <code>max</code> , <code>min</code> , <code>median</code> , <code>sum</code> , <code>range</code> , <code>prod</code> , <code>any</code> , <code>all</code> , <code>stdev</code> , <code>which.min</code> , <code>which.max</code>
<code>as.bool</code>	create a Boolean (logical) <code>SpatRaster</code>
<code>as.int</code>	create an integer (whole numbers) <code>SpatRaster</code>

---

#### Other methods:

<code>approximate</code>	Compute missing values for cells by interpolation across layers
<code>cellSize</code>	Compute the area of cells
<code>classify</code>	(Re-)classify values
<code>subst</code>	Substitute (replace) cell values
<code>cover</code>	First layer covers second layer except where the first layer is NA
<code>init</code>	Initialize cells with new values
<code>mask</code>	Replace values in a <code>SpatRaster</code> based on values in another <code>SpatRaster</code>
<code>which.lyr</code>	which is the first layer that is TRUE?
<code>segregate</code>	Make a 0/1 layer for each unique value

---

### IV. Zonal and global methods

<code>expanse</code>	Compute the summed area of cells
<code>crosstab</code>	Cross-tabulate two <code>SpatRasters</code>
<code>freq</code>	Frequency table of <code>SpatRaster</code> cell values
<code>global</code>	Summarize <code>SpatRaster</code> cell values with a function
<code>quantile</code>	Quantiles
<code>layerCor</code>	Correlation between layers



<code>stretch</code>	Stretch values
<code>scale</code>	Scale values
<code>summary</code>	Summary of the values of a SpatRaster (quartiles and mean)
<code>unique</code>	Get the unique values in a SpatRaster
<code>zonal</code>	Summarize a SpatRaster by zones in another SpatRaster

---

## V. Situation (spatial context) based methods

<code>adjacent</code>	Identify cells that are adjacent to a set of cells of a SpatRaster
<code>boundaries</code>	Detection of boundaries (edges)
<code>distance</code>	Shortest distance to a cell that is not NA or to or from a vector object
<code>gridDistance</code>	Shortest distance through adjacent grid cells
<code>costDistance</code>	Shortest distance considering cell-varying friction
<code>direction</code>	Direction (azimuth) to or from cells that are not NA
<code>focal</code>	Focal (neighborhood; moving window) functions
<code>focalCpp</code>	Faster focal by using custom C++ functions
<code>focalReg</code>	Regression between layers for focal areas
<code>focalCor</code>	Correlation between layers for focal areas
<code>patches</code>	Find patches (clumps)
<code>terrain</code>	Compute slope, aspect and other terrain characteristics from elevation data
<code>shade</code>	Compute hill shade from slope and aspect layers
<code>autocor</code>	Compute global or local spatial autocorrelation

---

## VI. Model predictions

<code>predict</code>	Predict a non-spatial model to a SpatRaster
<code>interpolate</code>	Predict a spatial model to a SpatRaster

---

## VII. Accessing cell values

Apart from the function listed below, you can also use indexing with `[]` with cell numbers, and row and/or column numbers

<code>values</code>	cell values (fails with very large rasters)
---------------------	---

<code>values&lt;-</code>	Set new values to the cells of a SpatRaster
<code>setValues</code>	Set new values to the cells of a SpatRaster
<code>as.matrix</code>	Get cell values as a matrix
<code>as.array</code>	Get cell values as an array
<code>extract</code>	Extract cell values from a SpatRaster (e.g., by cell, coordinates, polygon)
<code>spatSample</code>	Regular or random sample
<code>minmax</code>	Get the minimum and maximum value of the cells of a SpatRaster (if known)
<code>setMinMax</code>	Compute the minimum and maximum value of a SpatRaster if these are not known
<code>extract</code>	spatial queries of a SpatRaster with a SpatVector

---

## VIII. Getting and setting dimensions

Get or set basic parameters of SpatRasters. If there are values associated with a SpatRaster object (either in memory or via a link to a file) these are lost when you change the number of columns or rows or the resolution. This is not the case when the extent is changed (as the number of columns and rows will not be affected). Similarly, with `crs` you can set the coordinate reference system, but this does not transform the data (see [project](#) for that).

<code>ncol</code>	The number of columns
<code>nrow</code>	The number of rows
<code>ncell</code>	The number of cells (can not be set directly, only via <code>ncol</code> or <code>nrow</code> )
<code>res</code>	The resolution (x and y)
<code>nlyr</code>	Get or set the number of layers
<code>names</code>	Get or set the layer names
<code>xres</code>	The x resolution (can be set with <code>res</code> )
<code>yres</code>	The y resolution (can be set with <code>res</code> )
<code>xmin</code>	The minimum x coordinate (or longitude)
<code>xmax</code>	The maximum x coordinate (or longitude)
<code>ymin</code>	The minimum y coordinate (or latitude)
<code>ymax</code>	The maximum y coordinate (or latitude)
<code>ext</code>	Get or set the extent (minimum and maximum x and y coordinates ("bounding box"))
<code>origin</code>	The origin of a SpatRaster
<code>crs</code>	The coordinate reference system (map projection)
<code>is.lonlat</code>	Test if an object has (or may have) a longitude/latitude coordinate reference system
<code>sources</code>	Get the filename(s) to which a SpatRaster is linked
<code>inMemory</code>	Are the data sources in memory (or on disk)?
<code>compareGeom</code>	Compare the geometry of SpatRasters
<code>NAflag</code>	Set the NA value (for reading from a file with insufficient metadata)

---

## IX. Computing row, column, cell numbers and coordinates

Cell numbers start at 1 in the upper-left corner. They increase within rows, from left to right, and then row by row from top to bottom. Likewise, row numbers start at 1 at the top of the raster, and column numbers start at 1 at the left side of the raster.

<code>xFromCol</code>	x-coordinates from column numbers
<code>yFromRow</code>	y-coordinates from row numbers
<code>xFromCell</code>	x-coordinates from row numbers
<code>yFromCell</code>	y-coordinates from cell numbers
<code>xyFromCell</code>	x and y coordinates from cell numbers
<code>colFromX</code>	Column numbers from x-coordinates (or longitude)
<code>rowFromY</code>	Row numbers from y-coordinates (or latitude)
<code>rowColFromCell</code>	Row and column numbers from cell numbers
<code>cellFromXY</code>	Cell numbers from x and y coordinates
<code>cellFromRowCol</code>	Cell numbers from row and column numbers
<code>cellFromRowColCombine</code>	Cell numbers from all combinations of row and column numbers
<code>cells</code>	Cell numbers from an <code>SpatVector</code> or <code>SpatExtent</code>

---

## X. Time related methods

<code>time</code>	Get or set time
<code>fillTime</code>	can add empty layers in between existing layers to assure that the time step between layers is constant
<code>mergeTime</code>	combine multiple rasters, perhaps partly overlapping in time, into a single time series

---

## XI. Methods for categorical rasters

<code>is.factor</code>	Are there categorical layers?
<code>levels</code>	Get active categories, or set categories
<code>activeCat</code>	Get or set the active category
<code>cats</code>	Get categories (active and inactive)
<code>set.cats</code>	Set categories in place
<code>concats</code>	Combine <code>SpatRasters</code> with different categories
<code>catalyze</code>	Create a layer for each category
<code>as.numeric</code>	use the active category to create a non-categorical <code>SpatRaster</code>
<code>as.factor</code>	Make the layers of a <code>SpatRaster</code> categorical

---

## XII. Writing `SpatRaster` files

### Basic:

<code>writeRaster</code>	Write all values of <code>SpatRaster</code> to disk. You can set the filetype, datatype, compression.
<code>writeCDF</code>	Write <code>SpatRaster</code> data to a netCDF file

**Advanced:**


---

<code>readStart</code>	Open file connections for efficient multi-chunk reading
<code>readStop</code>	Close file connections
<code>writeStart</code>	Open a file for writing
<code>writeValues</code>	Write some values
<code>writeStop</code>	Close the file after writing

---

**XIII. Miscellaneous SpatRaster methods**


---

<code>terraOptions</code>	Show, set, or get session options, mostly to control memory use and to set write options
<code>sources</code>	Show the data sources of a SpatRaster
<code>tmpFiles</code>	Show or remove temporary files
<code>mem_info</code>	memory needs and availability
<code>inMemory</code>	Are the cell values in memory?

---

**SpatRasterDataSet****XIV. SpatRasterDataset**

A SpatRasterDataset contains SpatRaster objects that are sub-datasets for the same area. They all have the same extent and resolution.

---

<code>sds</code>	Create a SpatRasterDataset from a file with subdatasets (ncdf or hdf) or from SpatRaster objects
<code>[ or \$</code>	Extract a SpatRaster
<code>names</code>	Get the names of the sub-datasets

---

**SpatVector****XV. Create SpatVector objects**

<code>vect</code>	Create a <code>SpatVector</code> from a file (for example a "shapefile") or from another object
<code>vector_layers</code>	list or delete layers in a vector database such as GPKG
<code>rbind</code>	append <code>SpatVectors</code> of the same geometry type
<code>unique</code>	remove duplicates
<code>na.omit</code>	remove empty geometries and/or fields that are NA
<code>project</code>	Project a <code>SpatVector</code> to a different coordinate reference system
<code>writeVector</code>	Write <code>SpatVector</code> data to disk
<code>centroids</code>	Get the centroids of a <code>SpatVector</code>
<code>voronoi</code>	Voronoi diagram
<code>delaunay</code>	Delaunay triangles
<code>convHull</code>	Compute the convex hull of a <code>SpatVector</code>
<code>fillHoles</code>	Remove or extract holes from polygons

---

## XVI. Properties of `SpatVector` objects

<code>geom</code>	returns the geometries as matrix or WKT
<code>crds</code>	returns the coordinates as a matrix
<code>linearUnits</code>	returns the linear units of the crs (in meter)
<code>ncol</code>	The number of columns (of the attributes)
<code>nrow</code>	The number of rows (of the geometries and attributes)
<code>names</code>	Get or set the layer names
<code>ext</code>	Get the extent (minimum and maximum x and y coordinates ("bounding box"))
<code>crs</code>	The coordinate reference system (map projection)
<code>is.lonlat</code>	Test if an object has (or may have) a longitude/latitude coordinate reference system

---

## XVII. Geometric queries

<code>adjacent</code>	find adjacent polygons
<code>expanse</code>	computes the area covered by polygons
<code>nearby</code>	find nearby geometries
<code>nearest</code>	find the nearest geometries
<code>relate</code>	geometric relationships such as "intersects", "overlaps", and "touches"
<code>perim</code>	computes the length of the perimeter of polygons, and the length of lines

---

## XVIII. Geometric operations

<code>erase</code> or <code>"-"</code>	erase (parts of) geometries
<code>intersect</code> or <code>"*"</code>	intersect geometries
<code>union</code> or <code>"+"</code>	Merge geometries
<code>cover</code>	update polygons
<code>symdif</code>	symmetrical difference of two polygons
<code>aggregate</code>	dissolve smaller polygons into larger ones
<code>buffer</code>	buffer geometries
<code>disagg</code>	split multi-geometries into separate geometries
<code>crop</code>	clip geometries using a rectangle ( <code>SpatExtent</code> ) or <code>SpatVector</code>

---

## XIX. SpatVector attributes

We use the term "attributes" for the tabular data (`data.frame`) associated with vector geometries.

<code>extract</code>	spatial queries between <code>SpatVector</code> and <code>SpatVector</code> (e.g. point in polygons)
<code>sel</code>	select - interactively select geometries
<code>click</code>	identify attributes by clicking on a map
<code>merge</code>	Join a table with a <code>SpatVector</code>
<code>as.data.frame</code>	get attributes as a <code>data.frame</code>
<code>as.list</code>	get attributes as a list
<code>values</code>	Get the attributes of a <code>SpatVector</code>
<code>values&lt;-</code>	Set new attributes to the geometries of a <code>SpatRaster</code>

---

## XX. Change geometries (for display, experimentation)

<code>shift</code>	change the position geometries by shifting their coordinates in horizontal and/or vertical direction
<code>spin</code>	rotate geometries around an origin
<code>rescale</code>	shrink (or expand) geometries, for example to make an inset map
<code>flip</code>	flip geometries vertically or horizontally
<code>t</code>	transpose geometries (switch x and y)

---

## XXI. Geometry properties and topology

<code>width</code>	the minimum diameter of the geometries
<code>clearance</code>	the minimum clearance of the geometries

<code>sharedPaths</code>	shared paths (arcs) between line or polygon geometries
<code>simplifyGeom</code>	simplify geometries
<code>gaps</code>	find gaps between polygon geometries
<code>fillHoles</code>	get or remove the polygon holes
<code>makeNodes</code>	create nodes on lines
<code>mergeLines</code>	connect lines to form polygons
<code>removeDupNodes</code>	remove duplicate nodes in geometries and optionally rounds the coordinates
<code>is.valid</code>	check if geometries are valid
<code>makeValid</code>	attempt to repair invalid geometries
<code>snap</code>	make boundaries of geometries identical if they are very close to each other
<code>erase</code> (single argument)	remove parts of geometries that overlap
<code>union</code> (single argument)	create new polygons such that there are no overlapping polygons
<code>combineGeoms</code>	combine geometries that overlap, share a border, or are within a minimum distance of each other

---

## Spat\* Collections

### XXII. Collections

A `SpatRasterCollection` is a vector of `SpatRaster` objects. Unlike for a `SpatRasterDataset`, there the extent and resolution of the `SpatRasters` do not need to match each other. A `SpatVectorCollection` is a vector of `SpatVector` objects.

<code>svc</code>	create a <code>SpatRasterCollection</code> from a set of <code>SpatRaster</code> objects
<code>length</code>	how many <code>SpatRasters</code> does the <code>SpatRasterCollection</code> have?
<code>[</code>	extract a <code>SpatRaster</code>

---

## SpatExtent

### XXIII. SpatExtent

<code>ext</code>	Create a <code>SpatExtent</code> object. For example to <code>crop</code> a Spatial dataset
<code>intersect</code>	Intersect two <code>SpatExtent</code> objects, same as -
<code>union</code>	Combine two <code>SpatExtent</code> objects, same as +
<code>Math-methods</code>	round/floor/ceiling of a <code>SpatExtent</code>
<code>align</code>	Align a <code>SpatExtent</code> with a <code>SpatRaster</code>
<code>draw</code>	Create a <code>SpatExtent</code> by drawing it on top of a map (plot)

## General methods

---

### XXIV. Conversion between spatial data objects from different packages

You can coerce SpatRasters to Raster\* objects, after loading the raster package, with `as(object, "Raster")`, or `raster(object)` or `brick(object)` or `stack(object)`

<code>rast</code>	SpatRaster from matrix and other objects
<code>vect</code>	SpatVector from sf or Spatial* vector data
<code>sf::st_as_sf</code>	sf object from SpatVector
<code>rasterize</code>	Rasterizing points, lines or polygons
<code>rasterizeGeom</code>	Rasterize attributes of geometries such as "count", "area", or "length"
<code>as.points</code>	Create points from a SpatRaster or SpatVector
<code>as.lines</code>	Create points from a SpatRaster or SpatVector
<code>as.polygons</code>	Create polygons from a SpatRaster
<code>as.contour</code>	Contour lines from a SpatRaster

---

### XXV. Plotting

#### Maps:

<code>plot</code>	Plot a SpatRaster or SpatVector. The main method to create a map
<code>points</code>	Add points to a map
<code>lines</code>	Add lines to a map
<code>polys</code>	Add polygons to a map
<code>text</code>	Add text (such as the values of a SpatRaster or SpatVector) to a map
<code>image</code>	Alternative to plot to make a map with a SpatRaster
<code>plotRGB</code>	Combine three layers (red, green, blue channels) into a single "real color" plot
<code>sbar</code>	Add a scalebar to a map
<code>north</code>	Add a north arrow to a map
<code>inset</code>	Add a small inset (overview) map
<code>dots</code>	Make a dot-density map
<code>cartogram</code>	Make a cartogram
<code>persp</code>	Perspective plot of a SpatRaster
<code>contour</code>	Contour plot or filled-contour plot of a SpatRaster
<code>colorize</code>	Combine three layers (red, green, blue channels) into a single layer with a color-table

---

#### Interacting with a map:

<code>zoom</code>	Zoom in to a part of a map by drawing a bounding box on it
<code>click</code>	Query values of SpatRaster or SpatVector by clicking on a map
<code>sel</code>	Select a spatial subset of a SpatRaster or SpatVector by drawing on a map
<code>draw</code>	Create a SpatExtent or SpatVector by drawing on a map



**Other plots:**


---

<code>plot</code>	x-y scatter plot of the values of (a sample of) the layers of two <code>SpatRaster</code> objects
<code>hist</code>	Histogram of <code>SpatRaster</code> values
<code>barplot</code>	Bar plot of a <code>SpatRaster</code>
<code>density</code>	Density plot of <code>SpatRaster</code> values
<code>pairs</code>	Pairs plot for layers in a <code>SpatRaster</code>
<code>boxplot</code>	Box plot of the values of a <code>SpatRaster</code>

---

**Comparison with the raster package****XXVI. New method names**

terra has a single class `SpatRaster` for which raster has three (`RasterLayer`, `RasterStack`, `RasterBrick`). Likewise there is a single class for vector data `SpatVector` that replaces six `Spatial*` classes. Most method names are the same, but note the following important differences in methods names with the raster package

<b>raster package</b>	<b>terra package</b>
<code>raster</code> , <code>brick</code> , <code>stack</code>	<code>rast</code>
<code>rasterFromXYZ</code>	<code>rast( , type="xyz")</code>
<code>stack</code> , <code>addLayer</code>	<code>c</code>
<code>addLayer</code>	<code>add&lt;-</code>
<code>area</code>	<code>cellSize</code> or <code>expanse</code>
<code>approxNA</code>	<code>approximate</code>
<code>calc</code>	<code>app</code>
<code>cellFromLine</code> , <code>cellFromPolygon</code> ,	<code>cells</code>
<code>cellsFromExtent</code>	<code>cells</code>
<code>cellStats</code>	<code>global</code>
<code>corLocal</code>	<code>focalCor</code>
<code>coordinates</code>	<code>crds</code>
<code>clump</code>	<code>patches</code>
<code>compareRaster</code>	<code>compareGeom</code>
<code>disaggregate</code>	<code>disagg</code>
<code>drawExtent</code> , <code>drawPoly</code> , <code>drawLine</code>	<code>draw</code>
<code>dropLayer</code>	<code>subset</code>
<code>extent</code>	<code>ext</code>
<code>distanceFromPoints</code>	<code>distance</code>
<code>isLonLat</code> , <code>isGlobalLonLat</code>	<code>is.lonlat</code>
<code>couldBeLonLat</code>	<code>is.lonlat</code>
<code>layerize</code>	<code>segregate</code>
<code>layerStats</code>	<code>layerCor</code>

Nvalue	NAflag
nlayers	nlyr
overlay	lapp
projectRaster	project
rasterToPoints	as.points
rasterToPolygons	as.polygons
reclassify, subs, cut	classify
sampleRandom, sampleRegular	spatSample
shapefile	vect
stackApply	tapp
stackSelect	selectRange

## XXVII. Changed behavior

Also note that even if function names are the same in terra and raster, their output can be different. In most cases this was done to get more consistency in the returned values (and thus fewer errors in the downstream code that uses them). In other cases it simply seemed better. Here are some examples:

as.polygons	By default, terra returns dissolved polygons
quantile	computes by cell, across layers instead of the other way around
extract	By default, terra returns a matrix, with the first column the sequential ID of the vectors. raster returns a list (for lines or polygons) or a matrix (for points, but without the ID column). You can use <code>list=TRUE</code> to get the results as a list
values	terra always returns a matrix. raster returns a vector for a RasterLayer
Summary-methods	With raster, <code>mean(x, y)</code> and <code>mean(stack(x, y))</code> return the same result, a single layer with the mean of all cell values. This is also what terra returns with <code>mean(c(x, y))</code> , but with <code>mean(x, y)</code> the parallel mean is returned – that is, the computation is done layer-wise, and the number of layers in the output is the same as that of x and y (or the larger of the two if they are not the same). This affects all summary functions ( <code>sum</code> , <code>mean</code> , <code>median</code> , <code>which.min</code> , <code>which.max</code> , <code>min</code> , <code>max</code> , <code>prod</code> , <code>any</code> , <code>all</code> , <code>stdev</code> ), except <code>range</code> , which is not implemented for this case (you can use <code>min</code> and <code>max</code> instead)

---

## Authors

Except where indicated otherwise, the methods and functions in this package were written by Robert Hijmans. The configuration scripts were written by Roger Bivand. Some of code using the GEOS library was adapted from code by Edzer Pebesma for `sf`. Michael Sumner contributed various bits and pieces.

## Acknowledgments

This package is an attempt to climb on the shoulders of giants (GDAL, PROJ, GEOS, NCDF, GeographicLib, Rcpp, R). Many people have contributed by asking questions or **raising issues**. Feedback and suggestions by Márcia Barbosa, Kendon Bell, Andrew Gene Brown, Jean-Luc Dupouey,

Krzysztof Dyba, Alex Ilich, Gerald Nelson, Jakub Nowosad and Monika Tomaszewska have been especially helpful.

---

activeCat	<i>Active category</i>
-----------	------------------------

---

## Description

Get or set the active category of a multi-categorical SpatRaster layer

## Usage

```
## S4 method for signature 'SpatRaster'
activeCat(x, layer=1)
## S4 replacement method for signature 'SpatRaster'
activeCat(x, layer=1)<-value
```

## Arguments

x	SpatRaster
layer	positive integer, the layer number or name
value	a data.frame (ID, category)

## Value

integer

## See Also

[catalyze](#), [cats](#)

## Examples

```
set.seed(0)
r <- rast(nrows=10, ncols=10)
values(r) <- sample(3, ncell(r), replace=TRUE) + 10
d <- data.frame(id=11:13, cover=c("forest", "water", "urban"), letters=letters[1:3], value=10:12)
levels(r) <- d

activeCat(r)
activeCat(r) <- 3
activeCat(r)
```

---

add	<i>Add (in place) a SpatRaster to another SpatRaster object</i>
-----	---

---

**Description**

Add (in place) a SpatRaster to another SpatRaster object. Comparable with [c](#), but without copying the object.

**Usage**

```
## S4 replacement method for signature 'SpatRaster,SpatRaster'
add(x)<-value
```

**Arguments**

x	SpatRaster
value	SpatRaster

**Value**

SpatRaster

**See Also**

[c](#)

**Examples**

```
r <- rast(nrows=5, ncols=9, vals=1:45)
x <- c(r, r*2)
add(x) <- r*3
x
```

---

adjacent	<i>Adjacent cells</i>
----------	-----------------------

---

**Description**

Identify cells that are adjacent to a set of raster cells. Or identify adjacent polygons

**Usage**

```
## S4 method for signature 'SpatRaster'
adjacent(x, cells, directions="rook", pairs=FALSE, include=FALSE)

## S4 method for signature 'SpatVector'
adjacent(x, type="rook", pairs=TRUE, symmetrical=FALSE)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>cells</code>	vector of cell numbers for which adjacent cells should be found. Cell numbers start with 1 in the upper-left corner and increase from left to right and from top to bottom
<code>directions</code>	character or matrix to indicated the directions in which cells are considered connected. The following character values are allowed: "rook" or "4" for the horizontal and vertical neighbors; "bishop" to get the diagonal neighbors; "queen" or "8" to get the vertical, horizontal and diagonal neighbors; or "16" for knight and one-cell queen move neighbors. If <code>directions</code> is a matrix it should have odd dimensions and have logical (or 0, 1) values
<code>pairs</code>	logical. If TRUE, a two-column matrix of pairs of adjacent cells is returned. If <code>x</code> is a <code>SpatRaster</code> and <code>pairs</code> is FALSE, an <code>n*m</code> matrix is returned where the number of rows <code>n</code> is <code>length(cells)</code> and the number of columns <code>m</code> is the number of neighbors requested with <code>directions</code>
<code>include</code>	logical. Should the focal cells be included in the result?
<code>type</code>	character. One of "rook", "queen", "touches", or "intersects". "queen" and "touches" are synonyms. "rook" exclude polygons that touch at a single node only. "intersects" includes polygons that touch or overlap
<code>symmetrical</code>	logical. If TRUE, an adjacent pair is only included once. For example, if polygon 1 is adjacent to polygon 3, the implied adjacency between 3 and 1 is not reported

**Value**

matrix

**See Also**

[relate](#), [nearby](#)

**Examples**

```
r <- rast(nrows=10, ncols=10)
adjacent(r, cells=c(1, 5, 55), directions="queen")
r <- rast(nrows=10, ncols=10, crs="+proj=utm +zone=1 +datum=WGS84")
adjacent(r, cells=11, directions="rook")

#same as
rk <- matrix(c(0,1,0,1,0,1,0,1,0), 3, 3)
adjacent(r, cells=11, directions=rk)

## note that with global lat/lon data the E and W connect
r <- rast(nrows=10, ncols=10, crs="+proj=longlat +datum=WGS84")
adjacent(r, cells=11, directions="rook")

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
a <- adjacent(v, symmetrical=TRUE)
head(a)
```

---

 aggregate

---

*Aggregate raster or vector data*


---

## Description

Aggregate a SpatRaster to create a new SpatRaster with a lower resolution (larger cells). Aggregation groups rectangular areas to create larger cells. The value for the resulting cells is computed with a user-specified function.

Or aggregate ("dissolve") a SpatVector.

## Usage

```
## S4 method for signature 'SpatRaster'
aggregate(x, fact=2, fun="mean", ..., cores=1, filename="", overwrite=FALSE, wopt=list())

## S4 method for signature 'SpatVector'
aggregate(x, by=NULL, dissolve=TRUE, fun="mean", count=TRUE, ...)
```

## Arguments

x	SpatRaster
fact	positive integer. Aggregation factor expressed as number of cells in each direction (horizontally and vertically). Or two integers (horizontal and vertical aggregation factor) or three integers (when also aggregating over layers)
fun	function used to aggregate values. Either an actual function, or for the following, their name: "mean", "max", "min", "median", "sum" and "modal"
...	additional arguments passed to fun, such as na.rm=TRUE
cores	positive integer. If cores > 1, a 'parallel' package cluster with that many cores is created. Ignored for C++ level implemented functions "mean", "max", "min", "median", "sum" and "modal"
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>
by	character. The variable used to aggregate the geometries
dissolve	logical. Should borders between aggregated geometries be dissolved?
count	logical. If TRUE and by is not NULL, a variable "agg_n" is included that shows the number of input geometries for each output geometry

## Details

Aggregation starts at the upper-left end of a SpatRaster. If a division of the number of columns or rows with factor does not return an integer, the extent of the resulting SpatRaster will be somewhat larger than that of the original SpatRaster. For example, if an input SpatRaster has 100 columns, and

fact=12, the output `SpatRaster` will have 9 columns and the maximum x coordinate of the output `SpatRaster` is also adjusted.

The function `fun` should take multiple numbers, and return a single number. For example `mean`, `modal`, `min` or `max`.

It should also accept a `na.rm` argument (or ignore it as one of the 'dots' arguments).

### Value

`SpatRaster`

### See Also

[disagg](#) to disaggregate

### Examples

```
r <- rast()
# aggregated SpatRaster, no values
ra <- aggregate(r, fact=10)

values(r) <- runif(ncell(r))
# aggregated raster, max of the values
ra <- aggregate(r, fact=10, fun=max)

# multiple layers
s <- c(r, r*2)
x <- aggregate(s, 20)

## SpatVector
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
va <- aggregate(v, "ID_1")

plot(va, "NAME_1", lwd=5, plg=list(x="topright"), mar=rep(2,4))
lines(v, lwd=3, col="light gray")
lines(va)
text(v, "ID_1", halo=TRUE)
```

---

align

Align a *SpatExtent*


---

### Description

Align an `SpatExtent` with a `SpatRaster`. This can be useful to create a new `SpatRaster` with the same origin and resolution as an existing `SpatRaster`. Do not use this to force data to match that really does not match (use e.g. [resample](#) or [\(dis\)aggregate](#) for this).

It is also possible to align a `SpatExtent` to a clean divisor.

Usage

```
## S4 method for signature 'SpatExtent,SpatRaster'  
align(x, y, snap="near")  
  
## S4 method for signature 'SpatExtent,numeric'  
align(x, y)
```

Arguments

x	SpatExtent
y	SpatRaster or numeric
snap	Character. One of "near", "in", or "out", to determine in which direction the extent should be aligned. To the nearest border, inwards or outwards

Value

SpatExtent

See Also

[ext](#), [draw](#)

Examples

```
r <- rast()  
e <- ext(-10.1, 9.9, -20.1, 19.9)  
ea <- align(e, r)  
e  
ext(r)  
ea  
  
align(e, 0.5)
```

---

all.equal	<i>Compare two SpatRasters for equality</i>
-----------	---

---

Description

Compare two SpatRasters for (near) equality.  
First the attributes of the objects are compared. If these are the same, a (perhaps small) sample of the raster cells is compared as well.  
The sample size used can be increased with the maxcell argument. You can set it to Inf, but for large rasters your computer may not have sufficient memory. See the examples for a safe way to compare all values.



**Usage**

```
## S4 method for signature 'SpatRaster,SpatRaster'  
all.equal(target, current, maxcell=10000, ...)
```

**Arguments**

target	SpatRaster
current	SpatRaster
maxcell	positive integer. The size of the regular sample used to compare cell values
...	additional arguments passed to all.equal.numeric to compare cell values

**Value**

Either TRUE or a character vector describing the differences between target and current.

**See Also**

[compareGeom](#)

**Examples**

```
x <- sqrt(1:100)  
mat <- matrix(x, 10, 10)  
r1 <- rast(nrows=10, ncols=10, xmin=0, vals = x)  
r2 <- rast(nrows=10, ncols=10, xmin=0, vals = mat)  
  
all.equal(r1, r2)  
all.equal(r1, r1*1)  
all.equal(rast(r1), rast(r2))  
  
# compare geometries  
compareGeom(r1, r2)  
  
# Compare all cell values for near equality  
# as floating point number imprecision can be a problem  
m <- minmax(r1 - r2)  
all(abs(m) < 1e-7)  
  
# comparison of cell values to create new SpatRaster  
e <- r1 == r2
```

---

animate

*Animate a SpatRaster*

---

**Description**

Animate (sequentially plot) the layers of a SpatRaster to create a movie.

This does not work with R-Studio.

**Usage**

```
## S4 method for signature 'SpatRaster'
animate(x, pause=0.25, main, range, maxcell=50000, n=1, ...)
```

**Arguments**

x	SpatRaster
pause	numeric. How long should be the pause be between layers?
main	title for each layer. If not supplied the z-value is used if available. Otherwise the names are used.
range	numeric vector of length 2. Range of values to plot
maxcell	integer > 0. Maximum number of cells to use for the plot. If maxcell < ncell(x), spatSample(type="regular") is used before plotting
n	integer > 0. Number of loops
...	Additional arguments passed to <a href="#">plot</a>

**Value**

None

**See Also**

[plot](#)

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra"))
animate(s, n=1)
```

---

app

---

*Apply a function to the cells of a SpatRaster*


---

**Description**

Apply a function to the values of each cell of a SpatRaster. Similar to [apply](#) – think of each layer in a SpatRaster as a column (or row) in a matrix.

This is generally used to summarize the values of multiple layers into one layer; but this is not required.

app calls function fun with the raster data as first argument. Depending on the function supplied, the raster data is represented as either a matrix in which each layer is a column, or a vector representing a cell. The function should return a vector or matrix that is divisible by ncell(x). Thus, both "sum" and "rowSums" can be used, but "colSums" cannot be used.

You can also apply a function fun across datasets by layer of a SpatRasterDataset. In that case, summarization is by layer across SpatRasters.

**Usage**

```
## S4 method for signature 'SpatRaster'
app(x, fun, ..., cores=1, filename="", overwrite=FALSE, wopt=list())

## S4 method for signature 'SpatRasterDataset'
app(x, fun, ..., cores=1, filename="", overwrite=FALSE, wopt=list())
```

**Arguments**

x	SpatRaster or SpatRasterDataset
fun	a function that operates on a vector or matrix. This can be a function that is defined in base-R or in a package, or a function you write yourself (see examples). Functions that return complex output (e.g. a list) may need to be wrapped in your own function to simplify the output to a vector or matrix. The following functions have been re-implemented in C++ for speed: "sum", "mean", "median", "modal", "which", "which.min", "which.max", "min", "max", "prod", "any", "all", "sd", "std", "first". To use the base-R function for say, "min", you could use something like fun=function(i) min(i) or the equivalent fun = \ (i) min(i)
...	additional arguments for fun. These are typically numerical constants. They should <i>never</i> be another SpatRaster
cores	positive integer. If cores > 1, a 'parallel' package cluster with that many cores is created and used. You can also supply a cluster object. Ignored for functions that are implemented by terra in C++ (see under fun)
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Details**

To speed things up, parallelization is supported, but this is often not helpful, and it may actually be slower. There is only a speed gain if you have many cores (> 8) and/or a very complex (slow) function fun. If you write fun yourself, consider supplying a cppFunction made with the Rcpp package instead (or go have a cup of tea while the computer works for you).

**Value**

SpatRaster

**See Also**

[lapp](#), [tapp](#), [Math-methods](#)

**Examples**

```
r <- rast(ncols=10, nrows=10)
values(r) <- 1:ncell(r)
x <- c(r, sqrt(r), r+50)
```

```

s <- app(x, fun=sum)
s
# for a few generic functions like
# "sum", "mean", and "max" you can also do
sum(x)

## SpatRasterDataset
sd <- sds(x, x*2, x/3)
a <- app(sd, max)
a
# same as
max(x, x*2, x/3)
# and as (but slower)
b <- app(sd, \(i) max(i))

## also works for a single layer
f <- function(i) (i+1) * 2 * i + sqrt(i)
s <- app(r, f)
# same as above, but that is not memory-safe
# and has no filename argument
s <- f(r)

## Not run:
#### multiple cores
test0 <- app(x, sqrt)
test1 <- app(x, sqrt, cores=2)

testfun <- function(i) { 2 * sqrt(i) }
test2 <- app(x, fun=testfun, cores =2)

## this fails because testfun is not exported to the nodes
# test3 <- app(x, fun=function(i) testfun(i), cores=2)
## to export it, add it as argument to fun
test3 <- app(x, fun=function(i, ff) ff(i), cores =3, ff=testfun)

## End(Not run)

```

---

approximate

*Estimate values for cell values that are NA by interpolating between layers*


---

## Description

approximate uses the stats function [approx](#) to estimate values for cells that are NA by interpolation across layers. Layers are considered equidistant, unless argument `z` is used, or `time(x)` returns values that are not NA, in which case these values are used to determine distance between layers.

For estimation based on neighboring cells see [focal](#)

**Usage**

```
## S4 method for signature 'SpatRaster'
approximate(x, method="linear", yleft, yright,
            rule=1, f=0, ties=mean, z=NULL, NArule=1,filename="", ...)
```

**Arguments**

x	SpatRaster
method	specifies the interpolation method to be used. Choices are "linear" or "constant" (step function; see the example in <a href="#">approx</a>
yleft	the value to be returned before a non-NA value is encountered. The default is defined by the value of rule given below
yright	the value to be returned after the last non-NA value is encountered. The default is defined by the value of rule given below
rule	an integer (of length 1 or 2) describing how interpolation is to take place at for the first and last cells (before or after any non-NA values are encountered). If rule is 1 then NAs are returned for such points and if it is 2, the value at the closest data extreme is used. Use, e.g., rule = 2:1, if the left and right side extrapolation should differ
f	for method = "constant" a number between 0 and 1 inclusive, indicating a compromise between left- and right-continuous step functions. If y0 and y1 are the values to the left and right of the point then the value is $y_0 \cdot (1-f) + y_1 \cdot f$ so that $f = 0$ is right-continuous and $f = 1$ is left-continuous
ties	Handling of tied 'z' values. Either a function with a single vector argument returning a single number result or the string "ordered"
z	numeric vector to indicate the distance between layers (e.g., depth). The default is time(x) if these are not NA or else 1:nlys(x)
NArule	single integer used to determine what to do when only a single layer with a non-NA value is encountered (and linear interpolation is not possible). The default value of 1 indicates that all layers will get this value for that cell; all other values do not change the cell values
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[focal](#), [fillTime](#)

**Examples**

```

r <- rast(ncols=5, nrows=5)
r1 <- setValues(r, runif(ncell(r)))
r2 <- setValues(r, runif(ncell(r)))
r3 <- setValues(r, runif(ncell(r)))
r4 <- setValues(r, runif(ncell(r)))
r5 <- setValues(r, NA)
r6 <- setValues(r, runif(ncell(r)))
r1[6:10] <- NA
r2[5:15] <- NA
r3[8:25] <- NA
s <- c(r1,r2,r3,r4,r5,r6)
s[1:5] <- NA
x1 <- approximate(s)
x2 <- approximate(s, rule=2)
x3 <- approximate(s, rule=2, z=c(1,2,3,5,14,15))

```

Arith-methods

*Arithmetic***Description**

Standard arithmetic operators for computations with SpatRasters. Computations are local (applied on a cell by cell basis). If multiple SpatRaster objects are used, these must have the same geometry (extent and resolution). These operators have been implemented:

`+`, `-`, `*`, `/`, `^`, `%%`, `%/%`

The following methods have been implemented for SpatExtent:

for (SpatExtent, SpatExtent): `+`, `-`, and for (SpatExtent, numeric): `+`, `-`, `*`, `/`, `%%`

**Value**

SpatRaster or SpatExtent

**See Also**

[ifel](#) to conveniently combine operations and [Math-methods](#) or [app](#) to use mathematical functions not implemented by the package.

**Examples**

```

r1 <- rast(ncols=10, nrows=10)
v <- runif(ncell(r1))
v[10:20] <- NA
values(r1) <- v
r2 <- rast(r1)
values(r2) <- 1:ncell(r2) / ncell(r2)
r3 <- r1 + r2

```

```

r2 <- r1 / 10
r3 <- r1 * (r2 - 1 / r2)

b <- c(r1, r2, r3)
b2 <- b * 10

### SpatExtent methods
x <- ext(0.1, 2.2, 0, 3)
y <- ext(-2, 1, -2,2)
# union
x + y
# intersection
x * y

e <- x
e
e * 2
e / 2
e + 1
e - 1

```

as.character

*Create a text representation of (the skeleton of) an object***Description**

Create a text representation of (the skeleton of) an object

**Usage**

```

## S4 method for signature 'SpatExtent'
as.character(x)

## S4 method for signature 'SpatRaster'
as.character(x)

```

**Arguments**

x                      SpatRaster

**Value**

character

**Examples**

```

r <- rast()
ext(r)
ext(c(0, 20, 0, 20))

```

---

as.data.frame	<i>SpatRaster or SpatVector to data.frame</i>
---------------	---

---

## Description

Coerce a SpatRaster or SpatVector to a data.frame

## Usage

```
## S4 method for signature 'SpatVector'
as.data.frame(x, row.names=NULL, optional=FALSE, geom=NULL, ...)

## S4 method for signature 'SpatRaster'
as.data.frame(x, row.names=NULL, optional=FALSE, xy=FALSE, cells=FALSE, na.rm=NA, ...)
```

## Arguments

x	SpatRaster or SpatVector
geom	character or NULL. If not NULL, either "WKT" or "HEX", to get the geometry included in Well-Known-Text or hexadecimal notation. If x has point geometry, it can also be "XY" to add the coordinates of each point
xy	logical. If TRUE, the coordinates of each raster cell are included
cells	logical. If TRUE, the cell numbers of each raster cell are included
na.rm	logical. If TRUE, cells that have a NA value in at least one layer are removed. If the argument is set to NA only cells that have NA values in all layers are removed
...	Additional arguments passed to the <a href="#">data.frame</a>
row.names	This argument is ignored
optional	This argument is ignored

## Value

data.frame

## See Also

[as.list](#), [as.matrix](#). See [geom](#) to only extract the geometry of a SpatVector

## Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
as.data.frame(v)
```



---

as.list	<i>SpatRaster* or SpatVector to list</i>
---------	--

---

### Description

Coerce a `SpatRaster`, `SpatRasterCollection`, `SpatRasterDataset`, or `SpatVector` to a list. With a `SpatRaster`, each layer becomes a list element. With a `SpatRasterCollection` or `SpatRasterDataset`, each `SpatRaster` becomes a list element. With a `SpatVector`, each variable (attribute) becomes a list element.

### Usage

```
## S4 method for signature 'SpatRaster'
as.list(x, ...)

## S4 method for signature 'SpatRasterCollection'
as.list(x, ...)

## S4 method for signature 'SpatVector'
as.list(x, geom=NULL, ...)
```

### Arguments

<code>x</code>	<code>SpatRaster</code> , <code>SpatRasterDataset</code> , <code>SpatRasterCollection</code> , or <code>SpatVector</code>
<code>geom</code>	character or <code>NULL</code> . If not <code>NULL</code> , either "WKT" or "HEX", to get the geometry included in Well-Known-Text or hexadecimal notation. If <code>x</code> has point geometry, it can also be "XY" to add the coordinates of each point
<code>...</code>	Additional arguments. These are ignored

### Value

list

### See Also

see [coerce](#) for `as.data.frame` with a `SpatRaster`; and [geom](#) to only extract the geometry of a `SpatVector`

### Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
as.list(v)

s <- rast(system.file("ex/logo.tif", package="terra")) + 1
as.list(s)
```

---

as.raster	<i>Coerce to a "raster" object</i>
-----------	------------------------------------

---

**Description**

Implementation of the generic `as.raster` function to create a "raster" (small r) object. Such objects can be used for plotting with the `rasterImage` function. NOT TO BE CONFUSED with the Raster\* (big R) objects defined by the 'raster' package!

**Usage**

```
## S4 method for signature 'SpatRaster'
as.raster(x, maxcell=500000, col)
```

**Arguments**

- x                   SpatRaster
- maxcell           positive integer. Maximum number of cells to use for the plot
- col                vector of colors. Default is col=rev(terrain.colors(255)))

**Value**

'raster' object

**Examples**

```
r <- rast(ncols=3, nrows=3)
values(r) <- 1:ncell(r)
as.raster(r)
```

---

as.spatvector	<i>Conversion to a SpatVector, or to another SpatVector type</i>
---------------	--

---

**Description**

Conversion of a SpatRaster or SpatExtent to a SpatVector of points, lines, or polygons;  
And conversion of a SpatVector to a another SpatVector type.

**Usage**

```
## S4 method for signature 'SpatRaster'
as.polygons(x, trunc=TRUE, dissolve=TRUE, values=TRUE,
na.rm=TRUE, na.all=FALSE, extent=FALSE)
```

```
## S4 method for signature 'SpatRaster'
as.lines(x)
```

```
## S4 method for signature 'SpatRaster'
as.points(x, values=TRUE, na.rm=TRUE, na.all=FALSE)
```

```
## S4 method for signature 'SpatVector'
as.polygons(x, extent=FALSE)
```

```
## S4 method for signature 'SpatVector'
as.lines(x)
```

```
## S4 method for signature 'SpatVector'
as.points(x, multi=FALSE, skiplast=TRUE)
```

```
## S4 method for signature 'SpatExtent'
as.polygons(x, crs="")
```

```
## S4 method for signature 'SpatExtent'
as.lines(x, crs="")
```

```
## S4 method for signature 'SpatExtent'
as.points(x, crs="")
```

**Arguments**

x	SpatRaster or SpatVector
trunc	logical; truncate values to integers. Cells with the same value are merged. Therefore, if trunc=FALSE the object returned can have many cells and can be very large
dissolve	logical; combine cells with the same values? If TRUE only the first layer in x is processed
values	logical; include cell values as attributes?
multi	logical. If TRUE a multi-point geometry is returned
skiplast	logical. If TRUE the last point of a polygon (which is the same as the first point) is not included
extent	logical. if TRUE, a polygon for the extent of the SpatRaster or SpatVector is returned. If x is a SpatRaster, the polygon has vertices for each row and column, not just the four corners of the raster. This can be useful for more precise projection. If that is not required, it is more efficient to get the extent represented by only the four corners with <code>as.polygons(ext(x), crs=crs(x))</code>

<code>na.rm</code>	logical. If TRUE cells that are NA are ignored
<code>na.all</code>	logical. If TRUE cells are only ignored if <code>na.rm=TRUE</code> and their value is NA for <b>all</b> layers instead of for any layer
<code>crs</code>	character. The coordinate reference system (see <a href="#">crs</a> )

## Value

SpatVector

## Examples

```
r <- rast(ncols=2, nrows=2)
values(r) <- 1:ncell(r)

as.points(r)
as.lines(ext(r), crs=crs(r))

if (gdal() >= "3.0.0") {
  p <- as.polygons(r)
  p
  as.lines(p)
  as.points(p)
}
```

---

atan2

*Two argument arc-tangent*

---

## Description

For SpatRasters `x` and `y`, `atan2(y, x)` returns the angle in radians for the tangent `y/x`, handling the case when `x` is zero. See [Trig](#)

See [Math-methods](#) for other trigonometric and mathematical functions that can be used with SpatRasters.

## Usage

```
## S4 method for signature 'SpatRaster,SpatRaster'
atan2(y, x)

## S4 method for signature 'SpatRaster,SpatRaster'
atan_2(y, x, filename, ...)
```

## Arguments

<code>y</code>	SpatRaster
<code>x</code>	SpatRaster
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

See Also

[Math-methods](#)

Examples

```
r1 <- rast(nrows=10, ncols=10)
r2 <- rast(nrows=10, ncols=10)
values(r1) <- (runif(ncell(r1))-0.5) * 10
values(r2) <- (runif(ncell(r1))-0.5) * 10
atan2(r1, r2)
```

---

autocorrelation	<i>Spatial autocorrelation</i>
-----------------	--------------------------------

---

Description

Compute spatial autocorrelation for a numeric vector or a SpatRaster. You can compute standard (global) Moran's I or Geary's C, or local indicators of spatial autocorrelation (Anselin, 1995).

Usage

```
## S4 method for signature 'numeric'
autocor(x, w, method="moran")

## S4 method for signature 'SpatRaster'
autocor(x, w=matrix(c(1,1,1,1,0,1,1,1,1),3), method="moran", global=TRUE)
```

Arguments

x	numeric or SpatRaster
w	Spatial weights defined by or a rectangular matrix. For a SpatRaster this matrix must the sides must have an odd length (3, 5, ...)
global	logical. If TRUE global autocorrelation is computed instead of local autocorrelation
method	character. If x is numeric or SpatRaster: "moran" for Moran's I and "geary" for Geary's C. If x is numeric also: "Gi", "Gi*" (the Getis-Ord statistics), locmor (local Moran's I) and "mean" (local mean)

Details

The default setting uses a 3x3 neighborhood to compute "Queen's case" indices. You can use a filter (weights matrix) to do other things, such as "Rook's case", or different lags.

Value

numeric or SpatRaster

## References

- Moran, P.A.P., 1950. Notes on continuous stochastic phenomena. *Biometrika* 37:17-23
- Geary, R.C., 1954. The contiguity ratio and statistical mapping. *The Incorporated Statistician* 5: 115-145
- Anselin, L., 1995. Local indicators of spatial association-LISA. *Geographical Analysis* 27:93-115  
[https://en.wikipedia.org/wiki/Indicators\\_of\\_spatial\\_association](https://en.wikipedia.org/wiki/Indicators_of_spatial_association)

## See Also

The `spdep` package for additional and more general approaches for computing spatial autocorrelation

## Examples

```
### raster
r <- rast(nrows=10, ncols=10, xmin=0)
values(r) <- 1:ncell(r)

autocor(r)

# rook's case neighbors
f <- matrix(c(0,1,0,1,0,1,0,1,0,1,0), nrow=3)
autocor(r, f)

# local
rc <- autocor(r, w=f, global=FALSE)

### numeric (for vector data)
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
w <- relate(v, relation="touches")

# global
autocor(v$AREA, w)

# local
v$Gi <- autocor(v$AREA, w, "Gi")
plot(v, "Gi")
```

---

barplot

*Bar plot of a SpatRaster*


---

## Description

Create a barplot of the values of a the first layer of a `SpatRaster`. For large datasets a regular sample with a size of approximately `maxcells` is used.

**Usage**

```
## S4 method for signature 'SpatRaster'
barplot(height, maxcell=1000000, digits=0, breaks=NULL, col, ...)
```

**Arguments**

height	SpatRaster
maxcell	integer. To regularly subsample very large datasets
digits	integer used to determine how to <a href="#">round</a> the values before tabulating. Set to NULL or to a large number if you do not want any rounding
breaks	breaks used to group the data as in <a href="#">cut</a>
col	a color generating function such as <a href="#">rainbow</a> (the default), or a vector of colors
...	additional arguments for plotting as in <a href="#">barplot</a>

**Value**

A numeric vector (or matrix, when `beside = TRUE`) of the coordinates of the bar midpoints, useful for adding to the graph. See [barplot](#)

**See Also**

[hist](#), [boxplot](#)

**Examples**

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
barplot(r, digits=-1, las=2, ylab="Frequency")

op <- par(no.readonly = TRUE)
par(mai = c(1, 2, .5, .5))
barplot(r, breaks=10, col=c("red", "blue"), horiz=TRUE, digits=NULL, las=1)
par(op)
```

---

boundaries	<i>Detect boundaries (edges)</i>
------------	----------------------------------

---

**Description**

Detect boundaries (edges). Boundaries are cells that have more than one class in the 4 or 8 cells surrounding it, or, if `classes=FALSE`, cells with values and cells with NA.

**Usage**

```
## S4 method for signature 'SpatRaster'
boundaries(x, classes=FALSE, inner=TRUE,
           directions=8, falseval=0, filename="", ...)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>inner</code>	logical. If TRUE, "inner" boundaries are returned, else "outer" boundaries are returned
<code>classes</code>	character. Logical. If TRUE all different values are (after rounding) distinguished, as well as NA. If FALSE (the default) only edges between NA and non-NA cells are considered
<code>directions</code>	integer. Which cells are considered adjacent? Should be 8 (Queen's case) or 4 (Rook's case)
<code>falseval</code>	numeric. The value to use for cells that are not a boundary and not NA
<code>filename</code>	character. Output filename
<code>...</code>	options for writing files as in <a href="#">writeRaster</a>

**Value**

`SpatRaster`. Cell values are either 1 (a border) or 0 (not a border), or NA

**See Also**

[focal](#), [patches](#)

**Examples**

```
r <- rast(nrows=18, ncols=36, xmin=0)
r[150:250] <- 1
r[251:450] <- 2
bi <- boundaries(r)
bo <- boundaries(r, inner=FALSE)
bc <- boundaries(r, classes=TRUE)
#plot(bc)
```

---

boxplot

*Box plot of SpatRaster data*

---

**Description**

Box plot of layers in a `SpatRaster`

**Usage**

```
## S4 method for signature 'SpatRaster'
boxplot(x, y=NULL, maxcell=100000, ...)
```



**Arguments**

<code>x</code>	SpatRaster
<code>y</code>	NULL or a SpatRaster. If <code>x</code> is a SpatRaster it used to group the values of <code>x</code> by "zone"
<code>maxcell</code>	Integer. Number of cells to sample from datasets
<code>...</code>	additional arguments passed to <code>graphics::boxplot</code>

**Value**

`boxplot` returns a list (invisibly) that can be used with `bxp`

**See Also**

`pairs`, `hist`

**Examples**

```

r1 <- r2 <- r3 <- rast(ncols=10, nrows=10)
set.seed(409)
values(r1) <- rnorm(ncell(r1), 100, 40)
values(r2) <- rnorm(ncell(r1), 80, 10)
values(r3) <- rnorm(ncell(r1), 120, 30)
s <- c(r1, r2, r3)
names(s) <- c("Apple", "Pear", "Cherry")

boxplot(s, notch=TRUE, col=c("red", "blue", "orange"), main="Box plot", ylab="random", las=1)

op <- par(no.readonly = TRUE)
par(mar=c(4,6,2,2))
boxplot(s, horizontal=TRUE, col="lightskyblue", axes=FALSE)
axis(1)
axis(2, at=0:3, labels=c("", names(s)), las=1, cex.axis=.9, lty=0)
par(op)

## boxplot with 2 layers
v <- vect(system.file("ex/lux.shp", package="terra"))
r <- rast(system.file("ex/elev.tif", package="terra"))
y <- rasterize(v, r, "NAME_2")
b <- boxplot(r, y)
bxp(b)

```

**Description**

Calculate a buffer around all cells that are not NA in a `SpatRaster`, or around the geometries of a `SpatVector`

Note that the distance unit of the buffer width parameter is meters if the CRS is (+proj=longlat), and in map units (typically also meters) if not.

**Usage**

```
## S4 method for signature 'SpatRaster'
buffer(x, width, background=0, filename="", ...)
```

```
## S4 method for signature 'SpatVector'
buffer(x, width, quadsegs=10)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>width</code>	numeric. Unit is meter if <code>x</code> has a longitude/latitude CRS, or mapunits in other cases. Should be $> 0$ for <code>SpatRaster</code>
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>
<code>background</code>	numeric. value to assign to cells outside the buffer. If this value is zero or FALSE, a boolean <code>SpatRaster</code> is returned
<code>quadsegs</code>	positive integer. Number of line segments to use to draw a quart circle

**Value**

Same as `x` (`SpatRaster` or `SpatVector`). For `SpatRaster`: cells inside the buffers have the value 1.

**See Also**

[distance](#)

**Examples**

```
r <- rast(ncols=36, nrows=18)
r[500] <- 1
b <- buffer(r, width=5000000)
plot(b)

v <- vect(rbind(c(10,10), c(0,60)), crs="+proj=merc")
b <- buffer(v, 20)
plot(b)
points(v)

crs(v) <- "+proj=longlat"
b <- buffer(v, 1500000)
plot(b)
points(v)
```

**Description**

With `c` you can:

- Combine `SpatRaster` objects. They must have the same extent and resolution. However, if `x` is empty (has no cell values), its geometry is ignored with a warning. Two empty `SpatRasters` with the same geometry can also be combined (to get a summed number of layers). Also see [add<-](#)
  - Add a `SpatRaster` to a `SpatRasterDataset`
  - Add `SpatVector` objects to a new or existing `SpatVectorCollection`
- To append `SpatVectors`, use `rbind`.

**Usage**

```
## S4 method for signature 'SpatRaster'
c(x, ..., warn=TRUE)

## S4 method for signature 'SpatRasterDataset'
c(x, ...)

## S4 method for signature 'SpatVector'
c(x, ...)

## S4 method for signature 'SpatVectorCollection'
c(x, ...)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> , <code>SpatVector</code> , <code>SpatRasterDataset</code> or <code>SpatVectorCollection</code>
<code>warn</code>	logical. If <code>TRUE</code> , a warning is emitted if <code>x</code> is an empty <code>SpatRaster</code>
<code>...</code>	as for <code>x</code> (you can only combine raster with raster data and vector with vector data)

**Value**

Same class as `x`

**See Also**

[add<-](#)

**Examples**

```
r <- rast(nrows=5, ncols=9)
values(r) <- 1:ncell(r)
x <- c(r, r*2, r*3)
```

---

cartogram	<i>Cartogram</i>
-----------	------------------

---

**Description**

Make a cartogram, that is, a map where the area of polygons is made proportional to another variable. This can be a good way to map raw count data (e.g. votes).

**Usage**

```
## S4 method for signature 'SpatVector'
cartogram(x, var, type)
```

**Arguments**

- x                    SpatVector
- var                  character. A variable name in x
- type                character. Cartogram type, only "nc" (non-contiguous) is currently supported

**Value**

SpatVector

**See Also**

[plot](#), [rescale](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
v$value <- 1:12
p <- cartogram(v, "value", "nc")
plot(v, col="light gray", border="gray")
lines(p, col="red", lwd=2)
```

---

catalyze	<i>Factors to numeric</i>
----------	---------------------------

---

**Description**

Change a categorical layer into one or more numerical layers. With `as.numeric` you can transfer the active category values to cell values in a non-categorical SpatRaster. `catalyze` creates new layers for each category.

Usage

```
## S4 method for signature 'SpatRaster'
as.numeric(x, index=NULL, filename="", ...)

## S4 method for signature 'SpatRaster'
catalyze(x, filename="", ...)
```

Arguments

x	SpatRaster
index	positive integer, indicating the column in data.frame value to be used as the category, skipping the first column with the ID. If NULL the active category is used
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

Value

SpatRaster

See Also

[activeCat](#), [cats](#)

Examples

```
set.seed(0)
r <- rast(nrows=10, ncols=10)
values(r) <- sample(3, ncell(r), replace=TRUE) + 10
d <- data.frame(id=11:13, cover=c("forest", "water", "urban"), letters=letters[1:3], value=10:12)
levels(r) <- d
catalyze(r)

activeCat(r) <- 3
as.numeric(r)
```

---

cells	<i>Get cell numbers</i>
-------	-------------------------

---

Description

Get the cell numbers covered by a SpatVector or SpatExtent. Or that match values in a vector; or all non NA values.

**Usage**

```
## S4 method for signature 'SpatRaster,missing'
cells(x, y)

## S4 method for signature 'SpatRaster,numeric'
cells(x, y)

## S4 method for signature 'SpatRaster,SpatVector'
cells(x, y, method="simple", weights=FALSE, exact=FALSE, touches=is.lines(y))

## S4 method for signature 'SpatRaster,SpatExtent'
cells(x, y)
```

**Arguments**

x	SpatRaster
y	SpatVector, SpatExtent, 2-column matrix representing points, numeric representing values to match, or missing
method	character. Method for getting cell numbers for points. The default is "simple", the alternative is "bilinear". If it is "bilinear", the four nearest cells and their weights are returned
weights	logical. If TRUE and y has polygons, the approximate fraction of each cell that is covered is returned as well
exact	logical. If TRUE and y has polygons, the exact fraction of each cell that is covered is returned as well
touches	logical. If TRUE, values for all cells touched by lines or polygons are extracted, not just those on the line render path, or whose center point is within the polygon. Not relevant for points

**Value**

numeric vector or matrix

**Examples**

```
r <- rast(ncols=10, nrows=10)
values(r) <- 1:ncell(r)
r[c(1:25, 31:100)] <- NA
r <- ifel(r > 28, r + 10, r)

# all cell numbers of cells that are not NA
cells(r)

# cell numbers that match values
x <- cells(r, c(28,38))
x$lyr.1

# cells for points
```

```

m <- cbind(x=c(0,10,-30), y=c(40,-10,20))
cellFromXY(r, m)

v <- vect(m)
cells(r, v)
cells(r, v, method="bilinear")

# cells for polygons
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
r <- rast(v)
cv <- cells(r, v)

```

---

cellSize	<i>Area covered by each raster cell</i>
----------	---

---

## Description

Compute the area covered by individual raster cells. Computing the surface area of raster cells is particularly relevant for longitude/latitude rasters.

Note that for both angular (longitude/latitude) and for planar (projected) coordinate reference systems raster cells sizes are generally not constant, unless you are using an equal-area coordinate reference system.

For planar CRSs, the area is therefore not computed based on the linear units of the coordinate reference system, but on the *actual* area, correcting for distortion. If you do not want that, you can instead use `init(x, prod(res(x)))`

## Usage

```

## S4 method for signature 'SpatRaster'
cellSize(x, mask=TRUE, unit="m", transform=TRUE, rcx=100, filename="", ...)

```

## Arguments

x	SpatRaster
mask	logical. If TRUE, cells that are NA in x are also NA in the output
unit	character. One of "m", "km", or "ha"
transform	logical. If TRUE, planar CRS data are transformed to lon/lat for accuracy
rcx	positive integer. The maximum number of rows and columns to be used to compute area of planar data if transform=TRUE. If x has more rows and/or columns, the raster is aggregated to match this limit, and values for the original cells are estimated by bilinear interpolation (see <code>resample</code> ). This can save a lot of time
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

Value

numeric. The area of each cell, expressed in square meters, square kilometers, or hectares.

See Also

[expanse](#)

Examples

```
# SpatRaster
r <- rast(nrows=18, ncols=36)
v <- 1:ncell(r)
v[200:400] <- NA
values(r) <- v

# size of each raster cell
a <- cellSize(r)

# illustration of distortion
r <- rast(ncols=90, nrows=45, ymin=-80, ymax=80)
m <- project(r, "+proj=merc")

bad <- init(m, prod(res(m)) / 1000000, names="naive")
good <- cellSize(m, unit="km", names="corrected")
plot(c(good, bad), nc=1, mar=c(2,2,1,6))
```

---

centroids	<i>Centroids</i>
-----------	------------------

---

Description

Get the centroids of polygons or lines, or centroid-like points that are guaranteed to be inside the polygons or on the lines.

Usage

```
## S4 method for signature 'SpatVector'
centroids(x, inside=FALSE)
```

Arguments

x	SpatVector
inside	logical. If TRUE the points returned are guaranteed to be inside the polygons or on the lines, but they are not the true centroids. True centroids may be outside a polygon, for example when a polygon is "bean shaped", and they are unlikely to be on their line



**Value**

SpatVector of points

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
x <- centroids(v)
y <- centroids(v, TRUE)
```

---

clamp	<i>Clamp values</i>
-------	---------------------

---

**Description**

Clamp values to a minimum and maximum value. That is, all values below a lower threshold value and above the upper threshold value become either NA, or, if values=TRUE, become the threshold value

**Usage**

```
## S4 method for signature 'SpatRaster'
clamp(x, lower=-Inf, upper=Inf, values=TRUE, filename="", ...)

## S4 method for signature 'numeric'
clamp(x, lower=-Inf, upper=Inf, values=TRUE, ...)
```

**Arguments**

x	SpatRaster
lower	numeric. lowest value (you can specify a different value for each layer)
upper	numeric. highest value (you can specify a different value for each layer)
values	logical. If FALSE values outside the clamping range become NA, if TRUE, they get the extreme values
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[classify](#)

## Examples

```
r <- rast(ncols=10, nrows=10)
values(r) <- 1:ncell(r)
rc <- clamp(r, 25, 75)
rc
```

---

classify	<i>Classify (or reclassify) cell values</i>
----------	---

---

## Description

Classify values of a SpatRaster. The function (re-)classifies groups of values to other values.

The classification is done based on the argument `rcl`. You can classify ranges by specifying a three-column matrix "from-to-becomes" or change specific values by using a two-column matrix "is-becomes". You can also supply a vector with "cuts" or the "number of cuts".

With "from-to-becomes" or "is-becomes" classification is done in the row order of the matrix. Thus, if there are overlapping ranges or values, the first time a number is within a range determines the reclassification value.

With "cuts" the values are sorted, so that the order in which they are provided does not matter.

## Usage

```
## S4 method for signature 'SpatRaster'
classify(x, rcl, include.lowest=FALSE, right=TRUE,
         others=NULL, brackets=TRUE, filename="", ...)
```

## Arguments

<code>x</code>	SpatRaster
<code>rcl</code>	<p>matrix for classification. This matrix must have 1, 2 or 3 columns. If there are three columns, the first two columns are "from" "to" of the input values, and the third column "becomes" has the new value for that range.</p> <p>The two column matrix ("is", "becomes") can be useful for classifying integer values. In that case, the arguments <code>right</code> and <code>include.lowest</code> are ignored.</p> <p>A single column matrix (or a vector) is interpreted as a set of cuts if there is more than one value. In that case the values are classified based on their location in-between the cut-values.</p> <p>If a single number is provided, that is used to make that number of cuts, at equal intervals between the lowest and highest values of the SpatRaster.</p>
<code>include.lowest</code>	logical, indicating if a value equal to the lowest value in <code>rcl</code> (or highest value in the second column, for <code>right=FALSE</code> ) should be included.
<code>right</code>	<p>logical. If TRUE, the intervals are closed on the right (and open on the left). If FALSE they are open at the right and closed at the left. "open" means that the extreme value is <i>*not*</i> included in the interval. Thus, right-closed and left open is <math>(0, 1] = \{x \mid 0 &lt; x \leq 1\}</math>. You can also close both sides with <code>right=NA</code>, that</p>

	is only meaningful if you "from-to-becomes" classification with integers. For example to classify 1-5 -> 1, 6-10 -> 2, 11-15 -> 3. That may be easier to read and write than the equivalent 1-5 -> 1, 5-10 -> 2, 10-15 -> 3 with <code>right=TRUE</code> and <code>include.lowest=TRUE</code>
<code>others</code>	numeric. If not NULL all values that are not matched are set to this value. Otherwise they retain their original value.
<code>brackets</code>	logical. If TRUE, intervals are have parenthesis or brackets around them to indicate whether they are open or closed. Only applies if <code>rcl</code> is a vector (or single column matrix)
<code>filename</code>	character. Output filename
<code>...</code>	Additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Note**

`classify` works with the "raw" values of categorical rasters, ignoring the levels (labels, categories). To change the labels of categorical rasters, use [subst](#) instead.

For model-based classification see [predict](#)

**See Also**

[subst](#) for simpler from-to replacement

**Examples**

```
r <- rast(ncols=10, nrows=10)
values(r) <- (0:99)/99

## from-to-becomes
# classify the values into three groups
# all values >= 0 and <= 0.25 become 1, etc.
m <- c(0, 0.25, 1,
      0.25, 0.5, 2,
      0.5, 1, 3)
rclmat <- matrix(m, ncol=3, byrow=TRUE)
rc1 <- classify(r, rclmat, include.lowest=TRUE)

## cuts
# equivalent to the above, but now a categorical SpatRaster is returned
rc2 <- classify(r, c(0, 0.25, 0.5, 1), include.lowest=TRUE, brackets=TRUE)
freq(rc2)

## is-becomes
x <- round(r*3)
unique(x)
# replace 0 with NA
y <- classify(x, cbind(0, NA))
```

```

unique(y)

# multiple replacements
m <- rbind(c(2, 200), c(3, 300))
m

rcx1 <- classify(x, m)
unique(rcx1)

rcx2 <- classify(x, m, others=NA)
unique(rcx2)

```

---

click

*Query by clicking on a map*


---

## Description

Click on a map (plot) to get the coordinates or the values of a `SpatRaster` or `SpatVector` at that location. For a `SpatRaster` you can also get the coordinates and cell number of the location.

## Usage

```

## S4 method for signature 'SpatRaster'
click(x, n=10, id=FALSE, xy=FALSE, cell=FALSE, type="p", show=TRUE, ...)

## S4 method for signature 'SpatVector'
click(x, n=10, id=FALSE, xy=FALSE, type="p", show=TRUE, ...)

## S4 method for signature 'missing'
click(x, n=10, id=FALSE, type="p", show=TRUE, ...)

```

## Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code> , or missing
<code>n</code>	number of clicks on the plot (map)
<code>id</code>	logical. If TRUE, a numeric ID is shown on the map that corresponds to the row number of the output
<code>xy</code>	logical. If TRUE, xy coordinates are included in the output
<code>cell</code>	logical. If TRUE, cell numbers are included in the output
<code>type</code>	one of "n", "p", "l" or "o". If "p" or "o" the points are plotted; if "l" or "o" they are joined by lines. See <code>?locator</code>
<code>show</code>	logical. Print the values after each click?
<code>...</code>	additional graphics parameters used if type != "n" for plotting the locations. See <code>?locator</code>

**Value**

The value(s) of `x` at the point(s) clicked on (or touched by the box drawn). A `data.frame` with the value(s) of all layers of `SpatRaster` `x` for the cell(s) clicked on; or with the attributes of the geometries of `SpatVector` `x` that intersect with the box drawn).

**Note**

The plot only provides the coordinates for a spatial query, the values are read from the `SpatRaster` or `SpatVector` that is passed as an argument. Thus you can extract values from an object that has not been plotted, as long as it spatially overlaps with the extent of the plot.

Unless the process is terminated prematurely values at at most `n` positions are determined. The identification process can be terminated, depending on how you interact with R, by hitting `Esc`, or by clicking the right mouse button and selecting "Stop" from the menu, or from the "Stop" menu on the graphics window.

**See Also**

[draw](#)

**Examples**

```
## Not run:
r <-rast(system.file("ex/elev.tif", package="terra"))
plot(r)
click(r, n=1)
## now click on the plot (map)

## End(Not run)
```

---

coerce

---

*Coercion of a SpatRaster to a vector, matrix or array*


---

**Description**

Coercion to other object types

**Usage**

```
## S4 method for signature 'SpatRaster'
as.vector(x, mode='any')

## S4 method for signature 'SpatRaster'
as.matrix(x, wide=FALSE, ...)

## S4 method for signature 'SpatRaster'
as.array(x)
```

Arguments

x	SpatRaster or SpatVector
wide	logical. If FALSE each layer in the SpatRaster becomes a column in the matrix and each cell in the SpatRaster becomes a row. If TRUE each row in the SpatRaster becomes a row in the matrix and each column in the SpatRaster becomes a column in the matrix
mode	this argument is ignored
...	additional arguments (none implemented)

Value

vector, matrix, or array

See Also

[as.data.frame](#) and [as.polygons](#)

Examples

```
r <- rast(ncols=2, nrows=2)
values(r) <- 1:ncell(r)

as.vector(r)
as.matrix(r)
as.matrix(r, wide=TRUE)
as.data.frame(r, xy=TRUE)
as.array(r)
```

---

colors	<i>Color table</i>
--------	--------------------

---

Description

Get or set color table(s) associated with a SpatRaster. Color tables are used for associating colors with values, for use in mapping (plot).

Usage

```
## S4 method for signature 'SpatRaster'
coltab(x)

## S4 replacement method for signature 'SpatRaster'
coltab(x, layer=1)<-value

## S4 method for signature 'SpatRaster'
has.colors(x)
```

**Arguments**

x	SpatRaster
layer	positive integer, the layer number or name
value	a two-column data.frame (first column the cell value, the second column the color); a vector of colors (the first one is the color for value 0 and so on); or a three (red,green,blue) or four (alpha) column data.frame also from 0 to n; or NULL to remove the color table

**Value**

data.frame

**Examples**

```
r <- rast(ncols=3, nrows=2, vals=1:6)
coltb <- data.frame(value=1:6, col=rainbow(6, end=.9))
coltb

plot(r)

has.colors(r)
coltab(r) <- coltb
plot(r)
has.colors(r)

tb <- coltab(r)
class(tb)
dim(tb[[1]])
```

---

combineGeoms

*Combine geometries*

---

**Description**

Combine the geometries of one SpatVector with those of another. Geometries can be combined based on overlap, shared boundaries and distance (in that order of operation).

The typical use-case of this method is when you are editing geometries and you have a number of small polygons in one SpatVector that should be part of the geometries of the another SpatVector; perhaps because they were small holes inbetween the borders of two SpatVectors.

To append SpatVectors use 'rbind' and see methods like intersect and union for "normal" polygons combinations.

**Usage**

```
## S4 method for signature 'SpatVector,SpatVector'
combineGeoms(x, y, overlap=TRUE, boundary=TRUE, distance=TRUE,
append=TRUE, minover=0.1, maxdist=Inf, dissolve=TRUE, erase=TRUE)
```

**Arguments**

x	SpatVector of polygons
y	SpatVector of polygons geometries that are to be combined with x
overlap	logical. If TRUE, a geometry is combined with the geometry it has most overlap with, if the overlap is above minover
boundary	logical. If TRUE, a geometry is combined with the geometry it has most shared border with
distance	logical. If TRUE, a geometry is combined with the geometry it is nearest to
append	logical. Should remaining geometries be appended to the output? Not relevant if distance=TRUE
minover	numeric The fraction of the geometry in codey that overlaps with a geometry in x. Below this threshold, geometries are not considered overlapping
maxdist	numeric. Geometries further away from each other than this distance (in meters) will not be combined
dissolve	logical. Should internal boundaries be dissolved?
erase	logical. If TRUE no new overlapping areas are created

**Value**

SpatVector

**See Also**[union](#), [erase](#), [intersect](#)[sharedPaths](#), [erase](#), [intersect](#)**Examples**

```

x1 <- vect("POLYGON ((0 0, 8 0, 8 9, 0 9, 0 0))")
x2 <- vect("POLYGON ((10 4, 12 4, 12 7, 11 7, 11 6, 10 6, 10 4))")

y1 <- vect("POLYGON ((5 6, 15 6, 15 15, 5 15, 5 6))")
y2 <- vect("POLYGON ((8 2, 9 2, 9 3, 8 3, 8 2))")
y3 <- vect("POLYGON ((2 6, 3 6, 3 8, 2 8, 2 6))")
y4 <- vect("POLYGON ((2 12, 3 12, 3 13, 2 13, 2 12))")

x <- rbind(x1, x2)
values(x) <- data.frame(xid=1:2)
crs(x) <- "+proj=utm +zone=1"

y <- rbind(y1, y2, y3, y4)
values(y) <- data.frame(yid=letters[1:4])
crs(y) <- "+proj=utm +zone=1"

plot(rbind(x, y), border=c(rep("red",2), rep("blue", 4)), lwd=2)
text(x, "xid")
text(y, "yid")

```



```
v <- combineGeoms(x, y)
plot(v, col=c("red", "blue"))

v <- combineGeoms(x, y, boundary=FALSE, maxdist=1, minover=.05)
plot(v, col=rainbow(4))
```

---

Compare-methods

Compare and logical methods

---

## Description

Standard comparison and logical operators for computations with SpatRasters. Computations are local (applied on a cell by cell basis). If multiple SpatRaster objects are used, these must have the same geometry (extent and resolution). These operators have been implemented:

**Logical:** `!`, `&`, `|`, `isTRUE`, `isFALSE`

**Compare:** `==`, `!=`, `>`, `<`, `<=`, `>=`, `is.na`, `is.nan`, `is.finite`, `is.infinite`

The terra package does not distinguish between NA (not available) and NaN (not a number). In most cases this state is represented by NaN.

The following method has been implemented for

**(SpatExtent, SpatExtent):** `==`

## Value

SpatRaster or SpatExtent

## See Also

[all.equal](#), [Arith-methods](#). See [ifel](#) to conveniently combine operations and [Math-methods](#) or [app](#) to apply any R function to a SpatRaster.

## Examples

```
r1 <- rast(ncols=10, nrows=10)
values(r1) <- runif(ncell(r1))
r1[10:20] <- NA
r2 <- rast(r1)
values(r2) <- 1:ncell(r2) / ncell(r2)

x <- is.na(r1)
!x
r1 == r2
```

---

compareGeom

---

*Compare geometries of SpatRasters*


---

## Description

Evaluate whether two SpatRasters have the same extent, number of rows and columns, projection, resolution, and origin (or a subset of these comparisons). Or whether two SpatVectors have the same geometries, or whether a SpatVector has duplicated geometries.

## Usage

```
## S4 method for signature 'SpatRaster,SpatRaster'
compareGeom(x, y, ..., lyrs=FALSE, crs=TRUE, warncrs=FALSE, ext=TRUE,
rowcol=TRUE, res=FALSE, stopOnError=TRUE, messages=FALSE)
```

```
## S4 method for signature 'SpatVector,SpatVector'
compareGeom(x, y, tolerance=0)
```

```
## S4 method for signature 'SpatVector,missing'
compareGeom(x, y, tolerance=0)
```

## Arguments

x	SpatRaster
y	SpatRaster
...	Additional SpatRasters
lyrs	logical. If TRUE, the number of layers is compared
crs	logical. If TRUE, coordinate reference systems are compared
warncrs	logical. If TRUE, a warning is given if the crs is different (instead of an error)
ext	logical. If TRUE, bounding boxes are compared
rowcol	logical. If TRUE, number of rows and columns of the objects are compared
res	logical. If TRUE, resolutions are compared (redundant when checking extent and rowcol)
stopOnError	logical. If TRUE, code execution stops if raster do not match
messages	logical. If TRUE, warning/error messages are printed even if stopOnError=FALSE
tolerance	numeric

## Value

logical (SpatRaster) or matrix of logical (SpatVector)

## Examples

```
r1 <- rast()
r2 <- rast()
r3 <- rast()
compareGeom(r1, r2, r3)
nrow(r3) <- 10
```

```
## Not run:
compareGeom(r1, r3)
```

```
## End(Not run)
```

---

concats	<i>Concatenate categorical rasters</i>
---------	--

---

## Description

Combine two categorical rasters by concatenating their levels.

## Usage

```
## S4 method for signature 'SpatRaster'
concats(x, y, filename="", ...)
```

## Arguments

x	SpatRaster (with a single, categorical, layer)
y	SpatRaster (with a single, categorical, layer)
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## See Also

[cats](#)

## Examples

```
set.seed(0)
r <- rast(nrows=10, ncols=10)
values(r) <- sample(3, ncell(r), replace=TRUE)
levels(r) <- data.frame(id=1:3, cover=c("forest", "water", "urban"))

rr <- rast(r)
```

```

values(rr) <- sample(1:3, ncell(rr), replace=TRUE)
levels(rr) <- data.frame(id=c(1:3), color=c("red", "green", "blue"))

x <- concats(r, rr)
x
levels(x)[[1]]

```

---

contour

*Contour plot*


---

### Description

Contour lines of a SpatRaster. Use `add=TRUE` to add the lines to the current plot. See [contour](#) for details.

if `filled=TRUE`, a new filled contour plot is made. See [filled.contour](#) for details.

`as.contour` returns the contour lines as a SpatVector.

### Usage

```
## S4 method for signature 'SpatRaster'
contour(x, maxcells=100000, filled=FALSE, ...)
```

```
## S4 method for signature 'SpatRaster'
as.contour(x, maxcells=100000, ...)
```

### Arguments

<code>x</code>	SpatRaster. Only the first layer is used
<code>maxcells</code>	maximum number of pixels used to create the contours
<code>filled</code>	logical. If TRUE, a <a href="#">filled.contour</a> plot is made
<code>...</code>	any argument that can be passed to <a href="#">contour</a> or <a href="#">filled.contour</a> (graphics package)

### See Also

[plot](#)

### Examples

```

r <- rast(system.file("ex/elev.tif", package="terra"))
plot(r)
contour(r, add=TRUE)

v <- as.contour(r)
plot(r)
lines(v)

```

```

contour(r, filled=TRUE, nlevels=5)

## if you want a SpatVector with contour lines
template <- disagg(rast(r), 10)
rr <- resample(r, template)
rr <- floor(rr/100) * 100
v <- as.polygons(rr)
plot(v, 1, col=terrain.colors(7))

```

convHull

*Convex hull and minimal rotated rectangle***Description**

Get the convex hull or the minimal rotated rectangle of a SpatVector

**Usage**

```

## S4 method for signature 'SpatVector'
convHull(x, by="")

## S4 method for signature 'SpatVector'
minRect(x, by="")

```

**Arguments**

x	SpatVector
by	character (variable name), to make convex hulls by group

**Value**

SpatVector

**Examples**

```

p <- vect(system.file("ex/lux.shp", package="terra"))
h <- convHull(p)

hh <- convHull(p, "NAME_1")
rr <- minRect(p, "NAME_1")

plot(rr, lwd=5, border="gray")
plot(hh, "NAME_1", col=rainbow(10, alpha=.5), lwd=3, add=TRUE, plg=list(x="topright"))
lines(aggregate(p, "NAME_1"), col="blue", lty=2, lwd=2)

```

---

costDist	<i>Cost distance</i>
----------	----------------------

---

### Description

Use a friction (cost) surface to compute the cost-distance from any cell to one or more target cells.

Distances are computed by summing local distances between cells, which are connected with their neighbors in 8 directions, and assuming that the path has to go through the centers of one of the neighboring raster cells.

Distances are multiplied with the friction, thus to get the cost-distance, the friction surface must express the cost per unit distance (speed) of travel.

If the coordinate reference system (CRS) of the SpatRaster is longitude/latitude (+proj=longlat) the distance is in meters divided by variable m. The default of m is 1000, expressing distance in km. Otherwise the distance is in the units of the CRS (typically meters).

### Usage

```
## S4 method for signature 'SpatRaster'
costDist(x, target=0, scale=1000, maxiter=50, filename="", ...)
```

### Arguments

x	SpatRaster
target	numeric. value of the target cells (where to compute cost-distance to)
scale	numeric. Scale factor for longitude/latitude data (1 = m, 1000 = km)
maxiter	numeric. The maximum number of iterations. Increase this number if you get the warning that costDistance did not converge
filename	character. output filename (optional)
...	additional arguments as for <a href="#">writeRaster</a>

### Value

SpatRaster

### See Also

[gridDist](#), [distance](#)

### Examples

```
r <- rast(ncols=5, nrows=5, crs="+proj=utm +zone=1 +datum=WGS84",
xmin=0, xmax=5, ymin=0, ymax=5, vals=1)
r[13] <- 0
d <- costDist(r)
plot(d)
text(d, digits=1)
```

```

r <- rast(ncols=10, nrows=10, xmin=0, xmax=10, ymin=0, ymax=10,
  vals=10, crs="+proj=utm +zone=1 +datum=WGS84")
r[5, 1] <- -10
r[2:3, 1] <- r[1, 2:4] <- r[2, 5] <- 0
r[3, 6] <- r[2, 7] <- r[1, 8:9] <- 0
r[6, 6:10] <- NA
r[6:9, 6] <- NA

d <- costDist(r, -10)
plot(d)
text(d, digits=1, cex=.8)

```

cover

*Replace values with values from another object***Description**

Replace NA or other values in SpatRaster x with the values of SpatRaster y

For polygons: areas of x that overlap with y are replaced by y or, if identity=TRUE intersected with y.

**Usage**

```
## S4 method for signature 'SpatRaster,SpatRaster'
cover(x, y, values=NA, filename="", ...)
```

```
## S4 method for signature 'SpatVector,SpatVector'
cover(x, y, identity=FALSE, expand=TRUE)
```

**Arguments**

x	SpatRaster or SpatVector
y	Same as x
values	numeric. The cell values in x to be replaced by the values in y
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>
identity	logical. If TRUE overlapping areas are intersected rather than replaced
expand	logical. Should parts of y that are outside of x be included?

**Value**

SpatRaster

**Examples**

```

r1 <- r2 <- rast(ncols=36, nrows=18)
values(r1) <- 1:ncell(r1)
values(r2) <- runif(ncell(r2))
r2 <- classify(r2, cbind(-Inf, 0.5, NA))
r3 <- cover(r2, r1)

p <- vect(system.file("ex/lux.shp", package="terra"))
e <- as.polygons(ext(6, 6.4, 49.75, 50))
values(e) <- data.frame(y=10)

cv <- cover(p, e)
plot(cv, col=rainbow(12))
ci <- cover(p, e, identity=TRUE)
lines(e, lwd=3)

plot(ci, col=rainbow(12))
lines(e, lwd=3)

```

---

crds*Get the coordinates of SpatVector geometries or SpatRaster cells*

---

**Description**

Get the coordinates of a SpatVector or SpatRaster cells. A matrix or data.frame of the x (longitude) and y (latitude) coordinates is returned.

**Usage**

```

## S4 method for signature 'SpatVector'
crds(x, df=FALSE)

## S4 method for signature 'SpatRaster'
crds(x, df=FALSE, na.rm=TRUE)

```

**Arguments**

x	SpatRaster or SpatVector
df	logical. If TRUE a data.frame is returned instead of a matrix
na.rm	logical. If TRUE cells that are NA are excluded

**Value**

matrix or data.frame



**See Also**

[geom](#) returns the complete structure of SpatVector geometries. For SpatRaster see [xyFromCell](#)

**Examples**

```
x1 <- rbind(c(-175,-20), c(-140,55), c(10, 0), c(-140,-60))
x2 <- rbind(c(-125,0), c(0,60), c(40,5), c(15,-45))
x3 <- rbind(c(-10,0), c(140,60), c(160,0), c(140,-55))
x4 <- rbind(c(80,0), c(105,13), c(120,2), c(105,-13))
z <- rbind(cbind(object=1, part=1, x1), cbind(object=2, part=1, x2),
          cbind(object=3, part=1, x3), cbind(object=3, part=2, x4))
colnames(z)[3:4] <- c('x', 'y')
z <- cbind(z, hole=0)
z[(z[, "object"]==3 & z[, "part"]==2), "hole"] <- 1

p <- vect(z, "polygons")
crds(p)

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
g <- crds(v)
head(g)
```

---

crop

---

*Cut out a geographic subset*


---

**Description**

Cut out a part of a SpatRaster with a SpatExtent, or another object from which an extent can be obtained.

You can only crop rectangular areas, but see [mask](#) for setting cell values within SpatRaster to NA. Also note that the SpatRaster returned may not have the exactly the same extent as the SpatExtent supplied because you can only select entire cells (rows and columns), and you cannot add new areas. See methods like [resample](#) and [disagg](#) to force SpatRasters to align and [extend](#) to add rows and/or columns.

You can crop a SpatVector with another SpatVector. If these are not polygons, the minimum convex hull is used). Unlike with [intersect](#) the geometries and attributes of y are not transferred to the output. You can also crop a SpatVector with a rectangle (SpatRaster, SpatExtent).

**Usage**

```
## S4 method for signature 'SpatRaster'
crop(x, y, snap="near", mask=FALSE, touches=TRUE, extend=FALSE, filename="", ...)

## S4 method for signature 'SpatRasterDataset'
crop(x, y, snap="near", extend=FALSE)
```

```
## S4 method for signature 'SpatRasterCollection'
crop(x, y, snap="near", extend=FALSE)

## S4 method for signature 'SpatVector'
crop(x, y)
```

## Arguments

x	SpatRaster or SpatVector
y	SpatRaster, SpatVector, SpatExtent or other object that has a SpatExtent ( <a href="#">ext</a> returns a SpatExtent)
snap	character. One of "near", "in", or "out". Used to align y to the geometry of x
mask	logical. Should y be used to mask? Only used if y is a SpatVector
touches	logical. If TRUE and mask=TRUE, all cells touched by lines or polygons will be masked, not just those on the line render path, or whose center point is within the polygon
extend	logical. Should rows and/or columns be added if y is beyond the extent of x? Also see <a href="#">extend</a>
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## See Also

[intersect](#), [extend](#)

## Examples

```
r <- rast(xmin=0, xmax=10, ymin=0, ymax=10, nrows=25, ncols=25)
values(r) <- 1:ncell(r)
e <- ext(-5, 5, -5, 5)
rc <- crop(r, e)

# crop and mask
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
cm <- crop(r, v[9:12,], mask=TRUE)
plot(cm)
lines(v)

# crop vector
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
```

```
e <- ext(6.15, 6.3, 49.7, 49.8)
x <- crop(v, e)
plot(x, "NAME_1")
```

crosstab

*Cross-tabulate*

## Description

Cross-tabulate the layers of a SpatRaster to create a contingency table.

## Usage

```
## S4 method for signature 'SpatRaster,missing'
crosstab(x, digits=0, long=FALSE, useNA=FALSE)
```

## Arguments

x	SpatRaster
digits	integer. The number of digits for rounding the values before cross-tabulation
long	logical. If TRUE the results are returned in 'long' format data.frame instead of a table
useNA	logical, indicating if the table should include counts of NA values

## Value

A table or data.frame

## See Also

[freq](#), [zonal](#)

## Examples

```
r <- s <- rast(nc=5, nr=5)
set.seed(1)
values(r) <- runif(ncell(r)) * 2
values(s) <- runif(ncell(r)) * 3
x <- c(r, s)

crosstab(x)

rs <- r/s
r[1:5] <- NA
s[20:25] <- NA
x <- c(r, s, rs)
crosstab(x, useNA=TRUE, long=TRUE)
```

crs

*Get or set a coordinate reference system***Description**

Get or set the coordinate reference system (CRS), also referred to as a "projection", of a `SpatRaster` or `SpatVector`.

Setting a new CRS does not change the data itself, it just changes the label. So you should only set the CRS of a dataset (if it does not come with one) to what it *is*, not to what you would *like* it to be. See [project](#) to *transform* an object from one CRS to another.

**Usage**

```
## S4 method for signature 'SpatRaster'
crs(x, proj=FALSE, describe=FALSE, parse=FALSE)

## S4 method for signature 'SpatVector'
crs(x, proj=FALSE, describe=FALSE, parse=FALSE)

## S4 replacement method for signature 'SpatRaster'
crs(x)<-value

## S4 replacement method for signature 'SpatVector'
crs(x)<-value
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>proj</code>	logical. If TRUE the crs is returned in PROJ-string notation
<code>describe</code>	logical. If TRUE the name, EPSG code, and the name and extent of the area of use are returned if known
<code>value</code>	character string describing a coordinate reference system. This can be in a WKT format, as a <authority:number> code such as "EPSG:4326", or a PROJ-string format such as "+proj=utm +zone=12" (see Note)
<code>parse</code>	logical. If TRUE, wkt parts are parsed into a vector (each line becomes an element)

**Value**

character or modified `SpatRaster/Vector`

**Note**

Projections are handled by the PROJ/GDAL libraries. Recent changes in the PROJ library to improve transformations between datums have degraded the library's usability. The PROJ developers

suggest to no longer use the proj-string notation to define a CRS, but use the WKT2 or <authority>:<code> notation instead. These alternative systems work for formally described CRSs that are in databases, but they do not cover the infinite number of CRSs that exist. It is not practical to define one's own custom CRS with WKT2. Moreover, unlike the proj-notation, these newer systems are hard to read and that leads to code that cannot be easily understood and, therefore, is more error-prone.

It is still possible to use the PROJ-string notation with one major caveat: the datum should be WGS84 (or the equivalent NAD83) – if you want to transform your data to a coordinate reference system with a different datum. Thus as long as you use WGS84, or an ellipsoid instead of a datum, you can safely use PROJ-strings to represent your CRS; including to define your own custom CRS.

You can also set the crs to "local" to get an informal coordinate system on an arbitrary Euclidean (Cartesian) plane with units in meter.

### Examples

```
r <- rast()
crs(r)
crs(r, describe=TRUE, proj=TRUE)

crs(r) <- "+proj=lcc +lat_1=48 +lat_2=33 +lon_0=-100 +ellps=WGS84"
crs(r)

# You can also use epsg codes
crs(r) <- "epsg:25831"
crs(r, describe=TRUE)$area
```

---

deepcopy

*Deep copy*

---

### Description

Make a deep copy of a SpatRaster or SpatVector. This is occasionally useful when wanting to use a replacement function in a shallow copy. That is a copy that was created like this: `x <- y`. If you use a replacement function to change an object, its shallow copies also change.

### Usage

```
## S4 method for signature 'SpatRaster'
deepcopy(x)

## S4 method for signature 'SpatVector'
deepcopy(x)
```

### Arguments

x                      SpatRaster or SpatVector

**Value**

Same as x

**Examples**

```
r <- rast(ncols=10, nrows=10, nl=3)
tm <- as.Date("2001-05-03") + 1:3
time(r) <- tm
time(r)
x <- r
time(x) <- tm + 365
time(x)
time(r)

y <- deepcopy(r)
time(y) <- tm - 365
time(y)
time(r)

# or make a new object like this
z <- rast(r)
time(z) <- tm
time(z)
time(r)
```

---

densify	<i>Add additional nodes to lines or polygons</i>
---------	--

---

**Description**

Add additional nodes to lines or polygons. This can be useful to do prior to using project such that the path does not change too much.

**Usage**

```
## S4 method for signature 'SpatVector'
densify(x, interval, equalize=TRUE)
```

**Arguments**

x	SpatVector
interval	numeric larger than 1, specifying the desired minimum interval between nodes
equalize	logical. If TRUE, new nodes are spread at equal intervals between old nodes

**Value**

SpatVector

Examples

```
v <- vect(rbind(c(-120,-20), c(-80,5), c(-40,-60), c(-120,-20)),
  type="polygons", crs="+proj=longlat")
vd <- densify(v, 200000)

p <- project(v, "+proj=robin")
pd <- project(vd, "+proj=robin")

# good
plot(pd, col="gray", border="red", lwd=10)
points(pd, col="gray")

# bad
lines(p, col="blue", lwd=3)
points(p, col="blue", cex=2)
plot(p, col="blue", alpha=.1, add=TRUE)
legend("topright", c("good", "bad"), col=c("red", "blue"), lty=1, lwd=3)

## the other way around does not work
## unless the original data was truly planar (e.g. derived from a map)
x <- densify(p, 250000)
y <- project(x, "+proj=longlat")
# bad
plot(y)
# good
lines(vd, col="red")
```

---

density	Density plot
---------	--------------

---

Description

Create density plots of the cell values of a SpatRaster

Usage

```
## S4 method for signature 'SpatRaster'
density(x, maxcells=100000, plot=TRUE, main, ...)
```

Arguments

x	SpatRaster
maxcells	the maximum number of (randomly sampled) cells to be used for creating the plot
plot	if TRUE produce a plot, else return a density object
main	character. Caption of plot(s)
...	additional arguments passed to <a href="#">plot</a>

**Value**

density plot (and a density object, returned invisibly if plot=TRUE)

**Examples**

```
logo <- rast(system.file("ex/logo.tif", package="terra"))
density(logo)
```

---

deprecated	<i>deprecated methods</i>
------------	---------------------------

---

**Description**

These methods are deprecated and will be removed in future versions

**Usage**

```
## S4 method for signature 'SpatRaster'
setCats(x, ...)

## S4 method for signature 'SpatRaster'
area(x, ...)
```

**Arguments**

- x                    object
- ...                  additional arguments

---

depth	<i>depth of SpatRaster layers</i>
-------	-----------------------------------

---

**Description**

Get or set the depth of the layers of a SpatRaster. Experimental.

**Usage**

```
## S4 method for signature 'SpatRaster'
depth(x)

## S4 replacement method for signature 'SpatRaster'
depth(x)<-value
```



**Arguments**

x                   SpatRaster  
value               numeric vector

**Value**

numeric

**See Also**

[time](#)

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra"))  
  
depth(s) <- 1:3  
depth(s)
```

---

describe	<i>describe</i>
----------	-----------------

---

**Description**

Describe the properties of spatial data in a file as generated with the "GDALInfo" tool.

**Usage**

```
## S4 method for signature 'character'  
describe(x, sds=FALSE, meta=FALSE, parse=FALSE, options="", print=FALSE, open_opt="")
```

**Arguments**

x                   character. The name of a file with spatial data. Or a fully specified subdataset within a file such as "NETCDF:\\"AVHRR.nc\\":NDVI"

sds                 logical. If TRUE the description or metadata of the subdatasets is returned (if available)

meta                logical. Get the file level metadata instead

parse               logical. If TRUE, metadata for subdatasets is parsed into components (if meta=TRUE)

options             character. A vector of valid options (if meta=FALSE) including "json", "mm", "stats", "hist", "nogcp", "nomd", "norat", "noct", "nofl", "checksum", "proj4", "listmdd", "mdd <value>" where <value> specifies a domain or 'all', "wkt\_format <value>" where value is one of 'WKT1', 'WKT2', 'WKT2\_2015', or 'WKT2\_2018', "sd <subdataset>" where <subdataset> is the name or identifier of a sub-dataset. See <https://gdal.org/programs/gdalinfo.html>. Ignored if sds=TRUE

print               logical. If TRUE, print the results

open\_opt            character. Driver specific open options

**Value**

character (invisibly, if print=FALSE)

**Examples**

```
f <- system.file("ex/elev.tif", package="terra")
describe(f)
describe(f, meta=TRUE)
#g <- describe(f, options=c("json", "nomd", "proj4"))
#head(g)
```

---

diff	<i>Lagged differences</i>
------	---------------------------

---

**Description**

Compute the difference between consecutive layers in a SpatRaster.

**Usage**

```
## S4 method for signature 'SpatRaster'
diff(x, lag=1, filename="", ...)
```

**Arguments**

- x                    SpatRaster
- lag                  positive integer indicating which lag to use
- filename            character. Output filename
- ...                  additional arguments for writing files as in [writeRaster](#)

**Value**

SpatRaster

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra"))
d <- diff(s)
```

---

dimensions

---

*Dimensions of a SpatRaster or SpatVector and related objects*


---

### Description

Get the number of rows (nrow), columns (ncol), cells (ncell), layers (nlyr), sources (nsrc), the size size (nlyr(x)\*ncell(x)), or spatial resolution of a SpatRaster.

length returns the number of sub-datasets in a SpatRasterDataset or SpatVectorCollection.

For a SpatVector length(x) is the same as nrow(x).

You can also set the number of rows or columns or layers. When setting dimensions, all cell values are dropped.

### Usage

```
## S4 method for signature 'SpatRaster'
ncol(x)

## S4 method for signature 'SpatRaster'
nrow(x)

## S4 method for signature 'SpatRaster'
nlyr(x)

## S4 method for signature 'SpatRaster'
ncell(x)

## S4 method for signature 'SpatRaster'
nsrc(x)

## S4 replacement method for signature 'SpatRaster,numeric'
ncol(x)<-value

## S4 replacement method for signature 'SpatRaster,numeric'
nrow(x)<-value

## S4 replacement method for signature 'SpatRaster,numeric'
nlyr(x)<-value

## S4 method for signature 'SpatRaster'
res(x)

## S4 replacement method for signature 'SpatRaster,numeric'
res(x)<-value

## S4 method for signature 'SpatRaster'
xres(x)
```

```
## S4 method for signature 'SpatRaster'  
yres(x)  
  
## S4 method for signature 'SpatVector'  
ncol(x)  
  
## S4 method for signature 'SpatVector'  
nrow(x)  
  
## S4 method for signature 'SpatVector'  
length(x)
```

### Arguments

x	SpatRaster or SpatVector or related objects
value	For ncol and nrow: positive integer. For res: one or two positive numbers

### Value

integer

### See Also

[ext](#)

### Examples

```
r <- rast()  
ncol(r)  
nrow(r)  
nlyr(r)  
dim(r)  
nsrc(r)  
ncell(r)  
  
rr <- c(r,r)  
nlyr(rr)  
nsrc(rr)  
ncell(rr)  
  
nrow(r) <- 18  
ncol(r) <- 36  
# equivalent to  
dim(r) <- c(18, 36)  
  
dim(r)  
dim(r) <- c(10, 10, 5)  
dim(r)
```

```

xres(r)
yres(r)
res(r)

res(r) <- 1/120
# different xres and yres
res(r) <- c(1/120, 1/60)

```

---

direction

*Direction*


---

## Description

The direction (azimuth) to or from the nearest cell that is not NA. The direction is expressed in radians, unless you use argument degrees=TRUE.

## Usage

```

## S4 method for signature 'SpatRaster'
direction(x, from=FALSE, degrees=FALSE, filename="", ...)

```

## Arguments

x	SpatRaster
filename	Character. Output filename (optional)
degrees	Logical. If FALSE (the default) the unit of direction is radians.
from	Logical. Default is FALSE. If TRUE, the direction from (instead of to) the nearest cell that is not NA is returned
...	Additional arguments as for <a href="#">writeRaster</a>

## Value

SpatRaster

## See Also

[distance](#)

## Examples

```

r <- rast(ncol=36,nrow=18, crs="+proj=merc")
values(r) <- NA
r[306] <- 1
b <- direction(r, degrees=TRUE)
plot(b)

crs(r) <- "+proj=longlat"
b <- direction(r)
plot(b)

```

disagg

*Disaggregate raster cells or vector geometries***Description**

SpatRaster: Create a SpatRaster with a higher resolution (smaller cells). The values in the new SpatRaster are the same as in the larger original cells.

SpatVector: Separate multi-objects (points, lines, polygons) into single objects; or further into segments (for lines or polygons).

**Usage**

```
## S4 method for signature 'SpatRaster'
disagg(x, fact, method="near", filename="", ...)
```

```
## S4 method for signature 'SpatVector'
disagg(x, segments=FALSE)
```

**Arguments**

x	SpatRaster or SpatVector
fact	positive integer. Aggregation factor expressed as number of cells in each direction (horizontally and vertically). Or two integers (horizontal and vertical aggregation factor) or three integers (when also aggregating over layers)
method	character. Either "near" for nearest or "bilinear" for bilinear interpolation
segments	logical. Should (poly-)lines or polygons be disaggregated into their line-segments?
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[aggregate](#), [resample](#)

**Examples**

```
r <- rast(ncols=10, nrows=10)
rd <- disagg(r, fact=c(10, 2))
ncol(rd)
nrow(rd)
values(r) <- 1:ncell(r)
rd <- disagg(r, fact=c(4, 2))
```

---

distance	<i>Geographic distance</i>
----------	----------------------------

---

## Description

If *x* is a **SpatRaster**:

If *y* is missing this method computes the distance, for all cells that are NA in SpatRaster *x* to the nearest cell that is not NA (or other values, see arguments "target" and "exclude").

If *y* is a numeric value, the cells with that value are ignored. That is, distance to or from these cells is not computed (only if *grid*=FALSE).

If *y* is a SpatVector, the distance to that SpatVector is computed for all cells. For lines and polygons this is done after rasterization; and only the overlapping areas of the vector and raster are considered (for now).

The distance is always expressed in meter if the coordinate reference system is longitude/latitude, and in map units otherwise. Map units are typically meter, but inspect *crs(x)* if in doubt.

Results are more precise, sometimes much more precise, when using longitude/latitude rather than a planar coordinate reference system, as these distort distance.

If *x* is a **SpatVector**:

If *y* is missing, a distance matrix between all object in *x* is computed. An distance matrix object of class "dist" is returned.

If *y* is a SpatVector the geographic distance between all objects is computed (and a matrix is returned). If both sets have the same number of points, and *pairwise*=TRUE, the distance between each pair of objects is computed, and a vector is returned.

The distance is always expressed in meter, except when the coordinate reference system is longitude/latitude AND one of the SpatVector(s) consists of lines or polygons. In that case the distance is in degrees, and thus not very useful (this will be fixed soon). Otherwise, results are more precise, sometimes much more precise, when using longitude/latitude rather than a planar coordinate reference system, as these distort distance.

If *x* is a **matrix**:

*x* should consist of two columns, the first with "x" (or longitude) and the second with "y" coordinates (or latitude). If *y* is also a matrix, the distance between each points in *x* and all points in *y* is computed, unless *pairwise*=TRUE

If *y* is missing, the distance between each points in *x* with all other points in *x* is computed, unless *sequential*=TRUE

## Usage

```
## S4 method for signature 'SpatRaster,missing'
distance(x, y, target=NA, exclude=NULL, unit="m", haversine=TRUE, filename="", ...)
```

```
## S4 method for signature 'SpatRaster,SpatVector'
distance(x, y, unit="m", rasterize=FALSE, haversine=TRUE, filename="", ...)
```

```
## S4 method for signature 'SpatVector,ANY'
distance(x, y, sequential=FALSE, pairs=FALSE, symmetrical=TRUE, unit="m")

## S4 method for signature 'SpatVector,SpatVector'
distance(x, y, pairwise=FALSE, unit="m")

## S4 method for signature 'matrix,matrix'
distance(x, y, lonlat, pairwise=FALSE)

## S4 method for signature 'matrix,missing'
distance(x, y, lonlat, sequential=FALSE, pairs=FALSE, symmetrical=TRUE)
```

### Arguments

<code>x</code>	SpatRaster, SpatVector, or two-column matrix with coordinates (x,y) or (lon,lat)
<code>y</code>	missing, numeric, SpatVector, or two-column matrix
<code>target</code>	numeric. The value of the cells for which distances to cells that are not NA should be computed
<code>exclude</code>	numeric. The value of the cells that should not be considered for computing distances
<code>unit</code>	character. Can be either "m" or "km"
<code>haversine</code>	logical. Use the haversine formula for lon/lat data use the haversine formula? If FALSE, the more precise but slower method of Karney (2003) is used
<code>rasterize</code>	logical. If TRUE distance is computed from the cells covered by the geometries after rasterization. This can be much faster in some cases
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>
<code>sequential</code>	logical. If TRUE, the distance between sequential geometries is returned
<code>pairwise</code>	logical. If TRUE and if x and y have the same size (number of rows), the pairwise distances are returned instead of the distances between all elements
<code>lonlat</code>	logical. If TRUE the coordinates are interpreted as angular (longitude/latitude). If FALSE they are interpreted as planar
<code>pairs</code>	logical. If TRUE a "from", "to", "distance" matrix is returned
<code>symmetrical</code>	logical. If TRUE and pairs=TRUE, the distance between a pair is only included once. The distance between geometry 1 and 3 is included, but the (same) distance between 3 and 1 is not

### Value

SpatRaster or numeric or matrix or distance matrix (object of class "dist")

### Note

The distance unit is in meters.

A distance matrix can be coerced into a matrix with `as.matrix`



## References

Karney, C.F.F., 2013. Algorithms for geodesics, J. Geodesy 87: 43-55. doi:10.1007/s00190-012-0578-z.

## Examples

```
#lonlat
r <- rast(ncols=36, nrows=18, crs="+proj=longlat +datum=WGS84")
r[500] <- 1
d <- distance(r)
plot(d / 100000)

#planar
rr <- rast(ncols=36, nrows=18, crs="+proj=utm +zone=1 +datum=WGS84")
rr[500] <- 1
d <- distance(rr)

rr[3:10, 3:10] <- 99
e <- distance(rr, exclude=99)

p1 <- vect(rbind(c(0,0), c(90,30), c(-90,-30)), crs="+proj=longlat +datum=WGS84")
dp <- distance(r, p1)

d <- distance(p1)
d
as.matrix(d)

p2 <- vect(rbind(c(30,-30), c(25,40), c(-9,-3)), crs="+proj=longlat +datum=WGS84")
dd <- distance(p1, p2)
dd
pd <- distance(p1, p2, pairwise=TRUE)
pd
pd == diag(dd)

# polygons, lines
crs <- "+proj=utm +zone=1"
p1 <- vect("POLYGON ((0 0, 8 0, 8 9, 0 9, 0 0))", crs=crs)
p2 <- vect("POLYGON ((5 6, 15 6, 15 15, 5 15, 5 6))", crs=crs)
p3 <- vect("POLYGON ((2 12, 3 12, 3 13, 2 13, 2 12))", crs=crs)
p <- rbind(p1, p2, p3)
L1 <- vect("LINESTRING(1 11, 4 6, 10 6)", crs=crs)
L2 <- vect("LINESTRING(8 14, 12 10)", crs=crs)
L3 <- vect("LINESTRING(1 8, 12 14)", crs=crs)
lns <- rbind(L1, L2, L3)
pts <- vect(cbind(c(7,10,10), c(3,5,6)), crs=crs)

distance(p1,p3)
distance(p)
distance(p,pts)
distance(p,lns)
distance(pts,lns)
```

dots

*Make a dot-density map***Description**

Create the dots for a dot-density map and add these to the current map. Dot-density maps are made to display count data. For example of population counts, where each dot represents  $n$  persons. The dots are returned as a `SpatVector`. If there is an active graphics device, the dots are added to it with [points](#).

**Usage**

```
## S4 method for signature 'SpatVector'
dots(x, field, size, ...)
```

**Arguments**

<code>x</code>	<code>SpatVector</code>
<code>field</code>	character of numeric indicating field name. Or numeric vector of the same length as <code>x</code>
<code>size</code>	positive number indicating the number of cases associated with each dot
<code>...</code>	graphical arguments passed to <code>points</code>

**Value**

`SpatVector` (invisibly)

**See Also**

[plot](#), [cartogram](#), [points](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
v$population <- 1000*(1:12)^2
plot(v, lwd=3, col="light gray", border="white")
d <- dots(v, "population", 1000, col="red", cex=.75)
lines(v)
d
```

---

draw	<i>Draw a polygon, line, extent, or points</i>
------	--

---

### Description

Draw on a plot (map) to get a `SpatVector` or `SpatExtent` object for later use. After calling the function, start clicking on the map. When you are done, press ESC. You can also preset the maximum number of clicks.

### Usage

```
## S4 method for signature 'character'
draw(x="extent", col="red", lwd=2, id=FALSE, n=1000, ...)
```

### Arguments

<code>x</code>	character. The type of object to draw. One of "extent", "polygon", "line", or "points"
<code>col</code>	the color to be used
<code>lwd</code>	the width of the lines to be drawn
<code>id</code>	logical. If TRUE, a numeric ID is shown on the map
<code>n</code>	the maximum number of clicks (does not apply when <code>x=="extent"</code> in which case <code>n</code> is always 2)
<code>...</code>	additional graphics arguments for drawing

### Value

`SpatVector` or `SpatExtent`

### See Also

[click](#)

---

erase	<i>Erase parts of a SpatVector object</i>
-------	---

---

### Description

Erase parts of a `SpatVector` with another `SpatVector` or with a `SpatExtent`. You can also erase (parts of) polygons with the other polygons of the same `SpatVector`.

**Usage**

```
## S4 method for signature 'SpatVector,SpatVector'
erase(x, y)

## S4 method for signature 'SpatVector,missing'
erase(x, sequential=TRUE)

## S4 method for signature 'SpatVector,SpatExtent'
erase(x, y)
```

**Arguments**

x	SpatVector
y	SpatVector or SpatExtent
sequential	logical. Should areas be erased sequentially? See Details

**Details**

If polygons are erased sequentially, everything that is covered by the first polygon is removed from all other polygons, then everything that is covered by (what is remaining of) the second polygon is removed, etc.

If polygons are not erased sequentially, all overlapping areas are erased and only the areas covered by a single geometry are returned.

**Value**

SpatVector or SpatExtent

**See Also**

[crop](#) and [intersect](#) for the inverse.

The equivalent for SpatRaster is [mask](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)

# polygons with polygons or extent

e <- ext(5.6, 6, 49.55, 49.7)
x <- erase(v, e)

p <- vect("POLYGON ((5.8 49.8, 6 49.9, 6.15 49.8, 6 49.6, 5.8 49.8))")
y <- erase(v, p)

# lines with polygons
lns <- as.lines(rast(v, ncol=10, nrow=10))[12:22]
eln <- erase(lns, v)
```

```

plot(v)
lines(lns, col='blue', lwd=4, lty=3)
lines(eln, col='red', lwd=2)

## self-erase
h <- convHull(v[-12], "NAME_1")
he <- erase(h)
plot(h, lwd=2, border="red", lty=2)
lines(he, col="gray", lwd=3)

```

---

expanse	<i>Get the expanse (area) of individual polygons or for all (summed) raster cells</i>
---------	---

---

## Description

Compute the area covered by polygons or for all raster cells that are not NA.

This method computes areas for longitude/latitude rasters, as the size of the cells is constant in degrees, but not in square meters. But it can also be important if the coordinate reference system is planar, but not equal-area.

For vector data, the best way to compute area is to use the longitude/latitude CRS. This is contrary to (erroneous) popular belief that suggest that you should use a planar coordinate reference system. This is done automatically, if transform=TRUE.

## Usage

```

## S4 method for signature 'SpatRaster'
expanse(x, unit="m", transform=TRUE, byValue=FALSE)

## S4 method for signature 'SpatVector'
expanse(x, unit="m", transform=TRUE)

```

## Arguments

x	SpatRaster or SpatVector
unit	character. One of "m", "km", or "ha"
transform	logical. If TRUE, planar CRS are transformed to lon/lat for accuracy
byValue	logical. If TRUE, the area for each unique cell value is returned

## Value

numeric. If x has no values, the total size of all cells. Otherwise, the total area size of all cells that are not NA, expressed in square meters, square kilometers, or hectares.

If byValue=TRUE a matrix is returned with three columns (layer, value, area)

**See Also**

[cellSize](#) for a the size of individual cells of a raster, that can be summed with [global](#) or with [zonal](#) to get the area for different categories.

**Examples**

```
### SpatRaster
r <- rast(nrows=18, ncols=36)
v <- 1:ncell(r)
v[200:400] <- NA
values(r) <- v

# summed area in km2
expanse(r, unit="km")

# all cells
expanse(rast(r), unit="km")

r <- rast(ncols=90, nrows=45, ymin=-80, ymax=80)
m <- project(r, "+proj=merc")

expanse(m, unit="km")
expanse(m, unit="km", transform=FALSE)

m2 <- c(m, m)
values(m2) <- cbind(c(1,2,NA,NA), c(11:14))
expanse(m2, unit="km", byValue=TRUE)

### SpatVector
v <- vect(system.file("ex/lux.shp", package="terra"))

a <- expanse(v)
a
sum(a)
```

---

ext

---

*Create, get or set a SpatExtent*


---

**Description**

Get a SpatExtent of a SpatRaster, SpatVector, or other spatial objects. Or create a SpatExtent from a vector (length=4; order=xmin, xmax, ymin, ymax)

You can set the extent of a SpatRaster, but you cannot set the extent of a SpatVector (see [rescale](#) for that). See [set.ext](#) to set the extent in place.

**Usage**

```
## S4 method for signature 'SpatRaster'
ext(x, cells=NULL)

## S4 method for signature 'SpatVector'
ext(x)

## S4 method for signature 'numeric'
ext(x, ..., xy=FALSE)

## S4 replacement method for signature 'SpatRaster,SpatExtent'
ext(x)<-value

## S4 replacement method for signature 'SpatRaster,numeric'
ext(x)<-value
```

**Arguments**

x	SpatRaster
cells	positive integer (cell) numbers to subset the extent to area covered by these cells
value	SpatExtent, or numeric vector of length four (xmin, xmax, ymin, ymax)
...	if x is a single numeric value, additional numeric values for xmax, ymin, and ymax
xy	logical. Set this to TRUE to indicate that coordinates are in (xmin, ymin, xmax, ymax) order, instead of in the terra standard order of (xmin, xmax, ymin, ymax)

**Value**

A [SpatExtent](#) object.

**Examples**

```
r <- rast()
e <- ext(r)
as.vector(e)
as.character(e)

ext(r) <- c(0, 2.5, 0, 1.5)
r
er <- ext(r)

round(er)
# go "in"
floor(er)
# go "out"
ceiling(er)

ext(r) <- e
```

extend

*Extend***Description**

Enlarge the spatial extent of a `SpatRaster`. See [crop](#) if you (also) want to remove rows or columns.

You can also enlarge a `SpatExtent` with this method, or with algebraic notation (see examples)

**Usage**

```
## S4 method for signature 'SpatRaster'
extend(x, y, snap="near", fill=NA, filename="", overwrite=FALSE, ...)

## S4 method for signature 'SpatExtent'
extend(x, y)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> or <code>SpatExtent</code>
<code>y</code>	If <code>x</code> is a <code>SpatRaster</code> , <code>y</code> should be a <code>SpatExtent</code> , or an object from which it can be extracted (such as <code>SpatRaster</code> and <code>SpatVector</code> objects). Alternatively, you can provide two positive integers indicating the number of rows and columns that need to be added at each side (or a single positive integer when the number of rows and columns is equal) If <code>x</code> is a <code>SpatExtent</code> , <code>y</code> should be a numeric vector of 1, 2, or 4 elements
<code>snap</code>	character. One of "near", "in", or "out". Used to align <code>y</code> to the geometry of <code>x</code>
<code>fill</code>	numeric. The value used to for the new raster cells
<code>filename</code>	character. Output filename
<code>overwrite</code>	logical. If TRUE, filename is overwritten
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

`SpatRaster` or `SpatExtent`

**See Also**

[crop](#), [merge](#), [ext](#)

**Examples**

```
r <- rast(xmin=-150, xmax=-120, ymin=30, ymax=60, ncols=36, nrows=18)
values(r) <- 1:ncell(r)
e <- ext(-180, -100, 40, 70)
re <- extend(r, e)
```



```
# extend with a number of rows and columns (at each side)
re2 <- extend(r, c(2,10))

# SpatExtent
e <- ext(r)
e
extend(e, 10)
extend(e, c(10, -10, 0, 20))
```

---

extract

---

*Extract values from a SpatRaster*


---

## Description

Extract values from a `SpatRaster` for a set of locations. The locations can be a `SpatVector` (points, lines, polygons), a matrix with (x, y) or (longitude, latitude – in that order!) coordinates, or a vector with cell numbers.

When argument `y` is a `SpatVector` the first column has the ID (record number) of the `SpatVector` used (unless you set `ID=FALSE`).

## Usage

```
## S4 method for signature 'SpatRaster,SpatVector'
extract(x, y, fun=NULL, method="simple", cells=FALSE, xy=FALSE,
        ID=TRUE, weights=FALSE, exact=FALSE, touches=is.lines(y),
        layer=NULL, bind=FALSE, raw=FALSE, ...)
```

```
## S4 method for signature 'SpatRaster,SpatExtent'
extract(x, y, cells=FALSE, xy=FALSE)
```

```
## S4 method for signature 'SpatRaster,numeric'
extract(x, y, xy=FALSE)
```

```
## S4 method for signature 'SpatRaster,matrix'
extract(x, y, cells=FALSE)
```

```
## S4 method for signature 'SpatVector,SpatVector'
extract(x, y)
```

## Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code> of polygons
<code>y</code>	<code>SpatVector</code> (for points, lines, polygons), or for points, 2-column matrix or <code>data.frame</code> (x, y) or (lon, lat), or a vector with cell numbers
<code>fun</code>	function to summarize the data by geometry. If <code>weights=TRUE</code> or <code>exact=TRUE</code> only mean, sum, min and max are accepted).

method	character. method for extracting values with points ("simple" or "bilinear"). With "simple" values for the cell a point falls in are returned. With "bilinear" the returned values are interpolated from the values of the four nearest raster cells
cells	logical. If TRUE the cell numbers are also returned, unless fun is not NULL. Also see <a href="#">cells</a>
xy	logical. If TRUE the coordinates of the cells are also returned, unless fun is not NULL. Also see <a href="#">xyFromCell</a>
ID	logical. Should an ID column be added? If so, the first column returned has the IDs (record numbers) of input SpatVector y
weights	logical. If TRUE and y has polygons, the approximate fraction of each cell that is covered is returned as well, for example to compute a weighted mean
exact	logical. If TRUE and y has polygons, the exact fraction of each cell that is covered is returned as well, for example to compute a weighted mean
touches	logical. If TRUE, values for all cells touched by lines or polygons are extracted, not just those on the line render path, or whose center point is within the polygon. Not relevant for points; and always considered TRUE when weights=TRUE or exact=TRUE
layer	character or numeric to select the layer to extract from for each geometry. If layer is a character it can be a name in y or a vector of layer names. If it is numeric, it must be integer values between 1 and nlyr(x)
bind	logical. If TRUE, a SpatVector is returned consisting of the input SpatVector y and the cbind-ed extracted values
raw	logical. If TRUE, a matrix is returned with the "raw" numeric cell values. If FALSE, a data.frame is returned and the cell values are transformed to factor, logical, or integer values, where appropriate
...	additional arguments to fun if y is a SpatVector. For example na.rm=TRUE. Or arguments passed to the SpatRaster, SpatVector method if y is a matrix (such as the method and cells arguments)

**Value**

data.frame, matrix or SpatVector

**See Also**

[values](#)

**Examples**

```
r <- rast(ncols=5, nrows=5, xmin=0, xmax=5, ymin=0, ymax=5)
values(r) <- 1:25
xy <- rbind(c(0.5,0.5), c(2.5,2.5))
p <- vect(xy, crs="+proj=longlat +datum=WGS84")

extract(r, xy)
extract(r, p)
```

```
r[1,]  
r[5]  
r[,5]  
  
r[c(0:2, 99:101)]  
  
f <- system.file("ex/meuse.tif", package="terra")  
r <- rast(f)  
  
xy <- cbind(179000, 330000)  
xy <- rbind(xy-100, xy, xy+1000)  
extract(r, xy)  
  
p <- vect(xy)  
g <- geom(p)  
g  
  
extract(r, p)  
  
x <- r + 10  
extract(x, p)  
  
i <- cellFromXY(r, xy)  
x[i]  
r[i]  
  
y <- c(x,x*2,x*3)  
y[i]  
  
## extract with a polygon  
f <- system.file("ex/lux.shp", package="terra")  
v <- vect(f)  
v <- v[1:2,]  
z <- rast(v, resolution=.1, names="test")  
values(z) <- 1:ncell(z)  
  
rf <- system.file("ex/elev.tif", package="terra")  
x <- rast(rf)  
extract(x, v, mean, na.rm=TRUE)  
  
e <- extract(z, v)  
e  
tapply(e[,2], e[,1], mean, na.rm=TRUE)  
  
x <- c(z, z*2, z/3)  
names(x) <- letters[1:3]  
  
e <- extract(x, v)  
de <- data.frame(e)  
aggregate(de[,2:4], de[,1,drop=FALSE], mean)
```

---

 extremes

*Get or compute the minimum and maximum cell values*


---

### Description

The minimum and maximum value of a `SpatRaster` are returned or computed (from a file on disk if necessary) and stored in the object.

### Usage

```
## S4 method for signature 'SpatRaster'
minmax(x)
## S4 method for signature 'SpatRaster'
hasMinMax(x)
## S4 method for signature 'SpatRaster'
setMinMax(x, force=FALSE)
```

### Arguments

<code>x</code>	<code>SpatRaster</code>
<code>force</code>	logical. If TRUE min and max values are recomputed even if already available

### Value

`minmax`: numeric matrix of minimum and maximum cell values by layer

`hasMinMax`: logical indicating whether the min and max values are available.

`setMinMax`: nothing. Used for the side-effect of computing the minimum and maximum values of a `SpatRaster`

### Examples

```
r <- rast(system.file("ex/elev.tif", package="terra"))
minmax(r)
```

---

 factors

*Categorical rasters*


---

## Description

A `SpatRaster` layer can represent a categorical variable (factor). Like `factors`, `SpatRaster` categories are stored as integers that have an associated label.

The categories can be inspected with `levels` and `cats`. They are represented by a `data.frame` that must have two or more columns, the first one identifying the (integer) cell values and the other column(s) providing the category labels.

If there are multiple columns with categories, you can set the "active" category to choose the one you want to use.

`cats` returns the entire `data.frame`, whereas `levels` only return two columns: the index and the active category.

To set categories for the first layer of a `SpatRaster`, you can provide `levels<-` with a `data.frame` or a list with a `data.frame`. To set categories for multiple layers you can provide `levels<-` with a list with one element (that either has a `data.frame` or is `NULL`) for each layer. Use `categories` to set the categories for a specific layer or specific layers.

`droplevels` removes categories that are not used (declared but not present as values in the raster).

## Usage

```
## S4 method for signature 'SpatRaster'
levels(x)

## S4 replacement method for signature 'SpatRaster'
levels(x)<-value

## S4 method for signature 'SpatRaster'
cats(x, layer)

## S4 method for signature 'SpatRaster'
categories(x, layer=1, value, active=2, ...)

## S4 method for signature 'SpatRaster'
droplevels(x)
```

## Arguments

<code>x</code>	<code>SpatRaster</code>
<code>layer</code>	the layer name or number (positive integer); or 0 for all layers
<code>value</code>	a <code>data.frame</code> (ID, category) that define the categories. Or <code>NULL</code> to remove them
<code>active</code>	positive integer, indicating the column in <code>data.frame</code> value to be used as the active category, (not counting the first column with the cell values)
<code>...</code>	additional arguments

## Value

list of `data.frames` (levels, cats) or logical (`is.factor`)

**See Also**

[activeCat](#), [catalyze](#), [set.cats](#), [as.factor](#), [is.factor](#)

**Examples**

```
set.seed(0)
r <- rast(nrows=10, ncols=10)
values(r) <- sample(3, ncell(r), replace=TRUE)
is.factor(r)

cls <- data.frame(id=1:3, cover=c("forest", "water", "urban"))
levels(r) <- cls
is.factor(r)
r

plot(r, col=c("green", "blue", "light gray"))
text(r, digits=3, cex=.75, halo=TRUE)

# raster starts at 3
x <- r + 2
is.factor(x)

# Multiple categories
d <- data.frame(id=3:5, cover=cls[,2], letters=letters[1:3], value=10:12)
levels(x) <- d
x

# get current index
activeCat(x)
# set index
activeCat(x) <- 3
activeCat(x)
activeCat(x) <- "letters"
plot(x, col=c("green", "blue", "light gray"))
text(x, digits=3, cex=.75, halo=TRUE)

r <- as.numeric(x)
r

p <- as.polygons(x)
plot(p, "letters", col=c("green", "blue", "light gray"))
```

---

fillHoles

---

*Remove holes from polygons*


---

**Description**

Remove the holes in SpatVector polygons. If inverse=TRUE the holes are returned (as polygons).

**Usage**

```
## S4 method for signature 'SpatVector'
fillHoles(x, inverse=FALSE)
```

**Arguments**

x	SpatVector
inverse	logical. If TRUE the holes are returned as polygons

**Value**

SpatVector

**Examples**

```
x <- rbind(c(-10,0), c(140,60), c(160,0), c(140,-55))
hole <- rbind(c(80,0), c(105,13), c(120,2), c(105,-13))

z <- rbind(cbind(object=1, part=1, x, hole=0),
           cbind(object=1, part=1, hole, hole=1))
colnames(z)[3:4] <- c('x', 'y')
p <- vect(z, "polygons", atts=data.frame(id=1))
p

f <- fillHoles(p)
g <- fillHoles(p, inverse=TRUE)

plot(p, lwd=16, border="gray", col="light yellow")
polys(f, border="blue", lwd=3, density=4, col="orange")
polys(g, col="white", lwd=3)
```

---

fillTime	<i>Fill time gaps in a SpatRaster</i>
----------	---------------------------------------

---

**Description**

Add empty layers in between existing layers such that the time step between each layer is the same. See [approximate](#) to estimate values for these layer (and other missing values)

**Usage**

```
## S4 method for signature 'SpatRaster'
fillTime(x, filename="", ...)
```

**Arguments**

x	SpatRaster
filename	character. Output filename
...	list with named options for writing files as in <a href="#">writeRaster</a>

Value

SpatRaster

See Also

[approximate](#)

Examples

```
r <- rast(system.file("ex/logo.tif", package="terra"))
s <- c(r, r)
time(s) <- as.Date("2001-01-01") + c(0:2, 5:7)
time(s)
ss <- fillTime(s)
time(ss)

a <- approximate(ss)
```

---

flip	<i>Flip or reverse a raster</i>
------	---------------------------------

---

Description

Flip the values of a SpatRaster by inverting the order of the rows (vertical=TRUE) or the columns (vertical=FALSE).  
rev is the same as a horizontal *\*and\** a vertical flip.

Usage

```
## S4 method for signature 'SpatRaster'
flip(x, direction="vertical", filename="", ...)

## S4 method for signature 'SpatVector'
flip(x, direction="vertical")

## S4 method for signature 'SpatRaster'
rev(x)
```

Arguments

x	SpatRaster or SpatVector
direction	character. Should (partially) match "vertical" to flip by rows, or "horizontal" to flip by columns
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>



Value

SpatRaster

See Also

[trans](#), [rotate](#)

Examples

```
r <- rast(nrow=18, ncol=36)
m <- matrix(1:ncell(r), nrow=18)
values(r) <- as.vector(t(m))
rx <- flip(r, direction="h")

values(r) <- as.vector(m)
ry <- flip(r, direction="v")

v <- rev(r)
```

---

focal	<i>Focal values</i>
-------	---------------------

---

Description

Calculate focal ("moving window") values for each cell.

Usage

```
## S4 method for signature 'SpatRaster'
focal(x, w=3, fun="sum", ..., na.policy="all", fillvalue=NA,
      expand=FALSE, silent=TRUE, filename="", overwrite=FALSE, wopt=list())
```

Arguments

x	SpatRaster
w	window. The window can be defined as one (for a square) or two numbers (row, col); or with an odd-sized weights matrix. See Details.
fun	function that takes multiple numbers, and returns a numeric vector (one or multiple numbers). For example mean, modal, min or max
...	additional arguments passed to fun such as na.rm
na.policy	character. Can be used to determine the cells of x for which focal values should be computed. Must be one of "all" (compute for all cells), "only" (only for cells that are NA) or "omit" (skip cells that are NA). Note that the value of this argument does not affect which cells around each focal cell are included in the computations (use na.rm=TRUE to ignore cells that are NA for that)
fillvalue	numeric. The value of the cells in the virtual rows and columns outside of the raster

expand	logical. If TRUE The value of the cells in the virtual rows and columns outside of the raster are set to be the same as the value on the border. Only available for "build-in" funs such as mean, sum, min and max
silent	logical. If TRUE error messages are printed that may occur when trying fun to determine the length of the returned value. This can be useful in debugging a fun that does not work
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	additional arguments for writing files as in <a href="#">writeRaster</a>

## Details

**focal** The window used must have odd dimensions. If you need even sides, you can use a matrix and add a column or row with weights of zero.

Window values are typically 0 or 1, or a value between 0 and 1 if you are using a rectangular area and/or the "sum" function. They can also be NA; these are ignored in the computation. That can be useful to compute, for example, the minimum or maximum value for a non-rectangular area.

The "mean" function is a special case, as zero weights are ignored automatically.

The "sum" function returns NA if all focal cells are NA and `na.rm=TRUE`. R would normally return a zero in these cases. See the difference between `focal(x, fun=sum, na.rm=TRUE)` and `focal(x, fun=\(i) sum(i, na.rm=TRUE))`

Example weight matrices

Laplacian filter: `filter=matrix(c(0,1,0,1,-4,1,0,1,0), nrow=3)`

Sobel filters (for edge detection): `fx=matrix(c(-1,-2,-1,0,0,0,1,2,1), nrow=3)` `fy=matrix(c(1,0,-1,2,0,-2,1,0,-1), nrow=3)`

## Value

SpatRaster

## See Also

[focalMat](#), [focalValues](#), [focal3D](#), [focalCor](#), [focalReg](#), [focalCpp](#)

## Examples

```
r <- rast(ncols=10, nrows=10, ext(0, 10, 0, 10))
values(r) <- 1:ncell(r)

f <- focal(r, w=3, fun=function(x, ...) quantile(x, c(.25, .5, .75), ...), na.rm=TRUE)

f <- focal(r, w=3, fun="mean")

# the following two statements are equivalent:
a <- focal(r, w=matrix(1/9, nc=3, nr=3))
b <- focal(r, w=3, fun=mean, na.rm=FALSE)
```

```

# but this is different
d <- focal(r, w=3, fun=mean, na.rm=TRUE)

## illustrating the effect of different
## combinations of na.rm and na.policy
v <- vect(system.file("ex/lux.shp", package="terra"))
r <- rast(system.file("ex/elev.tif", package="terra"))
r[45:50, 45:50] <- NA

# also try "mean" or "min"
f <- "sum"
# na.rm=FALSE
plot(focal(r, 5, f) , fun=lines(v))

# na.rm=TRUE
plot(focal(r, 5, f, na.rm=TRUE), fun=lines(v))

# only change cells that are NA
plot(focal(r, 5, f, na.policy="only", na.rm=TRUE), fun=lines(v))

# do not change cells that are NA
plot(focal(r, 5, f, na.policy="omit", na.rm=TRUE), fun=lines(v))

# does not do anything
# focal(r, 5, f, na.policy="only", na.rm=FALSE)

```

focal3D

*Three-dimensional focal values*

## Description

Calculate focal ("moving window") values for the three-dimensional neighborhood (window) of focal cells. See [focal](#) for two-dimensional focal computation.

## Usage

```

## S4 method for signature 'SpatRaster'
focal3D(x, w=3, fun=mean, ..., na.policy="all", fillvalue=NA, pad=FALSE,
padvalue=fillvalue, expand=FALSE, silent=TRUE,
filename="", overwrite=FALSE, wopt=list())

```

## Arguments

x	SpatRaster
w	window. A rectangular prism (cuboid) defined by three numbers or by a three-dimensional array. The values are used as weights, and are usually zero, one, NA, or fractions. The window used must have odd dimensions. If you desire to use even sides, you can use an array, and pad the values with rows and/or columns that contain only NAs.

fun	function that takes multiple numbers, and returns one or multiple numbers for each focal area. For example mean, modal, min or max
...	additional arguments passed to fun such as <code>na.rm</code>
na.policy	character. Can be used to determine the cells of x for which focal values should be computed. Must be one of "all" (compute for all cells), "only" (only for cells that are NA) or "omit" (skip cells that are NA). Note that the value of this argument does not affect which cells around each focal cell are included in the computations (use <code>na.rm=TRUE</code> to ignore cells that are for that)
fillvalue	numeric. The value of the cells in the virtual rows and columns outside of the raster
pad	logical. Add virtual layers before the first and after the last layer
padvalue	numeric. The value of the cells in the virtual layers
expand	logical. Add virtual layers before the first or after the last layer that are the same as the first or last layers. If TRUE, arguments pad and padvalue are ignored
silent	logical. If TRUE error messages are printed that may occur when trying fun to determine the length of the returned value. This can be useful in debugging a function passed to fun that does not work
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## See Also

[focal](#)

## Examples

```
r <- rast(system.file("ex/logo.tif", package="terra"))
x <- focal3D(r, c(5,5,3), na.rm=TRUE)

a <- array(c(0,1,0,1,1,1,0,1,0, rep(1,9), 0,1,0,1,1,1,0,1,0), c(3,3,3))
a[a==0] <- NA
z <- focal3D(r, a, na.rm=TRUE)
```

---

focalCor	<i>Focal function across two layers</i>
----------	---

---

## Description

Calculate values such as a correlation coefficient for focal regions in two neighboring layers. A function is applied to the first and second layer, then to the second and third layer, etc.

## Usage

```
## S4 method for signature 'SpatRaster'
focalCor(x, w=3, fun, ..., fillvalue=NA,
         filename="", overwrite=FALSE, wopt=list())
```

## Arguments

x	SpatRaster with at least two layers
w	window. The window can be defined as one (for a square) or two numbers (row, col); or with an odd-sized weights matrix. See the Details section in <a href="#">focal</a>
fun	A function with at least two arguments (one for each layer)
...	additional arguments for fun
fillvalue	numeric. The value of the cells in the virtual rows and columns outside of the raster
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## See Also

[layerCor](#), [focalReg](#), [focal](#)

## Examples

```
r <- rast(system.file("ex/logo.tif", package="terra"))
set.seed(0)
r[[1]] <- flip(r[[1]], "horizontal")
r[[2]] <- flip(r[[2]], "vertical") + init(rast(r,1), runif)
r[[3]] <- init(rast(r,1), runif)

# suppress warning "the standard deviation is zero"
suppressWarnings(x <- focalCor(r, w=5, cor))
```

```
# this warning does not occur when using a larger window
x <- focalCor(r, w=9, function(x, y) cor(x, y))
plot(x)
```

focalCpp

*Compute focal values with an iterating C++ function*

## Description

Calculate focal values with a C++ function that iterates over cells to speed up computations by avoiding an R loop (with `apply`).

See [focal](#) for an easier to use method.

## Usage

```
## S4 method for signature 'SpatRaster'
focalCpp(x, w=3, fun, ..., fillvalue=NA,
silent=TRUE, filename="", overwrite=FALSE, wopt=list())
```

## Arguments

x	SpatRaster
w	window. The window can be defined as one (for a square) or two numbers (row, col); or with an odd-sized weights matrix. See the Details section in <a href="#">focal</a>
fun	<a href="#">cppFunction</a> that iterates over cells. For C++ functions that operate on a single focal window, or for R functions use <a href="#">focal</a> instead. The function must have at least three arguments. The first argument can have any name, but it must be a <code>Rcpp::NumericVector</code> , <code>Rcpp::IntegerVector</code> or a <code>std::vector&lt;double&gt;</code> . This is the container that receives the focal values. The other two arguments <code>ni</code> and <code>wi</code> must be of type <code>size_t</code> . <code>ni</code> represents the number of cells and <code>nw</code> represents the size of (number of elements in) the window
...	additional arguments to fun
fillvalue	numeric. The value of the cells in the virtual rows and columns outside of the raster
silent	logical. If TRUE error messages are printed that may occur when trying fun to determine the length of the returned value. This can be useful in debugging a fun that does not work
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

**See Also**

[focal](#), [focalValues](#)

**Examples**

```
## Not run:
library(Rcpp)
cppFunction(
  'NumericVector sum_and_multiply(NumericVector x, double m, size_t ni, size_t nw) {
    NumericVector out(ni);
    // loop over cells
    size_t start = 0;
    for (size_t i=0; i<ni; i++) {
      size_t end = start + nw;
      // compute something for a window
      double v = 0;
      // loop over the values of a window
      for (size_t j=start; j<end; j++) {
        v += x[j];
      }
      out[i] = v * m;
      start = end;
    }
    return out;
  }'
```

```
)

nr <- nc <- 10
r <- rast(ncols=nc, nrows=nr, ext= c(0, nc, 0, nr))
values(r) <- 1:ncell(r)

raw <- focalCpp(r, w=3, fun=sum_and_multiply, fillvalue=0, m=10)

# same as
f1 <- focal(r, w=3, fun=sum, fillvalue=0) *10
all(values(f1) == values(raw))

# and as
ffun <- function(x, m) { sum(x) * m }
f2 <- focal(r, w=3, fun=ffun, fillvalue=0, m=10)

# You can also use an R function with focalCpp but this
# is not recommended

R_sm_iter <- function(x, m, ni, nw) {
  out <- NULL
  for (i in 1:ni) {
    start <- (i-1) * nw + 1
    out[i] <- sum(x[start:(start+nw-1)]) * m
  }
  out
}
```

```
}  
  
fr <- focalCpp(r, w=3, fun=R_sm_iter, fillvalue=0, m=10)  
  
## End(Not run)
```

---

focalMat	<i>Focal weights matrix</i>
----------	-----------------------------

---

**Description**

Make a focal ("moving window") weight matrix for use in the [focal](#) function. The sum of the values adds up to one.

**Usage**

```
focalMat(x, d, type=c('circle', 'Gauss', 'rectangle'), fillNA=FALSE)
```

**Arguments**

x	SpatRaster
d	numeric. If type=circle, the radius of the circle (in units of the crs). If type=rectangle the dimension of the rectangle (one or two numbers). If type=Gauss the size of sigma, and optionally another number to determine the size of the matrix returned (default is 3*sigma)
type	character indicating the type of filter to be returned
fillNA	logical. If TRUE, zeros are set to NA such that they are ignored in the computations. Only applies to type="circle"

**Value**

matrix that can be used with [focal](#)

**Examples**

```
r <- rast(ncols=180, nrows=180, xmin=0)  
focalMat(r, 2, "circle")  
  
focalMat(r, c(2,3), "rect")  
  
# Gaussian filter for square cells  
gf <- focalMat(r, 1, "Gauss")
```



---

focalReg*Focal regression*

---

### Description

Calculate the coefficients for a focal ("moving window") OLS regression model.

### Usage

```
## S4 method for signature 'SpatRaster'  
focalReg(x, w=3, na.rm=TRUE,  
fillvalue=NA, filename="", ...)
```

### Arguments

x	SpatRaster with at least two layers. The first is the "Y" (dependent) variable and the remainder are the "X" (independent) variables
w	window. The window can be defined as one (for a square) or two numbers (row, col); or with an odd-sized weights matrix. See the Details section in <a href="#">focal</a>
na.rm	logical. Should missing values be removed?
fillvalue	numeric. The value of the cells in the virtual rows and columns outside of the raster
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

### Value

SpatRaster

### See Also

[focal](#), [focalValues](#)

### Examples

```
r <- rast(ncols=10, nrows=10, ext(0, 10, 0, 10))  
values(r) <- 1:ncell(r)  
x <- c(r, init(r, runif) * r)  
f <- focalReg(x, 3)
```

---

focalValues

*Get focal values*


---

### Description

Get a matrix in which each row had the focal values of a cell. These are the values of a cell and a rectangular window around it.

### Usage

```
## S4 method for signature 'SpatRaster'
focalValues(x, w=3, row=1, nrow=nrow(x), fill=NA)
```

### Arguments

x	SpatRaster or SpatVector
w	window. The window can be defined as one (for a square) or two odd numbers (row, col); or with an odd sized matrix
row	positive integer. Row number to start from, should be between 1 and nrow(x)
nrow	positive integer. How many rows?
fill	numeric used as values for imaginary cells outside the raster

### Value

matrix

### Examples

```
r <- rast(ncol=4, nrow=4, crs="+proj=utm +zone=1 +datum=WGS84")
values(r) <- 1:ncell(r)
focalValues(r)
```

---

freq

*Frequency table*


---

### Description

Frequency table of the values of a SpatRaster. NAs are not counted unless value=NA.

### Usage

```
## S4 method for signature 'SpatRaster'
freq(x, digits=0, value=NULL, bylayer=TRUE, usenames=FALSE)
```

**Arguments**

x	SpatRaster
digits	integer. Used for rounding the values before tabulation. Ignored if NA
value	numeric. An optional single value to only count the number of cells with that value. This value can be NA
bylayer	logical. If TRUE tabulation is done by layer
usenames	logical. If TRUE layers are identified by their names instead of their numbers. Only relevant if bylayer is TRUE

**Value**

A data.frame with 3 columns (layer, value, count) unless bylayer=FALSE in which case a data.frame with two columns is returned (value, count).

**Examples**

```
r <- rast(nrows=10, ncols=10)
set.seed(2)
values(r) <- sample(5, ncell(r), replace=TRUE)

freq(r)

x <- c(r, r/3)
freq(x, bylayer=FALSE)
freq(x)

freq(x, digits=1)
freq(x, digits=-1)

freq(x, value=5)
```

gaps

*Find gaps between polygons***Description**

Get the gaps between polygons of a SpatVector

**Usage**

```
## S4 method for signature 'SpatVector'
gaps(x)
```

**Arguments**

x	SpatVector
---	------------

**Value**

SpatVector

**See Also**

[sharedPaths](#), [topology](#), and [fillHoles](#) to get or remove polygon holes

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
h <- convHull(v[-12], "NAME_1")
g <- gaps(h)
```

---

gdal	<i>GDAL version, supported file formats, and cache size</i>
------	---

---

**Description**

Set the GDAL warning level or get a data.frame with the available GDAL drivers (file formats), or, if warn=NA and drivers=FALSE, you get the version numbers of one or all of the GDAL, PROJ and GEOS libraries.

GDAL is the software library that terra builds on to read and write spatial data and for some raster data processing. PROJ is used for transformation of coordinates ("projection") and GEOS is used for geometric operations with vector data.

**Usage**

```
gdal(warn=NA, drivers=FALSE, lib="gdal")
gdalCache(size=NA)
setGDALconfig(option, value="")
getGDALconfig(option)
```

**Arguments**

warn	If NA and drivers=FALSE, the version of the library specified by lib is returned. Otherwise, the value should be an integer between 1 and 4 representing the level of GDAL warnings and errors that are passed to R. 1 = warnings and errors; 2 = errors only (recoverable errors as a warning); 3 = irrecoverable errors only; 4 = ignore all errors and warnings. The default setting is 3
drivers	logical. If TRUE a data.frame with the raster and vector data formats that are available.
lib	character. "gdal", "proj", or "geos", or any other value to get the versions numbers of all three
size	numeric. The new cache size in MB

option	character. GDAL configuration option name, or a "name=value" string (in which case the value argument is ignored)
value	character. value for GDAL configuration option. Use "" to reset it to its default value

**Value**

character

**See Also**

[describe](#) for file-level metadata "GDALInfo"

**Examples**

```
gdal()
gdal(2)
head(gdal(drivers=TRUE))
```

---

geom

*Get the geometry (coordinates) of a SpatVector*

---

**Description**

Get the geometry of a SpatVector. If wkt=FALSE, this is a five-column matrix or data.frame: the vector object ID, the IDs for the parts of each object (e.g. five polygons that together are one spatial object), the x (longitude) and y (latitude) coordinates, and a flag indicating whether the part is a "hole" (only relevant for polygons).

If wkt=TRUE, the "well-known text" representation is returned as a character vector.

**Usage**

```
## S4 method for signature 'SpatVector'
geom(x, wkt=FALSE, hex=FALSE, df=FALSE, list=FALSE, xnm="x", ynm="y")
```

**Arguments**

x	SpatVector
wkt	logical. If TRUE the WKT geometry is returned (unless hex is also TRUE)
hex	logical. If TRUE the hexadecimal geometry is returned
df	logical. If TRUE a data.frame is returned instead of a matrix (only if wkt=FALSE, hex=FALSE, and list=FALSE)
list	logical. If TRUE a nested list is returned with data.frames of coordinates
xnm	character. If list=TRUE the "x" column name for the coordinates data.frame
ynm	character. If list=TRUE the "y" column name for the coordinates data.frame

**Value**

matrix, vector, data.frame, or list

**See Also**

[crds](#), [xyFromCell](#)

**Examples**

```
x1 <- rbind(c(-175,-20), c(-140,55), c(10, 0), c(-140,-60))
x2 <- rbind(c(-125,0), c(0,60), c(40,5), c(15,-45))
x3 <- rbind(c(-10,0), c(140,60), c(160,0), c(140,-55))
x4 <- rbind(c(80,0), c(105,13), c(120,2), c(105,-13))
z <- rbind(cbind(object=1, part=1, x1), cbind(object=2, part=1, x2),
          cbind(object=3, part=1, x3), cbind(object=3, part=2, x4))
colnames(z)[3:4] <- c('x', 'y')
z <- cbind(z, hole=0)
z[(z[, "object"]==3 & z[, "part"]==2), "hole"] <- 1

p <- vect(z, "polygons")
geom(p)

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
g <- geom(v)
head(g)

w <- geom(v, wkt=TRUE)
substr(w, 1, 60)
```

---

geomtype

*Geometry type of a SpatVector*

---

**Description**

Get the geometry type (points, lines, or polygons) of a SpatVector or the data types of the fields (attributes, variables) of a SpatVector.

**Usage**

```
## S4 method for signature 'SpatVector'
geomtype(x)

## S4 method for signature 'SpatVector'
datatype(x)

## S4 method for signature 'SpatVector'
is.points(x)
```

```
## S4 method for signature 'SpatVector'
is.lines(x)

## S4 method for signature 'SpatVector'
is.polygons(x)
```

### Arguments

x                      SpatVector

### Value

character

### Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)

geomtype(v)
is.polygons(v)
is.lines(v)
is.points(v)

names(v)
datatype(v)
```

---

global

*global statistics*

---

### Description

Compute global statistics, that is summarized values of an entire SpatRaster.

If x is very large global will fail, except when fun is one of "mean", "min", "max", "sum", "prod", "range" (min and max), "rms" (root mean square), "sd" (sample standard deviation), "sdpop" (population standard deviation), "isNA" (number of cells that are NA), "notNA" (number of cells that are not NA).

You can compute a weighted mean or sum by providing a SpatRaster with weights.

### Usage

```
## S4 method for signature 'SpatRaster'
global(x, fun="mean", weights=NULL, ...)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>fun</code>	function to be applied to summarize the values by zone. Either as one of these character values: "max", "min", "mean", "sum", "range", "rms" (root mean square), "sd", "std" (population sd, using n rather than n-1), "isNA", "notNA"; or a proper R function (but these may fail for very large <code>SpatRasters</code> )
<code>...</code>	additional arguments passed on to <code>fun</code>
<code>weights</code>	<code>NULL</code> or <code>SpatRaster</code>

**Value**

A `data.frame` with a row for each layer

**See Also**

[zonal](#) for "zonal" statistics, and [app](#) or [Summary-methods](#) for "local" statistics, and [extract](#) for summarizing values for polygons. Also see [focal](#) for "focal" or "moving window" operations.

**Examples**

```
r <- rast(ncols=10, nrows=10)
values(r) <- 1:ncell(r)
global(r, "sum")
global(r, "mean", na.rm=TRUE)
```

---

gridDistance

*Distance on a grid*


---

**Description**

The function calculates the distance to cells of a `SpatRaster` when the path has to go through the centers of the eight neighboring raster cells.

The distance is in meters if the coordinate reference system (CRS) of the `SpatRaster` is longitude/latitude (`+proj=longlat`) and in the units of the CRS (typically meters) in other cases.

Distances are computed by summing local distances between cells, which are connected with their neighbors in 8 directions.

The shortest distance to the cells with the target value is computed for all cells that are not NA. Cells that are NA cannot be traversed and are ignored, unless the target itself is NA, in which case the distance to the nearest cell that is not NA is computed for all cells that are NA.

**Usage**

```
## S4 method for signature 'SpatRaster'
gridDist(x, target=0, scale=1000, maxiter=50, filename="", ...)
```



**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>target</code>	numeric. value of the target cells (where to compute distance to)
<code>scale</code>	numeric. Scale factor for longitude/latitude data (1 = m, 1000 = km)
<code>maxiter</code>	numeric. The maximum number of iterations. Increase this number if you get the warning that <code>costDistance</code> did not converge
<code>filename</code>	character. output filename (optional)
<code>...</code>	additional arguments as for <a href="#">writeRaster</a>

**Value**

`SpatRaster`

**See Also**

See [distance](#) for "as the crow flies" distance, and [costDist](#) for distance across a landscape with variable friction

**Examples**

```
# global lon/lat raster
r <- rast(ncol=10,nrow=10, vals=1)
r[48] <- 0
r[66:68] <- NA
d <- gridDist(r)
plot(d)

# planar
crs(r) <- "+proj=utm +zone=15 +ellps=GRS80 +datum=NAD83 +units=m +no_defs"
d <- gridDist(r)
plot(d)

# distance to cells that are not NA
rr <- classify(r, cbind(1, NA))
dd <- gridDist(rr, NA)
```

---

head and tail

---

*Show the head or tail of a Spat\* object*


---

**Description**

Show the head (first values) or tail (last values) of a `SpatRaster` or of the attributes of a `SpatVector`.

**Usage**

```
head(x, ...)  
tail(x, ...)
```

**Arguments**

x	SpatRaster or SpatVector
...	additional arguments passed on to other methods

**Value**

matrix (SpatRaster) or data.frame (SpatVector)

**See Also**

[show](#), [geom](#)

**Examples**

```
r <- rast(nrows=25, ncols=25)  
values(r) <- 1:ncell(r)  
head(r)  
tail(r)
```

---

hist	<i>Histogram</i>
------	------------------

---

**Description**

Create a histogram of the values of a SpatRaster. For large datasets a sample of maxcell is used.

**Usage**

```
## S4 method for signature 'SpatRaster'  
hist(x, layer, maxcell=1000000, plot=TRUE, maxnl=16, main, ...)
```

**Arguments**

x	SpatRaster
layer	positive integer or character to indicate layer numbers (or names). If missing, all layers up to maxnl are used
maxcell	integer. To regularly sample very large objects
plot	logical. Plot the histogram or only return the histogram values
maxnl	positive integer. The maximum number of layers to use. Ignored if layer is not missing
main	character. Main title(s) for the plot. Default is the value of <a href="#">names</a>
...	additional arguments. See <a href="#">hist</a>

**Value**

This function is principally used for plotting a histogram, but it also returns an object of class "histogram" (invisibly if plot=TRUE).

**See Also**

[pairs](#), [boxplot](#)

**Examples**

```
r1 <- r2 <- rast(nrows=50, ncols=50)
values(r1) <- runif(ncell(r1))
values(r2) <- runif(ncell(r1))
rs <- r1 + r2
rp <- r1 * r2

opar <- par(no.readonly =TRUE)
par(mfrow=c(2,2))
plot(rs, main='sum')
plot(rp, main='product')
hist(rs)
a <- hist(rp)
a
x <- c(rs, rp, sqrt(rs))
hist(x)
par(opar)
```

---

ifel

*ifelse for SpatRasters*


---

**Description**

Implementation of [ifelse](#) for SpatRasters. This method allows for a concise expression of what can otherwise be achieved with a combination of [classify](#), [mask](#), and [cover](#).

ifel is an R equivalent to the Con method in ArcGIS (arcpy).

**Usage**

```
## S4 method for signature 'SpatRaster'
ifel(test, yes, no, filename="", ...)
```

**Arguments**

test	SpatRaster
yes	SpatRaster or numeric
no	SpatRaster or numeric
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Examples**

```

r <- rast(nrows=5, ncols=5, xmin=0, xmax=1, ymin=0, ymax=1)
values(r) <- c(-10:0, NA, NA, NA, 0:10)

x <- ifel(r > 1, 1, r)
# same as
a <- classify(r, cbind(1, Inf, 1))
# or
b <- app(r, fun=function(i) {i[i > 1] <- 1; i})
# or
d <- clamp(r, -Inf, 1)
# or (not recommended for large datasets)
e <- r
e[e>1] <- 1

## other examples
f <- ifel(is.na(r), 100, r)

z <- ifel(r > -2 & r < 2, 100, 0)

# nested expressions
y <- ifel(r > 1, 1, ifel(r < -1, -1, r))

k <- ifel(r > 0, r+10, ifel(r < 0, r-10, 3))

```

image

*SpatRaster image method***Description**

Plot (make a map of) the values of a SpatRaster via [image](#). See [plot](#) if you need more fancy options such as a legend.

**Usage**

```

## S4 method for signature 'SpatRaster'
image(x, y=1, maxcell=500000, ...)

```

**Arguments**

x	SpatRaster
y	positive integer indicating the layer to be plotted, or a character indicating the name of the layer
maxcell	positive integer. Maximum number of cells to use for the plot
...	additional arguments as for graphics:: <a href="#">image</a>

**See Also**[plot](#)**Examples**

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
image(r)
image(r, col=rainbow(24))
```

---

impose	<i>Impose the geometry of a SpatRaster to those in a SpatRasterCollection.</i>
--------	--

---

**Description**

Warp the members of a SpatRasterCollection to match the geometry of a SpatRaster.

**Usage**

```
## S4 method for signature 'SpatRasterCollection'
impose(x, y, filename="", ...)
```

**Arguments**

x	SpatRasterCollection
y	SpatRaster
filename	character. Output filename
...	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**[resample](#)

---

initialize	<i>Initialize a SpatRaster with values</i>
------------	--

---

## Description

Create a SpatRaster with values reflecting a cell property: 'x', 'y', 'col', 'row', 'cell' or 'chess'. Alternatively, a function can be used. In that case, cell values are initialized without reference to pre-existing values. E.g., initialize with a random number (fun=[runif](#)). While there are more direct ways of achieving this for small objects (see examples) for which a vector with all values can be created in memory, the init function will also work for SpatRaster objects with many cells.

## Usage

```
## S4 method for signature 'SpatRaster'
init(x, fun, filename="", ...)
```

## Arguments

x	SpatRaster
fun	function to be applied. This must be a either single number, multiple numbers, a function, or one of a set of known character values. A function must take the number of cells as a single argument to return a vector of values with a length equal to the number of cells, such as fun= <a href="#">runif</a> . Allowed character values are 'x', 'y', 'row', 'col', 'cell', and 'chess' to get the x or y coordinate, row, col or cell number or a chessboard pattern (alternating 0 and 1 values)
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## Examples

```
r <- rast(ncols=10, nrows=5, xmin=0, xmax=10, ymin=0, ymax=5)
x <- init(r, fun="cell")
y <- init(r, fun=runif)

# initialize with a single value
z <- init(r, fun=8)
```

inplace

*Change values in-place***Description**

These "in-place" replacement methods assign new value to an object without making a copy. That is efficient, but if there is a copy of the object that you made by standard assignment (e.g. with `y <- x`), that copy is also changed.

`set.names` is the in-place replacement version of `names<-`.

`set.ext` is the in-place replacement version of `ext<-`

`set.values` is the in-place replacement version of `[<-`.

`set.cats` is the in-place replacement version of `categories`

`set.crs` is the in-place replacement version of `crs<-`

**Usage**

```
## S4 method for signature 'SpatRaster'
set.names(x, value, index=1:nlyr(x), validate=FALSE)
## S4 method for signature 'SpatRasterDataset'
set.names(x, value, index=1:length(x), validate=FALSE)
## S4 method for signature 'SpatVector'
set.names(x, value, index=1:ncol(x), validate=FALSE)

## S4 method for signature 'SpatRaster'
set.ext(x, value)
## S4 method for signature 'SpatVector'
set.ext(x, value)

## S4 method for signature 'SpatRaster'
set.crs(x, value)
## S4 method for signature 'SpatVector'
set.crs(x, value)

## S4 method for signature 'SpatRaster'
set.values(x, cells, values, layer=0)

## S4 method for signature 'SpatRaster'
set.cats(x, layer=1, value, active=2)

## S4 method for signature 'SpatRaster'
set.RGB(x, value)
```

**Arguments**

`x` `SpatRaster`

value	character for <code>set.names</code> . For <code>set.cats</code> : a data.frame with columns (value, category) or vector with category names. For <code>set.RGB</code> 3 or 4 numbers indicating the RGB(A) layers
index	positive integer indicating layer(s) to assign a name to
validate	logical. Make names valid and/or unique?
cells	cell numbers or missing
values	replacement values or missing to load all values into memory
layer	positive integer(s) indicating to which layer(s) to you want to assign these categories or to which you want to set these values. A number < 1 indicates "all layers"
active	positive integer indicating the active category (column number in value

### Value

logical (invisibly)

### Examples

```
s <- rast(ncols=5, nrows=5, nlyrs=3)
x <- s
names(s)
names(s) <- c("a", "b", "c")
names(s)
names(x)

x <- s
set.names(s, c("e", "f", "g"))
names(s)
names(x)

set.ext(x, c(0,180,0,90))

f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)

#values from file to memory
set.values(r)

# change values
set.values(r, 1:1000, 900)
```

---

inset

---

*Make an inset map*


---

### Description

Make an inset map or scale the extent of a `SpatVector`



**Usage**

```
## S4 method for signature 'SpatVector'
inset(x, e, loc="", scale=0.2, background="white",
      perimeter=TRUE, box=NULL, pper, pbox, ...)

## S4 method for signature 'SpatRaster'
inset(x, e, loc="", scale=0.2, background="white",
      perimeter=TRUE, box=NULL, pper, pbox, ...)

## S4 method for signature 'SpatVector'
inext(x, e, y=NULL, gap=0)
```

**Arguments**

x	SpatVector, SpatRaster
e	SpatExtent to set the size and location of the inset. Or missing
loc	character. One of "bottomright", "bottom", "bottomleft", "left", "topleft", "top", "topright", "right", "center"
scale	numeric. The relative size of the inset, used when x is missing
background	color for the background of the inset. Use NA for no background color
perimeter	logical. If TRUE a perimeter (border) is drawn around the inset
box	SpatExtent or missing, to draw a box on the inset, e.g. to show where the map is located in a larger area
pper	list with graphical parameters (arguments) such as col and lwd for the perimeter line
pbox	list with graphical parameters (arguments) such as col and lwd for the box (line)
...	additional arguments passed to plot for the drawing of x
y	SpatVector. If not NULL, y is scaled based with the parameters for x. This is useful, for example, when x represent boundaries, and y points within these boundaries
gap	numeric to add space between the SpatVector and the SpatExtent

**Value**

scaled and shifted SpatVector or SpatRaster (returned invisibly)

**See Also**

[sbar](#), [rescale](#), [shift](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
x <- v[v$NAME_2 == "Diekirch", ]
```

```

plot(x, density=10, col="blue")
inset(v)

# more elaborate
plot(x, density=10, col="blue")
inset(v, col = "brown", border="lightgrey", perimeter=TRUE,
pper=list(col="orange", lwd=3, lty=2),
box=ext(x), pbox=list(col="blue", lwd=2))

cols <- rep("light grey", 12)
cols[2] <- "red"
e <- ext(c(6.2, 6.3, 49.9, 50))
b <- ext(x)+0.02
inset(v, e=e, col=cols, box=b)

# with a SpatRaster
ff <- system.file("ex/elev.tif", package="terra")
r <- rast(ff)
r <- crop(r, ext(x) + .01)
plot(r, type="int", mar=c(2,2,2,2), plg=list(x="topright"))
lines(v, lwd=1.5)
lines(x, lwd=2.5)
inset(v, col=cols, loc="topleft", scale=0.15)

# a more complex one
plot(r, plg=list(title="meter\n", shrink=.2, cex=.8))
lines(v, lwd=4, col="white")
lines(v, lwd=1.5)
lines(x, lwd=2.5)
text(x, "NAME_2", cex=1.5, halo=TRUE)
sbar(6, c(6.04, 49.785), type="bar", below="km", label=c(0,3,6), cex=.8)
s <- inset(v, col=cols, box=b, scale=.2, loc="topright", background="light yellow",
pbox=list(lwd=2, lty=5, col="blue"))

# note the returned inset SpatVector
s
lines(s, col="orange")

```

---

interpIDW

---

Interpolate points using a moving window

---

## Description

Interpolate points within a moving window using inverse distance weighting. The maximum number of points used can be restricted, optionally by selecting the nearest points.

## Usage

```

## S4 method for signature 'SpatRaster,SpatVector'
interpIDW(x, y, field, radius, power=2, smooth=0,

```

```

maxPoints=Inf, minPoints=1, near=FALSE, fill=NA, filename="", ...)

## S4 method for signature 'SpatRaster,matrix'
interpIDW(x, y, radius, power=2, smooth=0,
          maxPoints=Inf, minPoints=1, near=FALSE, fill=NA, filename="", ...)

```

## Arguments

<code>x</code>	<code>SpatRaster</code>
<code>y</code>	<code>SpatVector</code> or matrix with three columns (x,y,z)
<code>field</code>	character. field name in <code>SpatVector</code> <code>y</code>
<code>radius</code>	numeric. The radius of the circle (single number). If <code>near=FALSE</code> , it is also possible to use two or three numbers. Two numbers are interpreted as the radii of an ellipse (x and y-axis). A third number should indicated the desired, counter clockwise, rotation of the ellipse (in degrees)
<code>power</code>	numeric. Weighting power
<code>smooth</code>	numeric. Smoothing parameter
<code>minPoints</code>	numeric. The minimum number of points to use. If fewer points are found in a search ellipse it is considered empty and the fill value is returned
<code>maxPoints</code>	numeric. The maximum number of points to consider in a search area. Additional points are ignored. If fewer points are found, the fill value is returned
<code>near</code>	logical. If <code>maxPoints</code> is reached, should the nearest points within the neighborhood be used?
<code>fill</code>	numeric. value to use to fill empty cells
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

`SpatRaster`

## See Also

[rasterizeWin](#), [rasterize](#), [interpNear](#), [interpolate](#)

## Examples

```

r <- rast(ncol=100, nrow=100, crs="local", xmin=0, xmax=50, ymin=0, ymax=50)
set.seed(100)
x <- runif(25, 5, 45)
y <- runif(25, 5, 45)
z <- sample(25)
xyz <- cbind(x,y,z)

x <- interpIDW(r, xyz, radius=5, power=1, smooth=1, maxPoints=5)

```

---

interpNear	<i>Nearest neighbor interpolation</i>
------------	---------------------------------------

---

### Description

Nearest neighbor interpolation of points, using a moving window

### Usage

```
## S4 method for signature 'SpatRaster,SpatVector'
interpNear(x, y, field, radius, interpolate=FALSE, fill=NA, filename="", ...)

## S4 method for signature 'SpatRaster,matrix'
interpNear(x, y, radius, interpolate=FALSE, fill=NA, filename="", ...)
```

### Arguments

x	SpatRaster
y	SpatVector or matrix with three columns (x,y,z)
field	character. field name in SpatVector y
radius	numeric. The radius of the circle (single number). If interpolate=FALSE it is also possible to use two or three numbers. Two numbers are interpreted as the radii of an ellipse (x and y-axis). A third number should indicated the desired, counter clockwise, rotation of the ellipse (in degrees)
interpolate	logical. Should the nearest neighbor values be linearly interpolated between points?
fill	numeric. value to use to fill empty cells
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

### Value

SpatRaster

### See Also

[rasterizeWin](#), [rasterize](#), [interpIDW](#), [interpolate](#)

### Examples

```
r <- rast(ncol=100, nrow=100, crs="local", xmin=0, xmax=50, ymin=0, ymax=50)
set.seed(100)
x <- runif(25, 5, 45)
y <- runif(25, 5, 45)
z <- sample(25)
xyz <- cbind(x,y,z)
```

```

x <- interpNear(r, xyz, radius=5)

p <- vect(data.frame(xyz), geom=c("x", "y"))
v <- voronoi(p)

plot(x, col=rainbow(25))
lines(v)

# plot(v, col=rainbow(25)); points(p)

```

---

intersect

*Intersection*


---

### Description

You can intersect `SpatVectors` with each other or with a `SpatExtent`. Intersecting points with points uses the extent of `y` to get the intersection. Intersecting of points and lines is not supported because of numerical inaccuracies with that. You can use [buffer](#), to create polygons from lines and use these with `intersect`.

You can also intersect two `SpatExtents`.

When intersecting two `SpatRasters` these need to be aligned (have the same origin and spatial resolution). The values of the returned `SpatRaster` are `TRUE` where both have input rasters have values, `FALSE` where one has values, and `NA` in all other cells.

See [crop](#) for intersection of a `SpatRaster` with a `SpatExtent` (or the extent of a `SpatRaster` or `SpatVector`).

See [relate](#) to find out which geometries of a `SpatVector` intersect.

### Usage

```
## S4 method for signature 'SpatVector,SpatVector'
intersect(x, y)
```

```
## S4 method for signature 'SpatVector,SpatExtent'
intersect(x, y)
```

```
## S4 method for signature 'SpatExtent,SpatVector'
intersect(x, y)
```

```
## S4 method for signature 'SpatExtent,SpatExtent'
intersect(x, y)
```

```
## S4 method for signature 'SpatRaster,SpatRaster'
intersect(x, y)
```

**Arguments**

`x`                    `SpatVector`, `SpatExtent`, or `SpatRaster`  
`y`                    `SpatVector`, `SpatExtent`, or `SpatRaster` if `x` is a `SpatRaster`

**Value**

Same as `x`

**See Also**

[union](#), [crop](#), [relate](#)

**Examples**

```
e1 <- ext(-10, 10, -20, 20)
e2 <- ext(0, 20, -40, 5)
intersect(e1, e2)

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
e <- ext(5.6, 6, 49.55, 49.7)
x <- intersect(v, e)

p <- vect(c("POLYGON ((5.8 49.8, 6 49.9, 6.15 49.8, 6 49.6, 5.8 49.8))",
"POLYGON ((6.3 49.9, 6.2 49.7, 6.3 49.6, 6.5 49.8, 6.3 49.9))"), crs=crs(v))
values(p) <- data.frame(pid=1:2, area=expanses(p))

y <- intersect(v, p)

r <- s <- rast(ncol=5, nrow=5, xmin=1, xmax=5, ymin=1, ymax=5)
r[5:20] = 5:20
s[11:20] = 11:20
rs <- intersect(r, s)

u <- shift(r, .8)
us <- intersect(u, s)
```

---

is.bool

*Raster value types*


---

**Description**

The values in a `SpatRaster` layer are by default numeric, but they can also be logical (Boolean), integer, or categorical (factor).

For a `SpatRaster`, `as.logical` and `isTRUE` is equivalent to `as.bool`. `isFALSE` is equivalent to `!as.bool`, and `as.integer` is the same as `as.int`.

See [levels](#) and [cats](#) to create categorical layers by setting labels.

**Usage**

```
## S4 method for signature 'SpatRaster'
is.bool(x)

## S4 method for signature 'SpatRaster'
as.bool(x, filename, ...)

## S4 method for signature 'SpatRaster'
is.int(x)

## S4 method for signature 'SpatRaster'
as.int(x, filename, ...)

## S4 method for signature 'SpatRaster'
is.factor(x)

## S4 method for signature 'SpatRaster'
as.factor(x)
```

**Arguments**

x	SpatRaster
filename	character. Output filename
...	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

The `as.*` methods return a new `SpatRaster`, whereas the `is.*` methods return a logical value for each layer in `x`.

**See Also**

[levels](#) and [cats](#) to create categorical layers (and set labels).

**Examples**

```
r <- rast(nrows=10, ncols=10, vals=1:100)
is.bool(r)
z <- as.bool(r)
is.bool(z)

x <- r > 25
is.bool(x)

rr <- r/2
is.int(rr)
is.int(round(rr))
```

---

is.lonlat

---

*Check for longitude/latitude crs*


---

### Description

Test whether a `SpatRaster` or `SpatVector` has a longitude/latitude coordinate reference system (CRS), or perhaps has one. That is when the CRS is unknown ("" ) but the x coordinates are within -181 and 181 and the y coordinates are within -90.1 and 90.1. For a `SpatRaster` you can also test if it is longitude/latitude and "global" (covers all longitudes).

### Usage

```
## S4 method for signature 'SpatRaster'
is.lonlat(x, perhaps=FALSE, warn=TRUE, global=FALSE)

## S4 method for signature 'SpatVector'
is.lonlat(x, perhaps=FALSE, warn=TRUE)
```

### Arguments

x	<code>SpatRaster</code> or <code>SpatVector</code>
perhaps	logical. If TRUE and the CRS is unknown, the method returns TRUE if the coordinates are plausible for longitude/latitude
warn	logical. If TRUE, a warning is given if the CRS is unknown or when the CRS is longitude/latitude but the coordinates do not match that
global	logical. If TRUE, the method tests if the raster covers all longitudes (from -180 to 180 degrees) such that the extreme columns are in fact adjacent

### Value

logical or NA

### Examples

```
r <- rast()
is.lonlat(r)
is.lonlat(r, global=TRUE)

crs(r) <- ""
is.lonlat(r)
is.lonlat(r, perhaps=TRUE, warn=FALSE)

crs(r) <- "+proj=lcc +lat_1=48 +lat_2=33 +lon_0=-100 +ellps=WGS84"
is.lonlat(r)
```



---

lapp	<i>Apply a function to layers of a SpatRaster, or sub-datasets of a SpatRasterDataset</i>
------	---

---

## Description

Apply a function to a SpatRaster, using layers as arguments.

The number of arguments in function fun must match the number of layers in the SpatRaster (or the number of sub-datasets in the SpatRasterDataset). For example, if you want to multiply two layers, you could use this function: `fun=function(x,y){return(x*y)}` percentage: `fun=function(x,y){return(100 * x / y)}`. If you combine three layers you could use `fun=function(x,y,z){return((x + y) * z)}`

Before you use the function, test it to make sure that it is vectorized. That is, it should work for vectors longer than one, not only for single numbers. Or if the input SpatRaster(s) have multiple layers, it should work for a matrix (multiple cells) of input data (or matrices in the case of a SpatRasterDataset). The function must return the same number of elements as its input vectors, or multiples of that. Also make sure that the function is NA-proof: it should return the same number of values when some or all input values are NA. And the function must return a vector or a matrix, not a data.frame. To test it, run it with `do.call(fun, data)` (see examples).

Use [app](#) for summarize functions such as sum, that take any number of arguments; and [tapp](#) to do so for groups of layers.

## Usage

```
## S4 method for signature 'SpatRaster'
lapp(x, fun, ..., usernames=FALSE, cores=1, filename="", overwrite=FALSE, wopt=list())

## S4 method for signature 'SpatRasterDataset'
lapp(x, fun, ..., usernames=FALSE, recycle=FALSE,
     filename="", overwrite=FALSE, wopt=list())
```

## Arguments

x	SpatRaster or SpatRasterDataset
fun	a function that takes a vector and can be applied to each cell of x
...	additional arguments to be passed to fun
usernames	logical. Use the layer names (or dataset names if x is a SpatRasterDataset) to match the function arguments? If FALSE, argument matching is by position
cores	positive integer. If cores > 1, a 'parallel' package cluster with that many cores is created and used. You can also supply a cluster object
recycle	logical. Recycle layers to match the subdataset with the largest number of layers
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Note**

Use [sapp](#) or [lapply](#) to apply a function that takes a SpatRaster as argument to each layer of a SpatRaster (that is rarely necessary).

**See Also**

[app](#), [tapp](#), [math](#)

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra")) + 1
ss <- s[[2:1]]

fvi <- function(x, y){ (x - y) / (x + y) }
# test the function
data <- list(c(1:5,NA), 6:1)
do.call(fvi, data)

x <- lapp(ss, fun=fvi )

# which is the same as supplying the layers to "fun"
# in some cases this will be much faster
y <- fvi(s[[2]], s[[1]])

f2 <- function(x, y, z){ (z - y + 1) / (x + y + 1) }
p1 <- lapp(s, fun=f2 )

p2 <- lapp(s[[1:2]], f2, z=200)

# the usenames argument

fvi2 <- function(red, green){ (red - green) / (red + green) }
names(s)
x1 <- lapp(s[[1:2]], fvi2, usenames=TRUE)
x2 <- lapp(s[[2:1]], fvi2, usenames=TRUE)
# x1 and x2 are the same, despite the change in the order of the layers
# x4 is also the same, but x3 is not
x3 <- lapp(s[[2:1]], fvi2, usenames=FALSE)
x4 <- lapp(s, fvi2, usenames=TRUE)

# while this would fail because
# there are too many layers in s
# x5 <- lapp(s, fvi2, usenames=FALSE)

pairs(c(x1, x2, x3, x4))

## SpatRasterDataset
x <- sds(s, s[[1]]+50)
```

```

fun <- function(x, y) { x/y }

# test "fun"
data <- list(matrix(1:9, ncol=3), matrix(9:1, ncol=3))
do.call(fun, data)

lapp(x, fun, recycle=TRUE)

# the same, more concisely
z <- s / (s[[1]]+50)

```

---

layerCor	<i>Correlation and (weighted) covariance</i>
----------	--

---

## Description

Compute correlation, (weighted) covariance, or similar summary statistics that compare the values of all pairs of the layers of a SpatRaster.

## Usage

```

## S4 method for signature 'SpatRaster'
layerCor(x, fun, w, asSample=TRUE, na.rm=FALSE, maxcell=Inf, ...)

```

## Arguments

x	SpatRaster
fun	character. The statistic to compute: either "cov" (covariance), "weighted.cov" (weighted covariance), or "pearson" (correlation coefficient) or your own function that takes two vectors as argument to compute a single number
w	SpatRaster with the weights to compute the weighted covariance. It should have a single layer and the same geometry as x
asSample	logical. If TRUE, the statistic for a sample (denominator is n-1) is computed, rather than for the population (denominator is n). Only for the standard functions
na.rm	logical. Should missing values be removed?
maxcell	positive integer. The number of cells to be regularly sampled. Only used when fun is a function
...	additional arguments for fun (if it is a proper function)

## Value

If fun is one of the three standard statistics, you get a list with two items: the correlation or (weighted) covariance matrix, and the (weighted) means.

If fun is a function, you get a matrix.

## References

For the weighted covariance:

- Canty, M.J. and A.A. Nielsen, 2008. Automatic radiometric normalization of multitemporal satellite imagery with the iteratively re-weighted MAD transformation. Remote Sensing of Environment 112:1025-1036.
- Nielsen, A.A., 2007. The regularized iteratively reweighted MAD method for change detection in multi- and hyperspectral data. IEEE Transactions on Image Processing 16(2):463-478.

## See Also

[global](#), [cov.wt](#), [weighted.mean](#)

## Examples

```
b <- rast(system.file("ex/logo.tif", package="terra"))
layerCor(b, "pearson")

layerCor(b, "cov")

# weigh by column number
w <- init(b, fun="col")
layerCor(b, "weighted.cov", w=w)
```

---

linearUnits

*Linear units of the coordinate reference system*

---

## Description

Get the linear units of the coordinate reference system (crs) of a `SpatRaster` or `SpatVector` expressed in m. The value returned is used internally to transform area and perimeter measures to meters. The value returned for longitude/latitude crs is zero.

## Usage

```
## S4 method for signature 'SpatRaster'
linearUnits(x)

## S4 method for signature 'SpatVector'
linearUnits(x)
```

## Arguments

x                      `SpatRaster` or `SpatVector`

## Value

numeric (meter)

**See Also**[crs](#)**Examples**

```
x <- rast()
crs(x) <- ""
linearUnits(x)

crs(x) <- "+proj=longlat +datum=WGS84"
linearUnits(x)

crs(x) <- "+proj=utm +zone=1 +units=cm"
linearUnits(x)

crs(x) <- "+proj=utm +zone=1 +units=km"
linearUnits(x)

crs(x) <- "+proj=utm +zone=1 +units=us-ft"
linearUnits(x)
```

lines

*Add SpatVector data to a map***Description**

Add SpatVector data to a plot (map) with points, lines, or polys.

These are simpler alternatives for [plot\(x, add=TRUE\)](#)

**Usage**

```
## S4 method for signature 'SpatVector'
points(x, col, cex=0.7, pch=16, alpha=1, ...)

## S4 method for signature 'SpatVector'
lines(x, y=NULL, col, lwd=1, lty=1, arrows=FALSE, alpha=1, ...)

## S4 method for signature 'SpatVector'
polys(x, col, border="black", lwd=1, lty=1, alpha=1, ...)

## S4 method for signature 'SpatExtent'
points(x, col="black", alpha=1, ...)

## S4 method for signature 'SpatExtent'
lines(x, col="black", alpha=1, ...)

## S4 method for signature 'SpatExtent'
polys(x, col, alpha=1, ...)
```

**Arguments**

x	SpatVector or SpatExtent
y	missing or SpatVector. If both x and y have point geometry and the same number of rows, lines are drawn between pairs of points
col	character. Colors
border	character. color(s) of the polygon borders. Use NULL or NA to not draw a border
cex	numeric. point size magnifier. See <a href="#">par</a>
pch	positive integer, point type. See <a href="#">points</a> . On some (linux) devices, the default symbol "16" is a not a very smooth circle. You can use "20" instead (it takes a bit longer to draw) or "1" for an open circle
alpha	number between 0 and 1 to set transparency
lwd	numeric, line-width. See <a href="#">par</a>
lty	positive integer, line type. See <a href="#">par</a>
arrows	logical. If TRUE and y is a SpatVector, arrows are drawn instead of lines. See <a href="#">?arrows</a> for additional arguments
...	additional graphical arguments such as lwd, cex and pch

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)

r <- rast(v)
values(r) <- 1:ncell(r)
plot(r)
lines(v)
points(v)
```

---

makeTiles

*Make tiles*


---

**Description**

Divide a SpatRaster into "tiles". The cell of another SpatRaster (normally with a much lower resolution) are used to define the tiles.

**Usage**

```
## S4 method for signature 'SpatRaster'
makeTiles(x, y, filename="tile_.tif", extend=FALSE, na.rm=FALSE, ...)
```

Arguments

x	SpatRaster
y	SpatRaster or SpatVector
filename	character. Output filename template. Filenames will be altered by adding the tile number for each tile
extend	logical. If TRUE, the extent of y is expanded to assure that it covers all of x
na.rm	logical. If TRUE, tiles with only missing values are ignored
...	additional arguments for writing files as in <a href="#">writeRaster</a>

Value

character (filenames)

See Also

[vrt](#) to create a virtual raster from tiles

Examples

```
r <- rast(ncols=100, nrows=100)
values(r) <- 1:ncell(r)
x <- rast(ncols=2, nrows=2)
filename <- paste0(tempfile(), "_tif")
ff <- makeTiles(r, x, filename)
ff

vrt(ff)
```

---

makeVRT	<i>Make a VRT header file</i>
---------	-------------------------------

---

Description

Create a VRT header file for a "flat binary" raster file that needs a header file to be able to read it, but does not have it.

Usage

```
makeVRT(filename, nrow, ncol, nlyr=1, extent, xmin, ymin, xres, yres=xres, xycenter=TRUE,
  crs="+proj=longlat", lyrnms="", datatype, NAflag=NA, bandorder="BIL", byteorder="LSB",
  toptobottom=TRUE, offset=0, scale=1)
```

**Arguments**

filename	character. raster filename (without the ".vrt" extension)
nrow	positive integer, the number of rows
ncol	positive integer, the number of columns
nlyr	positive integer, the number of layers
extent	SpatExtent or missing
xmin	numeric. minimum x coordinate (only used if extent is missing)
ymin	numeric. minimum y coordinate (only used if extent is missing)
xres	positive number. x resolution
yres	positive number. y resolution)
xycenter	logical. If TRUE, xmin and xmax represent the coordinates of the center of the extreme cell, in stead of the coordinates of the outside corner. Only used of extent is missing
crs	character. Coordinate reference system description
lyrnms	character. Layer names
datatype	character. One of "INT2S", "INT4S", "INT1U", "INT2U", "INT4U", "FLT4S", "FLT8S". If missing, this is guessed from the file size (INT1U for 1 byte per value, INT2S for 2 bytes and FLT4S for 4 bytes per value). This may be wrong because, for example, 2 bytes per value may in fact be INT2U (with the U for unsigned) values
NAflag	numeric. The value used as the "NA flag"
bandorder	character. One of "BIL", "BIP", or "BSQ". That is Band Interleaved by Line, or by Pixel, or Band SeQuential
byteorder	character. One of "LSB", "MSB". "MSB" is common for files generated on Linux systems, whereas "LSB" is common for files generated on windows
toptobottom	logical. If FALSE, the values are read bottom to top
offset	numeric. offset to be applied
scale	numeric. scale to be applied

**Value**

character (.VRT filename)

**See Also**

[vrt](#) to create a vrt for a collection of raster tiles



mask

*Mask values in a SpatRaster or SpatVector***Description**

If *x* is a *SpatRaster*: Create a new *SpatRaster* that has the same values as *SpatRaster* *x*, except for the cells that are NA (or other *maskvalue*) in another *SpatRaster* (the '*mask*'), or the cells that are not covered by a *SpatVector*. These cells become NA (or another *updatevalue*).

If *x* is a *SpatVector*: Select geometries of *x* that intersect, or not intersect, with the geometries of *y*.

**Usage**

```
## S4 method for signature 'SpatRaster,SpatRaster'
mask(x, mask, inverse=FALSE, maskvalues=NA,
      updatevalue=NA, filename="", ...)
```

```
## S4 method for signature 'SpatRaster,SpatVector'
mask(x, mask, inverse=FALSE, updatevalue=NA,
      touches=TRUE, filename="", ...)
```

```
## S4 method for signature 'SpatVector,SpatVector'
mask(x, mask, inverse=FALSE)
```

**Arguments**

<i>x</i>	<i>SpatRaster</i> or <i>SpatVector</i>
<i>mask</i>	<i>SpatRaster</i> or <i>SpatVector</i>
<i>inverse</i>	logical. If TRUE, areas on <i>mask</i> that are <i>_not_</i> the <i>maskvalue</i> are masked
<i>maskvalues</i>	numeric. The value(s) in <i>mask</i> that indicate which cells of <i>x</i> should be masked (change their value to <i>updatevalue</i> (default = NA))
<i>updatevalue</i>	numeric. The value that masked cells should become (if they are not NA)
<i>touches</i>	logical. If TRUE, all cells touched by lines or polygons will be masked, not just those on the line render path, or whose center point is within the polygon
<i>filename</i>	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

*SpatRaster*

**See Also**

[crop](#)

Examples

```
r <- rast(ncols=10, nrows=10)
m <- rast(ncols=10, nrows=10)
values(r) <- 1:100
set.seed(1965)
x <- round(3 * runif(ncell(r)))
x[x==0] <- NA
values(m) <- x
mr <- mask(r, m)
```

---

match	<i>Value matching for SpatRasters</i>
-------	---------------------------------------

---

Description

match returns a SpatRaster with the position of the matched values. The cell values are the index of the table argument.

%in% returns a 0/1 (FALSE/TRUE) SpatRaster indicating if the cells values were matched or not.

Usage

```
match(x, table, nomatch = NA_integer_, incomparables = NULL)

x %in% table
```

Arguments

x	SpatRaster
table	vector of the values to be matched against
nomatch	the value to be returned in the case when no match is found. Note that it is coerced to integer
incomparables	a vector of values that cannot be matched. Any value in x matching a value in this vector is assigned the nomatch value. For historical reasons, FALSE is equivalent to NULL

Value

SpatRaster

See Also

[app](#), [match](#)

**Examples**

```
r <- rast(nrows=10, ncols=10)
values(r) <- 1:100
m <- match(r, c(5:10, 50:55))
n <- r %in% c(5:10, 50:55)
```

Math-methods

*General mathematical methods***Description**

Standard mathematical methods for computations with SpatRaster objects. Computations are local (applied on a cell by cell basis). If multiple SpatRaster objects are used, these must have the same extent and resolution. These have been implemented:

abs, sign, sqrt, ceiling, floor, trunc, cummax, cummin, cumprod, cumsum, log, log10, log2, log1p, acos, acosh, asin, asinh, atan, atanh, exp, expm1, cos, cosh, sin, sinh, tan, tanh, round, signif

Instead of directly calling these methods, you can also provide their name to the math method. This is useful if you want to provide an output filename.

The following methods have been implemented for SpatExtent: round, floor, ceiling

round has also been implemented for SpatVector, to round the coordinates of the geometries.

**Usage**

```
## S4 method for signature 'SpatRaster'
sqrt(x)

## S4 method for signature 'SpatRaster'
log(x, base=exp(1))

## S4 method for signature 'SpatRaster'
round(x, digits=0)

## S4 method for signature 'SpatRaster'
math(x, fun, digits=0, filename="", overwrite=FALSE, ...)

## S4 method for signature 'SpatVector'
round(x, digits=4)

## S4 method for signature 'SpatRaster'
cumsum(x)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>base</code>	a positive or complex number: the base with respect to which logarithms are computed
<code>digits</code>	Number of digits for rounding
<code>fun</code>	character. Math function name
<code>filename</code>	character. Output filename
<code>overwrite</code>	logical. If TRUE, filename is overwritten
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

`SpatRaster` or `SpatExtent`

**See Also**

See [app](#) to use mathematical functions not implemented by the package, and [Arith-methods](#) for arithmetical operations

**Examples**

```

r1 <- rast(ncols=10, nrows=10)
v <- runif(ncell(r1))
v[10:20] <- NA
values(r1) <- v
r2 <- rast(r1)
values(r2) <- 1:ncell(r2) / ncell(r2)
r <- c(r1, r2)

s <- sqrt(r)
# same as
math(r, "sqrt")

round(s, 1)

cumsum(r)

```

---

mem

*Memory available and needed*

---

**Description**

`mem_info` prints the amount of RAM that is required and available to process a `SpatRaster`.

`free_RAM` returns the amount of RAM that is available

**Usage**

```
mem_info(x, n=1)
```

```
free_RAM()
```

**Arguments**

**x**                      *SpatRaster*

**n**                      positive integer. The number of copies of *x* that are needed

**Value**

`free_RAM` returns the amount of available RAM in kilobytes

**Examples**

```
mem_info(rast())
```

```
free_RAM()
```

---

merge	<i>Merge multiple SpatRaster objects or SpatExtent objects, or merge a SpatVector with a data.frame</i>
-------	---

---

**Description**

Merge multiple *SpatRasters* to create a new *SpatRaster* object with a larger spatial extent. The *SpatRasters* must have the same origin and spatial resolution. In areas where the *SpatRasters* overlap, the values of the *SpatRaster* that is first in the sequence of arguments (or in the *SpatRasterCollection*) will be retained (unless `first=FALSE`).

See [classify](#) to merge a *SpatRaster* and a *data.frame*. You can also merge *SpatExtent* objects.

There is also a method for merging *SpatVector* with a *data.frame*; that is, to join the *data.frame* to the attribute table of the *SpatVector*.

**Usage**

```
## S4 method for signature 'SpatRaster,SpatRaster'
merge(x, y, ..., first=TRUE, filename="", overwrite=FALSE, wopt=list())
```

```
## S4 method for signature 'SpatRasterCollection,missing'
merge(x, first=TRUE, filename="", ...)
```

```
## S4 method for signature 'SpatExtent,SpatExtent'
merge(x, y, ...)
```

```
## S4 method for signature 'SpatVector,data.frame'
merge(x, y, ...)
```

**Arguments**

<code>x</code>	SpatRaster or SpatExtent
<code>y</code>	object of same class as <code>x</code>
<code>...</code>	if <code>x</code> is a SpatRaster: additional objects of the same class as <code>x</code> . If <code>x</code> is a SpatRasterCollection: options for writing files as in <a href="#">writeRaster</a> . If <code>x</code> is a SpatVector, the same arguments as in <a href="#">merge</a>
<code>first</code>	logical. If TRUE, in areas where rasters overlap, the first value that is not NA is used. Otherwise the last value that is not NA is used
<code>filename</code>	character. Output filename
<code>overwrite</code>	logical. If TRUE, filename is overwritten
<code>wopt</code>	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster or SpatExtent

**Note**

You can use `merge` with `do.call` to merge a list of SpatRasters (see example). But note that if the list is named, these names are used by `merge`. So if all elements are named, there should be one element with a SpatRaster called `x` and another one called `y`. For example with `names(x)[1:2] <- c("x" "m" "y")`. You can also removed the names of the the first two elements (assuming these are SpatRasters) with `names(x)[1:2] <- ""`.

**See Also**

Combining tiles with [vrt](#) may be more efficient. See [mosaic](#) for averaging overlapping regions.

**Examples**

```
x <- rast(xmin=-110, xmax=-80, ymin=40, ymax=70, res=1, vals=1)
y <- rast(xmin=-85, xmax=-55, ymax=60, ymin=30, res=1, vals=2)
z <- rast(xmin=-60, xmax=-30, ymax=50, ymin=20, res=1, vals=3)

m1 <- merge(x, y, z)
m2 <- merge(z, y, x)
m3 <- merge(y, x, z)

# if you have many SpatRasters make a SpatRasterCollection from a list
rlist <- list(x, y, z)
rsrc <- sprc(rlist)

m <- merge(rsrc)

## SpatVector with data.frame
f <- system.file("ex/lux.shp", package="terra")
p <- vect(f)
dfr <- data.frame(District=p$NAME_1, Canton=p$NAME_2, Value=round(runif(length(p), 100, 1000)))
```

```
dfr <- dfr[1:5, ]
pm <- merge(p, dfr, all.x=TRUE, by.x=c('NAME_1', 'NAME_2'), by.y=c('District', 'Canton'))
pm
values(pm)
```

---

mergeTime

---

*merge SpatRasters by timelines to create a single timeseries*


---

## Description

Combine SpatRasters with partly overlapping time-stamps to create a single time series. If there is no overlap between the SpatRasters there is no point in using this function (use [c](#) instead).

Also note that time gaps are not filled. You can use [fillTime](#) to do that.

## Usage

```
## S4 method for signature 'SpatRasterDataset'
mergeTime(x, fun=mean, filename="", ...)
```

## Arguments

x	SpatRasterDataset
fun	A function that reduces a vector to a single number, such as mean or min
filename	character. Output filename
...	list with named options for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## Examples

```
r <- rast(system.file("ex/logo.tif", package="terra"))
s1 <- c(r, r)
time(s1) <- as.Date("2001-01-01") + 0:5
s1 <- s1/10
time(s1) <- as.Date("2001-01-07") + 0:5
s2 <- s1*10
time(s2) <- as.Date("2001-01-05") + 0:5
x <- sds(s1, s1, s2)

m <- mergeTime(x, mean)
```

---

modal	<i>modal value</i>
-------	--------------------

---

**Description**

Compute the mode for each cell across the layers of a `SpatRaster`. The mode, or modal value, is the most frequent value in a set of values.

**Usage**

```
## S4 method for signature 'SpatRaster'
modal(x, ..., ties="first", na.rm=FALSE, filename="", overwrite=FALSE, wopt=list())
```

**Arguments**

x	<code>SpatRaster</code>
...	additional argument of the same type as x or numeric
ties	character. Indicates how to treat ties. Either "random", "lowest", "highest", "first", or "NA"
na.rm	logical. If TRUE, NA values are ignored. If FALSE, NA is returned if x has any NA values
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

`SpatRaster`

**Examples**

```
r <- rast(system.file("ex/logo.tif", package="terra"))
r <- c(r/2, r, r*2)
m <- modal(r)
```



mosaic

*mosaic SpatRasters***Description**

Combine adjacent and (partly) overlapping SpatRasters to form a single new SpatRaster. Values in overlapping cells are averaged (by default) or can be computed with another function.

The SpatRasters must have the same origin and spatial resolution.

This method is similar to the simpler, but much faster, [merge](#) method.

**Usage**

```
## S4 method for signature 'SpatRaster,SpatRaster'
mosaic(x, y, ..., fun="mean", filename="", overwrite=FALSE, wopt=list())

## S4 method for signature 'SpatRasterCollection,missing'
mosaic(x, fun="mean", filename="", ...)
```

**Arguments**

x	SpatRaster
y	object of same class as x
...	additional SpatRasters
fun	character. One of "sum", "mean", "median", "min", "max"
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[merge](#)

**Examples**

```
x <- rast(xmin=-110, xmax=-60, ymin=40, ymax=70, res=1, vals=1)
y <- rast(xmin=-95, xmax=-45, ymax=60, ymin=30, res=1, vals=2)
z <- rast(xmin=-80, xmax=-30, ymax=50, ymin=20, res=1, vals=3)

m1 <- mosaic(x, y, z)

m2 <- mosaic(z, y, x)
```

```
# with many SpatRasters, make a SpatRasterCollection from a list
rlist <- list(x, y, z)
rsrc <- sprc(rlist)

m <- mosaic(rsrc)
```

---

na.omit

*na.omit for SpatVector*


---

## Description

Remove empty geometries and/or records that are NA from a SpatVector.

## Usage

```
## S4 method for signature 'SpatVector'
na.omit(object, field=NA, geom=FALSE)
```

## Arguments

object	SpatVector
field	character or NA. If NA, missing values in the attributes are ignored. Other values are either one or more field (variable) names, or "" to consider all fields
geom	logical. If TRUE empty geometries are removed

## Value

SpatVector

## Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
v$test <- c(1,2,NA)
nrow(v)
x <- na.omit(v, "test")
nrow(x)
```

---

**NAflag***Set the NA flag*

---

### Description

The main purpose of this method is to allow correct reading of a `SpatRaster` that is based on a file that has an incorrect NA flag. The file is not changed, but flagged value is set to NA when values are read from the file ("lazy evaluation"). In contrast, if the values are in memory the change is made immediately.

To change values, it is generally better to use `classify`

### Usage

```
## S4 method for signature 'SpatRaster'
NAflag(x)

## S4 replacement method for signature 'SpatRaster'
NAflag(x)<-value
```

### Arguments

<code>x</code>	<code>SpatRaster</code>
<code>value</code>	numeric. The value to be interpreted as NA; set this before reading the values from the file. This can be a single value, or multiple values, one for each data source (file / subdataset)

### Value

none or numeric

### See Also

`classify`

### Examples

```
s <- rast(system.file("ex/logo.tif", package="terra"))[[1]]
NAflag(s) <- 255
plot(s)
NAflag(s)
```

---

names	<i>Names of Spat* objects</i>
-------	-------------------------------

---

### Description

Get or set the names of the layers of a `SpatRaster` or the attributes of a `SpatVector`. With `longnames` you can get or set the "long names" of a `SpatRaster` or `SpatRasterDataset`.

For a `SpatRaster`, you can also get/set a variable name or long name (one per data source).

See [set.names](#) for in-place setting of names.

### Usage

```
## S4 method for signature 'SpatRaster'
names(x)

## S4 replacement method for signature 'SpatRaster'
names(x)<-value

## S4 method for signature 'SpatRaster'
varnames(x)

## S4 replacement method for signature 'SpatRaster'
varnames(x)<-value

## S4 method for signature 'SpatRaster'
longnames(x)

## S4 replacement method for signature 'SpatRaster'
longnames(x)<-value

## S4 method for signature 'SpatRasterDataset'
names(x)

## S4 replacement method for signature 'SpatRasterDataset'
names(x)<-value

## S4 method for signature 'SpatRasterDataset'
varnames(x)

## S4 replacement method for signature 'SpatRasterDataset'
varnames(x)<-value

## S4 method for signature 'SpatRasterDataset'
longnames(x)
```

```
## S4 replacement method for signature 'SpatRasterDataset'
longnames(x)<-value

## S4 method for signature 'SpatVector'
names(x)

## S4 replacement method for signature 'SpatVector'
names(x)<-value
```

### Arguments

x	SpatRaster, SpatRasterDataset, or SpatVector
value	character (vector)

### Value

character

### Note

terra enforces neither unique nor valid names. See [make.unique](#) to create unique names and `{make.names}` to make syntactically valid names.

### Examples

```
s <- rast(ncols=5, nrows=5, nlyrs=3)
nlyr(s)
names(s)
names(s) <- c("a", "b", "c")
names(s)

# space is not valid
names(s)[2] <- "hello world"
names(s)

# two invalid names
names(s) <- c("a", " a ", "3")
names(s)

# SpatVector names
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
names(v)
names(v) <- paste0(substr(names(v), 1, 2), "_", 1:ncol(v))
names(v)
```

---

nearest	<i>nearby geometries</i>
---------	--------------------------

---

### Description

Identify geometries that are near to each other. Either get the index of all geometries within a certain distance, or the k nearest neighbors, or (with nearest) get the nearest points between two geometries.

### Usage

```
## S4 method for signature 'SpatVector'
nearby(x, y=NULL, distance=0, k=1, centroids=TRUE, symmetrical=TRUE)
```

```
## S4 method for signature 'SpatVector'
nearest(x, y, pairs=FALSE, centroids=TRUE, lines=FALSE)
```

### Arguments

x	SpatVector
y	SpatVector or NULL
distance	numeric. maximum distance
k	positive integer. number of neighbors. Ignored if distance > 0
centroids	logical. Should the centroids of polygons be used?
symmetrical	logical. If TRUE, a near pair is only included once. That is, if geometry 1 is near to geometry 3, the implied nearness between 3 and 1 is not reported. Ignored if k neighbors are returned
pairs	logical. If TRUE pairwise nearest points are returned (only relevant when using at least one SpatVector of lines or polygons)
lines	logical. If TRUE lines between the nearest points instead of (the nearest) points

### Value

matrix

### See Also

[relate](#), [adjacent](#)

### Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
nearby(v, distance=12000)
```

---

normalize.longitude	<i>normalize vector data that crosses the dateline</i>
---------------------	--

---

### Description

Normalize the longitude of geometries, that is move geometries to a bounding box of -180 to 180 degrees

### Usage

```
## S4 method for signature 'SpatVector'  
normalize.longitude(x)
```

### Arguments

x	SpatVector
---	------------

### Value

SpatVector

### See Also

[rotate](#) for SpatRaster

### Examples

```
p <- vect("POLYGON ((120 10, 230 75, 230 -75, 120 10))")  
normalize.longitude(p)
```

---

north	<i>North arrow</i>
-------	--------------------

---

### Description

Add a (North) arrow to a map

### Usage

```
north(xy=NULL, type=1, label="N", angle=0, d, head=0.1, xpd=TRUE, ...)
```

**Arguments**

xy	numeric. x and y coordinate to place the arrow. It can also be one of following character values: "bottomleft", "bottom", "bottomright", "topleft", "top", "topright", "left", "right", or NULL
type	integer between 1 and 12, or a character (unicode) representation of a right pointing arrow such as "\u27A9"
label	character, to be printed near the arrow
angle	numeric. The angle of the arrow in degrees
d	numeric. Distance covered by the arrow in plot coordinates. Only applies to type=1
head	numeric. The size of the arrow "head", for type=1
xpd	logical. If TRUE, the scale bar or arrow can be outside the plot area
...	graphical arguments to be passed to other methods

**Value**

none

**See Also**

[sbar](#), [plot](#), [inset](#)

**Examples**

```
f <- system.file("ex/meuse.tif", package="terra")
r <- rast(f)
plot(r)
north()
north(c(178550, 332500), d=250)

## Not run:
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
plot(r, type="interval")
sbar(15, c(6.3, 50), type="bar", below="km", label=c(0,7.5,15), cex=.8)
north(type=3, cex=.8)
north(xy=c(6.7, 49.9), type=2, angle=45, label="NE")
north(xy=c(6.6, 49.7), type=5, cex=1.25)
north(xy=c(5.5, 49.6), type=9)
north(d=.05, xy=c(5.5, 50), angle=180, label="S", lwd=2, col="blue")

## all arrows
r <- rast(res=10)
values(r) <- 1
plot(r, col="white", axes=FALSE, legend=FALSE, mar=c(0,0,0,0), reset=TRUE)
for (i in 1:12) {
  x = -200+i*30
  north(xy=cbind(x,30), type=i)
```



```
text(x, -20, i, xpd=TRUE)
}
```

```
## End(Not run)
```

---

not.na	<i>is not NA</i>
--------	------------------

---

## Description

Shortcut method to avoid the two-step `!is.na(x)`

## Usage

```
## S4 method for signature 'SpatRaster'
not.na(x, filename="", ...)
```

## Arguments

x	SpatRaster
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

## Value

SpatRaster

## See Also

[Compare-methods](#)

## Examples

```
r <- rast(ncols=10, nrows=10, vals=1)
r[10:20] <- NA
x <- not.na(r)
```

options

*Options***Description**

Class and methods for showing and setting general options for terra.

**Usage**

```
terraOptions(...)
```

**Arguments**

... option names and values (see Details). Or missing, to show the current options

**Details**

The following options are available.

**memfrac** - value between 0 and 0.9 (larger values give a warning). The fraction of RAM that may be used by the program.

**memmin** - if memory required is below this threshold (in GB), the memory is assumed to be available. Otherwise, terra checks if it is available.

**memmax** - the maximum amount of RAM (in GB) that terra is allowed to use when processing a raster dataset. Should be less than what is detected (see [mem\\_info](#)), and higher values are ignored. Set it to a negative number or NA to not set this option. `terraOptions` only shows the value of `memmax` if it is set.

**tempdir** - directory where temporary files are written. The default what is returned by `tempdir()`.

**datatype** - default data type. See [writeRaster](#)

**todisk** - logical. If TRUE write all raster data to disk (temp file if no file name is specified). For debugging.

**progress** - non-negative integer. A progress bar is shown if the number of chunks in which the data is processed is larger than this number. No progress bar is shown if the value is zero

**verbose** - logical. If TRUE debugging info is printed for some functions

**Examples**

```
terraOptions()
terraOptions(memfrac=0.5, tempdir = "c:/temp")
terraOptions(progress=10)
terraOptions()
```

---

origin	<i>Origin</i>
--------	---------------

---

**Description**

Get or set the coordinates of the point of origin of a SpatRaster. This is the point closest to (0, 0) that you could get if you moved towards that point in steps of the x and y resolution.

**Usage**

```
## S4 method for signature 'SpatRaster'
origin(x)

## S4 replacement method for signature 'SpatRaster'
origin(x)<-value
```

**Arguments**

- x                    SpatRaster
- value                numeric vector of length 1 or 2

**Value**

A vector of two numbers (x and y coordinates)

**Examples**

```
r <- rast(xmin=-0.5, xmax = 9.5, ncols=10)
origin(r)
origin(r) <- c(0,0)
r
```

---

pairs	<i>Pairs plot (matrix of scatterplots)</i>
-------	--

---

**Description**

Pair plots of layers in a SpatRaster. This is a wrapper around graphics function [pairs](#).

**Usage**

```
## S4 method for signature 'SpatRaster'
pairs(x, hist=TRUE, cor=TRUE, use="pairwise.complete.obs", maxcells=100000, ...)
```

**Arguments**

x	SpatRaster
hist	logical. If TRUE a histogram of the values is shown on the diagonal
cor	logical. If TRUE the correlation coefficient is shown in the upper panels
use	argument passed to the <a href="#">cor</a> function
maxcells	integer. Number of pixels to sample from each layer of a large SpatRaster
...	additional arguments (graphical parameters)

**See Also**

[boxplot](#), [hist](#)

**Examples**

```
r <-rast(system.file("ex/elev.tif", package="terra"))
s <- c(r, 1/r, sqrt(r))
names(s) <- c("elevation", "inverse", "sqrt")
pairs(s)

# to make individual histograms:
hist(r)
# or scatter plots:
plot(s[[1]], s[[2]])
```

---

patches	<i>Detect patches (clumps) of cells</i>
---------	---

---

**Description**

Detect patches (clumps). Patches are groups of cells that are surrounded by cells that are NA. Set zeroAsNA to TRUE to also identify patches separated by cells with values of zero.

**Usage**

```
## S4 method for signature 'SpatRaster'
patches(x, directions=4, zeroAsNA=FALSE, allowGaps=TRUE, filename="", ...)
```

**Arguments**

x	SpatRaster
directions	integer indicating which cells are considered adjacent. Should be 8 (Queen's case) or 4 (Rook's case)
zeroAsNA	logical. If TRUE treat cells that are zero as if they were NA
allowGaps	logical. If TRUE there may be gaps in the patch IDs (e.g. you may have patch IDs 1, 2, 3 and 5, but not 4). If it is FALSE, these numbers will be recoded from 1 to the number of patches (4 in this example)
filename	character. Output filename
...	options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster. Cell values are patch numbers

**See Also**

[focal](#), [boundaries](#)

**Examples**

```
r <- rast(nrows=18, ncols=36, xmin=0)
r[1:2, 5:8] <- 1
r[5:8, 2:6] <- 1
r[7:12, 22:36] <- 1
r[15:16, 18:29] <- 1
p <- patches(r)

# zero as background instead of NA
r <- rast(nrows=10, ncols=10, xmin=0, vals=0)
r[3, 3] <- 10
r[4, 4] <- 10
r[5, 5:8] <- 12
r[6, 6:9] <- 12

# treat zeros as NA

p4 <- patches(r, zeroAsNA=TRUE)
p8 <- patches(r, 8, zeroAsNA=TRUE)

### patches for different values
# remove zeros manually
rr <- classify(r, cbind(0, NA))

# make layers for each value
s <- segregate(rr, keep=TRUE, other=NA)
p <- patches(s)

### patch ID values are not guaranteed to be consecutive
r <- rast(nrows=5, ncols=10, xmin=0)
set.seed(0)
values(r)<- round(runif(ncell(r))*0.7)
rp <- patches(r, directions=8, zeroAsNA=TRUE)
plot(rp, type="classes"); text(rp)

## unless you set allowGaps=FALSE
rp <- patches(r, directions=8, zeroAsNA=TRUE, allowGaps=FALSE)
plot(rp, type="classes"); text(rp)

### use zonal to remove small patches
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
x <- classify(r, cbind(-Inf, 400, NA))
```

```
y <- patches(x)
# remove patches smaller than 100 ha
rz <- zonal(cellSize(y, unit="ha"), y, sum, as.raster=TRUE)
s <- ifel(rz < 100, NA, y)
```

---

perim	<i>Perimeter or length</i>
-------	----------------------------

---

**Description**

This method returns the length of lines or the perimeter of polygons.

When the crs is not longitude/latitude, you may get more accurate results by first unprojecting the SpatVector (you can use [project](#) to transform the crs to longitude/latitude)

**Usage**

```
## S4 method for signature 'SpatVector'
perim(x)
```

**Arguments**

x                      SpatVector

**Value**

numeric (m)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
perim(v)
```

---

persp	<i>Perspective plot</i>
-------	-------------------------

---

**Description**

Perspective plot of a SpatRaster. This is an implementation of a generic function in the graphics package.

**Usage**

```
## S4 method for signature 'SpatRaster'
persp(x, maxcells=100000, ...)
```

**Arguments**

<code>x</code>	SpatRaster. Only the first layer is used
<code>maxcells</code>	integer > 0. Maximum number of cells to use for the plot. If <code>maxpixels &lt; ncell(x)</code> , <code>spatSample(method="regular")</code> is used before plotting
<code>...</code>	Any argument that can be passed to <a href="#">persp</a> (graphics package)

**See Also**

[persp](#), [contour](#), [plot](#)

**Examples**

```
r <- rast(system.file("ex/elev.tif", package="terra"))
persp(r)
```

---

plet

---

*Plot with leaflet*


---

**Description**

Plot the values of a SpatRaster or SpatVector to make an interactive leaflet map that is displayed in a browser.

These methods require that `packageVersion("leaflet") > "2.1.1"` or the development version of leaflet that you can install with `remotes::install_github("rstudio/leaflet")`.

**Usage**

```
## S4 method for signature 'SpatRaster'
plet(x, y=1, col, alpha=0.8, main=names(x), tiles=NULL,
     wrap=TRUE, maxcell=500000, legend="bottomright",
     shared=FALSE, panel=FALSE, collapse=TRUE, map=NULL)

## S4 method for signature 'SpatVector'
plet(x, y="", col, alpha=1, fill=0, main=y, cex=1, lwd=2, popup=TRUE,
     label=FALSE, split=FALSE, tiles=c("Streets", "Esri.WorldImagery", "OpenTopoMap"),
     wrap=TRUE, legend="bottomright", collapse=FALSE, map=NULL)

## S4 method for signature 'SpatVectorCollection'
plet(x, col, alpha=1, fill=0, cex=1, lwd=2, popup=TRUE,
     label=FALSE, tiles=c("Streets", "Esri.WorldImagery", "OpenTopoMap"), wrap=TRUE,
     legend="bottomright", collapse=FALSE, map=NULL)

## S4 method for signature 'leaflet'
lines(x, y, col, lwd=2, alpha=1)
```

```
## S4 method for signature 'leaflet'
points(x, y, col, cex=1, alpha=1, popup=FALSE)
```

### Arguments

<code>x</code>	SpatRaster, SpatVector, or leaflet object
<code>y</code>	missing, or positive integer, or character (variable or layer name) indicating the layer(s) to be plotted. If <code>x</code> is a SpatRaster, you can select multiple layers
<code>col</code>	character. Vector of colors or color generating function
<code>alpha</code>	Number between 0 and 1 to set the transparency for lines (0 is transparent, 1 is opaque)
<code>fill</code>	Number between 0 and 1 to set the transparency for polygon areas (0 is transparent, 1 is opaque)
<code>tiles</code>	character or NULL. Names of background tile providers
<code>wrap</code>	logical. if TRUE, tiles wrap around
<code>maxcell</code>	positive integer. Maximum number of cells to use for the plot
<code>legend</code>	character to indicate the legend position ("bottomleft", "bottomright", "topleft" or "topright") or NULL to suppress the legend
<code>main</code>	character. Title for the legend. The length should be 1 if <code>x</code> is a SpatVector and length nlyr(x) if <code>x</code> is a SpatRaster
<code>shared</code>	logical. Should the legend be the same for all rasters (if multiple layers of SpatRaster <code>x</code> are mapped)
<code>map</code>	leaflet object
<code>collapse</code>	logical. Should the layers "control" panel be collapsed?
<code>split</code>	logical. IF TRUE a check-box is created to toggle each value in codey (If <code>x</code> is a SpatVector)
<code>cex</code>	numeric. point size magnifier. See <a href="#">par</a>
<code>lwd</code>	numeric, line-width. See <a href="#">par</a>
<code>popup</code>	logical. Should pop-ups be created?
<code>label</code>	logical. Should mouse-over labels be added?
<code>panel</code>	logical. Should SpatRaster layers be shown as a panel"

### See Also

[plot](#)

### Examples

```
## Not run:
if (require(leaflet)) {
  if (packageVersion("leaflet") > "2.1.1") {

    v <- vect(system.file("ex/lux.shp", package="terra"))
```



```

p <- spatSample(as.polygons(v, ext=T), 10)
values(p) = data.frame(id=11:20, name=letters[1:10])

m <- plet(v, "NAME_1", alpha=.5, tiles="")
m <- points(m, p, col="gray", cex=2, popup=T)
lines(m, v)

plet(v, "NAME_1", split=TRUE, alpha=.2) |>
  points(p, col="gray", cex=2, popup=T) |> lines(v)

s <- svc(v, p)
names(s) <- c("the polys", "set of points")
plet(s, col=c("red", "blue"), lwd=1)

r <- rast(system.file("ex/elev.tif", package="terra"))
plet(r, main="Hi\nthere") |> lines(v, lwd=1)

plet(r, tiles="Streets") |> lines(v, lwd=2, col="blue")

x <- c(r, 50*classify(r, 5))
names(x) <- c("first", "second")

# each their own legend
plet(x, 1:2, tiles="Streets", collapse=FALSE) |> lines(v, lwd=2, col="blue")

# shared legend
plet(x, 1:2, tiles="Streets", shared=TRUE, collapse=FALSE) |> lines(v, lwd=2, col="blue")

}}
## End(Not run)

```

---

plot

---

*Make a map*


---

## Description

Plot the values of a `SpatRaster` or `SpatVector` to make a map. See [lines](#) to add a `SpatVector` to an existing map.

## Usage

```

## S4 method for signature 'SpatRaster,numeric'
plot(x, y=1, col, type, mar=NULL, legend=TRUE, axes=TRUE, plg=list(), pax=list(),
      maxcell=500000, smooth=FALSE, range=NULL, levels=NULL, all_levels=FALSE,
      breaks=NULL, breakby="eqint", fun=NULL, colNA=NULL, alpha=NULL, sort=FALSE,
      decreasing=FALSE, grid=FALSE, ext=NULL, reset=FALSE, ...)

## S4 method for signature 'SpatRaster,missing'

```

```

plot(x, y, maxcell=500000, main, mar=NULL, nc, nr, maxnl=16, legend, ...)

## S4 method for signature 'SpatRaster,character'
plot(x, y, ...)

## S4 method for signature 'SpatVector,character'
plot(x, y, col, type, mar=NULL, legend=TRUE, add=FALSE, axes=!add,
     main=y, buffer=TRUE, background=NULL, grid=FALSE, ext=NULL,
     sort=TRUE, decreasing=FALSE, plg=list(), pax=list(), nr, nc, ...)

## S4 method for signature 'SpatVector,numeric'
plot(x, y, ...)

## S4 method for signature 'SpatVector,missing'
plot(x, y, values=NULL, ...)

## S4 method for signature 'SpatExtent,missing'
plot(x, y, ...)

```

### Arguments

x	SpatRaster or SpatVector
y	missing or positive integer or name indicating the layer(s) to be plotted
col	character. Colors. The default is <code>rev(grDevices::terrain.colors(50))</code> . If x is a SpatRaster, it can also be a data.frame with two columns (value, color) to get a "classes" type legend or with three columns (from, to, color) to get an "interval" type legend
type	character. Type of map/legend. One of "continuous", "classes", or "interval". If not specified, the type is chosen based on the data
mar	numeric vector of length 4 to set the margins of the plot (to make space for the legend). The default is (3.1, 3.1, 2.1, 7.1) for a single plot with a legend and (3.1, 3.1, 2.1, 2.1) otherwise. Use <code>mar=NA</code> to not set the margins
legend	logical or character. If not FALSE a legend is drawn. The character value can be used to indicate where the legend is to be drawn. For example "topright" or "bottomleft". Use <code>plg</code> for more refined placement. Not supported for continuous legends (the default for raster data)
axes	logical. Draw axes?
buffer	logical. If TRUE the plotting area is slightly larger than the extent of x
background	background color. Default is no color (white)
plg	list with parameters for drawing the legend. See the arguments for <a href="#">legend</a> . Argument <code>digits</code> can be used to set the number of digits to print (after the decimal point for a continuous legend)
pax	list with parameters for drawing axes. See the arguments for <a href="#">axis</a> . Arguments <code>side</code> , <code>tick</code> and <code>lab</code> can be used to indicate for which of the four axes to draw a line (side), tick mark, or label. The default is <code>c(1:4)</code> for side and <code>1:2</code> for the other two. If side is changed the other two default to that value. Logical

	argument <code>retro</code> can be used to use a sexagesimal notation for the labels (degrees/minutes/hemisphere) instead of the standard decimal notation
<code>maxcell</code>	positive integer. Maximum number of cells to use for the plot
<code>smooth</code>	logical. If TRUE the cell values are smoothed (only if a continuous legend is used)
<code>range</code>	numeric. minimum and maximum values to be used for the continuous legend
<code>levels</code>	character. labels for the legend when <code>type="classes"</code>
<code>all_levels</code>	logical. If TRUE, the legend shows all levels of a categorical raster, even if they are not present in the data
<code>breaks</code>	numeric. Either a single number to indicate the number of breaks desired, or the actual breaks. When providing this argument, the default legend becomes "interval"
<code>breakby</code>	character or function. Either "eqint" for equal interval breaks, "cases" for equal quantile breaks. If a function is supplied it should take a single argument (a vector of values) and create groups
<code>fun</code>	function to be called after plotting each <code>SpatRaster</code> layer to add something to each map (such as text, legend, lines). For example, with <code>SpatVector v</code> , you could do <code>fun=function() lines(v)</code> . The function may have one argument, representing the the layer that is plotted (1 to the number of layers)
<code>colNA</code>	character. color for the NA values
<code>alpha</code>	Either a single numeric between 0 and 1 to set the transparency for all colors (0 is transparent, 1 is opaque) or a <code>SpatRaster</code> with values between 0 and 1 to set the transparency by cell. To set the transparency for a given color, set it to the colors directly
<code>sort</code>	logical. If TRUE legends with categorical values are sorted. If <code>x</code> is a <code>SpatVector</code> you can also supply a vector of the unique values, in the order in which you want them to appear in the legend
<code>decreasing</code>	logical. If TRUE, legends are sorted in decreasing order
<code>grid</code>	logical. If TRUE grid lines are drawn. Their properties such as type and color can be set with the <code>pax</code> argument
<code>nc</code>	positive integer. Optional. The number of columns to divide the plotting device in (when plotting multiple layers)
<code>nr</code>	positive integer. Optional. The number of rows to divide the plotting device in (when plotting multiple layers)
<code>main</code>	character. Main plot titles (one for each layer to be plotted)
<code>maxnl</code>	positive integer. Maximum number of layers to plot (for a multi-layer object)
<code>add</code>	logical. If TRUE add the object to the current plot
<code>ext</code>	<code>SpatExtent</code> . Can be use instead of <code>xlim</code> and <code>ylim</code> to set the extent of the plot
<code>reset</code>	logical. If TRUE add the margins (see argument <code>mar</code> ) are reset to what they were before calling <code>plot</code> ; doing so may affect the display of additional objects that are added to the map (e.g. with <code>lines</code> )

values	Either a vector with values to be used for plotting or a two-column data.frame, where the first column matches a variable in x and the second column has the values to be plotted
...	arguments passed to plot("SpatRaster", "numeric") and additional graphical arguments

### See Also

[points](#), [lines](#), [polys](#), [image](#), [scatterplot](#), scale bar: [sbar](#), north arrow: [north](#)

### Examples

```
## raster
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
plot(r)

plot(r, type="interval")

e <- c(6.37, 6.41, 49.9, 50.1)
plot(r, plg=list(ext=e, title="Title\n", title.cex=1.25),
      pax=list(side=1:4, retro=TRUE))
north("topleft")

d <- classify(r, c(100,200,300,400,500,600))
plot(d, type="classes")

plot(d, type="interval", breaks=1:5)
plot(d, type="interval", breaks=c(1,4,5), plg=list(legend=c("1-4", "4-5")))
plot(d, type="classes", plg=list(legend=c("Mr", "Xx", "As", "Zx", "Bb"), x="bottomright"))

x <- trunc(r/200)
levels(x) <- data.frame(id=0:2, element=c("earth", "wind", "fire"))
plot(x, plg=list(x="topright"), mar=c(2,2,2,2))

# two plots with the same legend
dev.new(width=6, height=4, noRStudioGD = TRUE)
par(mfrow=c(1,2))
plot(r, range=c(50,600))
plot(r/2, range=c(50,600))

# as you only need one legend:
par(mfrow=c(1,2))
plot(r, range=c(50,600), mar=c(4, 3, 4, 3), plg=list(shrink=0.9, cex=.8),
      pax=list(side=1:2, cex.axis=.6))
#text(182500, 335000, "Two maps, one plot", xpd=NA)
plot(r/2, range=c(50,600), mar=c(4, 2, 4, 4), legend=FALSE,
      pax=list(side=c(1,4), cex.axis=.6))

# multi-layer with RGB
s <- rast(system.file("ex/logo.tif", package="terra"))
```

```

s
plot(s)
# remove RGB
plot(s*1)
# or use layers
plot(s, 1)
plot(s, 1:3)

# fix legend by linking values and colors

x = rast(nrows = 2, ncols = 2, vals=1)
y = rast(nrows = 2, ncols = 2, vals=c(1,2,2,1))
cols = data.frame(id=1:2, col=c("red", "blue"))
plot(c(x,y), col=cols)

r = rast(nrows=10, ncols=10, vals=1:100)
dr = data.frame(from=c(5,33,66,150), to=c(33, 66, 95,200), col=rainbow(4))
plot(r, col=dr)

### SpatVector

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)

plot(v)

plot(v, 2, pax=list(side=1:2), plg=list(x=6.2, y=50.2, cex=1.2))

plot(v, 4, pax=list(side=1:2), plg=list(x=6.2, y=50.2, ncol=2), main="")

plot(v, 1, plg=list(x=5.9, y=49.37, horiz=TRUE, cex=1.1), main="", mar=c(5,2,0.5,0.5))

plot(v, density=1:12, angle=seq(18, 360, 20), col=rainbow(12))

plot(v, "NAME_2", col=rainbow(12), border=c("gray", "blue"), lwd=3, type="classes")

plot(v, "AREA", type="interval", breaks=3, mar=c(3.1, 3.1, 2.1, 3.1),
     plg=list(x="topright"), main="")

plot(v, "AREA", type="interval", breaks=c(0,200,250,350), mar=c(2,2,2,2),
     plg=list(legend=c("<200", "200-250", ">250"), cex=1,
     bty="o", x=6.4, y=50.125, box.lwd=2, bg="light yellow", title="My Legend"))

```

---

plotRGB

---

*Red-Green-Blue plot of a multi-layered SpatRaster*


---

## Description

Make a Red-Green-Blue plot based on three layers in a SpatRaster. The layers (sometimes referred to as "bands" because they may represent different bandwidths in the electromagnetic spectrum) are

combined such that they represent the red, green and blue channel. This function can be used to make "true" (or "false") color images from Landsat and other multi-spectral satellite images.

Note that the margins of the plot are set to zero (no axes or titles are visible) but can be set with the `mar` argument.

An alternative way to plot RGB images is to first use `colorize` to create a single layer `SpatRaster` with a color-table and then use `plot`.

## Usage

```
## S4 method for signature 'SpatRaster'
plotRGB(x, r=1, g=2, b=3, a=NULL, scale, maxcell=500000, mar=0,
stretch=NULL, ext=NULL, smooth=FALSE, colNA="white", alpha, bgalpha,
addfun=NULL, zlim=NULL, zlimcol=NULL, axes=FALSE, xlab="", ylab="",
asp=NULL, add=FALSE, xlim, ylim,...)
```

## Arguments

<code>x</code>	<code>SpatRaster</code>
<code>r</code>	integer. Index of the Red channel, between 1 and <code>nlyr(x)</code>
<code>g</code>	integer. Index of the Green channel, between 1 and <code>nlyr(x)</code>
<code>b</code>	integer. Index of the Blue channel, between 1 and <code>nlyr(x)</code>
<code>a</code>	integer. Index of the alpha (transparency) channel, between 1 and <code>nlyr(x)</code> . If not <code>NULL</code> , argument <code>alpha</code> is ignored
<code>scale</code>	integer. Maximum (possible) value in the three channels. Defaults to 255 or to the maximum value of <code>x</code> if that is known and larger than 255
<code>maxcell</code>	integer > 0. Maximum number of pixels to use
<code>mar</code>	numeric vector recycled to length 4 to set the margins of the plot. Use <code>mar=NULL</code> or <code>mar=NA</code> to not set the margins
<code>stretch</code>	character. Option to stretch the values to increase contrast: "lin" (linear) or "hist" (histogram)
<code>ext</code>	An <code>SpatExtent</code> object to zoom in to a region of interest (see <code>draw</code> )
<code>smooth</code>	logical. If <code>TRUE</code> , smooth the image when drawing to get the appearance of a higher spatial resolution
<code>colNA</code>	color for the background (NA values)
<code>alpha</code>	transparency. Integer between 0 (transparent) and 255 (opaque)
<code>bgalpha</code>	Background transparency. Integer between 0 (transparent) and 255 (opaque)
<code>addfun</code>	Function to add additional items such as points or polygons to the plot (map). See <code>plot</code>
<code>zlim</code>	numeric vector of length 2. Range of values to plot (optional). If this is set, and <code>stretch="lin"</code> is used, then the values are stretched within the range of <code>zlim</code> . This allows creating consistent coloring between <code>SpatRasters</code> with different cell-value ranges, even when stretching the colors for improved contrast

zlimcol	If NULL the values outside the range of zlim get the color of the extremes of the range. If zlimcol has any other value, the values outside the zlim range get the color of NA values (see colNA)
axes	logical. If TRUE axes are drawn (and arguments such as main="title" will be honored)
xlab	character. Label of x-axis
ylab	character. Label of y-axis
asp	numeric. Aspect (ratio of x and y. If NULL, and appropriate value is computed to match data for the longitude/latitude coordinate reference system, and 1 for planar coordinate reference systems
add	logical. If TRUE add values to current plot
xlim	numeric. min and max values to set the extent of the x-axis
ylim	numeric. min and max values to set the extent of the y-axis
...	graphical parameters as in <a href="#">plot</a> or <a href="#">rasterImage</a>

**See Also**

[plot](#), [colorize](#), [RGB](#)

**Examples**

```
b <- rast(system.file("ex/logo.tif", package="terra"))
plotRGB(b)
plotRGB(b, mar=c(2,2,2,2))
plotRGB(b, 3, 2, 1)

b[1000:2000] <- NA
plotRGB(b, 3, 2, 1, stretch='hist')
```

---

predict

*Spatial model predictions*

---

**Description**

Make a SpatRaster object with predictions from a fitted model object (for example, obtained with `glm` or `randomForest`). The first argument is a SpatRaster object with the predictor variables. The [names](#) in the Raster object should exactly match those expected by the model. Any regression like model for which a predict method has been implemented (or can be implemented) can be used.

The method should work if the model's predict function returns a vector, matrix or data.frame (or a list that can be coerced to a data.frame). In other cases it may be necessary to provide a custom "predict" function that wraps the model's predict function to return the values in the required form. See the examples.

This approach of using model predictions is commonly used in remote sensing (for the classification of satellite images) and in ecology, for species distribution modeling.

**Usage**

```
## S4 method for signature 'SpatRaster'
predict(object, model, fun=predict, ..., factors=NULL, const=NULL, na.rm=FALSE,
        index=NULL, cores=1, cpgks=NULL, filename="", overwrite=FALSE, wopt=list())
```

**Arguments**

object	SpatRaster
model	fitted model of any class that has a "predict" method (or for which you can supply a similar method as fun argument. E.g. glm, gam, or randomForest
fun	function. The predict function that takes model as first argument. The default value is predict, but can be replaced with e.g. predict.se (depending on the type of model), or your own custom function
...	additional arguments for fun
const	data.frame. Can be used to add a constant value as a predictor variable so that you do not need to make a SpatRaster layer for it
factors	list with levels for factor variables. The list elements should be named with names that correspond to names in object such that they can be matched. This argument may be omitted for standard models such as "glm" as the predict function will extract the levels from the model object, but it is necessary in some other cases (e.g. cforest models from the party package)
na.rm	logical. If TRUE, cells with NA values in the predictors are removed from the computation. This option prevents errors with models that cannot handle NA values. In most other cases this will not affect the output. An exception is when predicting with a model that returns predicted values even if some (or all!) variables are NA
index	integer. To select subset of output variables
cores	positive integer. If cores > 1, a 'parallel' package cluster with that many cores is created and used
cpgks	character. The package(s) that need to be loaded on the nodes to be able to run the model.predict function (see examples)
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Examples**

```
logo <- rast(system.file("ex/logo.tif", package="terra"))
names(logo) <- c("red", "green", "blue")
p <- matrix(c(48, 48, 48, 53, 50, 46, 54, 70, 84, 85, 74, 84, 95, 85,
              66, 42, 26, 4, 19, 17, 7, 14, 26, 29, 39, 45, 51, 56, 46, 38, 31,
```



```

22, 34, 60, 70, 73, 63, 46, 43, 28), ncol=2)

a <- matrix(c(22, 33, 64, 85, 92, 94, 59, 27, 30, 64, 60, 33, 31, 9,
  99, 67, 15, 5, 4, 30, 8, 37, 42, 27, 19, 69, 60, 73, 3, 5, 21,
  37, 52, 70, 74, 9, 13, 4, 17, 47), ncol=2)

xy <- rbind(cbind(1, p), cbind(0, a))

# extract predictor values for points
e <- extract(logo, xy[,2:3])

# combine with response (excluding the ID column)
v <- data.frame(cbind(pa=xy[,1], e))

#build a model, here with glm
model <- glm(formula=pa~., data=v)

#predict to a raster
r1 <- predict(logo, model)

plot(r1)
points(p, bg='blue', pch=21)
points(a, bg='red', pch=21)

# logistic regression
model <- glm(formula=pa~., data=v, family="binomial")
r1log <- predict(logo, model, type="response")

# to get the probability and standard error
r1se <- predict(logo, model, se.fit=TRUE)

# or provide a custom predict function
predfun <- function(model, data) {
  v <- predict(model, data, se.fit=TRUE)
  cbind(p=as.vector(v$fit), se=as.vector(v$se.fit))
}

r2 <- predict(logo, model, fun=predfun)

# principal components of a SpatRaster
# here using sampling to simulate an object too large
# to feed all its values to prcomp

sr <- values(spatSample(logo, 100, as.raster=TRUE))
pca <- prcomp(sr)

x <- predict(logo, pca)
plot(x)

## parallelization
## Not run:
## simple case with GLM

```

```

model <- glm(formula=pa~., data=v)
p <- predict(logo, model, cores=2)

## The above does not work with a model from a contributed
## package, as the package needs to be loaded in each core.
## Below are three approaches to deal with that

library(randomForest)
rfm <- randomForest(formula=pa~., data=v)

## approach 0 (not parallel)
rp0 <- predict(logo, rfm)

## approach 1, use the "cpkgs" argument
rp1 <- predict(logo, rfm, cores=2, cpkgs="randomForest")

## approach 2, write a custom predict function that loads the package
rfun <- function(mod, dat, ...) {
  library(randomForest)
  predict(mod, dat, ...)
}
rp2 <- predict(logo, rfm, fun=rfun, cores=2)

## approach 3, write a parallelized custom predict function
rfun <- function(mod, dat, ...) {
  ncls <- length(cls)
  nr <- nrow(dat)
  s <- split(dat, rep(1:ncls, each=ceiling(nr/ncls), length.out=nr))
  unlist( parallel::clusterApply(cls, s, function(x, ...) predict(mod, x, ...)) )
}

library(parallel)
cls <- parallel::makeCluster(2)
parallel::clusterExport(cls, c("rfm", "rfun", "randomForest"))
rp3 <- predict(logo, rfm, fun=rfun)
parallel::stopCluster(cls)

plot(c(rp0, rp1, rp2, rp3))

### with two output variables (probabilities for each class)
v$pa <- as.factor(v$pa)
rfm2 <- randomForest(formula=pa~., data=v)
rfp <- predict(logo, rfm2, cores=2, type="prob", cpkgs="randomForest")

## End(Not run)

```

## Description

Change the coordinate reference system ("project") of a `SpatVector`, `SpatRaster` or a matrix with coordinates.

## Usage

```
## S4 method for signature 'SpatVector'
project(x, y)

## S4 method for signature 'SpatRaster'
project(x, y, method, mask=FALSE, align=FALSE,
        gdal=TRUE, res=NULL, origin=NULL, threads=FALSE, filename="", ...)

## S4 method for signature 'SpatExtent'
project(x, from, to)

## S4 method for signature 'matrix'
project(x, from, to)
```

## Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>y</code>	<p>if (<code>x</code> is a <code>SpatRaster</code>, the preferred approach is for <code>y</code> to be a <code>SpatRaster</code> as well, serving as a template for the geometry (extent and resolution) of the output <code>SpatRaster</code>. Alternatively, you can provide a coordinate reference system (CRS) description.</p> <p>You can use the following formats to define coordinate reference systems: WKT, PROJ.4 (e.g., <code>+proj=longlat +datum=WGS84</code>), or an EPSG code (e.g., <code>"epsg:4326"</code>). But note that the PROJ.4 notation has been deprecated, and you can only use it with the WGS84/NAD83 and NAD27 datums. Other datums are silently ignored.</p> <p>If <code>x</code> is a <code>SpatVector</code>, you can provide a crs definition as discussed above, or any other object from which such a crs can be extracted with <a href="#">crs</a></p>
<code>method</code>	<p>character. Method used for estimating the new cell values of a <code>SpatRaster</code>. One of:</p> <p><code>near</code>: nearest neighbor. This method is fast, and it can be the preferred method if the cell values represent classes. It is not a good choice for continuous values. This is used by default if the first layer of <code>x</code> is categorical.</p> <p><code>bilinear</code>: bilinear interpolation. This is the default if the first layer of <code>x</code> is numeric (not categorical).</p> <p><code>cubic</code>: cubic interpolation.</p> <p><code>cubicspline</code>: cubic spline interpolation.</p>
<code>mask</code>	logical. If <code>TRUE</code> , mask out areas outside the input extent (see example with Robinson projection)
<code>align</code>	logical. If <code>TRUE</code> , and <code>y</code> is a <code>SpatRaster</code> , the template is used for the spatial resolution and origin, but the extent is set such that all of the extent of <code>x</code> is included

<code>gdal</code>	logical. If TRUE the GDAL-warp algorithm is used. Otherwise a slower internal algorithm is used that may be more accurate if there is much variation in the cell sizes of the output raster. Only the near and bilinear algorithms are available for the internal algorithm
<code>res</code>	numeric. Can be used to set the resolution of the output raster if <code>y</code> is a CRS
<code>origin</code>	numeric. Can be used to set the origin of the output raster if <code>y</code> is a CRS
<code>threads</code>	logical. If TRUE multiple threads are used (faster for large files)
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>
<code>from</code>	character. Coordinate reference system of <code>x</code>
<code>to</code>	character. Output coordinate reference system

### Value

SpatVector or SpatRaster

### Note

The PROJ.4 notation of coordinate reference systems has been partly deprecated in the GDAL/PROJ library that is used by this function. You can still use this notation, but *\*only\** with the the WGS84 datum. Other datums are silently ignored.

Transforming (projecting) raster data is fundamentally different from transforming vector data. Vector data can be transformed and back-transformed without loss in precision and without changes in the values. This is not the case with raster data. In each transformation the values for the new cells are estimated in some fashion. Therefore, if you need to match raster and vector data for analysis, you should generally transform the vector data.

When using this method with a SpatRaster, the preferable approach is to provide a template SpatRaster as argument `y`. The template is then another raster dataset that you want your data to align with. If you do not have a template to begin with, you can do `project(x, crs)` and then manipulate the output to get the template you want. For example, where possible use whole numbers for the extent and resolution so that you do not have to worry about small differences in the future. You can use commands like `dim(z) = c(180, 360)` or `res(z) <- 100000`.

The output resolution should generally be similar to the input resolution, but there is no "correct" resolution in raster transformation. It is not obvious what this resolution is if you are using lon/lat data that spans a large North-South extent.

### See Also

[crs](#), [resample](#)

### Examples

```
## SpatRaster
a <- rast(ncols=40, nrows=40, xmin=-110, xmax=-90, ymin=40, ymax=60,
          crs="+proj=longlat +datum=WGS84")
values(a) <- 1:ncell(a)
newcrs="+proj=lcc +lat_1=48 +lat_2=33 +lon_0=-100 +datum=WGS84"
```

```

b <- rast(ncols=94, nrows=124, xmin=-944881, xmax=935118, ymin=4664377, ymax=7144377, crs=newcrs)
w <- project(a, b)

## SpatVector
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
crs(v, proj=TRUE)
cat(crs(v), "\n")

project(v, "+proj=moll")

project(v, "EPSG:2169")

```

quantile

*Quantiles of spatial data***Description**

Compute quantiles for each cell across the layers of a `SpatRaster`.

You can use `global(x, fun=quantile)` to instead compute quantiles across cells for each layer.

You can also use this method to compute quantiles of the numeric variables of a `SpatVector`.

**Usage**

```

## S4 method for signature 'SpatRaster'
quantile(x, probs=seq(0, 1, 0.25), na.rm=FALSE, filename="", ...)

## S4 method for signature 'SpatVector'
quantile(x, probs=seq(0, 1, 0.25), ...)

```

**Arguments**

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>probs</code>	numeric vector of probabilities with values in [0,1]
<code>na.rm</code>	logical. If TRUE, NA's are removed from x before the quantiles are computed
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

`SpatRaster` with layers representing quantiles

**See Also**

[app](#)

Examples

```
r <- rast(system.file("ex/logo.tif", package="terra"))
rr <- c(r/2, r, r*2)
qr <- quantile(rr)
qr

## Not run:
# same but slower
qa <- app(rr, quantile)

## End(Not run)

#quantile by layer instead of by cell
qg <- global(r, quantile)
```

---

query	<i>Query a SpatVectorProxy object</i>
-------	---------------------------------------

---

Description

Query a SpatVectorProxy to extract a subset

Usage

```
## S4 method for signature 'SpatVectorProxy'
query(x, start=1, n=nrow(x), vars=NULL, where=NULL,
      extent=NULL, filter=NULL)
```

Arguments

x	SpatVectorProxy
start	positive integer. The record to start reading at
n	positive integer. The number of records requested
vars	character. Variable names. Must be a subset of names(x)
where	character. expression like "NAME_1='California' AND ID > 3" , to subset records. Note that start and n are applied after executing the where statement
extent	Spat* object. The extent of the object is used as a spatial filter to select the geometries to read. Ignored if filter is not NULL
filter	SpatVector. Used as a spatial filter to select geometries to read (the convex hull is used for lines or points)

Value

SpatVector

**See Also**[vect](#)**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f, proxy=TRUE)
v

x <- query(v, vars=c("ID_2", "NAME_2"), start=5, n=2)
x

query(v, vars=c("ID_2", "NAME_1", "NAME_2"), where="NAME_1='Grevenmacher' AND ID_2 > 6")

## with an extent
e <- ext(5.9, 6.3, 49.9, 50)
x <- query(v, extent=e)

## with polygons
p <- as.polygons(e)
x <- query(v, filter=p)
x
```

---

rapp*Range-apply*

---

**Description**

Apply a function to a range of the layers of a `SpatRaster` that varies by cell. The range is specified for each cell with one or two `SpatRasters` (arguments `first` and `last`). For either `first` or `last` you can use a single number instead.

You cannot use single numbers for both `first` and `last` because in that case you could use [app](#) or [Summary-methods](#), perhaps [subsetting](#) the layers of a `SpatRaster`.

See [selectRange](#) to create a new `SpatRaster` by extracting one or more values starting at a cell-varying layer.

**Usage**

```
## S4 method for signature 'SpatRaster'
rapp(x, first, last, fun, ..., alllys=FALSE, fill=NA,
     clamp=FALSE, circular=FALSE, filename="", overwrite=FALSE, wopt=list())
```

**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>first</code>	<code>SpatRaster</code> or positive integer between 1 and <code>nlyr(x)</code> , indicating the first layer in the range of layers to be considered

last	SpatRaster or positive integer between 1 and nlyr(x), indicating the last layer in the range to be considered
fun	function to be applied
...	additional arguments passed to fun
allyrs	logical. If TRUE, values for all layers are passed to fun but the values outside of the range are set to fill
fill	numeric. The fill value for the the values outside of the range, for when allyrs=TRUE
clamp	logical. If FALSE and the specified range is outside 1:nlyr(x) all cells are considered NA. Otherwise, the invalid part of the range is ignored
circular	logical. If TRUE the values are considered circular, such as the days of the year. In that case, if first > last the layers used are c(first:nlyr(x), 1:last). Otherwise, the range would be considered invalid and NA would be returned
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

### Value

SpatRaster

### See Also

[selectRange](#), [app](#), [Summary-methods](#), [lapp](#), [tapp](#)

### Examples

```
r <- rast(ncols=9, nrows=9)
values(r) <- 1:ncell(r)
s <- c(r, r, r, r, r, r)
s <- s * 1:6
s[1:2] <- NA
start <- end <- rast(r)
start[] <- 1:3
end[] <- 4:6
a <- rapp(s, start, end, fun="mean")
b <- rapp(s, start, 2, fun="mean")

# cumsum from start to nlyr(x). return all layers
r <- rapp(s, start, nlyr(s), cumsum, allyrs=TRUE, fill=0)
# return only the final value
rr <- rapp(s, start, nlyr(s), function(i) max(cumsum(i)))
```



---

rast

---

Create a *SpatRaster*


---

## Description

Methods to create a *SpatRaster*. These objects can be created from scratch, from a filename, or from another object.

A *SpatRaster* represents a spatially referenced surface divided into three dimensional cells (rows, columns, and layers).

When a *SpatRaster* is created from a file, it does not load the cell (pixel) values into memory (RAM). It only reads the parameters that describe the geometry of the *SpatRaster*, such as the number of rows and columns and the coordinate reference system. The actual values will be read when needed.

## Usage

```
## S4 method for signature 'character'
rast(x, subds=0, lyrs=NULL, drivers=NULL, opts=NULL)

## S4 method for signature 'missing'
rast(x, nrows=180, ncols=360, nlyrs=1, xmin=-180, xmax=180,
      ymin=-90, ymax=90, crs, extent, resolution, vals, names, time, units)

## S4 method for signature 'SpatRaster'
rast(x, nlyrs=nlyr(x), names, vals, keeptime=TRUE, keepunits=FALSE, props=FALSE)

## S4 method for signature 'matrix'
rast(x, type="", crs="", digits=6, extent=NULL)

## S4 method for signature 'data.frame'
rast(x, type="xyz", crs="", digits=6, extent=NULL)

## S4 method for signature 'array'
rast(x, crs="", extent=NULL)

## S4 method for signature 'list'
rast(x, warn=TRUE)

## S4 method for signature 'SpatRasterDataset'
rast(x)

## S4 method for signature 'SpatVector'
rast(x, ...)

## S4 method for signature 'SpatExtent'
rast(x, ...)
```

**Arguments**

<code>x</code>	filename (character), missing, <code>SpatRaster</code> , <code>SpatRasterDataset</code> , <code>SpatExtent</code> , <code>SpatVector</code> , matrix, array, list of <code>SpatRaster</code> objects. For other types it will be attempted to create a <code>SpatRaster</code> via ( <code>as(x, "SpatRaster")</code> )
<code>subds</code>	positive integer or character to select a sub-dataset. If zero or "", all sub-datasets are returned (if possible)
<code>lyrs</code>	positive integer or character to select a subset of layers (a.k.a. "bands")
<code>drivers</code>	character. GDAL drivers to consider
<code>opts</code>	character. GDAL dataset open options
<code>nrows</code>	positive integer. Number of rows
<code>ncols</code>	positive integer. Number of columns
<code>nlyrs</code>	positive integer. Number of layers
<code>xmin</code>	minimum x coordinate (left border)
<code>xmax</code>	maximum x coordinate (right border)
<code>ymin</code>	minimum y coordinate (bottom border)
<code>ymax</code>	maximum y coordinate (top border)
<code>crs</code>	character. Description of the Coordinate Reference System (map projection) in PROJ.4, WKT or authority:code notation. See <a href="#">crs</a> . If this argument is missing, and the x coordinates are within -360 .. 360 and the y coordinates are within -90 .. 90, longitude/latitude is assigned
<code>keeptime</code>	logical. If FALSE the time stamps are discarded
<code>keepunits</code>	logical. If FALSE the layer units are discarded
<code>props</code>	logical. If TRUE the properties (categories and color-table) are kept
<code>extent</code>	object of class <code>SpatExtent</code> . If present, the arguments <code>xmin</code> , <code>xmax</code> , <code>ymin</code> and <code>ymax</code> are ignored
<code>resolution</code>	numeric vector of length 1 or 2 to set the spatial resolution (see <a href="#">res</a> ). If this argument is used, arguments <code>ncols</code> and <code>nrows</code> are ignored
<code>vals</code>	numeric. An optional vector with cell values (if fewer values are provided, these are recycled to reach the number of cells)
<code>names</code>	character. An optional vector with layer names (must match the number of layers)
<code>time</code>	time or date stamps for each layer
<code>units</code>	character. units for each layer
<code>type</code>	character. If the value is not "xyz", the raster has the same number of rows and columns as the matrix. If the value is "xyz", the matrix must have at least two columns, the first with x (or longitude) and the second with y (or latitude) coordinates that represent the centers of raster cells. The additional columns are the values associated with the raster cells.
<code>digits</code>	integer to set the precision for detecting whether points are on a regular grid (a low number of digits is a low precision). Only used when <code>type="xyz"</code>
<code>warn</code>	logical. If TRUE, a warnings about empty rasters may be emitted
<code>...</code>	additional arguments passed on to the <code>rast,missing-method</code>

## Details

Files are read with the GDAL library. GDAL guesses the file format from the name, and/or tries reading it with different "drivers" (see [gdal](#)) until it succeeds. In very few cases this may cause a file to be opened with the wrong driver, and some information may be lost. For example, when a netCDF file is opened with the HDF5 driver. You can avoid that by using argument `rast("filename.ncdf", drivers="NETCDF")`

These classes hold a C++ pointer to the data "reference class" and that creates some limitations. They cannot be recovered from a saved R session either or directly passed to nodes on a computer cluster. Generally, you should use [writeRaster](#) to save `SpatRaster` objects to disk (and pass a filename or cell values of cluster nodes). Also see [wrap](#).

## Value

`SpatRaster`

## See Also

[sds](#) to create a `SpatRasterDataset` (4 dimensions) and [vect](#) for vector (points, lines, polygons) data

## Examples

```
# Create a SpatRaster from scratch
x <- rast(nrows=108, ncols=21, xmin=0, xmax=10)

# Create a SpatRaster from a file
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)

s <- rast(system.file("ex/logo.tif", package="terra"))

# Create a skeleton with no associated cell values
rast(s)

# from a matrix
m <- matrix(1:25, nrow=5, ncol=5)
rm <- rast(m)

# from a "xyz" data.frame
d <- as.data.frame(rm, xy=TRUE)
head(d)
rast(d, type="xyz")
```

---

rasterize

*Rasterize vector data*


---

## Description

Transfer values associated with the geometries of vector data to a raster

**Usage**

```
## S4 method for signature 'SpatVector,SpatRaster'
rasterize(x, y, field="", fun, ..., background=NA, touches=FALSE,
update=FALSE, sum=FALSE, cover=FALSE, filename="", overwrite=FALSE, wopt=list())

## S4 method for signature 'matrix,SpatRaster'
rasterize(x, y, values=1, fun, ..., background=NA,
update=FALSE, filename="", overwrite=FALSE, wopt=list())
```

**Arguments**

x	SpatVector or a two-column matrix (point coordinates)
y	SpatRaster
field	character or numeric. If field is a character, it should a variable name in x. If field is numeric it typically is a single number or a vector of length nrow(x). The values are recycled to nrow(x)
values	typically a numeric vector of length 1 or nrow(x). If the length is below nrow(x) the values will be recycled to nrow(x). Only used when x is a matrix. Can also be a matrix or data.frame
fun	function, summarizing function that returns a single number; for when there are multiple points in one cell. For example mean, length (to get a count), min or max. Only used if x consists of points
...	additional arguments passed to fun if x has point geometries
background	numeric. Value to put in the cells that are not covered by any of the features of x. Default is NA
touches	logical. If TRUE, all cells touched by lines or polygons are affected, not just those on the line render path, or whose center point is within the polygon. If touches=TRUE, add cannot be TRUE
update	logical. If TRUE, the values of the input SpatRaster are updated
sum	logical. If TRUE, the values of overlapping geometries are summed instead of replaced; and background is set to zero. Only used if x does not consists of points
cover	logical. If TRUE and the geometry of x is polygons, the fraction of a cell that is covered by the polygons is returned. This is estimated by determining presence/absence of the polygon in at least 100 sub-cells (more of there are very few cells)
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[rasterizeGeom](#), [rasterizeWin](#), [mask](#)

**Examples**

```
r <- rast(xmin=0, ncols=18, nrows=18)

# generate points
set.seed(1)
p <- spatSample(r, 1000, xy=TRUE, replace=TRUE)

# rasterize points as a matrix
x <- rasterize(p, r, fun=sum)
y <- rasterize(p, r, value=1:nrow(p), fun=max)

# rasterize points as a SpatVector
pv <- vect(p)
xv <- rasterize(pv, r, fun=sum)

# Polygons
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
r <- rast(v, ncols=75, nrows=100)
z <- rasterize(v, r, "NAME_2")
plot(z)
lines(v)
```

---

rasterizeGeom

*Rasterize geometric properties of vector data*


---

**Description**

Rasterization of geometric properties of vector data. You can get the count of the number of geometries in each cell; the area covered by polygons; the length of the lines; or the number of lines that cross each cell. See [rasterize](#) for standard rasterization (of attribute values associated with geometries).

The area of polygons is intended for summing the area of polygons that are relatively small relative to the raster cells, and for when there may be multiple polygons per cell. See `rasterize(sum=TRUE)` for counting large polygons and `rasterize(cover=TRUE)` to get the fraction that is covered by larger polygons.

**Usage**

```
## S4 method for signature 'SpatVector,SpatRaster'
rasterizeGeom(x, y, fun="count", unit="m", filename="", ...)
```

**Arguments**

x	SpatVector
y	SpatRaster
fun	character. "count", "area", "length", or "crosses"
unit	character. "m" or "km"
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[rasterize](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
r <- rast(v, res=.1)

# length of lines
lms <- as.lines(v)
x <- rasterizeGeom(lms, r, fun="length", "km")

# count of points
set.seed(44)
pts <- spatSample(v, 100)
y <- rasterizeGeom(pts, r)

# area of polygons
pols <- buffer(pts, 1000)
z <- rasterizeGeom(pols, r, fun="area")
```

---

rasterizeWin

*Rasterize points with a moving window*


---

**Description**

Rasterize points using a circle (or ellipse) as moving window. For each raster cell, the points (x, y) that fall within the window centered on that cell are considered. A function is used to compute a summary value (e.g. "mean") for the values (z) associated with these points.

This can result in much smoother results compared to the standard [rasterize](#) method.

**Usage**

```
## S4 method for signature 'SpatVector,SpatRaster'
rasterizeWin(x, y, field, win="circle", pars, fun, ..., cvars=FALSE,
             minPoints=1, fill=NA, filename="", wopt=list())

## S4 method for signature 'data.frame,SpatRaster'
rasterizeWin(x, y, win="circle", pars, fun, ..., cvars=FALSE,
             minPoints=1, fill=NA, filename="", wopt=list())
```

**Arguments**

x	SpatVector or matrix with at least three columns ((x, y) coordinates and a variable to be rasterized)
y	SpatRaster
field	character. field name in SpatVector x with the values to rasterize
win	character to choose the window type. Can be "circle", "ellipse", "rectangle", or "buffer"
pars	parameters to define the window. If win="circle" or win="buffer", a single number to set the radius of the circle or the width of the buffer. If win="ellipse", either two numbers (the x and y-axis) or three numbers the axes and a rotation (in degrees). If win="rectangle", either two (width, height) or three (width, height) and the rotation in degrees. The unit of the radius/width/height/axis parameters is that of the coordinate reference system. That is, if you have a lon/lat crs, there is no conversion of degrees to meters or vice-versa
fun	function to summarize the values for each cell. If cvars=FALSE, functions must take a numeric vector and return (in all cases) one or more numbers. If cvars=TRUE, and multiple variables are used, the function must take a single argument (a data.frame with the names variables). For win="circle" and win="ellipse" there are two additional character values that can be used: "distto" (average distance to the points from the center of the cell) and "distbetween" (average distance between the points inside the window)
...	additional named arguments passed to fun
minPoints	numeric. The minimum number of points to use. If fewer points are found in a search ellipse it is considered empty and the fill value is returned
fill	numeric. value to use to fill cells with empty search areas
cvars	logical. When using multiple fields, should fun operate on all of them at once? If not, fun is applied to each variable separately
filename	character. Output filename
wopt	list with additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[rasterize](#), [rasterizeGeom](#), [interpNear](#), [interpIDW](#)

**Examples**

```
r <- rast(ncol=100, nrow=100, crs="local", xmin=0, xmax=50, ymin=0, ymax=50)
set.seed(100)
x <- runif(50, 5, 45)
y <- runif(50, 5, 45)
z <- sample(50)
xyz <- data.frame(x,y,z)

r <- rasterizeWin(xyz, r, fun="count", pars=5)

rfuns <- c("count", "min", "max", "mean")
x <- lapply(rfun, function(f) rasterizeWin(xyz, r, fun=f, pars=5))
names(x) <- rfuns
x <- rast(x)
#plot(x)
```

---

rcl

---

*Combine row, column, and layer numbers*


---

**Description**

Get a matrix with the combination of row, column, and layer numbers

**Usage**

```
## S4 method for signature 'SpatRaster'
rcl(x, row=NULL, col=NULL, lyr=NULL)
```

**Arguments**

x	SpatRaster
row	positive integer that are row number(s), a list thereof, or NULL for all rows
col	as above for columns
lyr	as above for layers

**Details**

If a list is used for at least one of row, col or lyr, these are evaluated in parallel. That is combinations are made for each list element, not across list elements. If, in this case another argument is not a list it has to have either length 1 (used for all cases) or have the same length as the (longest) list, in which case the value is coerced into a list with `as.list`

If multiple arguments are a list but they have different lengths, they are recycled to the longest list.



**Value**

matrix

**See Also**[rowColCombine](#), [cellFromRowCol](#)**Examples**

```
x <- rast(ncol=5, nrow=5, nlyr=2)
values(x) <- 1:size(x)

rcl(x, 1, 2:3, 1:2)

i <- rcl(x, 1, list(1:2, 3:4), 1:2)
i

# get the values for these cells
x[i]
```

---

read and write

*Read from, or write to, file*


---

**Description**

Methods to read from or write chunks of values to or from a file. These are low level methods for programmers. Use `writeRaster` if you want to save an entire `SpatRaster` to file in one step. It is much easier to use.

To write chunks, begin by opening a file with `writeStart`, then write values to it in chunks using the list that is returned by `writeStart`. When writing is done, close the file with `writeStop`.

`blocks` only returns chunk size information. This can be useful when reading, but not writing, raster data.

**Usage**

```
## S4 method for signature 'SpatRaster'
readStart(x)

## S4 method for signature 'SpatRaster'
readStop(x)

## S4 method for signature 'SpatRaster'
readValues(x, row=1, nrow=nrow(x), col=1, ncol=ncol(x), mat=FALSE, dataframe=FALSE, ...)

## S4 method for signature 'SpatRaster,character'
writeStart(x, filename="", overwrite=FALSE, n=4, sources="", ...)
```

```
## S4 method for signature 'SpatRaster'
writeStop(x)

## S4 method for signature 'SpatRaster,vector'
writeValues(x, v, start, nrow)

## S4 method for signature 'SpatRaster'
blocks(x, n=4)

fileBlocksize(x)
```

### Arguments

<code>x</code>	<code>SpatRaster</code>
<code>filename</code>	character. Output filename
<code>v</code>	vector with cell values to be written
<code>start</code>	integer. Row number (counting starts at 1) from where to start writing <code>v</code>
<code>row</code>	positive integer. Row number to start from, should be between 1 and <code>nrow(x)</code>
<code>nrow</code>	positive integer. How many rows?
<code>col</code>	positive integer. Column number to start from, should be between 1 and <code>ncol(x)</code>
<code>ncols</code>	positive integer. How many columns? Default is the number of columns left after the start column
<code>mat</code>	logical. If <code>TRUE</code> , values are returned as a numeric matrix instead of as a vector, except when <code>dataframe=TRUE</code> . If any of the layers of <code>x</code> is a factor, the level index is returned, not the label. Use <code>dataframe=TRUE</code> to get the labels
<code>dataframe</code>	logical. If <code>TRUE</code> , values are returned as a data.frame instead of as a vector (also if matrix is <code>TRUE</code> )
<code>overwrite</code>	logical. If <code>TRUE</code> , <code>filename</code> is overwritten
<code>n</code>	positive integer indicating how many copies the data may be in memory at any point in time. This is used to determine how many blocks (large) datasets need to be read
<code>sources</code>	character. Filenames that may not be overwritten because they are used as input to the function. Can be obtained with <code>sources(x)</code>
<code>...</code>	For <code>writeStart</code> : additional arguments for writing files as in <a href="#">writeRaster</a> For <code>readValues</code> : additional arguments for <a href="#">data.frame</a> (and thus only relevant when <code>dataframe=TRUE</code> )

### Value

`readValues` returns a vector, matrix, or data.frame

`writeStart` returns a list that can be used for processing the file in chunks.

The other methods invisibly return a logical value indicating whether they were successful or not. Their purpose is the side-effect of opening or closing files.

---

rectify	<i>Rectify a SpatRaster</i>
---------	-----------------------------

---

### Description

Rectify a rotated SpatRaster into a non-rotated object

### Usage

```
## S4 method for signature 'SpatRaster'
rectify(x, method="bilinear", aoI=NULL, snap=TRUE,
        filename="", ...)
```

### Arguments

x	SpatRaster to be rectified
method	character. Method used to for resampling. See <a href="#">resample</a>
aoi	SpatExtent or SpatRaster to crop x to a smaller area of interest; Using a SpatRaster allowing to set the exact output extent and output resolution
snap	logical. If TRUE, the origin and resolution of the output are the same as would the case when aoI = NULL. Only relevant if aoI is a SpatExtent
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

### Value

SpatRaster

---

relate	<i>Spatial relationships between geometries</i>
--------	---

---

### Description

relate returns a logical matrix indicating the presence or absence of a specific spatial relationships between the geometries in x and y.

is.related returns a logical vector indicating the presence or absence of a specific spatial relationships between x and any of the geometries in y

**Usage**

```
## S4 method for signature 'SpatVector,SpatVector'
relate(x, y, relation, pairs=FALSE, na.rm=TRUE)

## S4 method for signature 'SpatVector,missing'
relate(x, y, relation, pairs=FALSE, na.rm=TRUE)

## S4 method for signature 'SpatVector,SpatVector'
is.related(x, y, relation)
```

**Arguments**

x	SpatVector or SpatExtent
y	missing or as for x
relation	character. One of "intersects", "touches", "crosses", "overlaps", "within", "contains", "covers", "coveredby", "disjoint". Or a "DE-9IM" string such as "FF*FF*****". See <a href="#">wikipedia</a> or <a href="#">geotools doc</a>
pairs	logical. If TRUE a two-column matrix is returned with the indices of the cases where the requested relation is TRUE. This is especially helpful when dealing with many geometries as the returned value is generally much smaller
na.rm	logical. If TRUE and sparse=TRUE, geometries in x for which there is no related geometry in y are omitted

**Value**

matrix (relate) or vector (is.related)

**See Also**

[adjacent](#), [nearby](#), [intersect](#), [crop](#)

**Examples**

```
# polygons
p1 <- vect("POLYGON ((0 0, 8 0, 8 9, 0 9, 0 0))")
p2 <- vect("POLYGON ((5 6, 15 6, 15 15, 5 15, 5 6))")
p3 <- vect("POLYGON ((8 2, 9 2, 9 3, 8 3, 8 2))")
p4 <- vect("POLYGON ((2 6, 3 6, 3 8, 2 8, 2 6))")
p5 <- vect("POLYGON ((2 12, 3 12, 3 13, 2 13, 2 12))")
p6 <- vect("POLYGON ((10 4, 12 4, 12 7, 11 7, 11 6, 10 6, 10 4))")

p <- rbind(p1, p2, p3, p4, p5, p6)
plot(p, col=rainbow(6, alpha=.5))
lines(p, lwd=2)
text(p)

## relate SpatVectors
relate(p1, p2, "intersects")
relate(p1, p3, "touches")
```

```

relate(p1, p5, "disjoint")
relate(rbind(p1, p2), p4, "disjoint")

## relate geometries within SpatVectors
# which are completely separated?
relate(p, relation="disjoint")

# which touch (not overlap or within)?
relate(p, relation="touches")
# which overlap (not merely touch, and not within)?
relate(p, relation="overlaps")
# which are within (not merely overlap)?
relate(p, relation="within")

# do they touch or overlap or are within?
relate(p, relation="intersects")

all(relate(p, relation="intersects") ==
     (relate(p, relation="overlaps") |
      relate(p, relation="touches") |
      relate(p, relation="within")))

#for polygons, "coveredby" is "within"
relate(p, relation="coveredby")

# polygons, lines, and points

pp <- rbind(p1, p2)
L1 <- vect("LINESTRING(1 11, 4 6, 10 6)")
L2 <- vect("LINESTRING(8 14, 12 10)")
L3 <- vect("LINESTRING(1 8, 12 14)")
lns <- rbind(L1, L2, L3)
pts <- vect(cbind(c(7,10,10), c(3,5,6)))

plot(pp, col=rainbow(2, alpha=.5))
text(pp, paste0("POL", 1:2), halo=TRUE)
lines(pp, lwd=2)
lines(lns, col=rainbow(3), lwd=4)
text(lns, paste0("L", 1:3), halo=TRUE)
points(pts, cex=1.5)
text(pts, paste0("PT", 1:3), halo=TRUE, pos=4)

relate(lns, relation="crosses")
relate(lns, pp, relation="crosses")
relate(lns, pp, relation="touches")
relate(lns, pp, relation="intersects")

relate(lns, pp, relation="within")
# polygons can contain lines or points, not the other way around
relate(lns, pp, relation="contains")
relate(pp, lns, relation="contains")
# points and lines can be covered by polygons

```

```
relate(lns, pp, relation="coveredby")

relate(pts, pp, "within")
relate(pts, pp, "touches")
relate(pts, lns, "touches")
```

---

rep	<i>Replicate layers</i>
-----	-------------------------

---

**Description**

Replicate layers in a SpatRaster

**Usage**

```
## S4 method for signature 'SpatRaster'
rep(x, ...)
```

**Arguments**

- x                   SpatRaster
- ...                 arguments as in [rep](#)

**Value**

SpatRaster

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra"))
x <- rep(s, 2)
nlyr(x)
names(x)
x
```

---

replace_dollar	<i>Replace with \$&lt;-</i>
----------------	-----------------------------

---

## Description

Replace a layer of a `SpatRaster`, or an attribute variable of a `SpatVector`

## Usage

```
## S4 replacement method for signature 'SpatRaster'
x$name <- value

## S4 replacement method for signature 'SpatVector'
x$name<-value

## S4 replacement method for signature 'SpatExtent'
x$name <- value
```

## Arguments

<code>x</code>	<code>SpatRaster</code> , <code>SpatVector</code> or <code>SpatExtent</code>
<code>name</code>	character. If <code>x</code> is a <code>SpatRaster</code> : layer name. If <code>x</code> is a <code>SpatVector</code> : variable name. If <code>x</code> is a <code>SpatExtent</code> : "xmin", "xmax". "ymin" or "ymax"
<code>value</code>	if <code>x</code> is a <code>SpatRaster</code> , a <code>SpatRaster</code> for which this TRUE: <code>nlyr(value) == length(i)</code> ; if <code>x</code> is a <code>SpatVector</code> , a vector of new values; if <code>x</code> is a <code>SpatExtent</code> a single number

## Value

Same as `x`

## See Also

[\[\[<-](#), [\[<-](#), [\\$](#)

## Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
v$ID_1 <- LETTERS[1:12]
v$new <- sample(12)
values(v)
```

---

replace_layers	<i>Replace layers or variables</i>
----------------	------------------------------------

---

## Description

Replace the layers of `SpatRaster` with (layers from) another `SpatRaster` or replace variables of a `SpatVector`. You can also create new layers/variables with these methods.

## Usage

```
## S4 replacement method for signature 'SpatRaster,numeric'
x[[i]] <- value

## S4 replacement method for signature 'SpatRaster,character'
x[[i]] <- value

## S4 replacement method for signature 'SpatVector,numeric'
x[[i]] <- value

## S4 replacement method for signature 'SpatVector,character'
x[[i]] <- value
```

## Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>i</code>	if <code>x</code> is a <code>SpatRaster</code> : layer number(s) of name(s). If <code>x</code> is a <code>SpatVector</code> : variable number(s) or name(s) (column of the attributes)
<code>value</code>	if <code>x</code> is a <code>SpatRaster</code> : <code>SpatRaster</code> for which this TRUE: <code>nlyr(value) == length(i)</code> . if <code>x</code> is a <code>SpatVector</code> : vector or <code>data.frame</code>

## Value

`SpatRaster`

## See Also

[\\$<-](#), [\[<-](#)

## Examples

```
# raster
s <- rast(system.file("ex/logo.tif", package="terra"))
s[["red"]] <- mean(s)
s[[2]] <- sqrt(s[[1]])

# vector
v <- vect(system.file("ex/lux.shp", package="terra"))
v[["ID_1"]] <- 12:1
```



---

replace_values	<i>Replace values of a SpatRaster</i>
----------------	---------------------------------------

---

### Description

Replace values of a SpatRaster. These are convenience functions for smaller objects only. For larger rasters see [link{classify}](#) or [subst](#)

### Usage

```
## S4 replacement method for signature 'SpatRaster,ANY,ANY,ANY'
x[i, j, k] <- value

## S4 replacement method for signature 'SpatVector,ANY,ANY'
x[i, j] <- value

## S4 replacement method for signature 'SpatExtent,numeric,missing'
x[i, j] <- value
```

### Arguments

x	SpatRaster
i	row numbers. numeric, logical, or missing for all rows. Can also be a SpatRaster or SpatVector
j	column numbers. numeric, logical or missing for all columns
k	layer number. numeric, logical or missing for all layers
value	numeric, matrix, or data.frame

### Value

SpatRaster

### See Also

[classify](#), [subst](#), [set.values](#), [values](#), [\[\[<-](#)

### Examples

```
## SpatRaster
r <- rast(ncols=5, nrows=5, xmin=0, xmax=5, ymin=0, ymax=5)
r[] <- 1:25
r[1,] <- 5
r[,2] <- 10
r[r>10] <- NA

## SpatVector
f <- system.file("ex/lux.shp", package="terra")
```

```
v <- vect(f)
v[2,2] <- "hello"
v[1,] <- v[10,]
v[,3] <- v[,1]
v[2, "NAME_2"] <- "terra"
head(v, 3)
```

---

resample	<i>Transfer values of a SpatRaster to another one with a different geometry</i>
----------	---

---

## Description

resample transfers values between SpatRaster objects that do not align (have a different origin and/or resolution). See [project](#) to change the coordinate reference system (crs).

If the origin and extent of the input and output are the same, you should consider using these other functions instead: [aggregate](#), [disagg](#), [extend](#) or [crop](#).

## Usage

```
## S4 method for signature 'SpatRaster,SpatRaster'
resample(x, y, method, threads=FALSE, filename="", ...)
```

## Arguments

x	SpatRaster to be resampled
y	SpatRaster with the geometry that x should be resampled to
method	character. Method used for estimating the new cell values. One of: near: nearest neighbor. This method is fast, and it can be the preferred method if the cell values represent classes. It is not a good choice for continuous values. This is used by default if the first layer of x is categorical. bilinear: bilinear interpolation. This is the default if the first layer of x is numeric (not categorical). cubic: cubic interpolation. cubicspline: cubic spline interpolation. lanczos: Lanczos windowed sinc resampling. sum: the weighted sum of all non-NA contributing grid cells. min, q1, med, q3, max, average, mode, rms: the minimum, first quartile, median, third quartile, maximum, mean, mode, or root-mean-square value of all non-NA contributing grid cells.
threads	logical. If TRUE multiple threads are used (faster for large files)
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

Value

SpatRaster

See Also

[aggregate](#), [disagg](#), [crop](#), [project](#),

Examples

```
r <- rast(nrows=3, ncols=3, xmin=0, xmax=10, ymin=0, ymax=10)
values(r) <- 1:ncell(r)
s <- rast(nrows=25, ncols=30, xmin=1, xmax=11, ymin=-1, ymax=11)
x <- resample(r, s, method="bilinear")

opar <- par(no.readonly =TRUE)
par(mfrow=c(1,2))
plot(r)
plot(x)
par(opar)
```

---

rescale	<i>rescale</i>
---------	----------------

---

Description

Rescale a SpatVector or SpatRaster. This may be useful to make small [inset](#) maps or for georeferencing.

Usage

```
## S4 method for signature 'SpatRaster'
rescale(x, fx=0.5, fy=fx, x0, y0)

## S4 method for signature 'SpatVector'
rescale(x, fx=0.5, fy=fx, x0, y0)
```

Arguments

x	SpatVector or SpatRaster
fx	numeric > 0. The horizontal scaling factor
fy	numeric > 0. The vertical scaling factor
x0	numeric. x-coordinate of the center of rescaling. If missing, the center of the extent of x is used
y0	numeric. y-coordinate of the center of rescaling. If missing, the center of the extent of x is used

**Value**

Same as x

**See Also**

[t](#), [shift](#), [flip](#), [rotate](#), [inset](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
w <- rescale(v, 0.2)
plot(v)
lines(w, col="red")
```

---

RGB	<i>Layers representing colors</i>
-----	-----------------------------------

---

**Description**

With RGB you can get or set the layers to be used as Red, Green and Blue when plotting a SpatRaster. Currently, a benefit of this is that [plot](#) will send the object to [plotRGB](#)

With [colorize](#) you can convert a three-layer RGB SpatRaster into other color spaces. You can also convert it into a single-layer SpatRaster with a color-table.

**Usage**

```
## S4 method for signature 'SpatRaster'
RGB(x)

## S4 replacement method for signature 'SpatRaster'
RGB(x)<-value

## S4 method for signature 'SpatRaster'
colorize(x, to="hsv", alpha=FALSE, stretch=NULL,
grays=FALSE, NAzero=FALSE, filename="", overwrite=FALSE, ...)

## S4 method for signature 'SpatRaster'
has.RGB(x)
```

**Arguments**

x	SpatRaster
value	vector of three (or four) positive integers indicating the layers that are red, green and blue (and optionally a fourth transparency layer). Or NULL to remove the RGB settings

to	character. The color space to transform the values to. If x has RGB set, you can transform these to "hsv", "hsi" and "hsl", or use "col" to create a single layer with a color table. You can also use "rgb" to back transform to RGB
alpha	logical. Should an alpha (transparency) channel be included? Only used if x has a color-table and to="rgb"
stretch	character. Option to stretch the values to increase contrast: "lin" (linear) or "hist" (histogram). Only used for transforming RGB to col
grays	logical. If TRUE, a gray-scale color-table is created. Only used for transforming RGB to col
NAzero	logical. If TRUE, NAs are treated as zeros such that a color can be returned if at least one of the three channels has a value. Only used for transforming RGB to ("col")
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
...	additional arguments for writing files as in <a href="#">writeRaster</a>

### Examples

```

r <- rast(system.file("ex/logo.tif", package="terra"))
plot(r)
has.RGB(r)
RGB(r) <- NULL
has.RGB(r)
plot(r)
RGB(r) <- c(3,1,2)
plot(r)

RGB(r) <- 1:3
x <- colorize(r, "col")
y <- colorize(r, "hsv")
z <- colorize(y, "rgb")

```

---

rotate

*Rotate data along longitude*

---

### Description

Rotate a `SpatRaster` that has longitude coordinates from 0 to 360, to standard coordinates between -180 and 180 degrees (or vice-versa). Longitude between 0 and 360 is frequently used in global climate models.

Rotate a `SpatVector` as for a `SpatRaster` `split=TRUE`, or to correct for coordinates that are connected across the date line (and end up at the "other side" of the longitude scale) are reconnected.

**Usage**

```
## S4 method for signature 'SpatRaster'
rotate(x, left=TRUE, filename="", ...)

## S4 method for signature 'SpatVector'
rotate(x, longitude=0, split=FALSE, left=TRUE, normalize=FALSE)
```

**Arguments**

x	SpatRaster or SpatVector
left	logical. If TRUE, rotate to the left, else to the right
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>
longitude	numeric. The longitude around which to rotate
split	logical. Should geometries be split at longitude?
normalize	logical. Should the output be normalized to longitudes between -180 and 180? See <a href="#">normalize.longitude</a>

**Value**

SpatRaster

**See Also**

[shift](#) and [spin](#)

**Examples**

```
x <- rast(nrows=9, ncols=18, nl=3, xmin=0, xmax=360)
v <- rep(as.vector(t(matrix(1:ncell(x), nrow=9, ncol=18))), 3)
values(x) <- v
z <- rotate(x)

#SpatVector
p <- rbind(c(3847903, 1983584 ), c(3847903, 5801864), c(8301883, 5801864), c(8301883, 1983584 ))
p <- vect(p, "polygons", crs="+init=EPSG:3347")
d <- densify(p, 100000)
g <- project(d, "+proj=longlat")

x <- rotate(g, 50)
plot(g)
lines(x, col="red")

## rotate countries to 0-360 longitude
#w <- geodata::world(path=".")
#x <- rotate(w, long=0, split=TRUE, left=FALSE)
```

---

sapp	<i>Apply a terra function that takes only a single layer and returns a SpatRaster to all layers of a SpatRaster</i>
------	---

---

### Description

Apply to all layers of a SpatRaster a function that only takes a single layer SpatRaster and returns a SpatRaster (these are rare). In most cases you can also use `lapply` or `sapply` for this.

Or apply the same method to each sub-dataset (SpatRaster) in a SpatRasterDataset

### Usage

```
## S4 method for signature 'SpatRaster'
sapp(x, fun, ..., filename="", overwrite=FALSE, wopt=list())

## S4 method for signature 'SpatRasterDataset'
sapp(x, fun, ..., filename="", overwrite=FALSE, wopt=list())
```

### Arguments

x	SpatRaster or SpatRasterDataset
fun	if x is a SpatRaster: a function that takes a SpatRaster argument and can be applied to each layer of x (e.g. <a href="#">terrain</a> . if x is a SpatRasterDataset: a function that is applied to all layers of the SpatRasters in x (e.g. <code>mean</code> )
...	additional arguments to be passed to fun
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

### Value

SpatRaster

### See Also

[lapp](#), [app](#), [tapp](#), [lapply](#)

### Examples

```
s <- rast(system.file("ex/logo.tif", package="terra")) + 1

#SpatRasterDataset
sd <- sds(s*2, s/2)
y <- sapp(sd, mean)
z <- sapp(sd, \(i) 2 * mean(i))
```

---

sbar	<i>scale bar</i>
------	------------------

---

## Description

Add a scale bar to a map

## Usage

```
sbar(d, xy=NULL, type="line", divs=2, below="",
     lonlat=NULL, label, adj=c(0.5, -1), lwd=2, xpd=TRUE, ...)
```

## Arguments

d	numeric. Distance covered by the scale bar. For the scale bar, it should be in the units of the coordinates of the plot (map), and in km for angular (longitude/latitude) data; see argument <code>lonlat</code> . It can also be missing
xy	numeric. x and y coordinate to place the scale bar. It can also be one of following character values: "bottomleft", "bottom", "bottomright", "topleft", "top", "topright", "left", "right", or NULL
type	for sbar: "line" or "bar"
divs	number of divisions for a bar: 2 or 4
below	character. Text to go below the scale bar (e.g., "kilometers")
lonlat	logical or NULL. If logical, TRUE indicates if the plot is using longitude/latitude coordinates. If NULL this is guessed from the plot's coordinates
label	vector of three numbers to label the scale bar (beginning, midpoint, end)
adj	adjustment for text placement
lwd	line width for the "line" type of the scale bar
xpd	logical. If TRUE, the scale bar can be outside the plotting area
...	graphical arguments to be passed to other methods

## Value

none

## See Also

[north](#), [plot](#), [inset](#)



Examples

```
f <- system.file("ex/meuse.tif", package="terra")
r <- rast(f)
plot(r)
sbar()
sbar(1000, xy=c(178500, 333500), type="bar", divs=4, cex=.8)
sbar(1000, xy="bottomright", divs=4, cex=.8)
north(d=250, c(178550, 332500))

f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
plot(r, type="interval")
sbar(20, c(6.2, 50.1), type="bar", cex=.8, divs=4)
sbar(15, c(6.3, 50), type="bar", below="km", label=c(0,7.5,15), cex=.8)
sbar(15, c(6.65, 49.8), cex=.8, label=c(0,"km",15))
north(type=2)
sbar(15, c(6.65, 49.7), cex=.8, label="15 kilometer", lwd=5)
sbar(15, c(6.65, 49.6), divs=4, cex=.8, below="km")
```

---

scale	<i>Scale values</i>
-------	---------------------

---

Description

Center and/or scale raster data. For details see [scale](#)

Usage

```
## S4 method for signature 'SpatRaster'
scale(x, center=TRUE, scale=TRUE)
```

Arguments

x	SpatRaster
center	logical or numeric. If TRUE, centering is done by subtracting the layer means (omitting NAs), and if FALSE, no centering is done. If center is a numeric vector (recycled to nlyr(x)), then each layer of x has the corresponding value from center subtracted from it.
scale	logical or numeric. If TRUE, scaling is done by dividing the (centered) layers of x by their standard deviations if center is TRUE, and the root mean square otherwise. If scale is FALSE, no scaling is done. If scale is a numeric vector (recycled to nlyr(x)), each layer of x is divided by the corresponding value. Scaling is done after centering.

Value

SpatRaster

See Also

[scale](#)

Examples

```
r <- rast(system.file("ex/logo.tif", package="terra"))
s <- scale(r)

## the equivalent, computed in steps
m <- global(r, "mean")
rr <- r - m[,1]
rms <- global(rr, "rms")
ss <- rr / rms[,1]
```

---

scatterplot	<i>Scatterplot of two SpatRaster layers</i>
-------------	---

---

Description

Scatterplot of the values of two SpatRaster layers

Usage

```
## S4 method for signature 'SpatRaster,SpatRaster'
plot(x, y, maxcell=100000, warn=TRUE, nc, nr,
     maxnl=16, gridded=FALSE, ncol=25, nrow=25, ...)
```

Arguments

x	SpatRaster
y	SpatRaster
maxcell	positive integer. Maximum number of cells to use for the plot
nc	positive integer. Optional. The number of columns to divide the plotting device in (when plotting multiple layers)
nr	positive integer. Optional. The number of rows to divide the plotting device in (when plotting multiple layers)
maxnl	positive integer. Maximum number of layers to plot (for multi-layer objects)
gridded	logical. If TRUE the scatterplot is gridded (counts by cells)
warn	boolean. Show a warning if a sample of the pixels is used (for scatterplot only)
ncol	positive integer. Number of columns for gridding
nrow	positive integer. Number of rows for gridding
...	additional graphical arguments

### Examples

```
s <- rast(system.file("ex/logo.tif", package="terra"))
plot(s[[1]], s[[2]])
plot(s, sqrt(s[[3:1]]))
```

scoff

*Scale (gain) and offset*

### Description

These functions can be used to get or set the scale (gain) and offset parameters used to transform values when reading raster data from a file. The parameters are applied to the raw values using the formula below:

$$\text{value} \leftarrow \text{value} * \text{scale} + \text{offset}$$

The default value for scale is 1 and for offset is 0. 'scale' is sometimes referred to as 'gain'.

Note that setting the scale and/or offset are intended to be used with values that are stored in a file. When values are memory, assigning scale or offset values will lead to the immediate computation of new values; in such cases it would be clearer to use [Arith-methods](#).

### Usage

```
## S4 method for signature 'SpatRaster'
scoff(x)

## S4 replacement method for signature 'SpatRaster'
scoff(x)<-value
```

### Arguments

x	SpatRaster
value	two-column matrix with scale (first column) and offset (second column) for each layer. Or NULL to remove all scale and offset values

### Value

matrix or changed SpatRaster

### Examples

```
r <- rast(system.file("ex/elev.tif", package="terra"))
minmax(r)
scoff(r)
r[4603]

scoff(r) <- cbind(10, 5)
minmax(r)
scoff(r)
r[4603]
```

sds

*Create a SpatRasterDataset***Description**

Methods to create a SpatRasterDataset. This is an object to hold "sub-datasets", each a SpatRaster that in most cases will have multiple layers.

See [describe](#) for getting information about the sub-datasets present in a file.

**Usage**

```
## S4 method for signature 'missing'
sds(x)

## S4 method for signature 'character'
sds(x, ids=0)

## S4 method for signature 'SpatRaster'
sds(x, ...)

## S4 method for signature 'list'
sds(x)

## S4 method for signature 'array'
sds(x, crs="", extent=NULL)
```

**Arguments**

x	character (filename), or SpatRaster, or list of SpatRaster objects, or missing. If multiple filenames are provided, it is attempted to make SpatRasters from these, and combine them into a SpatRasterDataset
ids	optional. vector of integer subdataset ids. Ignored if the first value is not a positive integer
crs	character. Description of the Coordinate Reference System (map projection) in PROJ.4, WKT or authority:code notation. If this argument is missing, and the x coordinates are within -360 .. 360 and the y coordinates are within -90 .. 90, longitude/latitude is assigned
extent	<a href="#">SpatExtent</a>
...	additional SpatRaster objects

**Value**

SpatRasterDataset

**See Also**

[describe](#)

Examples

```
s <- rast(system.file("ex/logo.tif", package="terra"))
x <- sds(s, s/2)
names(x) <- c("first", "second")
x
length(x)

# extract the second SpatRaster
x[2]

a <- array(1:9, c(3,3,3,3))
sds(a)
```

---

segregate	<i>segregate</i>
-----------	------------------

---

Description

Create a SpatRaster with a layer for each class (value, or subset of the values) in the input SpatRaster. For example, if the input has vegetation types, this function will create a layer (presence/absence; dummy variable) for each of these classes.

This is called "one-hot encoding" or "dummy encoding" (for a dummy encoding scheme you can remove (any) one of the output layers as it is redundant).

Usage

```
## S4 method for signature 'SpatRaster'
segregate(x, classes=NULL, keep=FALSE, other=0, round=FALSE, digits=0, filename="", ...)
```

Arguments

x	SpatRaster
classes	numeric. The values (classes) for which layers should be made. If NULL all classes are used
keep	logical. If TRUE, cells that are of the class represented by a layer get that value, rather than a value of 1
other	numeric. Value to assign to cells that are not of the class represented by a layer
round	logical. Should the values be rounded first?
digits	integer. Number of digits to round the values to
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

Value

SpatRaster

**Examples**

```
r <- rast(nrows=5, ncols=5)
values(r) <- rep(c(1:4, NA), each=5)
b <- segregate(r)
bb <- segregate(r, keep=TRUE, other=NA)
```

sel

*Spatial selection***Description**

Geometrically subset SpatRaster or SpatVector (to be done) by drawing on a plot (map).

**Usage**

```
## S4 method for signature 'SpatRaster'
sel(x, ...)

## S4 method for signature 'SpatVector'
sel(x, use="rec", draw=TRUE, col="cyan", ...)
```

**Arguments**

x	SpatRaster or SpatVector
use	character indicating what to draw. One of "rec" (rectangle) or "pol" (polygon)
draw	logical. If TRUE the selection is drawn on the map
col	color to be used for drawing if draw=TRUE
...	additional graphics arguments for drawing

**Value**

SpatRaster or SpatVector

**See Also**

[crop](#) and [intersect](#) to make an intersection and [click](#) and [text](#) to see cell values or geometry attributes

**Examples**

```
## Not run:
# select a subset of a SpatRaster
r <- rast(nrows=10, ncols=10)
values(r) <- 1:ncell(r)
plot(r)
s <- sel(r) # now click on the map twice
```

```

# plot the selection on a new canvas:
x11()
plot(s)

# vector
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
plot(v)
x <- sel(v) # now click on the map twice
x

## End(Not run)

```

---

selectHighest	<i>select cells with high or low values</i>
---------------	---

---

## Description

Identify *n* cells that have the highest of lowest values in the first layer of a `SpatRaster`.

## Usage

```

## S4 method for signature 'SpatRaster'
selectHighest(x, n, low=FALSE)

```

## Arguments

<code>x</code>	<code>SpatRaster</code> . Only the first layer is processed
<code>n</code>	The number of cells to select
<code>low</code>	logical. If <code>TRUE</code> , the lowest values are selected instead of the highest values

## Value

`SpatRaster`

## Examples

```

f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
x <- selectHighest(r, 1000)
y <- selectHighest(r, 1000, TRUE)

m <- merge(y-1, x)
levels(m) <- data.frame(id=0:1, elevation=c("low", "high"))
plot(m)

```

---

selectRange	<i>Select the values of a range of layers, as specified by cell values in another SpatRaster</i>
-------------	--

---

### Description

Use a single layer SpatRaster to select cell values from different layers in a multi-layer SpatRaster. The values of the SpatRaster to select layers (y) should be whole numbers between 1 and nlyr(x) (values outside this range are ignored).

See [rapp](#) for applying a function to a range of variable size.

See [extract](#) for extraction of values by cell, point, or otherwise.

### Usage

```
## S4 method for signature 'SpatRaster'
selectRange(x, y, z=1, repint=0, filename="", ...)
```

### Arguments

x	SpatRaster
y	SpatRaster. Cell values must be positive integers. They indicate the first layer to select for each cell
z	positive integer. The number of layers to select
repint	integer > 1 and < nlyr(x) allowing for repeated selection at a fixed interval. For example, if x has 36 layers, and the value of a cell in y=2 and repint = 12, the values for layers 2, 14 and 26 are returned
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

### Value

SpatRaster

### See Also

[rapp](#), [tapp](#), [extract](#)

### Examples

```
r <- rast(ncols=10, nrows=10)
values(r) <- 1
s <- c(r, r+2, r+5)
s <- c(s, s)
set.seed(1)
values(r) <- sample(3, ncell(r), replace=TRUE)
x <- selectRange(s, r)
```



```
x <- selectRange(s, r, 3)
```

---

**serialize**
*serialize and saveRDS for SpatRaster and SpatVector*


---

## Description

serialize and saveRDS for SpatRaster and SpatVector. Note that these objects will first be "packed" with [wrap](#), and after unserialize/readRDS they need to be unpacked with [rast](#) or [vect](#).

Use of these functions is not recommended. Especially for SpatRaster it is generally much more efficient to use [writeRaster](#) and write, e.g., a GTiff file.

SpatRaster objects must have all values in memory (that is, the cell values are not in files) to be serialized. These functions use [set.values](#) to load values into memory if needed and if deemed possible given the amount of RAM available.

## Usage

```
## S4 method for signature 'SpatRaster'
saveRDS(object, file="", ascii = FALSE, version = NULL, compress=TRUE, refhook = NULL)

## S4 method for signature 'SpatVector'
saveRDS(object, file="", ascii = FALSE, version = NULL, compress=TRUE, refhook = NULL)

## S4 method for signature 'SpatRaster'
serialize(object, connection, ascii = FALSE, xdr = TRUE, version = NULL, refhook = NULL)

## S4 method for signature 'SpatVector'
serialize(object, connection, ascii = FALSE, xdr = TRUE, version = NULL, refhook = NULL)
```

## Arguments

object	SpatVector or SpatRaster
file	file name to save object to
connection	see <a href="#">serialize</a>
ascii	see <a href="#">serialize</a> or <a href="#">saveRDS</a>
version	see <a href="#">serialize</a> or <a href="#">saveRDS</a>
compress	see <a href="#">serialize</a> or <a href="#">saveRDS</a>
refhook	see <a href="#">serialize</a> or <a href="#">saveRDS</a>
xdr	see <a href="#">serialize</a> or <a href="#">saveRDS</a>

## Value

Packed\* object

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
p <- serialize(v, NULL)
head(p)
x <- unserialize(p)
x
```

setValues

*Set the values of raster cells or of geometry attributes***Description**

Set cell values of a `SpatRaster` or the attributes of a `SpatVector`. For large `SpatRaster` objects use `init` instead to set values.

**Usage**

```
## S4 replacement method for signature 'SpatRaster,ANY'
values(x)<-value

## S4 method for signature 'SpatRaster,ANY'
setValues(x, values, keeptime=TRUE, keepunits=TRUE, keepnames=FALSE, props=FALSE)

## S4 replacement method for signature 'SpatVector,ANY'
values(x)<-value
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>value</code>	For <code>SpatRaster</code> : numeric, matrix or data.frame. The length of the numeric values must match the total number of cells ( <code>ncell(x) * nlyr(x)</code> ), or be a single value. The number of columns of the matrix or data.frame must match the number of layers of <code>x</code> , and the number of rows must match the number of cells of <code>x</code> . For <code>SpatVector</code> : data.frame, matrix, vector, or <code>NULL</code>
<code>values</code>	Same as for <code>value</code>
<code>keeptime</code>	logical. If <code>TRUE</code> the time stamps are kept
<code>keepunits</code>	logical. If <code>FALSE</code> the units are discarded
<code>keepnames</code>	logical. If <code>FALSE</code> the layer names are replaced by the column names in <code>y</code> (if present)
<code>props</code>	logical. If <code>TRUE</code> the properties (categories and color-table) are kept

**Value**

The same object type as `x`

See Also

[values](#), [init](#)

Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
x <- setValues(r, 1:ncell(r))
x
values(x) <- runif(ncell(x))
x
head(x)

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
values(v) <- data.frame(ID=1:12, name=letters[1:12])
head(v)
```

---

shade	<i>Hill shading</i>
-------	---------------------

---

Description

Compute hill shade from slope and aspect layers (both in radians). Slope and aspect can be computed with function [terrain](#).  
A hill shade layer is often used as a backdrop on top of which another, semi-transparent, layer is drawn.

Usage

```
shade(slope, aspect, angle=45, direction=0, normalize=FALSE,
      filename="", overwrite=FALSE, ...)
```

Arguments

slope	SpatRaster with slope values (in radians)
aspect	SpatRaster with aspect values (in radians)
angle	The the elevation angle of the light source (sun), in degrees
direction	The direction (azimuth) angle of the light source (sun), in degrees
normalize	Logical. If TRUE, values below zero are set to zero and the results are multiplied with 255
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
...	additional arguments for writing files as in <a href="#">writeRaster</a>

References

Horn, B.K.P., 1981. Hill shading and the reflectance map. Proceedings of the IEEE 69(1):14-47

See Also

[terrain](#)

Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
alt <- disag(r, 10, method="bilinear")
slope <- terrain(alt, "slope", unit="radians")
aspect <- terrain(alt, "aspect", unit="radians")
hill <- shade(slope, aspect, 40, 270)
plot(hill, col=grey(0:100/100), legend=FALSE, mar=c(2,2,1,4))
plot(alt, col=rainbow(25, alpha=0.35), add=TRUE)
```

---

sharedPaths	<i>Shared paths</i>
-------------	---------------------

---

Description

Get shared paths of line or polygon geometries. This can for geometries in a single SpatVector, or between two SpatVectors

Usage

```
## S4 method for signature 'SpatVector'
sharedPaths(x, y=NULL)
```

Arguments

- x                      SpatVector of lines or polygons
- y                      missing or SpatVector of lines or polygons

Value

SpatVector

See Also

[gaps](#), [topology](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
plot(v, col="light gray")
text(v, halo=TRUE)

x <- sharedPaths(v)
lines(x, col="red", lwd=2)
text(x, col="blue", halo=TRUE, cex=0.8)
head(x)

z <- sharedPaths(v[3,], v[12,])
```

---

shift

*Shift*


---

**Description**

Shift a `SpatRaster`, `SpatVector` or `SpatExtent` to another location.

**Usage**

```
## S4 method for signature 'SpatRaster'
shift(x, dx=0, dy=0, filename="", ...)

## S4 method for signature 'SpatVector'
shift(x, dx=0, dy=0)

## S4 method for signature 'SpatExtent'
shift(x, dx=0, dy=0)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> , <code>SpatVector</code> or <code>SpatExtent</code>
<code>dx</code>	numeric. The shift in horizontal direction
<code>dy</code>	numeric. The shift in vertical direction
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

Same as `x`

**See Also**

[flip](#), [rotate](#)

Examples

```
r <- rast(xmin=0, xmax=1, ymin=0, ymax=1)
r <- shift(r, dx=1, dy=-1)

e <- ext(r)
shift(e, 5, 5)
```

---

sieve	<i>Sieve filter</i>
-------	---------------------

---

Description

Apply a sieve filter. That is, remove "noise", by changing small clumps of cells with a value that is different from the surrounding cells, to the value of the largest neighbouring clump.

Usage

```
## S4 method for signature 'SpatRaster'
sieve(x, threshold, directions=8, filename="", ...)
```

Arguments

x	SpatRaster, single layer with elevation values. Values should have the same unit as the map units
threshold	positive integer. Only clumps smaller than this threshold will be removed
directions	numeric to indicate which cells are connected. Either 4 to only consider the horizontal and vertical neighbors ("rook"), or 8 to consider the vertical, horizontal and diagonal neighbors
filename	character. Output filename
...	Options for writing files as in <a href="#">writeRaster</a>

See Also

[focal](#)

Examples

```
r <- rast(nrows=18, ncols=18, xmin=0, vals=0, crs="local")
r[2, 5] <- 1
r[5:8, 2:3] <- 2
r[7:12, 10:15] <- 3
r[15:16, 15:18] <- 4
freq(r, bylayer=FALSE)

x <- sieve(r, 8)
y <- sieve(r, 9)
```

---

simplifyGeom	<i>simplifyGeom geometries</i>
--------------	--------------------------------

---

## Description

Reduce the number of nodes used to represent geometries.

## Usage

```
## S4 method for signature 'SpatVector'  
simplifyGeom(x, tolerance=0.1, preserveTopology=TRUE, makeValid=TRUE)
```

## Arguments

x	SpatVector of lines or polygons
tolerance	numeric. The minimum distance between nodes in units of the crs (i.e. degrees for long/lat)
preserveTopology	logical. If TRUE the topology of output geometries is preserved
makeValid	logical. If TRUE, <code>link{makeValid}</code> is run after simplification to assure that the output polygons are valid

## Value

SpatVector

## See Also

[sharedPaths](#), [gaps](#), `link{is.valid()}`

## Examples

```
f <- system.file("ex/lux.shp", package="terra")  
v <- vect(f)  
w <- simplifyGeom(v, .02, makeValid=FALSE)  
e <- erase(w)  
g <- gaps(e)  
plot(e, lwd=5, border="light gray")  
polys(g, col="red", border="red")
```

---

sort	<i>Sort a SpatRaster</i>
------	--------------------------

---

**Description**

Sort the cell values of a SpatRaster across layers

**Usage**

```
## S4 method for signature 'SpatRaster'  
sort(x, decreasing=FALSE, filename="", ...)
```

**Arguments**

x	SpatRaster
decreasing	logical
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Examples**

```
f <- system.file("ex/elev.tif", package="terra")  
r <- rast(f)  
r <- c(r, r/2, r*2)  
sort(r)
```

---

sources	<i>Data sources of a SpatRaster</i>
---------	-------------------------------------

---

**Description**

Get the data sources of a SpatRaster or SpatVector or related object. Sources are either files (or similar resources) or "", meaning that they are in memory. You can use hasValues to check if in-memory layers actually have cell values.



Usage

```
## S4 method for signature 'SpatRaster'
sources(x, nlyr=FALSE, bands=FALSE)

## S4 method for signature 'SpatVector'
sources(x)

## S4 method for signature 'SpatRaster'
hasValues(x)

## S4 method for signature 'SpatRaster'
inMemory(x, bylayer=FALSE)
```

Arguments

x	SpatRaster, SpatRasterCollection, SpatVector or SpatVectorProxy
nlyr	logical. If TRUE for each source, the number of layers is returned
bands	logical. If TRUE for each source, the "bands" used, that is, the layer number in the source file, are returned
bylayer	logical. If TRUE a value is returned for each layer instead of for each source

Value

A vector of filenames, or "" when there is no filename, if nlyr and bands are both FALSE. Otherwise a data.frame

Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
s <- rast(r)
values(s) <- 1:ncell(s)
rs <- c(r,r,s,r)
sources(rs)
hasValues(r)
x <- rast()
hasValues(x)
```

---

SpatExtent-class	Class "SpatExtent"
------------------	--------------------

---

Description

Objects of class SpatExtent are used to define the spatial extent (extremes) of objects of the SpatRaster class.

### Objects from the Class

You can use the `ext` function to create `SpatExtent` objects, or to extract them from `SpatRaster` objects.

### Slots

`ptr`: pointer to the C++ class

### Methods

`show` display values of a `SpatExtent` object

### Examples

```
e <- ext(-180, 180, -90, 90)
e
```

---

Spatial interpolation *Interpolate*

---

### Description

Make a `SpatRaster` with interpolated values using a fitted model object of classes such as "gstat" (gstat package) or "Krig" (fields package), or any other model that has location (e.g., "x" and "y", or "longitude" and "latitude") as predictors (independent variables). If x and y are the only predictors, it is most efficient if you provide an empty (no associated data in memory or on file) `SpatRaster` for which you want predictions. If there are more spatial predictor variables provide these as a `SpatRaster` in the first argument of the function. If you do not have x and y locations as implicit predictors in your model you should use `predict` instead.

### Usage

```
## S4 method for signature 'SpatRaster'
interpolate(object, model, fun=predict, ..., xyNames=c("x", "y"),
            factors=NULL, const=NULL, index = NULL, na.rm=FALSE,
            filename="", overwrite=FALSE, wopt=list())
```

### Arguments

<code>object</code>	<code>SpatRaster</code>
<code>model</code>	model object
<code>fun</code>	function. Default value is "predict", but can be replaced with e.g. "predict.se" (depending on the class of <code>model</code> ), or a custom function (see examples)
<code>...</code>	additional arguments passed to <code>fun</code>
<code>xyNames</code>	character. variable names that the model uses for the spatial coordinates. E.g., <code>c("longitude", "latitude")</code>

factors	list with levels for factor variables. The list elements should be named with names that correspond to names in object such that they can be matched. This argument may be omitted for some models from which the levels can be extracted from the model object
const	data.frame. Can be used to add a constant for which there is no SpatRaster for model predictions. This is particularly useful if the constant is a character-like factor value
index	positive integer or NULL. Allows for selecting of the variable returned if the model returns multiple variables
na.rm	logical. If TRUE, cells with NA values in the predictors are removed from the computation. This option prevents errors with models that cannot handle NA values. In most other cases this will not affect the output. An exception is when predicting with a model that returns predicted values even if some (or all!) variables are NA
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**[predict](#)**Examples**

```

r <- rast(system.file("ex/elev.tif", package="terra"))
ra <- aggregate(r, 10)
xy <- data.frame(xyFromCell(ra, 1:ncell(ra)))
v <- values(ra)
i <- !is.na(v)
xy <- xy[i,]
v <- v[i]

## Not run:
library(fields)
tps <- Tps(xy, v)
p <- rast(r)

# use model to predict values at all locations
p <- interpolate(p, tps)
p <- mask(p, r)
plot(p)

### change "fun" from predict to fields::predictSE to get the TPS standard error
## need to use "rast(p)" to remove the values
se <- interpolate(rast(p), tps, fun=predictSE)

```

```

se <- mask(se, r)
plot(se)

### another predictor variable, "e"
e <- (init(r, "x") * init(r, "y")) / 100000000
names(e) <- "e"

z <- as.matrix(extract(e, xy)[-1])

## add as another independent variable
xyz <- cbind(xy, z)
tps2 <- Tps(xyz, v)
p2 <- interpolate(e, tps2, xyOnly=FALSE)

## as a linear coveriate
tps3 <- Tps(xy, v, Z=z)

## Z is a separate argument in Krig.predict, so we need a new function
## Internally (in interpolate) a matrix is formed of x, y, and elev (Z)

pfun <- function(model, x, ...) {
  predict(model, x[,1:2], Z=x[,3], ...)
}
p3 <- interpolate(e, tps3, fun=pfun)

#### gstat examples
library(gstat)
library(sp)
data(meuse)

### inverse distance weighted (IDW)
r <- rast(system.file("ex/meuse.tif", package="terra"))
mg <- gstat(id = "zinc", formula = zinc~1, locations = ~x+y, data=meuse,
           nmax=7, set=list(idp = .5))
z <- interpolate(r, mg, debug.level=0, index=1)
z <- mask(z, r)

## with a model built with an `sf` object you need to provide custom function

library(sf)
sfmeuse <- st_as_sf(meuse, coords = c("x", "y"), crs=crs(r))
mg_sf <- gstat(id = "zinc", formula = zinc~1, data=sfmeuse, nmax=7, set=list(idp = .5))

interpolate_gstat <- function(model, x, crs, ...) {
  v <- st_as_sf(x, coords=c("x", "y"), crs=crs)
  p <- predict(model, v, ...)
  as.data.frame(p)[,1:2]
}

zsf <- interpolate(r, mg_sf, debug.level=0, fun=interpolate_gstat, crs=crs(r), index=1)
zsf <- mask(zsf, r)

```

```

### kriging

### ordinary kriging
v <- variogram(log(zinc)~1, ~x+y, data=meuse)
mv <- fit.variogram(v, vgm(1, "Sph", 300, 1))
gOK <- gstat(NULL, "log.zinc", log(zinc)~1, meuse, locations=~x+y, model=mv)
OK <- interpolate(r, gOK, debug.level=0)

## universal kriging
vu <- variogram(log(zinc)~elev, ~x+y, data=meuse)
mu <- fit.variogram(vu, vgm(1, "Sph", 300, 1))
gUK <- gstat(NULL, "log.zinc", log(zinc)~elev, meuse, locations=~x+y, model=mu)
names(r) <- "elev"
UK <- interpolate(r, gUK, debug.level=0)

## co-kriging
gCoK <- gstat(NULL, 'log.zinc', log(zinc)~1, meuse, locations=~x+y)
gCoK <- gstat(gCoK, 'elev', elev~1, meuse, locations=~x+y)
gCoK <- gstat(gCoK, 'cadmium', cadmium~1, meuse, locations=~x+y)
gCoK <- gstat(gCoK, 'copper', copper~1, meuse, locations=~x+y)
coV <- variogram(gCoK)
plot(coV, type='b', main='Co-variogram')
coV.fit <- fit.lmc(coV, gCoK, vgm(model='Sph', range=1000))
coV.fit
plot(coV, coV.fit, main='Fitted Co-variogram')
coK <- interpolate(r, coV.fit, debug.level=0)
plot(coK)

## End(Not run)

```

SpatRaster-class

*SpatRaster class*

## Description

A *SpatRaster* represents a rectangular part of the world that is sub-divided into rectangular cells of equal area (in terms of the units of the coordinate reference system). For each cell can have multiple values ("layers").

An object of the *SpatRaster* class can point to one or more files on disk that hold the cell values, and/or it can hold these values in memory. These objects can be created with the [rast](#) method.

A *SpatRasterDataset* is a collection of sub-datasets, where each is a *SpatRaster* for the same area (extent) and coordinate reference system, but possibly with a different resolution. Sub-datasets are often used to capture variables (e.g. temperature and precipitation), or a fourth dimension (e.g. height, depth or time) if the sub-datasets already have three dimensions (multiple layers).

A *SpatRasterCollection* is a collection of *SpatRasters* with no restriction in the extent or other geometric parameters.

**Examples**

```
rast()
```

---

```
spatSample
```

---

*Take a regular sample*

---

**Description**

Take a spatial sample from a `SpatRaster`, `SpatVector` or `SpatExtent`. Sampling a `SpatVector` or `SpatExtent` always returns a `SpatVector` of points.

With a `SpatRaster`, you can get cell values, cell numbers (`cells=TRUE`), coordinates (`xy=TRUE`) or (when `type="regular"` and `as.raster=TRUE`) get a new `SpatRaster` with the same extent, but fewer cells.

In order to assure regularity when requesting a regular sample, the number of cells or points returned may not be exactly the same as the size requested.

**Usage**

```
## S4 method for signature 'SpatRaster'
spatSample(x, size, method="random", replace=FALSE, na.rm=FALSE,
  as.raster=FALSE, as.df=TRUE, as.points=FALSE, values=TRUE, cells=FALSE,
  xy=FALSE, ext=NULL, warn=TRUE, weights=NULL, exp=5)

## S4 method for signature 'SpatVector'
spatSample(x, size, method="random", strata=NULL, chess="")

## S4 method for signature 'SpatExtent'
spatSample(x, size, method="random", lonlat, as.points=FALSE)
```

**Arguments**

<code>x</code>	<code>SpatRaster</code> , <code>SpatVector</code> or <code>SpatExtent</code>
<code>size</code>	numeric. The sample size. If <code>x</code> is a <code>SpatVector</code> , you can also provide a vector of the same length as <code>x</code> in which case sampling is done separately for each geometry. If <code>x</code> is a <code>SpatRaster</code> , and you are using <code>method="regular"</code> you can specify the size as two numbers (number of rows and columns)
<code>method</code>	character. Should be "regular" or "random", If <code>x</code> is a <code>SpatRaster</code> , it can also be "stratified" (each value in <code>x</code> is a stratum) or "weights" (each value in <code>x</code> is a probability weight)
<code>replace</code>	logical. If <code>TRUE</code> , sampling is with replacement (if <code>method="random"</code> )
<code>na.rm</code>	logical. If <code>TRUE</code> , codeNAs are removed. Only used with random sampling of cell values. That is with <code>method="random"</code> , <code>as.raster=FALSE</code> , <code>cells=FALSE</code>
<code>as.raster</code>	logical. If <code>TRUE</code> , a <code>SpatRaster</code> is returned
<code>as.df</code>	logical. If <code>TRUE</code> , a data.frame is returned instead of a matrix

as.points	logical. If TRUE, a SpatVector of points is returned
values	logical. If TRUE cell values are returned
cells	logical. If TRUE, cell numbers are returned. If method="stratified" this is always set to TRUE if xy=FALSE
xy	logical. If TRUE, cell coordinates are returned
ext	SpatExtent or NULL to restrict sampling to a subset of the area of x
warn	logical. Give a warning if the sample size returned is smaller than requested
weights	SpatRaster. Used to provide weights when method="stratified"
strata	if not NULL, stratified random sampling is done, taking size samples from each stratum. If x has polygon geometry, strata must be a field name (or index) in x. If x has point geometry, strata can be a SpatVector of polygons or a SpatRaster
chess	character. One of "", "white", or "black". For stratified sampling if strata is a SpatRaster. If not "", samples are only taken from alternate cells, organized like the "white" or "black" fields on a chessboard
lonlat	logical. If TRUE, sampling of a SpatExtent is weighted by cos(latitude). For SpatRaster and SpatVector this done based on the <a href="#">crs</a> , but it is ignored if as.raster=TRUE
exp	numeric >= 1. 'Expansion factor' that is multiplied with size to get an initial sample. used for stratified samples and random samples with na.rm=TRUE to try to get at least size samples

## Value

numeric matrix, data.frame, SpatRaster or SpatVector

## Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
s <- spatSample(r, 10, as.raster=TRUE)
spatSample(r, 5)
spatSample(r, 5, na.rm=TRUE)
spatSample(r, 5, "regular")

## if you require cell numbers and/or coordinates
size <- 6
spatSample(r, 6, "random", cells=TRUE, xy=TRUE, values=FALSE)

# regular, with values
spatSample(r, 6, "regular", cells=TRUE, xy=TRUE)

# stratified
rr <- rast(ncol=10, nrow=10, names="stratum")
set.seed(1)
values(rr) <- round(runif(ncell(rr), 1, 3))
spatSample(rr, 2, "stratified", xy=TRUE)

s <- spatSample(rr, 5, "stratified", as.points=TRUE)
```

```
plot(rr, plg=list(title="raster"))
plot(s, 1, add=TRUE, plg=list(x=185, y=1, title="points"))

## SpatExtent
e <- ext(r)
spatSample(e, 10, "random", lonlat=TRUE)

## SpatVector
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)

#sample the geometries
i <- sample(v, 3)

# sample points in geometries
p <- spatSample(v, 3)
```

---

SpatVector-class	Class "SpatVector"
------------------	--------------------

---

**Description**

SpatVector can represent points, lines or polygons.  
SpatVectorCollection can hold a collection of SpatVectors  
SpatVectorProxy is a SpatVector for which the data are on-disk in-stead of in memory.

---

spin	spin a SpatVector
------	-------------------

---

**Description**

Spin (rotate) the geometry of a SpatVector.

**Usage**

```
## S4 method for signature 'SpatVector'
spin(x, angle, x0, y0)
```

**Arguments**

x	SpatVector
angle	numeric. Angle of rotation in degrees
x0	numeric. x-coordinate of the center of rotation. If missing, the center of the extent of x is used
y0	numeric. y-coordinate of the center of rotation. If missing, the center of the extent of x is used



**Value**

SpatVector

**See Also**

[rescale](#), [t](#), [shift](#)

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
w <- spin(v, 180)
plot(v)
lines(w, col="red")

# lower-right corner as center
e <- as.vector(ext(v))
x <- spin(v, 45, e[1], e[3])
```

---

split	<i>Split</i>
-------	--------------

---

**Description**

Split a SpatVector or SpatRaster

**Usage**

```
## S4 method for signature 'SpatRaster'
split(x, f)

## S4 method for signature 'SpatVector'
split(x, f)
```

**Arguments**

- x                    SpatRaster or SpatVector
- f                    If x is a SpatVector: a field (variable) name or a vector of the same length as x.  
                      If x is a SpatRaster: a vector of the length nlyr(x)

**Value**

Same as x

**Examples**

```
v <- vect(system.file("ex/lux.shp", package="terra"))
x <- split(v, "NAME_1")

s <- rast(system.file("ex/logo.tif", package="terra"))
y <- split(s, c(1,2,1))
sds(y)
```

---

sprc

---

*Create a SpatRasterCollection*


---

**Description**

Methods to create a SpatRasterCollection. This is an object to hold a collection (list) of SpatRaster objects. There are no restrictions on the similarity of the SpatRaster geometry.

They can be used to combine several SpatRasters to be used with [merge](#) or [mosaic](#)

You can create a SpatRasterCollection from a file with subdatasets.

**Usage**

```
## S4 method for signature 'SpatRaster'
sprc(x, ...)

## S4 method for signature 'list'
sprc(x)

## S4 method for signature 'missing'
sprc(x)

## S4 method for signature 'character'
sprc(x, ids=0)
```

**Arguments**

x	SpatRaster, list with SpatRaster objects, missing, or filename
ids	optional. vector of integer subdataset ids. Ignored if the first value is not a positive integer
...	additional SpatRaster objects

**Value**

SpatRasterCollection

**See Also**

[sds](#)

## Examples

```
x <- rast(xmin=-110, xmax=-50, ymin=40, ymax=70, ncols=60, nrows=30)
y <- rast(xmin=-80, xmax=-20, ymax=60, ymin=30)
res(y) <- res(x)
values(x) <- 1:ncell(x)
values(y) <- 1:ncell(y)

z <- sprc(x, y)
z
```

stretch

*Stretch*

## Description

Linear or histogram equalization stretch of values in a `SpatRaster`.

For linear stretch, provide the desired output range (`minv` and `maxv`) and the lower and upper bounds in the original data, either as quantiles (`minq` and `maxq`, or as cell values (`smin` and `smax`). If `smin` and `smax` are both not NA, `minq` and `maxq` are ignored.

For histogram equalization, these arguments are ignored, but you can provide the desired scale of the output.

## Usage

```
## S4 method for signature 'SpatRaster'
stretch(x, minv=0, maxv=255, minq=0, maxq=1, smin=NA, smax=NA,
histeq=FALSE, scale=1, filename="", ...)
```

## Arguments

<code>x</code>	<code>SpatRaster</code>
<code>minv</code>	numeric $\geq 0$ and smaller than <code>maxv</code> . lower bound of stretched value
<code>maxv</code>	numeric $\leq 255$ and larger than <code>minv</code> . upper bound of stretched value
<code>minq</code>	numeric $\geq 0$ and smaller than <code>maxq</code> . lower quantile bound of original value. Ignored if <code>smin</code> is supplied
<code>maxq</code>	numeric $\leq 1$ and larger than <code>minq</code> . upper quantile bound of original value. Ignored if <code>smax</code> is supplied
<code>smin</code>	numeric $< smax$ . user supplied lower value for the layers, to be used instead of a quantile computed by the function itself
<code>smax</code>	numeric $> smin$ . user supplied upper value for the layers, to be used instead of a quantile computed by the function itself
<code>histeq</code>	logical. If TRUE histogram equalization is used instead of linear stretch
<code>scale</code>	numeric. The scale (maximum value) of the output if <code>histeq=TRUE</code>
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Examples**

```
r <- rast(nc=10, nr=10)
values(r) <- rep(1:25, 4)
rs <- stretch(r)
s <- c(r, r*2)
sr <- stretch(s)
```

subset

*Subset a SpatRaster or a SpatVector***Description**

Select a subset of layers from a SpatRaster or select a subset of records (row) and/or variables (columns) from a SpatVector.

**Usage**

```
## S4 method for signature 'SpatRaster'
subset(x, subset, negate=FALSE, NSE=FALSE, filename="", overwrite=FALSE, ...)

## S4 method for signature 'SpatVector'
subset(x, subset, select, drop=FALSE, NSE=FALSE)
```

**Arguments**

x	SpatRaster or SpatVector
subset	if x is a SpatRaster: integer or character to select layers if x is a SpatVector: logical expression indicating the rows to keep (missing values are taken as FALSE)
select	expression, indicating columns to select
negate	logical. If TRUE all layers that are <b>not</b> in the subset are selected
NSE	logical. If TRUE, non-standard evaluation (the use of unquoted variable names) is allowed. Set this to FALSE when calling subset from a function
drop	logical. If TRUE, the geometries will be dropped, and a data.frame is returned
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

if x is a SpatRaster: SpatRaster  
if x is a SpatVector: SpatVector or, if drop=TRUE, a data.frame.

**Examples**

```

### SpatRaster
s <- rast(system.file("ex/logo.tif", package="terra"))
subset(s, 2:3)
subset(s, c(3,2,3,1))

#equivalent to
s[[ c(3,2,3,1) ]]

s[[c("red", "green")]]
s$red

# expression based (partial) matching of names with single brackets
s["re"]
s["^re"]

# not with double brackets
# s[["re"]]

### SpatVector
v <- vect(system.file("ex/lux.shp", package="terra"))

subset(v, v$NAME_1 == "Diekirch", c("NAME_1", "NAME_2"))

subset(v, NAME_1 == "Diekirch", c(NAME_1, NAME_2), NSE=TRUE)

# or like this
v[2:3,]
v[1:2, 2:3]
v[1:2, c("NAME_1", "NAME_2")]

```

subset\_dollar

*Subset a SpatRaster or a SpatVector***Description**

Select a subset of layers from a SpatRaster or select a subset of records (row) and/or variables (columns) from a SpatVector.

**Usage**

```

## S4 method for signature 'SpatExtent'
x$name

```

**Arguments**

x	SpatRaster, SpatVector or SpatExtent
name	character. If x is a SpatRaster: layer name. If x is a SpatVector: variable name. If x is a SpatExtent: xmin, xmax, ymin or ymax

**Value**

if x is a SpatRaster: SpatRaster

if x is a SpatVector: SpatVector or, if drop=TRUE, a data.frame.

**See Also**

link{subset}, link{[]}, link{[[}], link{extract}

**Examples**

```
### SpatRaster
s <- rast(system.file("ex/logo.tif", package="terra"))
subset(s, 2:3)
subset(s, c(3,2,3,1))
#equivalent to
s[[ c(3,2,3,1) ]]

s[[c("red", "green")]]
s$red

# expression based (partial) matching of names with single brackets
s["re"]
s["^re"]

# not with double brackets
# s[["re"]]

### SpatVector

v <- vect(system.file("ex/lux.shp", package="terra"))
v[2:3,]
v[1:2, 2:3]

subset(v, v$NAME_1 == "Diekirch", c("NAME_1", "NAME_2"))

subset(v, NAME_1 == "Diekirch", c(NAME_1, NAME_2), NSE=TRUE)
```

---

subset_double	<i>Subset a SpatRaster or a SpatVector</i>
---------------	--

---

## Description

Select a subset of layers from a `SpatRaster` or select a subset of records (row) and/or variables (columns) from a `SpatVector`.

## Usage

```
## S4 method for signature 'SpatRaster,numeric,missing'
x[[i, j]]

## S4 method for signature 'SpatRasterDataset,ANY,ANY'
x[[i, j, drop=TRUE]]

## S4 method for signature 'SpatVector,numeric,missing'
x[[i, j, drop=FALSE]]
```

## Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>i</code>	if <code>x</code> is a <code>SpatRaster</code> : integer, logical, or character to select layers if <code>x</code> is a <code>SpatVector</code> : integer, logical, or character to select variables)
<code>j</code>	missing, or, for <code>SpatRasterDataset</code> only, numeric
<code>drop</code>	logical. If <code>TRUE</code> , the geometries will be dropped, and a <code>data.frame</code> is returned

## Value

if `x` is a `SpatRaster` or `SpatRasterDataset`: `SpatRaster`  
if `x` is a `SpatVector`: a `data.frame`.

## See Also

`link{subset}`, `link{}`, `link{[]}`, `link{extract}`

## Examples

```
### SpatRaster
s <- rast(system.file("ex/logo.tif", package="terra"))
s[[ 1:2 ]]

s[[c("red", "green")]]

# expression based (partial) matching of names with single brackets
s["re"]
s["^re"]
```

```
# does not work with double brackets
# s[["re"]]

### SpatVector

v <- vect(system.file("ex/lux.shp", package="terra"))
v[[2:3]]

# to keep the geometry use
v[,2:3]
```

---

subset_single	<i>Extract values from a SpatRaster, SpatVector or SpatExtent</i>
---------------	---

---

### Description

Extract values from a SpatRaster; a subset of records (row) and/or variables (columns) from a SpatVector; or a number from a SpatExtent.

### Usage

```
## S4 method for signature 'SpatRaster,ANY,ANY,ANY'
x[i, j, k]

## S4 method for signature 'SpatVector,numeric,numeric'
x[i, j, drop=FALSE]

## S4 method for signature 'SpatExtent,numeric,missing'
x[i, j]
```

### Arguments

x	SpatRaster, SpatVector or SpatExtent
i	if x is a SpatRaster: numeric, logical or missing to select rows or, if j is missing, to select cells numbers. if x is a SpatVector: numeric or missing to select rows) if x is a SpatExtent: integer between 1 and 4)
j	numeric, logical, or missing to select columns
k	numeric, character, or missing to select layers
drop	logical. If FALSE an object of the same class as x is returned

### Value

numeric if x is a SpatExtent. Same as x if drop=FALSE. Otherwise a data.frame



See Also

linkextract, link{subset}, link{\${}}, link{[[},

Examples

```
### SpatRaster
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
r[3638]
rowColFromCell(r, 2638)
r[39, 28]
x <- r[39:40, 28:29, drop=FALSE]
as.matrix(x, wide=TRUE)

### SpatVector

v <- vect(system.file("ex/lux.shp", package="terra"))
v[2:3,]
v[1:2, 2:3]
v[1:2, 2:3, drop=TRUE]
```

---

subst	<i>replace cell values</i>
-------	----------------------------

---

Description

Substitute(replace) cell values of a SpatRaster with a new value. See [classify](#) for more complex/flexible replacement.

Usage

```
## S4 method for signature 'SpatRaster'
subst(x, from, to, others=NULL, raw=FALSE, filename="", ...)
```

Arguments

x	SpatRaster
from	numeric value(s). Normally a vector of the same length as ‘to’. If x has multiple layers, it can also be a matrix of numeric value(s) where nrow(x) == length(to). In that case the output has a single layer, with values based on the combination of the values of the input layers
to	numeric value(s). Normally a vector of the same length as ‘from’. If x has a single layer, it can also be a matrix of numeric value(s) where nrow(x) == length(from). In that case the output has multiple layers, one for each column in to
others	numeric. If not NULL all values that are not matched are set to this value. Otherwise they retain their original value.

raw	logical. If TRUE, the values in from and to are the raw cell values, not the categorical labels. Only relevant if is.factor(x)
filename	character. Output filename
...	Additional arguments for writing files as in <a href="#">writeRaster</a>

Value

SpatRaster

See Also

[classify](#)

Examples

```
r <- rast(ncols=5, nrows=5, xmin=0, xmax=1, ymin=0, ymax=1, crs="")
r <- init(r, 1:6)
x <- subst(r, 3, 7)
x <- subst(r, 2:3, NA)
x <- subst(x, NA, 10)

# multiple output layers
z <- subst(r, 2:3, cbind(20,30))

# multiple input layers
rr <- c(r, r+1, r+2)
m <- rbind(c(1:3), c(3:5))
zz <- subst(rr, m, c(100, 200))
```

---

summarize	<i>Summarize</i>
-----------	------------------

---

Description

Compute summary statistics for cells, either across layers or between layers (parallel summary).  
The following summary methods are available for SpatRaster: any, anyNA, all, allNA, max, min, mean, median, prod, range, stdev, sum, which.min, which.max. See [modal](#) to compute the mode and [app](#) to compute summary statistics that are not included here.  
Because generic functions are used, the method applied is chosen based on the first argument: "x". This means that if r is a SpatRaster, mean(r, 5) will work, but mean(5, r) will not work.  
The mean method has an argument "trim" that is ignored.  
If pop=TRUE stdev computes the population standard deviation, computed as:  
 $f \leftarrow \text{function}(x) \sqrt{\text{sum}((x-\text{mean}(x))^2) / \text{length}(x)}$   
This is different than the sample standard deviation returned by sd (which uses n-1 as denominator).

**Usage**

```
## S4 method for signature 'SpatRaster'  
min(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
max(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
range(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
prod(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
sum(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
any(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
all(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
range(x, ..., na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
which.min(x)  
  
## S4 method for signature 'SpatRaster'  
which.max(x)  
  
## S4 method for signature 'SpatRaster'  
stdev(x, ..., pop=TRUE, na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
mean(x, ..., trim=NA, na.rm=FALSE)  
  
## S4 method for signature 'SpatRaster'  
median(x, na.rm=FALSE, ...)
```

**Arguments**

x	SpatRaster
...	additional SpatRaster objects or numeric values; and arguments filename, overwrite and wopt as for <a href="#">writeRaster</a>
na.rm	logical. If TRUE, NA values are ignored. If FALSE, NA is returned if x has any NA values

trim	ignored
pop	logical. If TRUE, the population standard deviation is computed. Otherwise the sample standard deviation is computed

**Value**

SpatRaster

**See Also**

[app](#), [Math-methods](#), [modal](#), [which.lyr](#)

**Examples**

```
set.seed(0)
r <- rast(nrows=10, ncols=10, nlyrs=3)
values(r) <- runif(ncell(r) * nlyr(r))

x <- mean(r)
# note how this returns one layer
x <- sum(c(r, r[[2]]), 5)

# and this returns three layers
y <- sum(r, r[[2]], 5)

max(r)
max(r, 0.5)

y <- stdev(r)
# not the same as
yy <- app(r, sd)

z <- stdev(r, r*2)

x <- mean(r, filename=paste0(tempfile(), ".tif"))
```

---

summary	<i>summary</i>
---------	----------------

---

**Description**

Compute summary statistics (min, max, mean, and quartiles) for SpatRaster using base [summary](#) method. A sample is used for very large files.

For single or other statistics see [Summary-methods](#), [global](#), and [quantile](#)

**Usage**

```
## S4 method for signature 'SpatRaster'
summary(object, size=100000, warn=TRUE, ...)

## S4 method for signature 'SpatVector'
summary(object, ...)
```

**Arguments**

object	SpatRaster or SpatVector
size	positive integer. Size of a regular sample used for large datasets (see <a href="#">spatSample</a> )
warn	logical. If TRUE a warning is given if a sample is used
...	additional arguments passed on to the base <a href="#">summary</a> method

**Value**

matrix with (an estimate of) the median, minimum and maximum values, the first and third quartiles, and the number of cells with NA values

**See Also**

[Summary-methods](#), [global](#), [quantile](#)

**Examples**

```
set.seed(0)
r <- rast(nrows=10, ncols=10, nlyrs=3)
values(r) <- runif(nlyr(r)*ncell(r))
summary(r)
```

---

 svc

---

*Create a SpatVectorCollection*


---

**Description**

Methods to create a SpatVectorCollection. This is an object to hold "sub-datasets", each a SpatVector, perhaps of different geometry type.

**Usage**

```
## S4 method for signature 'missing'
svc(x)

## S4 method for signature 'SpatVector'
svc(x, ...)

## S4 method for signature 'list'
svc(x)
```

**Arguments**

x                   SpatVector, or list of a SpatVector, or missing  
...                  Additional SpatVectors

**Value**

SpatVectorCollection

**Examples**

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
x <- svc()
x <- svc(v, v[1:3,], as.lines(v[3:5,]), as.points(v))
length(x)
x

# extract
x[3]

# replace
x[2] <- as.lines(v[1,])
```

---

symdif	<i>Symmetrical difference</i>
--------	-------------------------------

---

**Description**

Symmetrical difference of polygons

**Usage**

```
## S4 method for signature 'SpatVector,SpatVector'
symdif(x, y)
```

**Arguments**

x                   SpatVector  
y                   SpatVector

**Value**

SpatVector

**See Also**

[erase](#)

## Examples

```
p <- vect(system.file("ex/lux.shp", package="terra"))
b <- as.polygons(ext(6, 6.4, 49.75, 50))
#sd <- symdif(p, b)
#plot(sd, col=rainbow(12))
```

---

tapp

*Apply a function to subsets of layers of a SpatRaster*


---

## Description

Apply a function to subsets of layers of a `SpatRaster` (similar to [tapply](#) and [aggregate](#)). The layers are combined based on the index.

The number of layers in the output `SpatRaster` equals the number of unique values in `index` times the number of values that the supplied function returns for a single vector of numbers.

For example, if you have a `SpatRaster` with 6 layers, you can use `index=c(1,1,1,2,2,2)` and `fun=sum`. This will return a `SpatRaster` with two layers. The first layer is the sum of the first three layers in the input `SpatRaster`, and the second layer is the sum of the last three layers in the input `SpatRaster`. Indices are recycled such that `index=c(1,2)` would also return a `SpatRaster` with two layers (one based on the odd layers (1,3,5), the other based on the even layers (2,4,6)).

The index can also be one of the following values to group by time period (if `x` has the appropriate [time](#) values): "years", "months", "yearmonths", "days", "week" (ISO 8601 week number), or "doy" (day of the year).

See [app](#) or [Summary-methods](#) if you want to use a more efficient function that returns multiple layers based on **all** layers in the `SpatRaster`.

## Usage

```
## S4 method for signature 'SpatRaster'
tapp(x, index, fun, ..., cores=1, filename="", overwrite=FALSE, wopt=list())
```

## Arguments

<code>x</code>	<code>SpatRaster</code>
<code>index</code>	factor or numeric (integer). Vector of length <code>nlyr(x)</code> (shorter vectors are recycled) grouping the input layers. It can also be one of the following values: "years", "months", "yearmonths", "days", "week" (ISO 8601 week number), or "doy" (day of the year)
<code>fun</code>	function to be applied. The following functions have been re-implemented in C++ for speed: "sum", "mean", "median", "modal", "which", "which.min", "which.max", "min", "max", "prod", "any", "all", "sd", "std", "first". To use the base-R function for say, "min", you could use something like <code>fun = \(\i) min(i)</code>
<code>...</code>	additional arguments passed to <code>fun</code>

cores	positive integer. If cores > 1, a 'parallel' package cluster with that many cores is created and used. You can also supply a cluster object. Ignored for functions that are implemented by terra in C++ (see under fun)
filename	character. Output filename
overwrite	logical. If TRUE, filename is overwritten
wopt	list with named options for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**

[app](#), [Summary-methods](#)

**Examples**

```
r <- rast(ncols=10, nrows=10)
values(r) <- 1:ncell(r)
s <- c(r, r, r, r, r, r)
s <- s * 1:6
b1 <- tapp(s, index=c(1,1,1,2,2,2), fun=sum)
b1
b2 <- tapp(s, c(1,2,3,1,2,3), fun=sum)
b2
```

---

terrain	<i>terrain characteristics</i>
---------	--------------------------------

---

**Description**

Compute terrain characteristics from elevation data. The elevation values should be in the same units as the map units (typically meter) for projected (planar) raster data. They should be in meter when the coordinate reference system is longitude/latitude.

For accuracy, always compute these values on the original data (do not first change the projection). Distances (needed for slope and aspect) for longitude/latitude data are computed on the WGS84 ellipsoid with Karney's algorithm.

**Usage**

```
## S4 method for signature 'SpatRaster'
terrain(x, v="slope", neighbors=8, unit="degrees", filename="", ...)
```



## Arguments

<code>x</code>	SpatRaster, single layer with elevation values. Values should have the same unit as the map units, or in meters when the crs is longitude/latitude
<code>v</code>	character. One or more of these options: slope, aspect, TPI, TRI, roughness, flowdir (see Details)
<code>unit</code>	character. "degrees" or "radians" for the output of "slope" and "aspect"
<code>neighbors</code>	integer. Indicating how many neighboring cells to use to compute slope or aspect with. Either 8 (queen case) or 4 (rook case)
<code>filename</code>	character. Output filename
<code>...</code>	additional arguments for writing files as in <a href="#">writeRaster</a>

## Details

When `neighbors=4`, slope and aspect are computed according to Fleming and Hoffer (1979) and Ritter (1987). When `neighbors=8`, slope and aspect are computed according to Horn (1981). The Horn algorithm may be best for rough surfaces, and the Fleming and Hoffer algorithm may be better for smoother surfaces (Jones, 1997; Burrough and McDonnell, 1998).

If `slope = 0`, aspect is set to  $0.5 \cdot \pi$  radians (or 90 degrees if `unit="degrees"`). When computing slope or aspect, the coordinate reference system of `x` must be known for the algorithm to differentiate between planar and longitude/latitude data.

`terrain` is not vectorized over "neighbors" or "unit" – only the first value is used.

`flowdir` returns the "flow direction" (of water), that is the direction of the greatest drop in elevation (or the smallest rise if all neighbors are higher). They are encoded as powers of 2 (0 to 7). The cell to the right of the focal cell is 1, the one below that is 2, and so on:

32	64	128
16	x	1
8	4	2

If two cells have the same drop in elevation, a random cell is picked. That is not ideal as it may prevent the creation of connected flow networks. ArcGIS implements the approach of Greenlee (1987) and I might adopt that in the future.

The terrain indices are according to Wilson et al. (2007), as in [gdaldem](#). TRI (Terrain Ruggedness Index) is the mean of the absolute differences between the value of a cell and the value of its 8 surrounding cells. TPI (Topographic Position Index) is the difference between the value of a cell and the mean value of its 8 surrounding cells. Roughness is the difference between the maximum and the minimum value of a cell and its 8 surrounding cells.

Such measures can also be computed with the [focal](#) function:

```
f <- matrix(1, nrow=3, ncol=3)
TRI <- focal(x, w=f, fun=function(x, ...) sum(abs(x[-5]-x[5]))/8)
TPI <- focal(x, w=f, fun=function(x, ...) x[5] - mean(x[-5]))
rough <- focal(x, w=f, fun=function(x, ...) max(x) - min(x), na.rm=TRUE)
```

References

Burrough, P., and R.A. McDonnell, 1998. Principles of Geographical Information Systems. Oxford University Press.

Fleming, M.D. and Hoffer, R.M., 1979. Machine processing of Landsat MSS data and DMA topographic data for forest cover type mapping. LARS Technical Report 062879. Laboratory for Applications of Remote Sensing, Purdue University, West Lafayette, Indiana.

Horn, B.K.P., 1981. Hill shading and the reflectance map. Proceedings of the IEEE 69:14-47

Jones, K.H., 1998. A comparison of algorithms used to compute hill terrain as a property of the DEM. Computers & Geosciences 24: 315-323

Karney, C.F.F., 2013. Algorithms for geodesics, J. Geodesy 87: 43-55. doi:10.1007/s00190-012-0578-z.

Ritter, P., 1987. A vector-based terrain and aspect generation algorithm. Photogrammetric Engineering and Remote Sensing 53: 1109-1111

See Also

[viewshed](#)

Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
x <- terrain(r, "slope")
```

---

text	<i>Add labels to a map</i>
------	----------------------------

---

Description

Plots labels, that is a textual (rather than color) representation of values, on top an existing plot (map).

Usage

```
## S4 method for signature 'SpatRaster'
text(x, labels, digits=0, halo=FALSE, ...)

## S4 method for signature 'SpatVector'
text(x, labels, halo=FALSE, inside=FALSE, ...)
```

**Arguments**

<code>x</code>	SpatRaster or SpatVector
<code>labels</code>	character. Optional. Vector of labels with <code>length(x)</code> or a variable name from <code>names(x)</code>
<code>digits</code>	integer. How many digits should be used?
<code>halo</code>	logical. If TRUE a "halo" is printed around the text. If TRUE, additional arguments <code>hc="white"</code> and <code>hw=0.1</code> can be modified to set the color and width of the halo
<code>inside</code>	logical. Should the text always be placed inside one the sub-geometries?
<code>...</code>	additional arguments to pass to graphics function <a href="#">text</a>

**See Also**

[text](#), [plot](#)

**Examples**

```
r <- rast(nrows=4, ncols=4)
values(r) <- 1:ncell(r)
plot(r)
text(r)

plot(r)
text(r, halo=TRUE, hc="blue", col="white", hw=0.2)

plot(r, col=rainbow(16))
text(r, col=c("black", "white"), vfont=c("sans serif", "bold"), cex=2)
```

---

`tighten`

*tighten SpatRaster or SpatRasterDataset objects*

---

**Description**

Combines data sources within a SpatRaster object (that are in memory, or from the same file) to allow for faster processing.

Or combine sub-datasets into a SpatRaster.

**Usage**

```
## S4 method for signature 'SpatRaster'
tighten(x)

## S4 method for signature 'SpatRasterDataset'
tighten(x)
```

**Arguments**

<code>x</code>	SpatRaster or SpatRasterDataset
----------------	---------------------------------

Value

SpatRaster

Examples

```
r <- rast(nrow=5, ncol=9, vals=1:45)
x <- c(r, r*2, r*3)
x
tighten(x)
```

---

time	<i>time of SpatRaster layers</i>
------	----------------------------------

---

Description

Get or set the time of the layers of a SpatRaster. Time can be stored as [POSIXlt](#) (date and time, with a resolution of seconds, and a time zone), [Date](#), "months", "years", or "yearmonths".

Usage

```
## S4 method for signature 'SpatRaster'
time(x, format="")

## S4 replacement method for signature 'SpatRaster'
time(x, tstep="")<-value

## S4 method for signature 'SpatRaster'
timeInfo(x)
```

Arguments

x	SpatRaster
format	One of "", "seconds" (POSIXlt), "days" (Date), "yearmonths" (decimal years), "years", "months". If "", the returned format is (based on) the format that was used to set the time
value	Date, POSIXt, yearmon (defined in package zoo), or numeric
tstep	One of "years", "months", "yearmonths". Used when value is numeric. Ignored when value is of type Date, POSIXt, or yearmon

Value

time: POSIXlt, Date, or numeric timeInfo: data.frame

See Also

[depth](#)

**Examples**

```

s <- rast(system.file("ex/logo.tif", package="terra"))

# Date"
d <- as.Date("2001-05-04") + 0:2
time(s) <- d
time(s)

# POSIX (date/time with a resolution of seconds)
time(s) <- as.POSIXlt(d)
time(s)

# with time zone
time(s) <- as.POSIXlt(Sys.time(), "America/New_York") + 0:2
time(s)
timeInfo(s)

# years
time(s, tstep="years") <- 2000 + 0:2
s

time(s, tstep="months") <- 1:3
s

```

tmpFiles

*Temporary files***Description**

List and optionally remove temporary files created by the terra package. These files are created when an output SpatRaster may be too large to store in memory (RAM). This can happen when no filename is provided to a function and when using functions where you cannot provide a filename.

Temporary files are automatically removed at the end of each R session that ends normally. You can use tmpFiles to see the files in the current sessions, including those that are orphaned (not connect to a SpatRaster object any more) and from other (perhaps old) sessions, and remove all the temporary files.

**Usage**

```
tmpFiles(current=TRUE, orphan=FALSE, old=FALSE, remove=FALSE)
```

**Arguments**

current	logical. If TRUE, temporary files from the current R session are included
orphan	logical. If TRUE, temporary files from the current R session that are no longer associated with a SpatRaster object (if current is TRUE these are also included)

old	logical. If TRUE, temporary files from other "R" sessions. Unless you are running multiple instances of R at the same time, these are from old (possibly crashed) R sessions and should be removed
remove	logical. If TRUE, temporary files are removed

**Value**

character

**See Also**

[terraOptions](#)

**Examples**

tmpFiles()

---

topology	<i>Vector topology methods</i>
----------	--------------------------------

---

**Description**

makeNodes create nodes on lines  
mergeLines connect lines to form polygons  
removeDupNodes removes duplicate nodes in geometries and optionally rounds the coordinates  
emptyGeoms returns the indices of empty (null) geometries  
snap makes boundaries of geometries identical if they are very close to each other.

**Usage**

```
## S4 method for signature 'SpatVector'  
mergeLines(x)  
## S4 method for signature 'SpatVector'  
snap(x, y=NULL, tolerance)  
## S4 method for signature 'SpatVector'  
removeDupNodes(x, digits = -1)  
## S4 method for signature 'SpatVector'  
makeNodes(x)
```

**Arguments**

x	SpatVector of lines or polygons
y	SpatVector of lines or polygons to snap to. If NULL snapping is to the other geometries in x
tolerance	numeric. Snapping tolerance (distance between geometries)
digits	numeric. Number of digits used in rounding. Ignored if < 0

**Value**

SpatVector

**See Also**

[sharedPaths](#), [gaps](#), [simplifyGeom](#)

**Examples**

```
p1 <- as.polygons(ext(0,1,0,1))
p2 <- as.polygons(ext(1.1,2,0,1))

p <- rbind(p1, p2)

y <- snap(p, tol=.15)
plot(p, lwd=3, col="light gray")
lines(y, col="red", lwd=2)
```

---

transpose	<i>Transpose</i>
-----------	------------------

---

**Description**

Transpose a SpatRaster

**Usage**

```
## S4 method for signature 'SpatRaster'
t(x)

## S4 method for signature 'SpatVector'
t(x)

## S4 method for signature 'SpatRaster'
trans(x, filename="", ...)
```

**Arguments**

x	SpatRaster
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**See Also**[flip](#), [rotate](#)**Examples**

```

r <- rast(nrows=18, ncols=36)
values(r) <- 1:ncell(r)
tr1 <- t(r)
tr2 <- trans(r)
ttr <- trans(tr2)

```

trim

*Trim a SpatRaster***Description**

Trim (shrink) a SpatRaster by removing outer rows and columns that are NA or another value.

**Usage**

```

## S4 method for signature 'SpatRaster'
trim(x, padding=0, value=NA, filename="", ...)

```

**Arguments**

x	SpatRaster
padding	integer. Number of outer rows/columns to keep
value	numeric. The value of outer rows or columns that are to be removed
filename	character. Output filename
...	additional arguments for writing files as in <a href="#">writeRaster</a>

**Value**

SpatRaster

**Examples**

```

r <- rast(ncols=10, nrows=10, xmin=0,xmax=10,ymin=0,ymax=10)
v <- rep(NA, ncell(r))
v[c(12,34,69)] <- 1:3
values(r) <- v
s <- trim(r)

```



---

**union***Union SpatVector or SpatExtent objects*

---

**Description**

Overlapping polygons (between, not within, objects) are intersected. Union for lines and points simply combines the two data sets; without any geometric intersections. This is equivalent to [c](#). Attributes are joined. See [c](#) if you want to combine polygons without intersection.

If x and y have a different geometry type, a SpatVectorCollection is returned.

If a single SpatVector is supplied, overlapping polygons are intersected. Original attributes are lost. New attributes allow for determining how many, and which, polygons overlapped.

SpatExtent: Objects are combined into their union; this is equivalent to +.

**Usage**

```
## S4 method for signature 'SpatVector,SpatVector'
union(x, y)

## S4 method for signature 'SpatVector,missing'
union(x, y)

## S4 method for signature 'SpatExtent,SpatExtent'
union(x, y)
```

**Arguments**

x	SpatVector or SpatExtent
y	Same as x or missing

**Value**

SpatVector or SpatExtent

**See Also**

[intersect](#)

[merge](#) and [mosaic](#) to union SpatRaster objects.

[crop](#) and [extend](#) for the union of SpatRaster and SpatExtent.

[merge](#) for merging a data.frame with attributes of a SpatVector.

[aggregate](#) to dissolve SpatVector objects.

Examples

```
e1 <- ext(-10, 10, -20, 20)
e2 <- ext(0, 20, -40, 5)
union(e1, e2)

#SpatVector
v <- vect(system.file("ex/lux.shp", package="terra"))
v <- v[,3:4]
p <- vect(c("POLYGON ((5.8 49.8, 6 49.9, 6.15 49.8, 6 49.65, 5.8 49.8))",
"POLYGON ((6.3 49.9, 6.2 49.7, 6.3 49.6, 6.5 49.8, 6.3 49.9))"), crs=crs(v))
values(p) <- data.frame(pid=1:2, value=expansion(p))
u <- union(v, p)
plot(u, "pid")

b <- buffer(v, 1000)

u <- union(b)
u$sum <- rowSums(as.data.frame(u))
plot(u, "sum")
```

---

unique	<i>Unique values</i>
--------	----------------------

---

Description

This method returns the unique values in a SpatRaster, or removes duplicates records (geometry and attributes) in a SpatVector.

Usage

```
## S4 method for signature 'SpatRaster'
unique(x, incomparables=FALSE, na.rm=TRUE, as.raster=FALSE)

## S4 method for signature 'SpatVector'
unique(x, incomparables=FALSE, ...)
```

Arguments

x	SpatRaster or SpatVector
incomparables	logical. If FALSE and x is a SpatRaster: the unique values are determined for all layers together, and the result is a matrix. If TRUE, each layer is evaluated separately, and a list is returned. If x is a SpatVector this argument is as for a data.frame
na.rm	logical. If TRUE, NaN is included if there are any missing values
as.raster	logical. If TRUE, a single-layer categorical SpatRaster with the unique values is returned
...	additional arguments passed on to <a href="#">unique</a>

**Value**

If x is a `SpatRaster`: `data.frame` or `list` (if `incomparables=FALSE`)

If x is a `SpatVector`: `SpatVector`

**Examples**

```
r <- rast(ncols=5, nrows=5)
values(r) <- rep(1:5, each=5)
unique(r)
s <- c(r, round(r/3))
unique(s)
unique(s,TRUE)

unique(s, as.raster=TRUE)

v <- vect(cbind(x=c(1:5,1:5), y=c(5:1,5:1)),
crs="+proj=utm +zone=1 +datum=WGS84")
nrow(v)
u <- unique(v)
nrow(u)

values(v) <- c(1:5, 1:3, 5:4)
unique(v)
```

---

units

*units of `SpatRaster` or `SpatRasterDataSet`*


---

**Description**

Get or set the units of the layers of a `SpatRaster` or the datasets in a `SpatRasterDataSet`.

**Usage**

```
## S4 method for signature 'SpatRaster'
units(x)

## S4 replacement method for signature 'SpatRaster'
units(x)<-value

## S4 method for signature 'SpatRasterDataSet'
units(x)

## S4 replacement method for signature 'SpatRasterDataSet'
units(x)<-value
```

**Arguments**

x	SpatRaster
value	character

**Value**

character

**See Also**

[time](#), [names](#)

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra"))

units(s) <- c("m/s", "kg", "ha")
units(s)
s

units(s) <- "kg"
units(s)
```

---

update	<i>Change values in a file</i>
--------	--------------------------------

---

**Description**

Change the contents of a file that is the data source of a SpatRaster. BE CAREFUL as you are overwriting values in an existing file.

**Usage**

```
## S4 method for signature 'SpatRaster'
update(object, names=FALSE, crs=FALSE, extent=FALSE)
```

**Arguments**

object	SpatRaster
names	logical. Should the names be updated?
crs	logical. Should the coordinate reference system be updated?
extent	logical. Should the extent be updated?

**Value**

SpatRaster (invisibly)

Examples

```
s <- rast(system.file("ex/logo.tif", package="terra"))
fname <- paste0(tempfile(), ".tif")
x <- writeRaster(s, fname)
names(x) <- c("A", "B", "C")
ext(x) <- ext(x) + 1
crs(x) <- "+proj=utm +zone=1"

update(x, names=TRUE, crs=TRUE, extent=TRUE)

rast(fname)
```

---

valid	<i>Check or fix polygon validity</i>
-------	--------------------------------------

---

Description

Check the validity of polygons or attempt to fix it

Usage

```
## S4 method for signature 'SpatVector'
is.valid(x, messages=FALSE, as.points=FALSE)

## S4 method for signature 'SpatVector'
makeValid(x)
```

Arguments

- x                      SpatVector
- messages             logical. If TRUE the error messages are returned
- as.points             logical. If TRUE, it is attempted to return locations where polygons are invalid as a SpatVector or points

Value

logical

Examples

```
w <- vect("POLYGON ((0 -5, 10 0, 10 -10, 0 -5))")
is.valid(w)

w <- vect("POLYGON ((0 -5, 10 0, 10 -10, 4 -2, 0 -5))")
is.valid(w)
is.valid(w, TRUE)

plot(w)
```

```
points(cbind(4.54, -2.72), cex=2, col="red")
```

---

values	<i>Cell values and geometry attributes</i>
--------	--

---

**Description**

Get the cell values of a `SpatRaster` or the attributes of a `SpatVector`.  
By default all values returned are numeric. This is because a vector or matrix can only store one data type, and a `SpatRaster` may consist of multiple data types. However, with `values(x, dataframe=TRUE)` and `as.data.frame(x)` the values returned match the type of each layer, and can be numeric, logical, integer, or factor.

**Usage**

```
## S4 method for signature 'SpatRaster'
values(x, mat=TRUE, dataframe=FALSE, row=1,
       nrows=nrow(x), col=1, ncols=ncol(x), na.rm=FALSE, ...)

## S4 method for signature 'SpatVector'
values(x, ...)
```

**Arguments**

x	<code>SpatRaster</code> or <code>SpatVector</code>
mat	logical. If TRUE, values are returned as a matrix instead of as a vector, except when dataframe is TRUE
dataframe	logical. If TRUE, values are returned as a <code>data.frame</code> instead of as a vector (also if matrix is TRUE)
row	positive integer. Row number to start from, should be between 1 and <code>nrow(x)</code>
nrows	positive integer. How many rows?
col	positive integer. Column number to start from, should be between 1 and <code>ncol(x)</code>
ncols	positive integer. How many columns? Default is the number of columns left after the start column
na.rm	logical. Remove NAs?
...	additional arguments passed to <code>data.frame</code>

**Details**

If `x` is a `SpatRaster`, and `mat=FALSE`, the values are returned as a vector. In cell-order by layer. If `mat=TRUE`, a matrix is returned in which the values of each layer are represented by a column (with `ncell(x)` rows). The values per layer are in cell-order, that is, from top-left, to top-right and then down by row. Use `as.matrix(x, wide=TRUE)` for an alternative matrix representation where the number of rows and columns matches that of `x`.

**Value**

matrix or data.frame

**See Also**

[values<-](#), [focalValues](#)

**Examples**

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
r
x <- values(r)
x[3650:3655, ]
r[3650:3655]
```

```
ff <- system.file("ex/lux.shp", package="terra")
v <- vect(ff)
y <- values(v)
head(y)
```

---

vect

*Create SpatVector objects*

---

**Description**

Methods to create a SpatVector from a filename or other R object.

A filename can be for a shapefile or any spatial file format.

You can use a data.frame to make a SpatVector of points; or a "geom" matrix to make a SpatVector of any supported geometry (see examples and [geom](#)).

You can supply a list of SpatVectors to append them into a single SpatVector.

SpatVectors can also be created from "Well Known Text", and from spatial vector data objects defined in the sf or sp packages.

**Usage**

```
## S4 method for signature 'character'
vect(x, layer="", query="", extent=NULL, filter=NULL,
     crs="", proxy=FALSE, what="")
```

```
## S4 method for signature 'matrix'
vect(x, type="points", atts=NULL, crs="")
```

```
## S4 method for signature 'data.frame'
vect(x, geom=c("lon", "lat"), crs="", keepgeom=FALSE)
```

```
## S4 method for signature 'list'
vect(x)

## S4 method for signature 'sf'
vect(x)
```

## Arguments

x	character. A filename; or a "Well Known Text" string; or a data.frame (only to make a SpatVector of points); or a "geom" matrix to make a SpatVector of any supported geometry (see examples and <a href="#">geom</a> ); or a spatial vector data object defined in the sf or sp packages
layer	character. layer name to select a layer from a file (database) with multiple layers
query	character. An query to subset the dataset in the <b>OGR-SQL dialect</b>
extent	Spat* object. The extent of the object is used as a spatial filter to select the geometries to read. Ignored if filter is not NULL
filter	SpatVector. Used as a spatial filter to select geometries to read (the convex hull is used for lines or points). It is guaranteed that all features that overlap with the extent of filter will be returned. It can happen that additional geometries are returned
type	character. Geometry type. Must be "points", "lines", or "polygons"
atts	data.frame with the attributes. The number of rows must match the number of geometrical elements
crs	character. The coordinate reference system in one of the following formats: WKT/WKT2, <authority>:<code>, or PROJ-string notation (see <a href="#">crs</a> ). See <a href="#">crs</a>
proxy	logical. If TRUE a SpatVectorProxy is returned
what	character indicating what to read. Either "" for geometries and attributes, geoms to only read the geometries, attributes to only read the attributes (that are returned as a data.frame)
geom	character. The field name(s) with the geometry data. Either two names for x and y coordinates of points, or a single name for a single column with WKT geometries)
keepgeom	logical. If TRUE the geom variable(s) is (are) also included in the attributes

## Value

SpatVector

## See Also

[geom](#)



## Examples

```

### SpatVector from file
f <- system.file("ex/lux.shp", package="terra")
f
v <- vect(f)
v

## subsetting (large) files
## with attribute query
v <- vect(f, query="SELECT NAME_1, NAME_2, ID_2 FROM lux WHERE ID_2 < 4")
v

## with an extent
e <- ext(5.9, 6.3, 49.9, 50)
v <- vect(f, extent=e)

## with polygons
p <- as.polygons(e)
v <- vect(f, filter=p)

### SpatVector from a geom matrix
x1 <- rbind(c(-180,-20), c(-140,55), c(10, 0), c(-140,-60))
x2 <- rbind(c(-10,0), c(140,60), c(160,0), c(140,-55))
x3 <- rbind(c(-125,0), c(0,60), c(40,5), c(15,-45))
hole <- rbind(c(80,0), c(105,13), c(120,2), c(105,-13))
z <- rbind(cbind(object=1, part=1, x1, hole=0), cbind(object=2, part=1, x3, hole=0),
cbind(object=3, part=1, x2, hole=0), cbind(object=3, part=1, hole, hole=1))
colnames(z)[3:4] <- c('x', 'y')

p <- vect(z, "polygons")
p

z[z[, "hole"]==1, "object"] <- 4
lns <- vect(z[,1:4], "lines")
plot(p)
lines(lns, col="red", lwd=2)

### from wkt
v <- vect("POLYGON ((0 -5, 10 0, 10 -10, 0 -5))")

wkt <- c("MULTIPOLYGON ( ((40 40, 20 45, 45 30, 40 40)),
((20 35, 10 30, 10 10, 30 5, 45 20, 20 35),(30 20, 20 15, 20 25, 30 20)))",
"POLYGON ((0 -5, 10 0, 10 -10, 0 -5))")
w <- vect(wkt)

# combine two SpatVectors
vw <- rbind(w, v)

# add a data.frame
d <- data.frame(id=1:2, name=c("a", "b"))
values(w) <- d

```

```
# add data.frame on creation, here from a geom matrix
g <- geom(w)
d <- data.frame(id=1:2, name=c("a", "b"))
m <- vect(g, "polygons", atts=d, crs="+proj=longlat +datum=WGS84")

### SpatVector from a data.frame
d$wkt <- wkt
x <- vect(d, geom="wkt")

d$wkt <- NULL
d$lon <- c(0,10)
d$lat <- c(0,10)
x <- vect(d, geom=c("lon", "lat"))

# SpatVector to sf
#sf::st_as_sf(x)
```

---

vector_layers	List or remove layers from a vector file
---------------	--

---

**Description**

List or remove layers from a vector file that supports layers such as GPKG

**Usage**

```
vector_layers(filename, delete="", return_error=FALSE)
```

**Arguments**

filename	character. filename
delete	character. layers to be deleted (ignored if the value is "")
return_error	logical. If TRUE, an error occurs if some layers cannot be deleted. Otherwise a warning is given

---

viewshed	Compute a viewshed
----------	--------------------

---

**Description**

Use elevation data to compute the locations that can be seen, or how much higher they would have to be to be seen, from a certain position. The raster data coordinate reference system must planar (not lon/lat), with the elevation values in the same unit as the distance unit of the coordinate reference system.

**Usage**

```
## S4 method for signature 'SpatRaster'
viewshed(x, loc, observer=1.80, target=0, curvcoef=6/7, output="yes/no", filename="", ...)
```

**Arguments**

x	SpatRaster, single layer with elevation values. Values should have the same unit as the map units
loc	location (x and y coordinates) or a cell number
observer	numeric. The height above the elevation data of the observer
target	numeric. The height above the elevation data of the targets
curvcoef	numeric. Coefficient to consider the effect of the curvature of the earth and refraction of the atmosphere. The elevation values are corrected with: $\text{elevation} = \text{elevation} - \text{curvcoef} * (\text{distance})^2 / (\text{earth\_diameter})$ . This means that with the default value of 0.85714, you lose sight of about 1 meter of elevation for each 385 m of planar distance
output	character. Can be "yes/no" to get a binary (logical) output showing what areas are visible; "land" to get the height above the current elevation that would be visible; or "sea" the elevation above sea level that would be visible
filename	character. Output filename
...	Options for writing files as in <a href="#">writeRaster</a>

**References**

The algorithm used is by Wang et al.: [https://www.asprs.org/wp-content/uploads/pers/2000journal/january/2000\\_jan\\_87-90.pdf](https://www.asprs.org/wp-content/uploads/pers/2000journal/january/2000_jan_87-90.pdf).

**See Also**

[terrain](#)

**Examples**

```
if (gdal() >= 3.1) {
  f <- system.file("ex/elev.tif", package="terra")
  r <- rast(f)
  x <- project(r, "EPSG:2169")
  p <- cbind(70300, 96982)
  v <- viewshed(x, p, 0, 0, 0.85714)
}
```

---

 voronoi

*Voronoi diagram and Delaunay triangles*


---

## Description

Get a Voronoi diagram or Delaunay triangles for points, or the nodes of lines or polygons

## Usage

```
## S4 method for signature 'SpatVector'
voronoi(x, bnd=NULL, tolerance=0, as.lines=FALSE, deldir=FALSE)
```

```
## S4 method for signature 'SpatVector'
delaunay(x, tolerance=0, as.lines=FALSE)
```

## Arguments

x	SpatVector
bnd	SpatVector to set the outer boundary of the voronoi diagram
tolerance	numeric >= 0, snapping tolerance (0 is no snapping)
as.lines	logical. If TRUE, lines are returned without the outer boundary
deldir	logical. If TRUE, the <a href="#">deldir</a> is used instead of the GEOS C++ library method. It has been reported that deldir does not choke on very large data sets

## Value

SpatVector

## Examples

```
wkt <- c("MULTIPOLYGON ( ((40 40, 20 45, 45 30, 40 40)),
  ((20 35, 10 30, 10 10, 30 5, 45 20, 20 35),(30 20, 20 15, 20 25, 30 20)))",
  "POLYGON ((0 -5, 10 0, 10 -10, 0 -5))")
x <- vect(wkt)
v <- voronoi(x)
v

d <- delaunay(x)
d

plot(v, lwd=2, col=rainbow(15))
lines(x, col="gray", lwd=2)
points(x)
```

---

vrt	<i>Virtual Raster Dataset</i>
-----	-------------------------------

---

**Description**

Create a Virtual Raster Dataset (VRT) from a collection of file-based raster datasets (tiles).

**Usage**

```
## S4 method for signature 'character'
vrt(x, filename="", options=NULL, overwrite=FALSE)
```

**Arguments**

x	character. Filenames of raster "tiles". See <a href="#">tiles</a>
filename	character. Output VRT filename
options	character. All arguments as separate vector elements. Options as for <a href="#">gdalbuild-vrt</a>
overwrite	logical. Should filename be overwritten if it exists?

**Value**

SpatRaster

**Note**

A VRT can reference very many datasets. These are not all opened at the same time. The default is to open not more than 100 files. To increase performance, this maximum limit can be increased by setting the GDAL\_MAX\_DATASET\_POOL\_SIZE configuration option to a bigger value with [setGDALconfig](#). Note that a typical user process on Linux is limited to 1024 simultaneously opened files.

**See Also**

[makeTiles](#) to create tiles; [makeVRT](#) to create a .vrt file for a binary raster file that does not have a header file.

**Examples**

```
r <- rast(ncols=100, nrows=100)
values(r) <- 1:ncell(r)
x <- rast(ncols=2, nrows=2)
filename <- paste0(tempfile(), "_tif")
ff <- makeTiles(r, x, filename)
ff

#vrtfile <- paste0(tempfile(), ".vrt")
#v <- vrt(ff, vrtfile)
```

```
## output in lower resolution
#vrtfile <- paste0(tempfile(), ".vrt")
#v <- vrt(ff, vrtfile, options = c("-tr", 5, 5))
#head(readLines(vrtfile))
#v
```

---

weighted.mean	<i>Weighted mean of layers</i>
---------------	--------------------------------

---

**Description**

Compute the weighted mean for each cell of the layers of a `SpatRaster`. The weights can be spatially variable or not.

**Usage**

```
## S4 method for signature 'SpatRaster,numeric'
weighted.mean(x, w, na.rm=FALSE, filename="", ...)

## S4 method for signature 'SpatRaster,SpatRaster'
weighted.mean(x, w, na.rm=FALSE, filename="", ...)
```

**Arguments**

x	<code>SpatRaster</code>
w	A vector of weights (one number for each layer), or for spatially variable weights, a <code>SpatRaster</code> with weights (should have the same extent, resolution and number of layers as x)
na.rm	Logical. Should missing values be removed?
filename	character. Output filename
...	options for writing files as in <a href="#">writeRaster</a>

**Value**

`SpatRaster`

**See Also**

[Summary-methods](#), [weighted.mean](#)

**Examples**

```

b <- rast(system.file("ex/logo.tif", package="terra"))

# give least weight to first layer, most to last layer
wm1 <- weighted.mean(b, w=1:3)

# spatially varying weights
# weigh by column number
w1 <- init(b, "col")

# weigh by row number
w2 <- init(b, "row")
w <- c(w1, w2, w2)

wm2 <- weighted.mean(b, w=w)

```

---

where

*Where are the cells with the min or max values?*


---

**Description**

This method returns the cell numbers for the cells with the min or max values of each layer in a `SpatRaster`.

**Usage**

```

## S4 method for signature 'SpatRaster'
where.min(x, values=TRUE, list=FALSE)

## S4 method for signature 'SpatRaster'
where.max(x, values=TRUE, list=FALSE)

```

**Arguments**

<code>x</code>	<code>SpatRaster</code>
<code>values</code>	logical. If TRUE the min or max values are also returned
<code>list</code>	logical. If TRUE a list is returned instead of a matrix

**Value**

matrix or list

**See Also**

[which](#) and [Summary-methods](#) for `which.min` and `which.max`

**Examples**

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
where.min(r)
```

---

which.lyr

*Which cells are TRUE?*


---

**Description**

This method returns a single layer `SpatRaster` with cell values indicating the the first layer in the input that is `TRUE`. All numbers that are not zero (or `FALSE`), are considered to be `TRUE`.

**Usage**

```
## S4 method for signature 'SpatRaster'
which.lyr(x)
```

**Arguments**

x                      `SpatRaster`

**Value**

`SpatRaster`

**See Also**

[isTRUE](#), [which](#), See [Summary-methods](#) for `which.min` and `which.max`

**Examples**

```
s <- rast(system.file("ex/logo.tif", package="terra"))
x <- which.lyr(s > 100)
```



---

width

---

*SpatVector* geometric properties

---

### Description

`width` returns the minimum diameter of the geometry, defined as the smallest band that contains the geometry, where a band is a strip of the plane defined by two parallel lines. This can be thought of as the smallest hole that the geometry can be moved through, with a single rotation.

`clearance` returns the minimum clearance of a geometry. The minimum clearance is the smallest amount by which a vertex could be moved to produce an invalid polygon, a non-simple linestring, or a multipoint with repeated points. If a geometry has a minimum clearance of 'mc', it can be said that:

No two distinct vertices in the geometry are separated by less than 'mc'. No vertex is closer than 'mc' to a line segment of which it is not an endpoint. If the minimum clearance cannot be defined for a geometry (such as with a single point, or a multipoint whose points are identical, NA is returned.

### Usage

```
## S4 method for signature 'SpatVector'
width(x, as.lines=FALSE)
## S4 method for signature 'SpatVector'
clearance(x, as.lines=FALSE)
```

### Arguments

<code>x</code>	<code>SpatVector</code> of lines or polygons
<code>as.lines</code>	logical. If TRUE lines are returned that define the width or clearance

### Value

numeric or `SpatVector`

### See Also

[minRect](#)

### Examples

```
f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
width(v)
clearance(v)
```

---

window

*Set a window*


---

## Description

**Experimental:** Assign a window (area of interest) to a `SpatRaster` with a `SpatExtent`, or set it to `NULL` to remove the window. This is similar to [crop](#) without actually creating a new dataset.

Currently, the window will be forced to intersect with the extent of the `SpatRaster`. It is envisioned that in future versions, the window may also go outside these boundaries.

## Usage

```
## S4 replacement method for signature 'SpatRaster'
window(x) <- value

## S4 method for signature 'SpatRaster'
window(x)
```

## Arguments

x	<code>SpatRaster</code>
value	<code>SpatExtent</code>

## Value

none for `window<-` and logical for `window`

## See Also

[crop](#), [extend](#)

## Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
global(r, "mean", na.rm=TRUE)
e <- ext(c(5.9, 6, 49.95, 50))

window(r) <- e
global(r, "mean", na.rm=TRUE)
r

x <- rast(f)
xe <- crop(x, e)
global(xe, "mean", na.rm=TRUE)

b <- c(xe, r)
window(b)
```

```

b

window(r) <- NULL
r

```

---

wrap

*wrap and unwrap*


---

## Description

Use `wrap` to pack a `SpatRaster` or `SpatVector` object to create a `Packed*` object. Packed objects can be passed over a connection that serializes (e.g. to nodes on a computer cluster). At the receiving end they need to be unpacked with `unwrap`.

## Usage

```

## S4 method for signature 'SpatRaster'
wrap(x, proxy=FALSE)

## S4 method for signature 'SpatVector'
wrap(x)

## S4 method for signature 'ANY'
unwrap(x)

```

## Arguments

<code>x</code>	<code>SpatVector</code> or <code>SpatRaster</code>
<code>proxy</code>	logical. If <code>FALSE</code> raster cell values are forced to memory if possible. If <code>TRUE</code> , a reference to source filenames is stored for data sources that are not in memory

## Value

`wrap`: `Packed*` object

`unwrap`: `SpatRaster` or `SpatVector`

## Examples

```

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
p <- wrap(v)
p
vv <- vect(p)
vv

```

---

writeCDF

---

Write raster data to a NetCDF file

---

### Description

Write a `SpatRaster` or `SpatRasterDataset` to a NetCDF file.

When using a `SpatRasterDataset`, the `varname`, `longname`, and `unit` should be set in the object (see examples).

Always use the ".nc" or ".cdf" file extension to assure that the file can be properly read again by GDAL

### Usage

```
## S4 method for signature 'SpatRaster'
writeCDF(x, filename, varname, longname="", unit="", ...)
```

```
## S4 method for signature 'SpatRasterDataset'
writeCDF(x, filename, overwrite=FALSE, zname="time",
         prec="float", compression=NA, missval, ...)
```

### Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatRasterDataset</code>
<code>filename</code>	character. Output filename
<code>varname</code>	character. Name of the dataset
<code>longname</code>	character. Long name of the dataset
<code>unit</code>	character. Unit of the data
<code>overwrite</code>	logical. If TRUE, filename is overwritten
<code>zname</code>	character. The name of the "time" dimension
<code>prec</code>	character. One of "double", "float", "integer", "short", "byte" or "char"
<code>compression</code>	Can be set to an integer between 1 (least compression) and 9 (most compression)
<code>missval</code>	numeric, the number used to indicate missing values
<code>...</code>	additional arguments passed on to <a href="#">ncvar_def</a>

### Value

`SpatRaster` or `SpatDataSet`

### See Also

see [writeRaster](#) for writing other file formats

## Examples

```
f <- system.file("ex/elev.tif", package="terra")
r <- rast(f)
fname <- paste0(tempfile(), ".nc")
#rr <- writeCDF(r, fname, overwrite=TRUE, varname="alt",
#             longname="elevation in m above sea level", unit="m")

a <- rast(ncols=5, nrows=5, nl=50)
values(a) <- 1:prod(dim(a))
time(a) <- as.Date("2020-12-31") + 1:nlyr(a)
#aa <- writeCDF(a, fname, overwrite=TRUE, varname="power",
#             longname="my nice data", unit="U/Pa")

b <- sqrt(a)
s <- sds(a, b)
names(s) <- c("temp", "prec")
longnames(s) <- c("temperature (C)", "precipitation (mm)")
units(s) <- c("C", "mm")
#ss <- writeCDF(s, fname, overwrite=TRUE)

# for CRAN
#file.remove(fname)
```

---

writeRaster

Write raster data to a file

---

## Description

Write a SpatRaster object to a file.

## Usage

```
## S4 method for signature 'SpatRaster,character'
writeRaster(x, filename, overwrite=FALSE, ...)
```

## Arguments

x	SpatRaster
filename	character. Output filename. Can be a single filename, or as many filenames as nlyr(x) to write a file for each layer
overwrite	logical. If TRUE, filename is overwritten
...	additional arguments for for writing files. See Details

## Details

In writeRaster, and in other methods that generate SpatRaster objects, options for writing raster files to disk can be provided as additional arguments or, in a few cases, as the wopt argument (a named list) if the additional arguments are already used for a different purpose. The following options are available:

name	description
datatype	values for datatype are "INT1U", "INT2U", "INT2S", "INT4U", "INT4S", "FLT4S", "FLT8S". The first three le
filetype	file format expresses as <b>GDAL driver names</b> . If this argument is not supplied, the driver is derived from the filena
gdal	GDAL driver specific datasource creation options. See the GDAL documentation. For example, with the <b>GeoTiff</b>
tempdir	the path where temporary files are to be written to.
progress	positive integer. If the number of chunks is larger, a progress bar is shown.
memfrac	numeric between 0 and 0.9 (higher values give a warning). The fraction of available RAM that terra is allowed to
memmax	memmax - the maximum amount of RAM (in GB) that terra can use when processing a raster dataset. Should be
names	output layer names.
NAflag	numeric. value to represent missing (NA or NaN) values. See note
verbose	logical. If TRUE debugging information is printed.
steps	positive integers. In how many steps (chunks) do you want to process the data (for debugging)
todisk	logical. If TRUE processing operates as if the dataset is very large and needs to be written to a temporary file (for c

## Value

SpatRaster. This function is used for the side-effect of writing values to a file.

## Note

GeoTiff files are, by default, written with LZW compression. If you do not want compression, use `gdal="COMPRESS=NONE"`.

When writing integer values the lowest available value (given the datatype) is used to represent NA for signed types, and the highest value is used for unsigned values. This can be a problem with byte data (between 0 and 255) as the value 255 is reserved for NA. To keep the value 255, you need to set another value as NAflag, or do not set a NAflag (with NAflag=NA)

## See Also

see [writeCDF](#) for writing NetCDF files.

## Examples

```
r <- rast(nrows=5, ncols=5, vals=1:25)

# create a temporary filename for the example
f <- file.path(tempdir(), "test.tif")

writeRaster(r, f, overwrite=TRUE)

writeRaster(r, f, overwrite=TRUE, gdal=c("COMPRESS=NONE", "TFW=YES"), datatype='INT1U')
```

```
## Or with a wopt argument:

writeRaster(r, f, overwrite=TRUE, wopt= list(gdal=c("COMPRESS=NONE"), datatype='INT1U'))

## remove the file
unlink(f)
```

---

writeVector

*Write SpatVector data to a file*


---

## Description

Write a SpatVector to a file. You can choose one of many file formats.

## Usage

```
## S4 method for signature 'SpatVector,character'
writeVector(x, filename, filetype=NULL, layer=NULL, insert=FALSE,
            overwrite=FALSE, options="ENCODING=UTF-8")
```

## Arguments

x	SpatVector
filename	character. Output filename
filetype	character. A file format associated with a GDAL "driver" such as "ESRI Shapefile". See <code>gdal(drivers=TRUE)</code> or the <a href="#">GDAL docs</a> . If NULL it is attempted to guess the filetype from the filename extension
layer	character. Output layer name. If NULL the filename is used
insert	logical. If TRUE, a new layer is inserted into the file, if the format allows it (e.g. GPKG allows that). See <a href="#">vector_layers</a> to remove a layer
overwrite	logical. If TRUE, filename is overwritten
options	character. Format specific GDAL options such as "ENCODING=UTF-8". Use NULL or "" to not use any options

## Examples

```
v <- vect(cbind(1:5,1:5))
crs(v) <- "+proj=longlat +datum=WGS84"
v$id <- 1:length(v)
v$name <- letters[1:length(v)]
tmpf1 <- tempfile()
writeVector(v, tmpf1)
x <- vect(tmpf1)

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)
tmpf2 <- tempfile()
writeVector(v, tmpf2)
y <- vect(tmpf2)
```

---

xmin

---

*Get or set single values of an extent*


---

### Description

Get or set single values of an extent. Values can be set for a SpatExtent or SpatRaster, but not for a SpatVector)

### Usage

```
## S4 method for signature 'SpatExtent'
xmin(x)

## S4 method for signature 'SpatExtent'
xmax(x)

## S4 method for signature 'SpatExtent'
ymin(x)

## S4 method for signature 'SpatExtent'
ymax(x)

## S4 method for signature 'SpatRaster'
xmin(x)

## S4 method for signature 'SpatRaster'
xmax(x)

## S4 method for signature 'SpatRaster'
ymin(x)

## S4 method for signature 'SpatRaster'
ymax(x)

## S4 method for signature 'SpatVector'
xmin(x)

## S4 method for signature 'SpatVector'
xmax(x)

## S4 method for signature 'SpatVector'
ymin(x)

## S4 method for signature 'SpatVector'
ymax(x)

## S4 replacement method for signature 'SpatRaster,numeric'
```



```

xmin(x)<-value

## S4 replacement method for signature 'SpatRaster,numeric'
xmax(x)<-value

## S4 replacement method for signature 'SpatRaster,numeric'
ymin(x)<-value

## S4 replacement method for signature 'SpatRaster,numeric'
ymax(x)<-value

```

### Arguments

x	SpatRaster, SpatExtent, or SpatVector
value	numeric

### Value

SpatExtent or numeric coordinate

### Examples

```

r <- rast()
ext(r)
ext(c(0, 20, 0, 20))

xmin(r)
xmin(r) <- 0
xmin(r)

```

---

xyRowColCell

---

*Coordinates from a row, column or cell number and vice versa*


---

### Description

Get coordinates of the center of raster cells for a row, column, or cell number of a SpatRaster object. Or get row, column, or cell numbers from coordinates or from each other.

Cell numbers start at 1 in the upper left corner, and increase from left to right, and then from top to bottom. The last cell number equals the number of cells of the SpatRaster object. row numbers start at 1 at the top, column numbers start at 1 at the left.

### Usage

```

## S4 method for signature 'SpatRaster,numeric'
xFromCol(object, col)

## S4 method for signature 'SpatRaster,numeric'
yFromRow(object, row)

```

```

## S4 method for signature 'SpatRaster,numeric'
xyFromCell(object, cell)

## S4 method for signature 'SpatRaster,numeric'
xFromCell(object, cell)

## S4 method for signature 'SpatRaster,numeric'
yFromCell(object, cell)

## S4 method for signature 'SpatRaster,numeric'
colFromX(object, x)

## S4 method for signature 'SpatRaster,numeric'
rowFromY(object, y)

## S4 method for signature 'SpatRaster,numeric,numeric'
cellFromRowCol(object, row, col)

## S4 method for signature 'SpatRaster,numeric,numeric'
cellFromRowColCombine(object, row, col)

## S4 method for signature 'SpatRaster,numeric,numeric'
rowColCombine(object, row, col)

## S4 method for signature 'SpatRaster,numeric'
rowFromCell(object, cell)

## S4 method for signature 'SpatRaster,numeric'
colFromCell(object, cell)

## S4 method for signature 'SpatRaster,numeric'
rowColFromCell(object, cell)

## S4 method for signature 'SpatRaster,matrix'
cellFromXY(object, xy)

```

### Arguments

object	SpatRaster
cell	integer. cell number(s)
col	integer. column number(s) or missing (equivalent to all columns)
row	integer. row number(s) or missing (equivalent to all rows)
x	x coordinate(s)
y	y coordinate(s)
xy	matrix of x and y coordinates

**Details**

Cell numbers start at 1 in the upper left corner, and increase from left to right, and then from top to bottom. The last cell number equals the number of cells of the SpatRaster (see [ncell](#)).

**Value**

xFromCol, yFromCol, xFromCell, yFromCell: vector of x or y coordinates

xyFromCell: matrix(x,y) with coordinate pairs

colFromX, rowFromY, cellFromXY, cellFromRowCol, rowFromCell, colFromCell: vector of row, column, or cell numbers

rowColFromCell, rowColCombine: matrix of row and column numbers

**See Also**

[crds](#)

**Examples**

```
r <- rast()

xFromCol(r, c(1, 120, 180))
yFromRow(r, 90)
xyFromCell(r, 10000)
xyFromCell(r, c(0, 1, 32581, ncell(r), ncell(r)+1))

cellFromRowCol(r, 5, 5)
cellFromRowCol(r, 1:2, 1:2)
cellFromRowCol(r, 1, 1:3)

# all combinations
cellFromRowColCombine(r, 1:2, 1:2)

colFromX(r, 10)
rowFromY(r, 10)
xy <- cbind(lon=c(10,5), lat=c(15, 88))
cellFromXY(r, xy)

# if no row/col specified all are returned
range(xFromCol(r))
length(yFromRow(r))
```

## Description

Compute zonal statistics, that is summarize values of a `SpatRaster` for each "zone" defined by another `SpatRaster`.

If `fun` is a true R function, `zonal` may fail for very large `SpatRaster` objects, except for the functions ("mean", "min", "max", "sum", "isNA", and "notNA").

You can also summarize values of a `SpatVector` for each polygon (zone) defined by another `SpatVector`.

See [extract](#) to summarize values of a `SpatRaster` with a `SpatVector`.

## Usage

```
## S4 method for signature 'SpatRaster,SpatRaster'
zonal(x, z, fun=mean, ..., as.raster=FALSE, filename="", wopt=list())

## S4 method for signature 'SpatVector,SpatVector'
zonal(x, z, fun=mean, ..., weighted=FALSE, as.polygons=FALSE)
```

## Arguments

<code>x</code>	<code>SpatRaster</code> or <code>SpatVector</code>
<code>z</code>	Object of the same class as <code>x</code> . That is, either a <code>SpatRaster</code> with cell-values representing zones or a <code>SpatVector</code> with each polygon geometry representing a zone
<code>fun</code>	function to be applied to summarize the values by zone. Either as character: "mean", "min", "max", "sum", "isNA", and "notNA" and, for relatively small <code>SpatRasters</code> , a proper function
<code>...</code>	additional arguments passed to <code>fun</code>
<code>as.raster</code>	logical. If TRUE, a <code>SpatRaster</code> is returned with the zonal statistic for each zone
<code>filename</code>	character. Output filename (ignored if <code>as.raster=FALSE</code> )
<code>wopt</code>	list with additional arguments for writing files as in <a href="#">writeRaster</a>
<code>weighted</code>	logical. If TRUE, a <code>weighted.mean</code> is computed and <code>fun</code> is ignored. Weights are based on the length of the lines or the area of the polygons in <code>x</code> that intersect with <code>z</code> . This argument is ignored if <code>x</code> is a <code>SpatVector</code> or points
<code>as.polygons</code>	logical. Should the results be merged with the attributes of <code>z</code> ?

## Value

A data.frame with a value for each zone) or a `SpatRaster` or `SpatVector` of polygons

## See Also

See [global](#) for "global" statistics (i.e., all of `x` is considered a single zone), [app](#) for local statistics, and [extract](#) for summarizing values for polygons

## Examples

```

r <- rast(ncols=10, nrows=10)
values(r) <- 1:ncell(r)
z <- rast(r)
values(z) <- rep(c(1:2, NA, 3:4), each=20)
names(z) <- "zone"
zonal(r, z, "sum", na.rm=TRUE)

# multiple layers
r <- rast(system.file("ex/logo.tif", package = "terra"))
# zonal layer
z <- rast(r, 1)
names(z) <- "zone"
values(z) <- rep(c(1:2, NA, c(3:4)), each=ncell(r)/5, length.out=ncell(r))

zonal(r, z, "mean", na.rm = TRUE)

# raster of zonal values
zr <- zonal(r, z, "mean", na.rm = TRUE, as.raster=TRUE)

### SpatVector

f <- system.file("ex/lux.shp", package="terra")
v <- vect(f)[,c(2,4)]

p <- spatSample(v, 100)
values(p) <- data.frame(b2=1:100, ssep1=100:1)

zonal(p, v, mean)

```

---

zoom

*Zoom in on a map*


---

## Description

Zoom in on a map (plot) by providing a new extent, by default this is done by clicking twice on the map.

## Usage

```

## S4 method for signature 'SpatRaster'
zoom(x, e=draw(), maxcell=100000, layer=1, new=FALSE, ...)

## S4 method for signature 'SpatVector'
zoom(x, e=draw(), new=FALSE, ...)

```

**Arguments**

x	SpatRaster
e	SpatExtent
maxcell	positive integer. Maximum number of cells used for the map
layer	positive integer to select the layer to be used
new	logical. If TRUE, the zoomed in map will appear on a new device (window)
...	additional arguments passed to <a href="#">plot</a>

**Value**

SpatExtent (invisibly)

**See Also**

[draw](#), [plot](#)

# Index

- !, SpatRaster-method (Compare-methods), 57
- \* **classes**
  - options, 154
  - SpatExtent-class, 217
  - SpatRaster-class, 221
  - SpatVector-class, 224
- \* **math**
  - Arith-methods, 30
  - atan2, 36
  - Compare-methods, 57
  - Math-methods, 139
  - modal, 144
- \* **methods**
  - activeCat, 19
  - aggregate, 22
  - animate, 25
  - app, 26
  - Arith-methods, 30
  - as.data.frame, 32
  - as.list, 33
  - as.raster, 34
  - barplot, 38
  - boundaries, 39
  - cartogram, 44
  - catalyze, 44
  - cells, 45
  - cellSize, 47
  - colors, 54
  - combineGeoms, 55
  - Compare-methods, 57
  - concat, 59
  - contour, 60
  - convHull, 61
  - cover, 63
  - crosstab, 67
  - deepcopy, 69
  - densify, 70
  - diff, 74
  - disagg, 78
  - dots, 82
  - erase, 83
  - expanse, 85
  - extract, 89
  - extremes, 92
  - factors, 92
  - fillHoles, 94
  - fillTime, 95
  - focalValues, 106
  - gaps, 107
  - geomtype, 110
  - head and tail, 113
  - hist, 114
  - image, 116
  - impose, 117
  - inset, 120
  - intersect, 125
  - is.bool, 126
  - lapp, 129
  - lines, 133
  - makeTiles, 134
  - makeVRT, 135
  - mask, 137
  - match, 138
  - Math-methods, 139
  - merge, 141
  - mergeTime, 143
  - mosaic, 145
  - normalize.longitude, 151
  - not.na, 153
  - patches, 156
  - perim, 158
  - persp, 158
  - plet, 159
  - plot, 161
  - plotRGB, 165
  - predict, 167
  - quantile, 173

- query, 174
- rapp, 175
- rast, 177
- read and write, 185
- relate, 187
- replace\_layers, 192
- replace\_values, 193
- RGB, 196
- sapp, 199
- scatterplot, 202
- scoff, 203
- sds, 204
- selectRange, 208
- serialize, 209
- setValues, 210
- sharedPaths, 212
- simplifyGeom, 215
- sources, 216
- Spatial interpolation, 218
- split, 225
- sprc, 226
- summarize, 234
- summary, 236
- svc, 237
- symdif, 238
- tapp, 239
- text, 242
- topology, 246
- union, 249
- values, 254
- vect, 255
- vector\_layers, 258
- vrt, 261
- width, 265
- window, 266
- wrap, 267
- writeCDF, 268
- writeRaster, 269
- writeVector, 271
- \* **package**
  - terra-package, 6
- \* **spatial**
  - activeCat, 19
  - add, 20
  - adjacent, 20
  - aggregate, 22
  - align, 23
  - all.equal, 24
  - animate, 25
  - app, 26
  - approximate, 28
  - Arith-methods, 30
  - as.character, 31
  - as.data.frame, 32
  - as.list, 33
  - as.raster, 34
  - as.spatvector, 34
  - atan2, 36
  - autocorrelation, 37
  - barplot, 38
  - boundaries, 39
  - boxplot, 40
  - buffer, 41
  - c, 43
  - cartogram, 44
  - catalyze, 44
  - cells, 45
  - cellSize, 47
  - centroids, 48
  - clamp, 49
  - classify, 50
  - click, 52
  - coerce, 53
  - colors, 54
  - combineGeoms, 55
  - Compare-methods, 57
  - compareGeom, 58
  - concat, 59
  - contour, 60
  - convHull, 61
  - costDist, 62
  - cover, 63
  - crds, 64
  - crop, 65
  - crosstab, 67
  - crs, 68
  - deepcopy, 69
  - densify, 70
  - density, 71
  - depth, 72
  - describe, 73
  - diff, 74
  - dimensions, 75
  - direction, 77
  - disagg, 78
  - distance, 79



dots, 82  
draw, 83  
erase, 83  
expanse, 85  
ext, 86  
extend, 88  
extract, 89  
extremes, 92  
factors, 92  
fillHoles, 94  
fillTime, 95  
flip, 96  
focal, 97  
focal3D, 99  
focalCor, 101  
focalCpp, 102  
focalMat, 104  
focalReg, 105  
focalValues, 106  
freq, 106  
gaps, 107  
gdal, 108  
geom, 109  
geomtype, 110  
global, 111  
gridDistance, 112  
head and tail, 113  
hist, 114  
ifel, 115  
image, 116  
impose, 117  
initialize, 118  
inplace, 119  
inset, 120  
interpIDW, 122  
interpNear, 124  
intersect, 125  
is.bool, 126  
is.lonlat, 128  
lapp, 129  
linearUnits, 132  
lines, 133  
makeTiles, 134  
makeVRT, 135  
mask, 137  
match, 138  
Math-methods, 139  
mem, 140  
merge, 141  
mergeTime, 143  
mosaic, 145  
na.omit, 146  
NAflag, 147  
names, 148  
nearest, 150  
normalize.longitude, 151  
north, 151  
not.na, 153  
options, 154  
origin, 155  
pairs, 155  
patches, 156  
perim, 158  
persp, 158  
plet, 159  
plot, 161  
plotRGB, 165  
predict, 167  
project, 170  
quantile, 173  
query, 174  
rapp, 175  
rast, 177  
rasterize, 179  
rasterizeGeom, 181  
rasterizeWin, 182  
rcl, 184  
read and write, 185  
rectify, 187  
relate, 187  
rep, 190  
replace\_dollar, 191  
replace\_layers, 192  
replace\_values, 193  
resample, 194  
rescale, 195  
RGB, 196  
rotate, 197  
sapp, 199  
sbar, 200  
scale, 201  
scatterplot, 202  
scoff, 203  
sds, 204  
segregate, 205  
sel, 206

- selectHighest, 207
- selectRange, 208
- serialize, 209
- setValues, 210
- shade, 211
- sharedPaths, 212
- shift, 213
- sieve, 214
- simplifyGeom, 215
- sort, 216
- sources, 216
- SpatExtent-class, 217
- Spatial interpolation, 218
- SpatRaster-class, 221
- spatSample, 222
- SpatVector-class, 224
- spin, 224
- split, 225
- sprc, 226
- stretch, 227
- subset, 228
- subset\_dollar, 229
- subset\_double, 231
- subset\_single, 232
- subst, 233
- summarize, 234
- summary, 236
- svc, 237
- syndif, 238
- tapp, 239
- terra-package, 6
- terrain, 240
- text, 242
- tighten, 243
- time, 244
- tmpFiles, 245
- topology, 246
- transpose, 247
- trim, 248
- union, 249
- unique, 250
- units, 251
- update, 252
- valid, 253
- values, 254
- vect, 255
- vector\_layers, 258
- viewshed, 258
- voronoi, 260
- vrt, 261
- where, 263
- which.lyr, 264
- width, 265
- window, 266
- wrap, 267
- writeCDF, 268
- writeRaster, 269
- writeVector, 271
- xmin, 272
- xyRowColCell, 273
- zonal, 275
- zoom, 277
- \* univar**
  - freq, 106
  - modal, 144
- [, 15
- [(subset\_single), 232
- [,SpatExtent,missing,missing-method (subset\_single), 232
- [,SpatExtent,numeric,missing-method (subset\_single), 232
- [,SpatRaster,ANY,ANY,ANY-method (subset\_single), 232
- [,SpatRaster,ANY,ANY-method (subset\_single), 232
- [,SpatRaster,SpatExtent,missing-method (extract), 89
- [,SpatRaster,SpatRaster,missing-method (extract), 89
- [,SpatRaster,SpatVector,missing-method (extract), 89
- [,SpatRaster,data.frame,missing-method (extract), 89
- [,SpatRaster,matrix,missing-method (extract), 89
- [,SpatRaster,missing,missing-method (extract), 89
- [,SpatRaster,missing,numeric-method (extract), 89
- [,SpatRaster,numeric,missing-method (extract), 89
- [,SpatRaster,numeric,numeric-method (extract), 89
- [,SpatRasterCollection,numeric,missing-method (subset\_single), 232
- [,SpatRasterDataset,character,missing-method

- (subset\_single), 232
- [, SpatRasterDataset, logical, missing-method (subset\_single), 232
- [, SpatRasterDataset, numeric, missing-method (subset\_single), 232
- [, SpatRasterDataset, numeric, numeric-method (subset\_single), 232
- [, SpatVector, SpatExtent, missing-method (extract), 89
- [, SpatVector, SpatVector, missing-method (extract), 89
- [, SpatVector, data.frame, missing-method (subset\_single), 232
- [, SpatVector, logical, character-method (subset\_single), 232
- [, SpatVector, logical, logical-method (subset\_single), 232
- [, SpatVector, logical, missing-method (subset\_single), 232
- [, SpatVector, logical, numeric-method (subset\_single), 232
- [, SpatVector, matrix, missing-method (subset\_single), 232
- [, SpatVector, missing, character-method (subset\_single), 232
- [, SpatVector, missing, logical-method (subset\_single), 232
- [, SpatVector, missing, missing-method (subset\_single), 232
- [, SpatVector, missing, numeric-method (subset\_single), 232
- [, SpatVector, numeric, character-method (subset\_single), 232
- [, SpatVector, numeric, logical-method (subset\_single), 232
- [, SpatVector, numeric, missing-method (subset\_single), 232
- [, SpatVector, numeric, numeric-method (subset\_single), 232
- [, SpatVectorCollection, numeric, missing-method (svc), 237
- [<- (replace\_values), 193
- [<-, SpatExtent, numeric, missing-method (replace\_values), 193
- [<-, SpatRaster, ANY, ANY, ANY-method (replace\_values), 193
- [<-, SpatRaster, ANY, ANY-method (replace\_values), 193
- [<-, SpatRasterDataset, numeric, missing-method (sds), 204
- [<-, SpatVector, ANY, ANY-method (replace\_values), 193
- [<-, SpatVector, ANY, missing-method (replace\_values), 193
- [<-, SpatVector, missing, ANY-method (replace\_values), 193
- [<-, SpatVectorCollection, numeric, missing-method (svc), 237
- [[ (subset\_double), 231
- [[, SpatRaster, ANY, missing-method (subset\_double), 231
- [[, SpatRaster, character, missing-method (subset\_double), 231
- [[, SpatRaster, logical, missing-method (subset\_double), 231
- [[, SpatRaster, numeric, missing-method (subset\_double), 231
- [[, SpatRasterDataset, ANY, ANY-method (subset\_double), 231
- [[, SpatVector, character, missing-method (subset\_double), 231
- [[, SpatVector, logical, missing-method (subset\_double), 231
- [[, SpatVector, numeric, missing-method (subset\_double), 231
- [[, SpatVectorCollection, numeric, missing-method (svc), 237
- [[<- (replace\_layers), 192
- [[<-, SpatRaster, character-method (replace\_layers), 192
- [[<-, SpatRaster, numeric-method (replace\_layers), 192
- [[<-, SpatVector, character-method (replace\_layers), 192
- [[<-, SpatVector, numeric-method (replace\_layers), 192
- \$, 191
- \$(subset\_dollar), 229
- \$.SpatExtent-method (subset\_dollar), 229
- \$.SpatRaster-method (subset\_dollar), 229
- \$.SpatRasterDataset-method (subset\_dollar), 229
- \$.SpatVector-method (subset\_dollar), 229
- \$<- (replace\_dollar), 191
- \$<-, SpatExtent-method (replace\_dollar), 191

- \$<- , SpatRaster-method (replace\_dollar), 191
- \$<- , SpatVector-method (replace\_dollar), 191
- %in% (match), 138
- %in%, SpatRaster-method (match), 138
- activeCat, 11, 19, 45, 94
- activeCat, SpatRaster-method (activeCat), 19
- activeCat<- (activeCat), 19
- activeCat<- , SpatRaster-method (activeCat), 19
- add, 20
- add<- , 7, 17
- add<- (add), 20
- add<- , SpatRaster, SpatRaster-method (add), 20
- adjacent, 9, 13, 20, 150, 188
- adjacent, SpatRaster-method (adjacent), 20
- adjacent, SpatVector-method (adjacent), 20
- aggregate, 7, 14, 22, 78, 194, 195, 239, 249
- aggregate, SpatRaster-method (aggregate), 22
- aggregate, SpatVector-method (aggregate), 22
- align, 15, 23
- align, SpatExtent, numeric-method (align), 23
- align, SpatExtent, SpatRaster-method (align), 23
- all (summarize), 234
- all, SpatRaster-method (summarize), 234
- all.equal, 24, 57
- all.equal, SpatRaster, SpatRaster-method (all.equal), 24
- allNA (summarize), 234
- allNA, SpatRaster-method (summarize), 234
- animate, 25
- animate, SpatRaster-method (animate), 25
- any (summarize), 234
- any, SpatRaster-method (summarize), 234
- anyNA (summarize), 234
- anyNA, SpatRaster-method (summarize), 234
- app, 8, 17, 26, 30, 57, 112, 129, 130, 138, 140, 173, 175, 176, 199, 234, 236, 239, 240, 276
- app, SpatRaster-method (app), 26
- app, SpatRasterDataset-method (app), 26
- apply, 26
- approx, 28, 29
- approximate, 8, 17, 28, 95, 96
- approximate, SpatRaster-method (approximate), 28
- area (deprecated), 72
- area, SpatRaster-method (deprecated), 72
- Arith, logical, SpatRaster-method (Arith-methods), 30
- Arith, missing, SpatRaster-method (Arith-methods), 30
- Arith, numeric, SpatExtent-method (Arith-methods), 30
- Arith, numeric, SpatRaster-method (Arith-methods), 30
- Arith, SpatExtent, numeric-method (Arith-methods), 30
- Arith, SpatExtent, SpatExtent-method (Arith-methods), 30
- Arith, SpatRaster, logical-method (Arith-methods), 30
- Arith, SpatRaster, missing-method (Arith-methods), 30
- Arith, SpatRaster, numeric-method (Arith-methods), 30
- Arith, SpatRaster, SpatRaster-method (Arith-methods), 30
- Arith, SpatVector, SpatVector-method (Arith-methods), 30
- Arith-methods, 8, 30, 57
- arrows, 134
- as.array, 10
- as.array (coerce), 53
- as.array, SpatRaster-method (coerce), 53
- as.bool, 8
- as.bool (is.bool), 126
- as.bool, SpatRaster-method (is.bool), 126
- as.character, 31
- as.character, SpatExtent-method (as.character), 31
- as.character, SpatRaster-method (as.character), 31
- as.contour, 16
- as.contour (contour), 60
- as.contour, SpatRaster-method (contour), 60

- as.data.frame, [14](#), [32](#), [54](#), [254](#)
- as.data.frame, SpatRaster-method  
(as.data.frame), [32](#)
- as.data.frame, SpatVector-method  
(as.data.frame), [32](#)
- as.factor, [11](#), [94](#)
- as.factor (is.bool), [126](#)
- as.factor, SpatRaster-method (is.bool),  
[126](#)
- as.int, [8](#)
- as.int (is.bool), [126](#)
- as.int, SpatRaster-method (is.bool), [126](#)
- as.integer, SpatRaster-method (is.bool),  
[126](#)
- as.lines, [16](#)
- as.lines (as.spatvector), [34](#)
- as.lines, SpatExtent-method  
(as.spatvector), [34](#)
- as.lines, SpatRaster-method  
(as.spatvector), [34](#)
- as.lines, SpatVector-method  
(as.spatvector), [34](#)
- as.list, [14](#), [32](#), [33](#)
- as.list, SpatRaster-method (as.list), [33](#)
- as.list, SpatRasterCollection-method  
(as.list), [33](#)
- as.list, SpatRasterDataset-method  
(as.list), [33](#)
- as.list, SpatVector-method (as.list), [33](#)
- as.logical, SpatRaster-method (is.bool),  
[126](#)
- as.matrix, [10](#), [32](#), [254](#)
- as.matrix (coerce), [53](#)
- as.matrix, SpatRaster-method (coerce), [53](#)
- as.numeric, [11](#)
- as.numeric (catalyze), [44](#)
- as.numeric, SpatRaster-method  
(catalyze), [44](#)
- as.points, [16](#), [18](#)
- as.points (as.spatvector), [34](#)
- as.points, SpatExtent-method  
(as.spatvector), [34](#)
- as.points, SpatRaster-method  
(as.spatvector), [34](#)
- as.points, SpatVector-method  
(as.spatvector), [34](#)
- as.polygons, [16](#), [18](#), [54](#)
- as.polygons (as.spatvector), [34](#)
- as.polygons, SpatExtent-method  
(as.spatvector), [34](#)
- as.polygons, SpatRaster-method  
(as.spatvector), [34](#)
- as.polygons, SpatVector-method  
(as.spatvector), [34](#)
- as.raster, [34](#), [34](#)
- as.raster, SpatRaster-method  
(as.raster), [34](#)
- as.spatvector, [34](#)
- as.vector (coerce), [53](#)
- as.vector, SpatRaster-method (coerce), [53](#)
- atan2, [36](#)
- atan2, SpatRaster, SpatRaster-method  
(atan2), [36](#)
- atan\_2 (atan2), [36](#)
- atan\_2, SpatRaster, SpatRaster-method  
(atan2), [36](#)
- autocor, [9](#)
- autocor (autocorrelation), [37](#)
- autocor, numeric-method  
(autocorrelation), [37](#)
- autocor, SpatRaster-method  
(autocorrelation), [37](#)
- autocorrelation, [37](#)
- axis, [162](#)
- barplot, [17](#), [38](#), [39](#)
- barplot, SpatRaster-method (barplot), [38](#)
- blocks (read and write), [185](#)
- blocks, SpatRaster-method (read and  
write), [185](#)
- boundaries, [9](#), [39](#), [157](#)
- boundaries, SpatRaster-method  
(boundaries), [39](#)
- boxplot, [17](#), [39](#), [40](#), [41](#), [115](#), [156](#)
- boxplot, SpatRaster-method (boxplot), [40](#)
- buffer, [14](#), [41](#), [125](#)
- buffer, SpatRaster-method (buffer), [41](#)
- buffer, SpatVector-method (buffer), [41](#)
- bxp, [41](#)
- c, [7](#), [17](#), [20](#), [43](#), [143](#), [249](#)
- c, SpatRaster-method (c), [43](#)
- c, SpatRasterDataset-method (c), [43](#)
- c, SpatVector-method (c), [43](#)
- c, SpatVectorCollection-method (c), [43](#)
- cartogram, [16](#), [44](#), [82](#)

- cartogram, SpatVector-method
  - (cartogram), 44
- catalyze, 11, 19, 44, 94
- catalyze, SpatRaster-method (catalyze), 44
- categories, 119
- categories (factors), 92
- categories, SpatRaster-method (factors), 92
- cats, 11, 19, 45, 59, 126, 127
- cats (factors), 92
- cats, SpatRaster-method (factors), 92
- cellFromRowCol, 11, 185
- cellFromRowCol (xyRowColCell), 273
- cellFromRowCol, SpatRaster, numeric, numeric-method (xyRowColCell), 273
- cellFromRowColCombine, 11
- cellFromRowColCombine (xyRowColCell), 273
- cellFromRowColCombine, SpatRaster, numeric, numeric-method (xyRowColCell), 273
- cellFromXY, 11
- cellFromXY (xyRowColCell), 273
- cellFromXY, SpatRaster, data.frame-method (xyRowColCell), 273
- cellFromXY, SpatRaster, matrix-method (xyRowColCell), 273
- cells, 11, 17, 45, 90
- cells, SpatRaster, missing-method (cells), 45
- cells, SpatRaster, numeric-method (cells), 45
- cells, SpatRaster, SpatExtent-method (cells), 45
- cells, SpatRaster, SpatVector-method (cells), 45
- cellSize, 8, 17, 47, 86
- cellSize, SpatRaster-method (cellSize), 47
- centroids, 13, 48
- centroids, SpatVector-method (centroids), 48
- clamp, 49
- clamp, numeric-method (clamp), 49
- clamp, SpatRaster-method (clamp), 49
- classify, 8, 18, 49, 50, 115, 141, 147, 193, 233, 234
- classify, SpatRaster-method (classify), 50
- clearance, 14
- clearance (width), 265
- clearance, SpatVector-method (width), 265
- click, 14, 16, 52, 83, 206
- click, missing-method (click), 52
- click, SpatRaster-method (click), 52
- click, SpatVector-method (click), 52
- coerce, 33, 53
- colFromCell (xyRowColCell), 273
- colFromCell, SpatRaster, numeric-method (xyRowColCell), 273
- colFromX, 11
- colFromX (xyRowColCell), 273
- colFromX, SpatRaster, numeric-method (xyRowColCell), 273
- colorize, 16, 166, 167
- colorize (RGB), 196
- colorize, SpatRaster-method (RGB), 196
- colors, 54
- coltab (colors), 54
- coltab, SpatRaster-method (colors), 54
- coltab<- (colors), 54
- coltab<-, SpatRaster-method (colors), 54
- combineGeoms, 15, 55
- combineGeoms, SpatVector, SpatVector-method (combineGeoms), 55
- Compare, numeric, SpatRaster-method (Compare-methods), 57
- Compare, SpatExtent, SpatExtent-method (Compare-methods), 57
- Compare, SpatRaster, character-method (Compare-methods), 57
- Compare, SpatRaster, numeric-method (Compare-methods), 57
- Compare, SpatRaster, SpatRaster-method (Compare-methods), 57
- Compare-methods, 8, 57
- compareGeom, 10, 17, 25, 58
- compareGeom, SpatRaster, SpatRaster-method (compareGeom), 58
- compareGeom, SpatVector, missing-method (compareGeom), 58
- compareGeom, SpatVector, SpatVector-method (compareGeom), 58
- concat, 11, 59
- concat, SpatRaster-method (concat), 59
- contour, 16, 60, 60

- contour, SpatRaster-method (contour), 60
- convHull, 13, 61
- convHull, SpatVector-method (convHull), 61
- cor, 156
- costDist, 62, 113
- costDist, SpatRaster-method (costDist), 62
- costDistance, 9
- costDistance (costDist), 62
- costDistance, SpatRaster-method (costDist), 62
- cov.wt, 132
- cover, 8, 14, 63, 115
- cover, SpatRaster, SpatRaster-method (cover), 63
- cover, SpatVector, SpatVector-method (cover), 63
- cppFunction, 102
- crds, 13, 17, 64, 110, 275
- crds, SpatRaster-method (crds), 64
- crds, SpatVector-method (crds), 64
- crop, 7, 14, 15, 65, 84, 88, 125, 126, 137, 188, 194, 195, 206, 249, 266
- crop, SpatRaster-method (crop), 65
- crop, SpatRasterCollection-method (crop), 65
- crop, SpatRasterDataset-method (crop), 65
- crop, SpatVector-method (crop), 65
- crosstab, 8, 67
- crosstab, SpatRaster, missing-method (crosstab), 67
- crs, 10, 13, 36, 68, 133, 171, 172, 178, 223, 256
- crs, sf-method (crs), 68
- crs, SpatRaster-method (crs), 68
- crs, SpatRasterDataset-method (crs), 68
- crs, SpatVector-method (crs), 68
- crs, SpatVectorProxy-method (crs), 68
- crs<- (crs), 68
- crs<-, SpatRaster, ANY-method (crs), 68
- crs<-, SpatRaster-method (crs), 68
- crs<-, SpatVector, ANY-method (crs), 68
- crs<-, SpatVector-method (crs), 68
- cumsum (Math-methods), 139
- cumsum, SpatRaster-method (Math-methods), 139
- cut, 39
- data.frame, 32, 186, 254
- datatype (geomtype), 110
- datatype, SpatRaster-method (geomtype), 110
- datatype, SpatVector-method (geomtype), 110
- Date, 244
- deepcopy, 69
- deepcopy, SpatRaster-method (deepcopy), 69
- deepcopy, SpatVector-method (deepcopy), 69
- delaunay, 13
- delaunay (voronoi), 260
- delaunay, SpatVector-method (voronoi), 260
- deldir, 260
- densify, 70
- densify, SpatVector-method (densify), 70
- density, 17, 71
- density, SpatRaster-method (density), 71
- deprecated, 72
- depth, 72, 244
- depth, SpatRaster-method (depth), 72
- depth<- (depth), 72
- depth<-, SpatRaster-method (depth), 72
- describe, 73, 109, 204
- describe, character-method (describe), 73
- diff, 74
- diff, SpatRaster-method (diff), 74
- dim (dimensions), 75
- dim, SpatRaster-method (dimensions), 75
- dim, SpatRasterCollection-method (dimensions), 75
- dim, SpatRasterDataset-method (dimensions), 75
- dim, SpatVector-method (dimensions), 75
- dim, SpatVectorProxy-method (dimensions), 75
- dim<-, SpatRaster-method (dimensions), 75
- dimensions, 75
- direction, 9, 77
- direction, SpatRaster-method (direction), 77
- disagg, 7, 14, 17, 23, 65, 78, 194, 195
- disagg, SpatRaster-method (disagg), 78
- disagg, SpatVector-method (disagg), 78
- distance, 9, 17, 42, 62, 77, 79, 113



- distance, matrix, matrix-method (distance), 79
- distance, matrix, missing-method (distance), 79
- distance, SpatRaster, missing-method (distance), 79
- distance, SpatRaster, sf-method (distance), 79
- distance, SpatRaster, SpatVector-method (distance), 79
- distance, SpatVector, ANY-method (distance), 79
- distance, SpatVector, SpatVector-method (distance), 79
- dots, 16, 82
- dots, SpatVector-method (dots), 82
- draw, 15–17, 24, 53, 83, 166, 278
- draw, character-method (draw), 83
- draw, missing-method (draw), 83
- droplevels (factors), 92
- droplevels, SpatRaster-method (factors), 92
  
- emptyGeoms (topology), 246
- emptyGeoms, SpatVector-method (topology), 246
- erase, 14, 15, 56, 83, 238
- erase, SpatVector, missing-method (erase), 83
- erase, SpatVector, SpatExtent-method (erase), 83
- erase, SpatVector, SpatVector-method (erase), 83
- expanse, 8, 13, 17, 48, 85
- expanse, SpatRaster-method (expanse), 85
- expanse, SpatVector-method (expanse), 85
- ext, 10, 13, 15, 17, 24, 66, 76, 86, 88, 218
- ext, bbox-method (ext), 86
- ext, Extent-method (ext), 86
- ext, matrix-method (ext), 86
- ext, missing-method (ext), 86
- ext, numeric-method (ext), 86
- ext, Raster-method (ext), 86
- ext, sf-method (ext), 86
- ext, SpatExtent-method (ext), 86
- ext, Spatial-method (ext), 86
- ext, SpatRaster-method (ext), 86
- ext, SpatRasterCollection-method (ext), 86
- ext, SpatRasterDataset-method (ext), 86
- ext, SpatVector-method (ext), 86
- ext, SpatVectorProxy-method (ext), 86
- ext<- (ext), 86
- ext<-, SpatRaster, numeric-method (ext), 86
- ext<-, SpatRaster, SpatExtent-method (ext), 86
- extend, 7, 65, 66, 88, 194, 249, 266
- extend, SpatExtent-method (extend), 88
- extend, SpatRaster-method (extend), 88
- extract, 10, 14, 18, 89, 112, 208, 276
- extract, SpatRaster, data.frame-method (extract), 89
- extract, SpatRaster, matrix-method (extract), 89
- extract, SpatRaster, numeric-method (extract), 89
- extract, SpatRaster, sf-method (extract), 89
- extract, SpatRaster, SpatExtent-method (extract), 89
- extract, SpatRaster, SpatVector-method (extract), 89
- extract, SpatVector, data.frame-method (extract), 89
- extract, SpatVector, matrix-method (extract), 89
- extract, SpatVector, SpatVector-method (extract), 89
- extremes, 92
  
- factor, 93
- factors, 92
- fileBlocksize (read and write), 185
- filled.contour, 60
- fillHoles, 13, 15, 94, 108
- fillHoles, SpatVector-method (fillHoles), 94
- fillTime, 11, 29, 95, 143
- fillTime, SpatRaster-method (fillTime), 95
- flip, 7, 14, 96, 196, 213, 248
- flip, SpatRaster-method (flip), 96
- flip, SpatVector-method (flip), 96
- focal, 9, 28, 29, 40, 97, 99–105, 112, 157, 214, 241
- focal, SpatRaster-method (focal), 97
- focal3D, 98, 99



- focal3D, SpatRaster-method (focal3D), 99
- focalCor, 9, 17, 98, 101
- focalCor, SpatRaster-method (focalCor), 101
- focalCpp, 9, 98, 102
- focalCpp, SpatRaster-method (focalCpp), 102
- focalMat, 98, 104
- focalReg, 9, 98, 101, 105
- focalReg, SpatRaster-method (focalReg), 105
- focalValues, 98, 103, 105, 106, 255
- focalValues, SpatRaster-method (focalValues), 106
- free\_RAM (mem), 140
- freq, 8, 67, 106
- freq, SpatRaster-method (freq), 106
- gaps, 15, 107, 212, 215, 247
- gaps, SpatVector, SpatExtent-method (gaps), 107
- gaps, SpatVector-method (gaps), 107
- gdal, 108, 179
- gdalCache (gdal), 108
- geom, 13, 32, 33, 65, 109, 114, 255, 256
- geom, SpatVector-method (geom), 109
- geomtype, 110
- geomtype, Spatial-method (geomtype), 110
- geomtype, SpatVector-method (geomtype), 110
- geomtype, SpatVectorProxy-method (geomtype), 110
- getGDALconfig (gdal), 108
- global, 8, 17, 86, 111, 132, 173, 236, 237, 276
- global, SpatRaster-method (global), 111
- gridDist, 62
- gridDist (gridDistance), 112
- gridDist, SpatRaster-method (gridDistance), 112
- gridDistance, 9, 112
- gridDistance, SpatRaster-method (gridDistance), 112
- has.colors (colors), 54
- has.colors, SpatRaster-method (colors), 54
- has.RGB (RGB), 196
- has.RGB, SpatRaster-method (RGB), 196
- hasMinMax (extremes), 92
- hasMinMax, SpatRaster-method (extremes), 92
- hasValues (sources), 216
- hasValues, SpatRaster-method (sources), 216
- head (head and tail), 113
- head and tail, 113
- head, SpatRaster-method (head and tail), 113
- head, SpatVector-method (head and tail), 113
- hist, 17, 39, 41, 114, 114, 156
- hist, SpatRaster-method (hist), 114
- ifel, 30, 57, 115
- ifel, SpatRaster-method (ifel), 115
- ifelse, 115
- image, 16, 116, 116, 164
- image, SpatRaster-method (image), 116
- impose, 117
- impose, SpatRasterCollection-method (impose), 117
- inext (inset), 120
- inext, SpatVector-method (inset), 120
- init, 8, 210, 211
- init (initialize), 118
- init, SpatRaster-method (initialize), 118
- initialize, 118
- inMemory, 10, 12
- inMemory (sources), 216
- inMemory, SpatRaster-method (sources), 216
- inplace, 119
- inset, 16, 120, 152, 195, 196, 200
- inset, SpatRaster-method (inset), 120
- inset, SpatVector-method (inset), 120
- interpIDW, 122, 124, 184
- interpIDW, SpatRaster, matrix-method (interpIDW), 122
- interpIDW, SpatRaster, SpatVector-method (interpIDW), 122
- interpNear, 123, 124, 184
- interpNear, SpatRaster, matrix-method (interpNear), 124
- interpNear, SpatRaster, SpatVector-method (interpNear), 124
- interpolate, 9, 123, 124
- interpolate (Spatial interpolation), 218

- interpolate, SpatRaster-method (Spatial interpolation), 218
- intersect, 14, 15, 56, 65, 66, 84, 125, 188, 206, 249
- intersect, SpatExtent, SpatExtent-method (intersect), 125
- intersect, SpatExtent, SpatVector-method (intersect), 125
- intersect, SpatRaster, SpatRaster-method (intersect), 125
- intersect, SpatVector, SpatExtent-method (intersect), 125
- intersect, SpatVector, SpatVector-method (intersect), 125
- is.bool, 126
- is.bool, SpatRaster-method (is.bool), 126
- is.factor, 11, 94
- is.factor (is.bool), 126
- is.factor, SpatRaster-method (is.bool), 126
- is.finite, SpatRaster-method (Compare-methods), 57
- is.infinite, SpatRaster-method (Compare-methods), 57
- is.int (is.bool), 126
- is.int, SpatRaster-method (is.bool), 126
- is.lines (geomtype), 110
- is.lines, SpatVector-method (geomtype), 110
- is.lonlat, 10, 13, 17, 128
- is.lonlat, SpatRaster-method (is.lonlat), 128
- is.lonlat, SpatVector-method (is.lonlat), 128
- is.na, SpatRaster-method (Compare-methods), 57
- is.nan, SpatRaster-method (Compare-methods), 57
- is.points (geomtype), 110
- is.points, SpatVector-method (geomtype), 110
- is.polygons (geomtype), 110
- is.polygons, SpatVector-method (geomtype), 110
- is.related (relate), 187
- is.related, SpatExtent, SpatRaster-method (relate), 187
- is.related, SpatExtent, SpatVector-method (relate), 187
- is.related, SpatRaster, SpatExtent-method (relate), 187
- is.related, SpatRaster, SpatRaster-method (relate), 187
- is.related, SpatRaster, SpatVector-method (relate), 187
- is.related, SpatVector, SpatExtent-method (relate), 187
- is.related, SpatVector, SpatRaster-method (relate), 187
- is.related, SpatVector, SpatVector-method (relate), 187
- is.valid, 15
- is.valid (valid), 253
- is.valid, SpatVector-method (valid), 253
- isFALSE, SpatRaster-method (is.bool), 126
- isTRUE, 264
- isTRUE, SpatRaster-method (is.bool), 126
- lapp, 8, 18, 27, 129, 176, 199
- lapp, SpatRaster-method (lapp), 129
- lapp, SpatRasterDataset-method (lapp), 129
- lapply, 199
- layerCor, 8, 17, 101, 131
- layerCor, SpatRaster-method (layerCor), 131
- legend, 162
- length, 15
- length (dimensions), 75
- length, SpatRasterCollection-method (dimensions), 75
- length, SpatRasterDataset-method (dimensions), 75
- length, SpatVector-method (dimensions), 75
- length, SpatVectorCollection-method (dimensions), 75
- levels, 11, 126, 127
- levels (factors), 92
- levels, SpatRaster-method (factors), 92
- levels<- (factors), 92
- levels<- , SpatRaster-method (factors), 92
- linearUnits, 13, 132
- linearUnits, SpatRaster-method (linearUnits), 132
- linearUnits, SpatVector-method (linearUnits), 132

- lines, [16](#), [133](#), [161](#), [163](#), [164](#)
- lines, leaflet-method (plet), [159](#)
- lines, SpatExtent-method (lines), [133](#)
- lines, SpatRaster-method (lines), [133](#)
- lines, SpatVector-method (lines), [133](#)
- log (Math-methods), [139](#)
- log, SpatRaster-method (Math-methods), [139](#)
- Logic, logical, SpatRaster-method (Compare-methods), [57](#)
- Logic, numeric, SpatRaster-method (Compare-methods), [57](#)
- Logic, SpatRaster, logical-method (Compare-methods), [57](#)
- Logic, SpatRaster, numeric-method (Compare-methods), [57](#)
- Logic, SpatRaster, SpatRaster-method (Compare-methods), [57](#)
- Logic-methods, [8](#)
- Logic-methods (Compare-methods), [57](#)
- longnames (names), [148](#)
- longnames, SpatRaster-method (names), [148](#)
- longnames, SpatRasterDataset-method (names), [148](#)
- longnames<- (names), [148](#)
- longnames<-, SpatRaster-method (names), [148](#)
- longnames<-, SpatRasterDataset-method (names), [148](#)
- make.unique, [149](#)
- makeNodes, [15](#)
- makeNodes (topology), [246](#)
- makeNodes, SpatVector-method (topology), [246](#)
- makeTiles, [134](#), [261](#)
- makeTiles, SpatRaster-method (makeTiles), [134](#)
- makeValid, [15](#)
- makeValid (valid), [253](#)
- makeValid, SpatVector-method (valid), [253](#)
- makeVRT, [135](#), [261](#)
- mask, [8](#), [65](#), [84](#), [115](#), [137](#), [181](#)
- mask, SpatRaster, sf-method (mask), [137](#)
- mask, SpatRaster, SpatRaster-method (mask), [137](#)
- mask, SpatRaster, SpatVector-method (mask), [137](#)
- mask, SpatVector, sf-method (mask), [137](#)
- mask, SpatVector, SpatVector-method (mask), [137](#)
- match, [138](#), [138](#)
- match, SpatRaster-method (match), [138](#)
- math, [130](#)
- math (Math-methods), [139](#)
- Math, SpatExtent-method (Math-methods), [139](#)
- Math, SpatRaster-method (Math-methods), [139](#)
- math, SpatRaster-method (Math-methods), [139](#)
- Math-methods, [8](#), [15](#), [139](#)
- Math2, SpatExtent-method (Math-methods), [139](#)
- Math2, SpatRaster-method (Math-methods), [139](#)
- Math2, SpatVector-method (Math-methods), [139](#)
- Math2-methods (Math-methods), [139](#)
- max (summarize), [234](#)
- max, SpatRaster-method (summarize), [234](#)
- mean (summarize), [234](#)
- mean, SpatExtent-method (summarize), [234](#)
- mean, SpatRaster-method (summarize), [234](#)
- mean, SpatVector-method (summarize), [234](#)
- median (summarize), [234](#)
- median, SpatRaster-method (summarize), [234](#)
- median, SpatVector-method (summarize), [234](#)
- mem, [140](#)
- mem\_info, [12](#), [154](#), [270](#)
- mem\_info (mem), [140](#)
- merge, [7](#), [14](#), [88](#), [141](#), [142](#), [145](#), [226](#), [249](#)
- merge, SpatExtent, SpatExtent-method (merge), [141](#)
- merge, SpatRaster, SpatRaster-method (merge), [141](#)
- merge, SpatRasterCollection, missing-method (merge), [141](#)
- merge, SpatVector, data.frame-method (merge), [141](#)
- merge, SpatVector, SpatVector-method (merge), [141](#)
- mergeLines, [15](#)
- mergeLines (topology), [246](#)
- mergeLines, SpatVector-method

- (topology), 246
- mergeTime, 11, 143
- mergeTime, SpatRasterDataset-method (mergeTime), 143
- min (summarize), 234
- min, SpatRaster-method (summarize), 234
- minmax, 10
- minmax (extremes), 92
- minmax, SpatRaster-method (extremes), 92
- minRect, 265
- minRect (convHull), 61
- minRect, SpatVector-method (convHull), 61
- modal, 144, 234, 236
- modal, SpatRaster-method (modal), 144
- mosaic, 7, 142, 145, 226, 249
- mosaic, SpatRaster, SpatRaster-method (mosaic), 145
- mosaic, SpatRasterCollection, missing-method (mosaic), 145
- na.omit, 13, 146
- na.omit, SpatVector-method (na.omit), 146
- NAflag, 10, 18, 147
- NAflag, SpatRaster-method (NAflag), 147
- NAflag<- (NAflag), 147
- NAflag<-, SpatRaster-method (NAflag), 147
- name (names), 148
- name<- (names), 148
- names, 10, 12, 13, 114, 148, 167, 252
- names, SpatRaster-method (names), 148
- names, SpatRasterCollection-method (names), 148
- names, SpatRasterDataset-method (names), 148
- names, SpatVector-method (names), 148
- names, SpatVectorCollection-method (names), 148
- names, SpatVectorProxy-method (names), 148
- names<- (names), 148
- names<-, SpatRaster-method (names), 148
- names<-, SpatRasterCollection-method (names), 148
- names<-, SpatRasterDataset-method (names), 148
- names<-, SpatVector-method (names), 148
- names<-, SpatVectorCollection-method (names), 148
- ncell, 10, 275
- ncell (dimensions), 75
- ncell, ANY-method (dimensions), 75
- ncell, SpatRaster-method (dimensions), 75
- ncell, SpatRasterDataset-method (dimensions), 75
- ncol, 10, 13
- ncol (dimensions), 75
- ncol, SpatRaster-method (dimensions), 75
- ncol, SpatRasterCollection-method (dimensions), 75
- ncol, SpatRasterDataset-method (dimensions), 75
- ncol, SpatVector-method (dimensions), 75
- ncol<- (dimensions), 75
- ncol<-, SpatRaster, numeric-method (dimensions), 75
- ncvar\_def, 268
- nearby, 13, 21, 188
- nearby (nearest), 150
- nearby, SpatVector-method (nearest), 150
- nearest, 13, 150
- nearest, SpatVector-method (nearest), 150
- nlyr, 10, 18
- nlyr (dimensions), 75
- nlyr, SpatRaster-method (dimensions), 75
- nlyr, SpatRasterCollection-method (dimensions), 75
- nlyr, SpatRasterDataset-method (dimensions), 75
- nlyr<- (dimensions), 75
- nlyr<-, SpatRaster, numeric-method (dimensions), 75
- normalize.longitude, 151, 198
- normalize.longitude, SpatVector-method (normalize.longitude), 151
- north, 16, 151, 164, 200
- not.na, 153
- not.na, SpatRaster-method (not.na), 153
- nrow, 10, 13
- nrow (dimensions), 75
- nrow, SpatRaster-method (dimensions), 75
- nrow, SpatRasterCollection-method (dimensions), 75
- nrow, SpatRasterDataset-method (dimensions), 75
- nrow, SpatVector-method (dimensions), 75
- nrow<- (dimensions), 75
- nrow<-, SpatRaster, numeric-method

- (dimensions), [75](#)
- nsrsrc (dimensions), [75](#)
- nsrsrc, SpatRaster-method (dimensions), [75](#)
- options, [154](#)
- origin, [10](#), [155](#)
- origin, SpatRaster-method (origin), [155](#)
- origin<- (origin), [155](#)
- origin<- , SpatRaster-method (origin), [155](#)
- PackedSpatRaster-class
  - (SpatRaster-class), [221](#)
- PackedSpatVector-class
  - (SpatVector-class), [224](#)
- pairs, [17](#), [41](#), [115](#), [155](#), [155](#)
- pairs, SpatRaster-method (pairs), [155](#)
- par, [134](#), [160](#)
- patches, [9](#), [17](#), [40](#), [156](#)
- patches, SpatRaster-method (patches), [156](#)
- perim, [13](#), [158](#)
- perim, SpatVector-method (perim), [158](#)
- perimeter (perim), [158](#)
- perimeter, SpatVector-method (perim), [158](#)
- persp, [16](#), [158](#), [159](#)
- persp, SpatRaster-method (persp), [158](#)
- plet, [159](#)
- plet, missing-method (plet), [159](#)
- plet, SpatRaster-method (plet), [159](#)
- plet, SpatVector-method (plet), [159](#)
- plet, SpatVectorCollection-method (plet), [159](#)
- plot, [16](#), [17](#), [26](#), [44](#), [60](#), [71](#), [82](#), [116](#), [117](#), [152](#), [160](#), [161](#), [164](#), [166](#), [167](#), [196](#), [200](#), [243](#), [278](#)
- plot, SpatExtent, missing-method (plot), [161](#)
- plot, SpatRaster, character-method (plot), [161](#)
- plot, SpatRaster, missing-method (plot), [161](#)
- plot, SpatRaster, numeric-method (plot), [161](#)
- plot, SpatRaster, SpatRaster-method (scatterplot), [202](#)
- plot, SpatVector, character-method (plot), [161](#)
- plot, SpatVector, data.frame-method (plot), [161](#)
- plot, SpatVector, missing-method (plot), [161](#)
- plot, SpatVector, numeric-method (plot), [161](#)
- plot, SpatVectorProxy, missing-method (plot), [161](#)
- plotRGB, [16](#), [165](#), [196](#)
- plotRGB, SpatRaster-method (plotRGB), [165](#)
- points, [16](#), [82](#), [134](#), [164](#)
- points (lines), [133](#)
- points, leaflet-method (plet), [159](#)
- points, SpatExtent-method (lines), [133](#)
- points, SpatVector-method (lines), [133](#)
- polys, [16](#), [164](#)
- polys (lines), [133](#)
- polys, SpatExtent-method (lines), [133](#)
- polys, SpatVector-method (lines), [133](#)
- POSIXlt, [244](#)
- predict, [9](#), [51](#), [167](#), [218](#), [219](#)
- predict, SpatRaster-method (predict), [167](#)
- prod (summarize), [234](#)
- prod, SpatRaster-method (summarize), [234](#)
- project, [7](#), [10](#), [13](#), [18](#), [68](#), [158](#), [170](#), [194](#), [195](#)
- project, matrix-method (project), [170](#)
- project, SpatExtent-method (project), [170](#)
- project, SpatRaster-method (project), [170](#)
- project, SpatVector-method (project), [170](#)
- quantile, [8](#), [18](#), [173](#), [236](#), [237](#)
- quantile, SpatRaster-method (quantile), [173](#)
- quantile, SpatVector-method (quantile), [173](#)
- query, [174](#)
- query, SpatVectorProxy-method (query), [174](#)
- rainbow, [39](#)
- range (summarize), [234](#)
- range, SpatRaster-method (summarize), [234](#)
- rapp, [8](#), [175](#), [208](#)
- rapp, SpatRaster-method (rapp), [175](#)
- rast, [7](#), [16](#), [17](#), [177](#), [221](#)
- rast, ANY-method (rast), [177](#)
- rast, array-method (rast), [177](#)
- rast, character-method (rast), [177](#)
- rast, data.frame-method (rast), [177](#)
- rast, list-method (rast), [177](#)
- rast, matrix-method (rast), [177](#)

- `rast,missing-method (rast)`, 177
- `rast,PackedSpatRaster-method (rast)`, 177
- `rast,SpatExtent-method (rast)`, 177
- `rast,SpatRaster-method (rast)`, 177
- `rast,SpatRasterDataset-method (rast)`, 177
- `rast,SpatVector-method (rast)`, 177
- `rast,stars-method (rast)`, 177
- `rast,stars_proxy-method (rast)`, 177
- `rasterImage`, 34, 167
- `rasterize`, 16, 123, 124, 179, 181, 182, 184
- `rasterize,matrix,SpatRaster-method (rasterize)`, 179
- `rasterize,sf,SpatRaster-method (rasterize)`, 179
- `rasterize,SpatVector,SpatRaster-method (rasterize)`, 179
- `rasterizeGeom`, 16, 181, 181, 184
- `rasterizeGeom,SpatVector,SpatRaster-method (rasterizeGeom)`, 181
- `rasterizeWin`, 123, 124, 181, 182
- `rasterizeWin,data.frame,SpatRaster-method (rasterizeWin)`, 182
- `rasterizeWin,SpatVector,SpatRaster-method (rasterizeWin)`, 182
- `RasterSource (SpatRaster-class)`, 221
- `RasterSource-class (SpatRaster-class)`, 221
- `rcl`, 184
- `rcl,SpatRaster-method (rcl)`, 184
- `Rcpp_RasterSource-class (SpatRaster-class)`, 221
- `Rcpp_SpatCategories-class (SpatRaster-class)`, 221
- `Rcpp_SpatExtent-class (SpatExtent-class)`, 217
- `Rcpp_SpatRaster-class (SpatRaster-class)`, 221
- `Rcpp_SpatVector-class (SpatVector-class)`, 224
- `read and write`, 185
- `readRDS (serialize)`, 209
- `readRDS,character-method (serialize)`, 209
- `readStart`, 12
- `readStart (read and write)`, 185
- `readStart,SpatRaster-method (read and write)`, 185
- `readStart,SpatRasterDataset-method (read and write)`, 185
- `readStop`, 12
- `readStop (read and write)`, 185
- `readStop,SpatRaster-method (read and write)`, 185
- `readStop,SpatRasterDataset-method (read and write)`, 185
- `readValues (read and write)`, 185
- `readValues,SpatRaster-method (read and write)`, 185
- `rectify`, 187
- `rectify,SpatRaster-method (rectify)`, 187
- `relate`, 13, 21, 125, 126, 150, 187
- `relate,SpatExtent,SpatExtent-method (relate)`, 187
- `relate,SpatExtent,SpatRaster-method (relate)`, 187
- `relate,SpatExtent,SpatVector-method (relate)`, 187
- `relate,SpatRaster,SpatExtent-method (relate)`, 187
- `relate,SpatRaster,SpatRaster-method (relate)`, 187
- `relate,SpatRaster,SpatVector-method (relate)`, 187
- `relate,SpatVector,missing-method (relate)`, 187
- `relate,SpatVector,SpatExtent-method (relate)`, 187
- `relate,SpatVector,SpatRaster-method (relate)`, 187
- `relate,SpatVector,SpatVector-method (relate)`, 187
- `removeDupNodes`, 15
- `removeDupNodes (topology)`, 246
- `removeDupNodes,SpatVector-method (topology)`, 246
- `rep`, 190, 190
- `rep,SpatRaster-method (rep)`, 190
- `replace_dollar`, 191
- `replace_layers`, 192
- `replace_values`, 193
- `res`, 10, 178
- `res (dimensions)`, 75
- `res,SpatRaster-method (dimensions)`, 75
- `res,SpatRasterDataset-method (dimensions)`, 75

- `res<-` (dimensions), 75
- `res<-`, `SpatRaster`, numeric-method (dimensions), 75
- `res<-`, `SpatRaster`-method (dimensions), 75
- `resample`, 7, 23, 65, 78, 117, 172, 187, 194
- `resample`, `SpatRaster`, `SpatRaster`-method (resample), 194
- `rescale`, 14, 44, 86, 121, 195, 225
- `rescale`, `SpatRaster`-method (rescale), 195
- `rescale`, `SpatVector`-method (rescale), 195
- `rev` (flip), 96
- `rev`, `SpatRaster`-method (flip), 96
- `RGB`, 167, 196
- `RGB`, `SpatRaster`-method (RGB), 196
- `RGB<-` (RGB), 196
- `RGB<-`, `SpatRaster`-method (RGB), 196
- `rotate`, 7, 97, 151, 196, 197, 213, 248
- `rotate`, `SpatRaster`-method (rotate), 197
- `rotate`, `SpatVector`-method (rotate), 197
- `round`, 39
- `round` (Math-methods), 139
- `round`, `SpatRaster`-method (Math-methods), 139
- `round`, `SpatVector`-method (Math-methods), 139
- `rowColCombine`, 185
- `rowColCombine` (xyRowColCell), 273
- `rowColCombine`, `SpatRaster`, numeric, numeric-method (xyRowColCell), 273
- `rowColFromCell`, 11
- `rowColFromCell` (xyRowColCell), 273
- `rowColFromCell`, `SpatRaster`, numeric-method (xyRowColCell), 273
- `rowFromCell` (xyRowColCell), 273
- `rowFromCell`, `SpatRaster`, numeric-method (xyRowColCell), 273
- `rowFromY`, 11
- `rowFromY` (xyRowColCell), 273
- `rowFromY`, `SpatRaster`, numeric-method (xyRowColCell), 273
- `runif`, 118
- `sapp`, 8, 130, 199
- `sapp`, `SpatRaster`-method (sapp), 199
- `sapp`, `SpatRasterDataset`-method (sapp), 199
- `saveRDS`, 209
- `saveRDS` (serialize), 209
- `saveRDS`, `SpatRaster`-method (serialize), 209
- `saveRDS`, `SpatVector`-method (serialize), 209
- `sbar`, 16, 121, 152, 164, 200
- `scale`, 9, 201, 201, 202
- `scale`, `SpatRaster`-method (scale), 201
- `scatterplot`, 202
- `scoff`, 203
- `scoff`, `SpatRaster`-method (scoff), 203
- `scoff<-` (scoff), 203
- `scoff<-`, `SpatRaster`-method (scoff), 203
- `sds`, 12, 179, 204, 226
- `sds`, array-method (sds), 204
- `sds`, character-method (sds), 204
- `sds`, list-method (sds), 204
- `sds`, missing-method (sds), 204
- `sds`, `SpatRaster`-method (sds), 204
- `sds`, stars-method (sds), 204
- `sds`, stars\_proxy-method (sds), 204
- `segregate`, 8, 17, 205
- `segregate`, `SpatRaster`-method (segregate), 205
- `sel`, 14, 16, 206
- `sel`, `SpatRaster`-method (sel), 206
- `sel`, `SpatVector`-method (sel), 206
- `selectHighest`, 207
- `selectHighest`, `SpatRaster`-method (selectHighest), 207
- `selectRange`, 7, 18, 175, 176, 208
- `selectRange`, `SpatRaster`-method (selectRange), 208
- `serialize`, 209, 209
- `serialize`, `SpatRaster`-method (serialize), 209
- `serialize`, `SpatVector`-method (serialize), 209
- `set.cats`, 11, 94
- `set.cats` (inplace), 119
- `set.cats`, `SpatRaster`-method (inplace), 119
- `set.crs` (inplace), 119
- `set.crs`, `SpatRaster`-method (inplace), 119
- `set.crs`, `SpatVector`-method (inplace), 119
- `set.ext`, 86
- `set.ext` (inplace), 119
- `set.ext`, `SpatRaster`-method (inplace), 119
- `set.ext`, `SpatVector`-method (inplace), 119



- set.names, [148](#)
- set.names (inplace), [119](#)
- set.names, SpatRaster-method (inplace), [119](#)
- set.names, SpatRasterCollection-method (inplace), [119](#)
- set.names, SpatRasterDataset-method (inplace), [119](#)
- set.names, SpatVector-method (inplace), [119](#)
- set.names, SpatVectorCollection-method (inplace), [119](#)
- set.RGB (inplace), [119](#)
- set.RGB, SpatRaster-method (inplace), [119](#)
- set.values, [193](#), [209](#)
- set.values (inplace), [119](#)
- set.values, SpatRaster-method (inplace), [119](#)
- setCats (deprecated), [72](#)
- setCats, SpatRaster-method (deprecated), [72](#)
- setGDALconfig, [261](#)
- setGDALconfig (gdal), [108](#)
- setMinMax, [10](#)
- setMinMax (extremes), [92](#)
- setMinMax, SpatRaster-method (extremes), [92](#)
- setValues, [10](#), [210](#)
- setValues, SpatRaster, ANY-method (setValues), [210](#)
- setValues, SpatRaster-method (setValues), [210](#)
- setValues, SpatVector, ANY-method (setValues), [210](#)
- setValues, SpatVector-method (setValues), [210](#)
- shade, [9](#), [211](#)
- sharedPaths, [15](#), [56](#), [108](#), [212](#), [215](#), [247](#)
- sharedPaths, SpatVector-method (sharedPaths), [212](#)
- shift, [7](#), [14](#), [121](#), [196](#), [198](#), [213](#), [225](#)
- shift, SpatExtent-method (shift), [213](#)
- shift, SpatRaster-method (shift), [213](#)
- shift, SpatVector-method (shift), [213](#)
- show, [114](#)
- show, SpatExtent-method (SpatExtent-class), [217](#)
- show, SpatRaster-method (SpatRaster-class), [221](#)
- show, SpatVector-method (SpatVector-class), [224](#)
- sieve, [214](#)
- sieve, SpatRaster-method (sieve), [214](#)
- simplifyGeom, [15](#), [215](#), [247](#)
- simplifyGeom, SpatVector-method (simplifyGeom), [215](#)
- size (dimensions), [75](#)
- size, SpatRaster-method (dimensions), [75](#)
- snap, [15](#)
- snap (topology), [246](#)
- snap, SpatVector-method (topology), [246](#)
- sort, [216](#)
- sort, SpatRaster-method (sort), [216](#)
- sources, [10](#), [12](#), [216](#)
- sources, SpatRaster-method (sources), [216](#)
- sources, SpatRasterCollection-method (sources), [216](#)
- sources, SpatRasterDataset-method (sources), [216](#)
- sources, SpatVector-method (sources), [216](#)
- sources, SpatVectorProxy-method (sources), [216](#)
- SpatCategories (SpatRaster-class), [221](#)
- SpatCategories-class (SpatRaster-class), [221](#)
- SpatExtent, [87](#), [166](#), [204](#)
- SpatExtent (SpatExtent-class), [217](#)
- SpatExtent-class, [217](#)
- Spatial interpolation, [218](#)
- SpatRaster (SpatRaster-class), [221](#)
- SpatRaster-class, [221](#)
- SpatRasterCollection (SpatRaster-class), [221](#)
- SpatRasterCollection-class (SpatRaster-class), [221](#)
- SpatRasterDataset (SpatRaster-class), [221](#)
- SpatRasterDataset-class (SpatRaster-class), [221](#)
- spatSample, [10](#), [18](#), [222](#), [237](#)
- spatSample, SpatExtent-method (spatSample), [222](#)
- spatSample, SpatRaster-method (spatSample), [222](#)
- spatSample, SpatVector-method (spatSample), [222](#)



- SpatVector (SpatVector-class), 224
- SpatVector-class, 224
- SpatVectorCollection
  - (SpatVector-class), 224
- SpatVectorCollection-class
  - (SpatVector-class), 224
- SpatVectorProxy (SpatVector-class), 224
- SpatVectorProxy-class
  - (SpatVector-class), 224
- spin, 14, 198, 224
- spin, SpatVector-method (spin), 224
- split, 225
- split, SpatRaster-method (split), 225
- split, SpatVector-method (split), 225
- sprc, 226
- sprc, character-method (sprc), 226
- sprc, list-method (sprc), 226
- sprc, missing-method (sprc), 226
- sprc, SpatRaster-method (sprc), 226
- sqrt (Math-methods), 139
- sqrt, SpatRaster-method (Math-methods), 139
- stdev (summarize), 234
- stdev, SpatRaster-method (summarize), 234
- stretch, 9, 227
- stretch, SpatRaster-method (stretch), 227
- subset, 7, 17, 175, 228
- subset, SpatRaster-method (subset), 228
- subset, SpatVector-method (subset), 228
- subset\_dollar, 229
- subset\_double, 231
- subset\_single, 232
- subst, 8, 51, 193, 233
- subst, SpatRaster-method (subst), 233
- sum (summarize), 234
- sum, SpatRaster-method (summarize), 234
- summarize, 234
- summary, 9, 236, 236, 237
- Summary, SpatExtent-method (summary), 236
- Summary, SpatRaster-method (summary), 236
- summary, SpatRaster-method (summary), 236
- Summary, SpatVector-method (summary), 236
- summary, SpatVector-method (summary), 236
- Summary-methods, 8, 18
- Summary-methods (summarize), 234
- svc, 15, 237
- svc, list-method (svc), 237
- svc, missing-method (svc), 237
- svc, sf-method (svc), 237
- svc, SpatVector-method (svc), 237
- symdif, 14, 238
- symdif, SpatVector, SpatVector-method (symdif), 238
- t, 7, 14, 196, 225
- t (transpose), 247
- t, SpatRaster-method (transpose), 247
- t, SpatVector-method (transpose), 247
- tail (head and tail), 113
- tail, SpatRaster-method (head and tail), 113
- tail, SpatVector-method (head and tail), 113
- tapp, 8, 18, 27, 129, 130, 176, 199, 208, 239
- tapp, SpatRaster-method (tapp), 239
- tapply, 239
- terra (terra-package), 6
- terra-package, 6
- terrain, 9, 199, 211, 212, 240, 259
- terrain, SpatRaster-method (terrain), 240
- terraOptions, 12, 246
- terraOptions (options), 154
- text, 16, 206, 242, 243
- text, SpatRaster-method (text), 242
- text, SpatVector-method (text), 242
- tighten, 243
- tighten, SpatRaster-method (tighten), 243
- tighten, SpatRasterDataset-method (tighten), 243
- tiles, 261
- tiles (makeTiles), 134
- tiles, SpatRaster-method (makeTiles), 134
- time, 11, 73, 239, 244, 252
- time, SpatRaster-method (time), 244
- time<- (time), 244
- time<-, SpatRaster-method (time), 244
- timeInfo (time), 244
- timeInfo, SpatRaster-method (time), 244
- tmpFiles, 12, 245
- topology, 108, 212, 246
- trans, 97
- trans (transpose), 247
- trans, SpatRaster-method (transpose), 247
- transpose, 247
- Trig, 36
- trim, 7, 248
- trim, SpatRaster-method (trim), 248

- union, [14](#), [15](#), [56](#), [126](#), [249](#)
- union, SpatExtent, SpatExtent-method (union), [249](#)
- union, SpatVector, missing-method (union), [249](#)
- union, SpatVector, SpatExtent-method (union), [249](#)
- union, SpatVector, SpatVector-method (union), [249](#)
- unique, [9](#), [13](#), [250](#), [250](#)
- unique, SpatRaster, ANY-method (unique), [250](#)
- unique, SpatRaster-method (unique), [250](#)
- unique, SpatVector, ANY-method (unique), [250](#)
- unique, SpatVector-method (unique), [250](#)
- units, [251](#)
- units, SpatRaster-method (units), [251](#)
- units, SpatRasterDataset-method (units), [251](#)
- units<- (units), [251](#)
- units<-, SpatRaster-method (units), [251](#)
- units<-, SpatRasterDataset-method (units), [251](#)
- unserialize (serialize), [209](#)
- unserialize, ANY-method (serialize), [209](#)
- unwrap (wrap), [267](#)
- unwrap, ANY-method (wrap), [267](#)
- unwrap, PackedSpatRaster-method (wrap), [267](#)
- unwrap, PackedSpatVector-method (wrap), [267](#)
- update, [252](#)
- update, SpatRaster-method (update), [252](#)
- valid, [253](#)
- values, [9](#), [14](#), [18](#), [90](#), [193](#), [211](#), [254](#)
- values, SpatRaster-method (values), [254](#)
- values, SpatVector-method (values), [254](#)
- values<-, [10](#), [14](#)
- values<- (setValues), [210](#)
- values<-, SpatRaster, ANY-method (setValues), [210](#)
- values<-, SpatVector, ANY-method (setValues), [210](#)
- values<-, SpatVector, data.frame-method (setValues), [210](#)
- values<-, SpatVector, matrix-method (setValues), [210](#)
- values<-, SpatVector, NULL-method (setValues), [210](#)
- varnames (names), [148](#)
- varnames, SpatRaster-method (names), [148](#)
- varnames, SpatRasterDataset-method (names), [148](#)
- varnames<- (names), [148](#)
- varnames<-, SpatRaster-method (names), [148](#)
- varnames<-, SpatRasterDataset-method (names), [148](#)
- vect, [13](#), [16](#), [18](#), [175](#), [179](#), [255](#)
- vect, character-method (vect), [255](#)
- vect, data.frame-method (vect), [255](#)
- vect, list-method (vect), [255](#)
- vect, matrix-method (vect), [255](#)
- vect, missing-method (vect), [255](#)
- vect, PackedSpatVector-method (vect), [255](#)
- vect, sf-method (vect), [255](#)
- vect, sfc-method (vect), [255](#)
- vect, Spatial-method (vect), [255](#)
- vect, XY-method (vect), [255](#)
- vector\_layers, [13](#), [258](#), [271](#)
- viewshed, [242](#), [258](#)
- viewshed, SpatRaster-method (viewshed), [258](#)
- voronoi, [13](#), [260](#)
- voronoi, SpatVector-method (voronoi), [260](#)
- vrt, [135](#), [136](#), [142](#), [261](#)
- vrt, character-method (vrt), [261](#)
- weighted.mean, [132](#), [262](#), [262](#)
- weighted.mean, SpatRaster, numeric-method (weighted.mean), [262](#)
- weighted.mean, SpatRaster, SpatRaster-method (weighted.mean), [262](#)
- where, [263](#)
- which, [263](#), [264](#)
- which.lyr, [8](#), [236](#), [264](#)
- which.lyr, SpatRaster-method (which.lyr), [264](#)
- which.max (summarize), [234](#)
- which.max, SpatRaster-method (summarize), [234](#)
- which.min (summarize), [234](#)
- which.min, SpatRaster-method (summarize), [234](#)
- width, [14](#), [265](#)
- width, SpatVector-method (width), [265](#)

- window, [266](#)
- window, SpatRaster-method (window), [266](#)
- window<- (window), [266](#)
- window<-, SpatRaster-method (window), [266](#)
- wrap, [7](#), [179](#), [209](#), [267](#)
- wrap, SpatRaster-method (wrap), [267](#)
- wrap, SpatVector-method (wrap), [267](#)
- writeCDF, [11](#), [268](#), [270](#)
- writeCDF, SpatRaster-method (writeCDF), [268](#)
- writeCDF, SpatRasterDataset-method (writeCDF), [268](#)
- writeRaster, [7](#), [11](#), [22](#), [27](#), [29](#), [36](#), [40](#), [42](#), [45](#), [47](#), [49](#), [51](#), [59](#), [62](#), [63](#), [66](#), [74](#), [77](#), [78](#), [80](#), [88](#), [95](#), [96](#), [98](#), [100–102](#), [105](#), [113](#), [115](#), [117](#), [118](#), [123](#), [124](#), [127](#), [129](#), [135](#), [137](#), [140](#), [142–145](#), [153](#), [154](#), [156](#), [168](#), [172](#), [173](#), [176](#), [179](#), [180](#), [182](#), [183](#), [186](#), [187](#), [194](#), [197–199](#), [205](#), [208](#), [209](#), [211](#), [213](#), [214](#), [216](#), [219](#), [227](#), [228](#), [234](#), [235](#), [240](#), [241](#), [247](#), [248](#), [259](#), [262](#), [268](#), [269](#), [276](#)
- writeRaster, SpatRaster, character-method (writeRaster), [269](#)
- writeStart, [12](#)
- writeStart (read and write), [185](#)
- writeStart, SpatRaster, character-method (read and write), [185](#)
- writeStop, [12](#)
- writeStop (read and write), [185](#)
- writeStop, SpatRaster-method (read and write), [185](#)
- writeValues, [12](#)
- writeValues (read and write), [185](#)
- writeValues, SpatRaster, vector-method (read and write), [185](#)
- writeVector, [13](#), [271](#)
- writeVector, SpatVector, character-method (writeVector), [271](#)
- xFromCell, [11](#)
- xFromCell (xyRowColCell), [273](#)
- xFromCell, SpatRaster, numeric-method (xyRowColCell), [273](#)
- xFromCol, [11](#)
- xFromCol (xyRowColCell), [273](#)
- xFromCol, SpatRaster, missing-method (xyRowColCell), [273](#)
- xFromCol, SpatRaster, numeric-method (xyRowColCell), [273](#)
- xmax, [10](#)
- xmax (xmin), [272](#)
- xmax, SpatExtent-method (xmin), [272](#)
- xmax, SpatRaster-method (xmin), [272](#)
- xmax, SpatVector-method (xmin), [272](#)
- xmax<- (xmin), [272](#)
- xmax<-, SpatExtent, numeric-method (xmin), [272](#)
- xmax<-, SpatRaster, numeric-method (xmin), [272](#)
- xmin, [10](#), [272](#)
- xmin, SpatExtent-method (xmin), [272](#)
- xmin, SpatRaster-method (xmin), [272](#)
- xmin, SpatVector-method (xmin), [272](#)
- xmin<- (xmin), [272](#)
- xmin<-, SpatExtent, numeric-method (xmin), [272](#)
- xmin<-, SpatRaster, numeric-method (xmin), [272](#)
- xres, [10](#)
- xres (dimensions), [75](#)
- xres, SpatRaster-method (dimensions), [75](#)
- xyFromCell, [11](#), [65](#), [90](#), [110](#)
- xyFromCell (xyRowColCell), [273](#)
- xyFromCell, SpatRaster, numeric-method (xyRowColCell), [273](#)
- xyRowColCell, [273](#)
- yFromCell, [11](#)
- yFromCell (xyRowColCell), [273](#)
- yFromCell, SpatRaster, numeric-method (xyRowColCell), [273](#)
- yFromRow, [11](#)
- yFromRow (xyRowColCell), [273](#)
- yFromRow, SpatRaster, missing-method (xyRowColCell), [273](#)
- yFromRow, SpatRaster, numeric-method (xyRowColCell), [273](#)
- ymax, [10](#)
- ymax (xmin), [272](#)
- ymax, SpatExtent-method (xmin), [272](#)
- ymax, SpatRaster-method (xmin), [272](#)
- ymax, SpatVector-method (xmin), [272](#)
- ymax<- (xmin), [272](#)
- ymax<-, SpatExtent, numeric-method (xmin), [272](#)

`ymin<-`, `SpatRaster`, numeric-method  
    (`xmin`), [272](#)  
`ymin`, [10](#)  
`ymin`(`xmin`), [272](#)  
`ymin`, `SpatExtent`-method (`xmin`), [272](#)  
`ymin`, `SpatRaster`-method (`xmin`), [272](#)  
`ymin`, `SpatVector`-method (`xmin`), [272](#)  
`ymin<-` (`xmin`), [272](#)  
`ymin<-`, `SpatExtent`, numeric-method  
    (`xmin`), [272](#)  
`ymin<-`, `SpatRaster`, numeric-method  
    (`xmin`), [272](#)  
`yres`, [10](#)  
`yres` (`dimensions`), [75](#)  
`yres`, `SpatRaster`-method (`dimensions`), [75](#)  
  
`zonal`, [9](#), [67](#), [86](#), [112](#), [275](#)  
`zonal`, `SpatRaster`, `SpatRaster`-method  
    (`zonal`), [275](#)  
`zonal`, `SpatVector`, `SpatVector`-method  
    (`zonal`), [275](#)  
`zoom`, [16](#), [277](#)  
`zoom`, `SpatRaster`-method (`zoom`), [277](#)  
`zoom`, `SpatVector`-method (`zoom`), [277](#)